

PATNA SMART CITY LTD.



Volume 1 of 2

DETAIL PROJECT REPORT OF OPEN SPACES AT BHAGALPUR

Under Smart City Mission

SIR MATTHER FEETH 2. ON VID.

PATNANovember, 2019



Open Spaces



Proprietary & Confidential

No part of this document can be reproduced in any form or by any means, disclosed or distributed to any person without the prior consent of Bhagalpur Smart City, except to the extent required for submitting bid and no more.

The information contained in this document is only disclosed for the purposes of understanding the detailed project for preparation of RFP in accordance with the requirements of this document and no more.

This document contains proprietary information furnished for evaluation by "Technical committee" of Bhagalpur Smart City only; except with the written permission of BHAGALPUR SMART CITY, such information may not be published, disclosed, or used for any other purpose. Reader of this document acknowledge and agree that this document and all portions thereof, including, but not limited to, any copyright, trade secret and other intellectual property rights relating thereto, are and at all times shall remain the sole property of BHAGALPUR SMART CITY and that title and full ownership rights in the information contained herein and all portions thereof are reserved to and at all times shall remain with BHAGALPUR SMART CITY. Readers also agree to take utmost care in protecting the proprietary and confidential nature of the information contained herein.



Open Spaces



Preamble

Proposal for Assistance / handholding for the preparation of DPR/RFPs of major projects of Bhagalpur Smart City Limited (BSCL) was considered by the UD&HD Department, Government of Bihar and subsequent correspondence on this are narrated hereunder. Ultimately, it was decided that Patna Smart City Limited will extend that support to the Bhagalpur Smart City Limited through the existing PMC under their existing condition of contract with PSCL. The references are-

Review meeting of Principal Secretary, UD&HD, and Government of Bihar on 02.04.2019 as his advice in the matter.

Letter no 147/BSCL of MD, BSCL dated 02.04.2019 addressed to MD, PSCL, forwarded by CEO, PSCL to PMC, PSCL dated 06.04.2019 and Letter no 154/BSCL dated 06.04.2019, of BSCL.

Order No. 768 dt 11-04-2019 of MD, PSCL

This office letter No. EPTISA/PMC/PATNA/557/2019 dated:- 8th April 2019 addressed to the IV MD, Patna Smart City Ltd.

Reports on PMC visit to Bhagalpur during 9-10 April 2019 vide PMC letter No. EPTISA/PMC/PATNA/562/2019 dated 11.04.2019

Order No. 831 dt 27-04-2019 of MD, PSCL

VII Agreement dated 21st December 2017 between PSCL and EPTISA.

VIII Letter No. 1127 dt 21-06-2019 of CGM, PSCL

IX Letter No. 1194 dt 03-07-2019 of CGM, PSCL


M/S Eptisa Servicios de Ingenieria S.L. has been engaged as Project Management Consultant for providing assistance to Patna Smart City Limited (PSCL) to design, develop, manage and implement Smart City Projects. PSCL has entrusted PMC (Eptisa) for additional support for Bhagalpur Smart City Limited (BSCL) vide letter no. Letter No. 1127 dt 21-06-2019 of CGM, PSCL.

2. The scope of Project Management Consultancy services under the proposed additional assignment is "Preparation and Submission of deliverables" in reference to BSCL for the

following 6 projects:

Sl. No.	Projects
1	ICCC - Data Centre
2	Solid Waste Management
3	River Front Development
4	ICCC Building
5	Open spaces
6	Smart Road Network

- Tentative cost of the project is be Rs. 932.00 cr. Eptisa will prepare the SAR, FR, DPR, RFP up to the issuance of the LOA for procurement of agency/ agencies of the above mentioned project as per the existing terms with PSCL within the time lines as mentioned in the letter no. 1127 dt 21.06.2019.
- 4. All deliverables will be presented and submitted to PSCL at Patna and the Eptisa team will interact with the Nodal officer (Md Shahid - Sr. Manager, Technical, PSCL) in this respect to coordinate with Bhagalpur Smart City Limited for necessary activities and feedback. (Reference-Letter No. 1194 dt 03-07-2019 of CGM, PSCL)
- PMC (Eptisa) made the survey investigation of all the sites and made several site visits at Bhagalpur by the different experts from time to time.
- The SAR for all the 6 (six) projects are submitted in one vol. for convenience and for approval.



Project Management Consultant Patna Smart City Limited







REVISION INDEX

Ver No	Date	Revisions Details	Document Description	Pre by	App by
1.0	27-Sept-2019		Detailed Project Report	PMC	PSCL
2.0	21-Nov-2019	R1	Detailed Project Report	РМС	PSCL
				5	



Open Spaces



TABLE OF CONTENTS

		ABLES	
		IGURES	
		ATIONS	
1.		ackground	
	1.1	About Bhagalpur Smart City Project	
	1.2	About Bhagalpur City	
2.		roduction	
3.		ope of Work	
4.	Pro	oject Location	22
4.1	San	ndy's Compound	22
4.2	Lajp	path Complex	22
5.	Exis	sting Situation	23
5.1	San	ndy's Compound	23
5.2	Lajp	pat Complex2	24
6.	Prop	posals of Work	26
6.1	Reju	uvenation of Existing Large Open Space2	27
6.1.1	Red	design of Stage2	!7
6.1.2	Lanc	dscaping and Drainage2	.7
6.2	Deve	velopment of Badminton Stadium 2	7
6.3	Deve	relopment of Sports Complex	9
6.3.1	Entra	rance and Parking2	9
6.3.2	Stad	dium 2	9
6.3.3	Bask	ketball Court3	0
6.3.4	Volle	ey Ball Court Renovation 3	1
6.3.5	Gym	n Renovation3	1
6.3.6	Lawn	n Tennis 3:	3
6.3.7	Swim	nming Pool33	3
6.3.8	Cafet	teria and Food Plaza	4
6.4	Deve	elopment of Theme Based Parks 35	5
6.4.1	Kids F	Play Area	5
		Play Area	02





Open Spaces

6.4.2	Sculpture Court cum Open Art Gallery
6.4.3	Outdoor Gymnasium
6.4.4	Yoga Park37
6.4.5	Nursery
6.4.6	Open Zoo
6.5.1	Vehicular cum Cycle Track:
6.5.2	Joggers Track
6.5.3	Walkways and Natural Trail
6.5.4	Drive Way
6.5.5	Battery Operated Vehicle39
6.13	Development of Adventure Zone
6.13.1	Zip Line
6.13.2	Rappelling43
	Wall Climbing44
6.13.4	Rope climbing44
6.13.5	Paintball44
6.13.6	Zorbing
6.13.7	Archery
6.13.8	Mechanical Bull Ride
6.13.9	Human Foosball
6.14	Camping Area47
6.15	Drainage
6.16	Compost and Gray water Treatment
6.17	CCTV Surveillance
6.18	Audio System49
6.19	Solar Roof
6.20	Shared Bicycle System49
6.21	Kiosks
6.22	Landscape Feature and Furniture
7.	Scope of work & Specifications51
7.1	Scope of Work



Open Spaces

7.2	Construction Scope 5
7.3	General Specifications5
7.4	Civil Works specifications 54
7.5	Details of Electrical items with specifications
7.6	Details of signages, Furniture's with specifications
7.7	Details for fountains and specification
7.8	Details of Plants
8.	Financial Viability 85
8.1	Estimated Project Cost: 85
8.2	Funding 87
8.3	Operation and maintenance:
8.4	Institutional Arrangements:
8.5	Project Revenue
8.6	Risks and Allocation of Risks
8.7	Project Phasing98
9.	Environmental Proposals
9.1	Environmental considerations:
9.2	Resettlement proposals
10.	Conclusions and recommendations

Volume 2:

1. Annexure 1: Drawings

2. Annexure 2: Detailed Estimates



(A)

DETAIL PROJECT REPORT

Open Spaces



LIST OF TABLES

Table 1.1: Climate Data for Bhagalpur	16
Table 1.1: Cliffate Data for Bridgerpur	32
Table 2: List of Proposed Gym Equipment for each Floor	25
Table 3: Kids Play Equipment	33
Table 4: Entrance	41
Table 7.4.1: Specifications for building works	54
Table 7.4.2: Details of materials and specifications for outdoor works	56
Table 7.5.1: Types of lights used in project	61
Table 8: List of Proposed Plants	78
Table 7.8.3: List of other Trees that can be considered	82
Table 8.2.1 : Funding Availability as per SCM	87
Table 8.1.1: Abstract of Detailed Cost estimate of the project (Phase I)	88
Table 8.1.1: Abstract of Detailed Cost estimate of the project (Finase),	90
Table 8.4.1: Manpower requirement	01
Table 8.4.2: Equipment requirement	51
Table 8.5.1: Revenue Estimation	92
Table 8.5.2: Annual Revenues (Rs.)	93
Table 8.6.1: Typical Risks	94
Table 8.6.2: Risk Allocation during Construction Phase	97
Table 8.6.3: Risk Allocation during Operating Phase	97
Table 8.6.4: Risk Allocation of Other Risks	97
Table 8.7.1: Milestones	98
Table 8.7.1: Milestones	100
Table 21: Anticinated Environmental Impacts and Milligation Measures	100



Open Spaces



LIST OF FIGURES

Figure 1 Location Map of Bhagalpur City in Bihar State	13
Figure 2 Land Use Map of Bhagalpur City (source: CDP)	15
Figure 3 Map showing Road Network of Bhagalpur	19
Figure 4: Location of Lajpat Complex and Sandy's Compound	
Figure 5: Sandy's Compound	23
Figure 6: Mound Sandy's Compound	23
Figure 7: Entrance Gate, Sandy's Compound	23
Figure 8: Volleyball Court, Sandy's Compound	23
Figure 9: Lajpat Park	24
Figure 10: Open Gym, Lajpat Park	24
Figure 11: Children's Park	25
Figure 12: Pavement Pathways, Children's Park	25
Figure 13: Kala Kendra, Bhagalpur	25
Figure 14: Sculpture in Kala Kendra	25
Figure 15: Town Hall	25
Figure 16: Town Hall Building	25
Figure 17 Truss for Stage	27
Figure 18: Badminton Court	27
Figure 19: Stadium	29
Figure 20: Cricket Pitch	29
Figure 21: Basket Dimension	30
Figure 22: Basketball Court Dimension	30
Figure 23: Volley Ball Court Dimension	31
Figure 24: Indicative Gym Interior	
Figure 25: Lawn Tennis Size	
Figure 26: Swimming Pool Dimension	.33
Figure 27: Indicative Cafeteria with Food Plaza	
Figure 28: Indicative Food Plaza	.34
Figure 29: Representative Kids Play Area.	. 35
Figure 30: Art Exhibition Area	.36
Figure 31: Modern Sculpture Representation	.36
Figure 32: Representation of Open Zoo	.37
Figure 31: Modern Sculpture Representation Figure 32: Representation of Open Zoo Figure 33: Representation of Yoga Platform Figure 34: Representation of Nursery Figure 35: Representation of Open Zoo Figure 36: Representative Plaza	37
Figure 34: Representation of Nursery	37
Figure 35: Representation of Open Zoo	38
Figure 36: Representation of Battery Operated Car	39
Figure 37: Representative Plaza	39





Open Spaces

Figure 38: Cobble Stone	40
Figure 39: Water Fountain	40
Figure 40: Broken Dance Floor	40
Figure 42: Existing Station Club Building	40
Figure 41: Roof Condition	40
Figure 43: Billiard Board	40
Figure 44: Representative Fountain at Entrance	41
Figure 45: Representation of OAT	41
Figure 46: Boundary Wall	42
Figure 48: Zip Line	43
Figure 49: Rappelling	43
Figure 50: Wall Climbing	44
Figure 51: Rope Climbing	44
Figure 52: Paintball	45
Figure 53: Zorbing	45
Figure 54: Archery	46
Figure 55: Mech. Bull ride	46
Figure 56: Human Foosball	47
Figure 57: Human Chess	47
Figure 58: Representation of Camping Area	47
Figure 59: Swale Landform	47
Figure 60: App based bicycle sharing System	49
Figure 61: Mounds	50
Figure 62: Metallic Dustbin	50
Figure 63: Bridge	50
Figure 64: Gazeebo	50
Figure 65: Trellis Walkway	50
Figure 66: Typical construction specifications	59
Figure 67: Paving area details	59
Figure 67: Paving area details	68
Figure 68: Lighting Fixtures reference images Figure 69: Garden Furniture	75
Figure 69: Garden Furniture	76
Figure 70: Details of Dustbin and Signage	Ω1
Figure 71: Proposed trees on site	04



Open Spaces



ABBREVIATIONS

ABD	Area-Based Development
BPR	Business Process Re-Engineering
BSRTC	Bihar State Road Transport Corporation
CBD	Central Business District
DPR	Detailed Project Report
EBP	Early Bird Project
GIS	Geographical Information System
Gol	Government of India
GPS	Global Positioning System
LPCD	Litre Per Capita Day
MoPNG	Ministry of Petroleum & Natural Gas
MoUD	Ministry of Urban Development
NRW	Non-Revenue Water
PCP	Pan City Proposal
PMC	Project Management Consultant
ВМС	Bhagalpur Municipal Corporation
PMKVY	Prime Minister Kaushal Vikas Yojana
PPP	Public Private Partnership
BSCL	Bhagalpur Smart City Limited
PSU	Public Sector Undertaking
RFP	Request for Proposal
SCADA	Supervisory Control and Data Acquisition
SCM	Smart City Mission
SCP	Smart City Proposal
SLA	Service Level Agreement
SPV	Special Purpose Vehicle
ToR	Terms of Reference

SR. MANAGER TECH. 2

BHAGALPUR SMART CITY LTD.

BHAGALPUR



Open Spaces



1. Background

Government of India (GoI) through Ministry of Housing & Urban Affairs (MoHUA) launched 'Smart Cities Mission' in the year 2015 with an objective to promote cities that provide core infrastructure and give a decent quality of life to its citizens, a clean and sustainable environment and application of smart solutions. The focus is on sustainable and inclusive development and the idea is to look at compact areas, create a replicable model which will act like a light house to other aspiring cities. The Smart Cities Mission is a bold, new initiative. It is meant to set examples that can be replicated both within and outside the Smart City, catalyzing the creation of similar Smart Cities in various regions and parts of the country.

Accordingly, the purpose of the Smart Cities Mission is to drive economic growth and improve the quality of life of people by enabling local area development and harnessing technology, especially technology that leads to smart outcomes. Areabased development will transform existing areas (retrofit and redevelop), including slums, into better planned ones, thereby improving livability of the whole City. New areas (Greenfield) will be developed around cities in order to accommodate the expanding population in urban areas. Application of Smart Solutions will enable cities to use technology, information and data to improve infrastructure and services. Comprehensive development in this way will improve quality of life, create employment and enhance incomes for all, especially the poor and the disadvantaged, leading to inclusive Cities.

The Smart City Mission envisages interventions in across 100 cities in the country over a period of 5 years i.e. Mission Period 2015-2020. Government of India will give a Grant of Rs 100 Crore per city for 5 years. Smart cities Selection is through competition after evaluation of the Smart City Proposals (SCP) prepared through Intense Citizen Consultation by the cities by a Panel of Experts put in place by MoUD, GoI. The strategic components of Area-based Development (ABD) in the Smart Cities Mission are city improvement (retrofitting), city renewal (redevelopment) and city extension (Greenfield development) plus a Pan-city initiative in which Smart Solutions are applied covering larger parts of the city. The Mission aims to development, design, build and operationalize smart and innovative solutions across core city infrastructures including:

The core infrastructure elements in a Smart City would include:

- Adequate water supply,
- Assured electricity supply,
- Sanitation, including solid waste management,
- Efficient urban mobility and public transport,



Open Spaces



- · Affordable housing, especially for the poor,
- Robust IT connectivity and digitalization,
- Good governance, especially e-Governance and citizen participation,
- Sustainable environment,
- Safety and security of citizens, particularly women, children and the elderly, and
- Health and education.

To bridge the gap and provide a society in line with the vision of inclusive growth the smart city mission has been launched in India. The purpose of the Smart Cities Mission is to drive economic growth and improve the quality of life of people by enabling local area development and harnessing technology, especially technology that leads to Smart outcomes. Bhagalpur Smart City as part of its vision to provide Good Governance to its citizens, initiated steps to harness the potential of IT to provide integrated services to the citizens by deploying the tools of Information and Communication Technology (ICT) so as to enhance Quality, Transparency, Convenience, Certainty and Accountability in providing such services.

1.1 About Bhagalpur Smart City Project

The city of Bhagalpur has been selected among 100 potential Indian cities to be developed as smart cities under the Smart City Mission. It was selected in the first round. The Bhagalpur Municipal Corporation has formed a Special Purpose Vehicle (SPV) called 'Bhagalpur Smart City Limited' (BSCL) as per mission guidelines for implementation of projects identified in the proposal.

Implementing	Bhagalpur Smart City Limited (BSCL) - Special Purpose
Agency	Vehicle
Funding Agency	Government of India/Government of Bihar/Bhagalpur Nagar
	Nigam (BNN)

Citizens of Bhagalpur have collectively envisioned a progressive city, dedicated towards promoting its unique identity, good governance, enhanced quality of life, sustainable utilization of its distinctive historical, cultural and ecological assets to attract tourism, investments and business. Goals of Bhagalpur Smart City Project are:

- Sushaasit Bhagalpur: a city with smart and quality governance
- Samrudh Bhagalpur: city of eco-tourism, progressive economy, employment
- Gatimaan Bhagapur: a well-connected city with enhanced public transport
- Sudrid Bhagalpur: a well-functioning, smart and efficient city
- Sarvabhoumik Vikas: socially inclusive city

Page 12 of 102

(A)

DETAIL PROJECT REPORT

Open Spaces



The entire project is divided into many sub-projects under two main category; ABD projects and Pan City Projects. The projects under ABD are limited within a specific area of the city and mostly include projects of retrofitting and re-development nature. Whereas PAN city projects are mostly based on use of ICT technology systems and solid waste management component. Other important part of the project is the technology based Smart solution which will help to extend the different need-based services to be provided to the citizen (G2C, B2C and many more) including e-governance through digital services.

1.2 About Bhagalpur City

Bhagalpur, the 3rd largest city in Bihar state is a divisional town with historical importance situated on the southern bank of the Ganga river. Distorted but derived from Bhagdatpuram, meaning City of Good Luck, Bhagalpur City is situated in the planes of the Ganga basin, at about 141 feet above sea level. Bhagalpur is located 220 km east of Patna and 410 km North West of Kolkata. Geographically, it is located at 25° 15' 0" North latitude and 87° 0' 0" East longitude on the southern alluvial plains of River Ganga. The Gangetic plains surrounding the city are very fertile. The city is a district headquarters serving multiple functions of an administrative, trade and commerce, service and distribution centre. Vikramshila Dolphin Sanctuary established near the town is the only sanctuary in Asia for conservation of Gangetic Dolphins. World's second largest rescue and rehabilitation area for Garuda is located in Bhagalpur. The city is well connected through rail and road networks. NH-80 runs through the city and connects with Patna. SH-19 and 25 are the main arterial roads. Bhagalpur has been associated with silk industry for hundreds of years and is also known as Silk City and ranks 2nd after Karnataka in silk fabric production and exports. The city is also famous for its Manjusha paintings, a unique art found only in Bihar.




Figure 1 Location Map of Bhagalpur City in Bihar State



Open Spaces



Bhagalpur Nagar Nigam covering 30.17 sq.km. area is divided into 51 wards. As of 2011 census, Bhagalpur town has a population of more than 4 lakhs with average literacy rate of 81%. The competitive advantage of Bhagalpur lies in its tradition as a silk weaving centre, the potential for river front development, the potential to develop it as a logistics hub to promote trade and commerce and development of open spaces. The city development plan prepared for Bhagalpur envisions its development as premier silk production centre and hub for agriculture produce with higher order infrastructure facilities. Maximum Summer Temp. & Minimum Winter temp. are 44°C and 10°C.

Demography of Bhagalpur

30.17 Sq .Km.
25°15' 0" N ; 87°0' 0"E
51
4,00,146 (212813 M + 187333 F)
878
54,818
85,784
5.72
13,263
81.16%
10.74
165
8136
8.4
25.95 %

Land use pattern

Bhagalpur is growing and emerging as trade, business and education centre in last decade and witnessing increase in migration from immediate hinterland and different part of the state of Bihar. It resulted in to rapid urbanization in neighbouring areas of Bhagalpur Municipal Area become outgrowths of Bhagalpur City. In the absence of planning interventions, rapid growth led to haphazard development which resulted into deterioration of open space and green area, uncontrolled and unregulated construction activities, formation of slum and unregulated construction within core city. Mixed land use is prevalent along major roads. Road frontage are dominated by commercial activities and retail shops. The city has about 86,000 households with average density of 13,263 persons per sq.km. There are about 165 slums spread within city with population of about 9,000 persons.



Open Spaces






Figure 2 Land Use Map of Bhagalpur City (source: CDP)

Climate

In general a warm and humid climate prevails in the district. Winter starts from November and extends up to February. Temperature usually does not drop below 150 C but during the coldest months (late December to early January) temperature even comes down to 80 C. During this period, wind blows from northwest and west. The summer period begins from March with the peak temperature of 40 – 450 C in May. The month of March and April are the driest months of the year with the relative humidity of 50 – 55 % in the morning and 35 – 40 % in the afternoon. The humidity increases in May and June to 80 % or more. About 80 % of the rainfall is under the influence of southwest monsoon, which normally breaks in the second fortnight of June. The monsoon lasts till the later part of the September. Generally the eastern and northeastern part of the district receives higher amount of rainfall. The annual normal rainfall in the district remains above 1148 mm.



Open Spaces



Table 1.1: Climate Data for Bhagalpur

Climate data for Bhagalpur City (Avg. High-Low - 2000-2012) (Record High-Low - 2015)

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec	Year
Record high °C	25	32	38	40	42	44	37	37	37	37	33	30	44
Average high °C	17	18	23	20	27	24	25	27	19	20	18	17	21
Average low °C	10	11	16	16	23	23	22	24	21	24	17	14	18
Record low °C	8	8	12	20	23	24	24	24	24	17	16	6	6
Average precipitation mm	9	15	45	0	66	72	147	150	243	111	0	27	885

Social Infrastructure

Bhagalpur, being a district headquarters has good quality social infrastructure facilities including higher level education and health facilities. However, recreational and community facilities are insufficient. Jawaharlal Nehru Medical College & Hospital is the largest hospital in the city as well as district with more than 700 beds and modern equipment's. Recreational facilities include Jayaprakash Udyan (city level park), Lajpat Park, Forest and Railway Park, Town Hall and Vivah Bhawan. The city has more than 160 slums housing about 30% of city population. About more than 40% of households are below poverty line. Basic facilities are practically absent in slums. Situation is aggravated by poor coverage of poverty and slum upgradation schemes. 90% of road length in slums is kutchha without any drainage network. Handpump is the primary source of water and one pump serves more than 70 households. 90% of slums are of kutcha or semi-kutcha in nature with inadequate access to health facilities. Annual tourist inflow of tourist is estimated at 6% with highest inflow recorded during July-August at time of regional festivals. Tourist infrastructure is inadequate, heritage structures are poorly maintained.

Institutions

The city is a hub of educational activities for surrounding towns and villages. There are more than 400 government schools comprising more than 300 primary school, more than 70 middle schools and more than 20 high schools, including about 6 degree colleges, 1 engineering college, 1 medical college, agriculture university, ITI and polytechnic for higher and technical education facilities. There are both, private and government schools. Some famous institutions are Tilakamanjhi Bhagalpur university, Bhagalpur college of engineering, Bihar agricultural university, Indian Institute of Information Technology, St. Joseph's school, Delhi Public School, TNB college etc.

MAGALPHR SMARION Rage 16 of 102

Open Spaces



Civic Amenities

Water supply in Bhagalpur is based on surface water and ground water. Town receives about 17 MLD of piped water from river Ganga. Tube wells account for 18 MLD of supply and hand pumps account for 2.25 MLD. It is estimated that 38 MLD water is supplied covering 19% of the town. Current installed storage capacity is 67% of supply, there are 7 over head tanks. Ground water is high in nitrate and arsenic. Per capita water supply is estimated at 33 lpcd and supply is for 7 hours a day. The city is implementing an integrated water supply scheme from state funds. Bhagalpur has minimal sewerage system. The estimated generation is 44 MLD waste water. Town has one treatment plant with installed capacity of 11 MLD. Only 4 MLD of waste water is collected and treated (primary) with remaining waste water being discharged into river Ganga with no treatment. 75% households have individual toilets with septic tanks and soak pits. Town has 26 community toilets but all are poorly maintained. Only 20% of town has sewage network services. The total drainage network in Bhagalpur municipal area covers 162 km. of which 112 km. drains are pucca open and 50 km. are kutcha open drains. Drains are normally seen on one side of the road. Natural drainage is from south to north. Existing drainage system is highly chocked by indiscriminate garbage dumping and silting. All discharge from drains is disposed directly into river Ganga. Storm water drains carry waste water from households. Bhagalpur generates about 225 tonnes of waste per day of which 87% is collected. Door to door collection and transportation system was introduced last year with road sweeping and drain cleaning through a private operator in 10 wards of the town. Nagar Nigam has limited equipment's for solid waste management. There is no treatment of garbage prior to disposal. At present, garbage is dumped on available open spaces. There are more than 2000 street light poles in the city.

Economy

Workforce participation in the town is about 26%. Main workers account for 84%. Bhagalpur's economic base depends on silk production, trade and commerce. Annual silk production is estimated 2 million meters per year of tussar silk. The town is district level wholesale market for agriculture produce. Barari industrial area is the largest industrial belt in the district covering 51 acres and Bahadurpur is bout 15 acres both dedicated to cottage industries. kahalgaon industrial area also being equally important. Government of India has established a handloom park and food park has been established by private entrepreneurs. The town has a strong presence of informal sectorabout 6800 units contributing to 30-40% of city economy. Bhagalpur has significant potential to develop as a 'silk city' of India. About 50% of silk produced is exported.

Bhagalpur is a major distribution centre for agricultural produces. Grains like rice (paddy), wheat, maize, pulses and oilseeds are under the main food crops and mango, banana, litchi, citrus, guava and tomato are under horticulture crops.



Open Spaces



The major cash crops are banana, potatoes and chilies. Based on location major market of the city can be classified in four zones. a) Nath Nagar Bazar b) Muzahidpur, Ali Ganj and Mirjan Hat Bazar c) Tilka Manjhi and d) Main City.

- Nath Nagar Bazar: It covers the area of west Bhagalpur, Nath Nagar and Champa Nagar.
- Muzahidpur, Ali Ganj and Mirjan Hat Bazaar: It covers the area of south Bhagalpur.
- Tilka Manjhi: It covers the area of east Bhagalpur, Tilka Manjhi and Barari
- Main City: It covers the area of Suja Ganj Bazar, Khalifa Bagh, Variety Chowk, Station Chowk, Kotwali Chowk, Mal Godam, Koyla Dipo chowk etc.

The Old Mandi at Mirzan Hat Bazar had been found in dilapidated condition. A huge campus (40-50 Acre) of this Mandi is used unofficially by beverage industry. The shops, warehouse, godown and cold storage are losing their attraction because of poor administrative support from district and state government.

The mentioned Old Mandi at Mirzan Hat Bazar requires immediate renovation. It can be also developed as logistic hub for trade as well as Silk Park to encourage trade and commerce and silk industry in the city. The relocation of commercial activities in the mentioned locations of the city is required for future growth of the city. The development of each location as Central Business District (CBD) can meet the future requirement of the city.

Informal shops are integral part of economy of the city. It contributes significantly (30-40%) to the economy of the city. The station road, stretch of NH-80 from station to Bheropatti Chowk, Ultapul to Ghantaghar Chowk, Ghurni Peerbaba Chowk to Adampur Chowk, Tilka Manjhi Chowk, Suja Ganj Bazar, Khalifa Bagh, Variety Chowk, Kotwali Chowk, Mal Godam and Koyla Dipo chowk has been identified as the major locations of informal shops. As mentioned thousands of street vendors are involved in trading of fruits, vegetables, garment, leather goods, food items, toys and grocery items in the city. Based on structure permanent and mobile both types of informal shops contribute to the economy of the city.

Transport and Connectivity

Bhagalpur is situated roughly at a distance of 220 km east of state capital Patna and 410 km North West of Kolkata. NH 80 runs through the city and connects it directly to Patna. A branch railway line connects Bhagalpur to Mandar Hills (51 kms). The city is railway connected by broad gauge loop line of Eastern Railway from Kiul to Bardwan. In terms of air connectivity, Bhagalpur has an airport with a single air strip that is not used now. Patna airport and Malda Airport (West Bengal) are 220 km and 120 km from Bhagalpur respectively.

Page 18 of 102



Open Spaces



Air Connectivity

At present there is an air strip at Bhagalpur. The Airport Authority of India (AAI) is considering to develop a civil airport at Bhagalpur.

Rail Connectivity

Bhagalpur Junction railway station is connected to most of the major cities in India by the railway network. It lies in the Sahibganj loop-line which serves Bhagalpur with numerous trains. It is the third busiest line in Bihar. About 100 pairs of Express and 44 pairs of passenger train pass through this line. Bhagalpur Junction is an A1 grade railway station.

It is the highest revenue generator in the Malda Rail Division. It is the third major railway station in Eastern Railway after Howrah and Sealdah. Bhagalpur is well connected to Delhi, Mumbai, Kolkata, Bangalore, Ajmer, Kanpur, Patna, Guwahati, Surat, Jammu, Munger, Gaya and other cities.

Road Network Connectivity, Transport and Traffic Characteristics

Bhagalpur town has 175km of roads with a density of 5.8 (ratio of total road length to city area). The main roads in the town include NH80, SH25 and SH19. The overall traffic characteristics are heterogeneous and the town has 21810 registered vehicles. The road network is largely undivided with no footpaths, high levels of encroachment, lack of road over-bridges that contribute to traffic jams. Intra city transport is mainly by way of cycles and auto rickshaws while, for inter-city transport, there are State Transport buses.




Figure 3 Map showing Road Network of Bhagalpur



Open Spaces



2. Introduction

The Smart Cities Mission is an innovative and new initiative by the Government of India to drive economic growth and improve the quality of life of people by enabling local development and harnessing technology as a means to create smart outcomes for citizens.

In the approach to the Smart Cities Mission, the objective is to promote cities that provide core infrastructure and give a decent quality of life to its citizens, a clean and sustainable environment and application of 'Smart' Solutions. The focus is on sustainable and inclusive. The Smart Cities Mission is meant to set examples that can be replicated both within and outside the Smart City, catalysing the creation of similar Smart Cities in various regions and parts of the country.

The core infrastructure elements in a Smart City would include:

- I. Adequate water supply,
- II. Assured electricity supply,
- III. Sanitation, including solid waste management
- IV. Efficient urban mobility and public transport
- V. Affordable housing, especially for the poor
- VI. Robust IT connectivity and digitalization
- VII. Good governance, especially e-Governance and citizen participation
- VIII. Sustainable environment
 - IX. Safety and security of citizens, particularly women, children and the elderly
 - X. Health and education.

One major component under Bhagalpur Smart City Project is to develop open and green spaces. Under this, two parks are proposed to be developed viz. Sandy's Compound along with Cleveland Memorial and Lajpat Complex which includes Lajpat Park, Children's Park, Kala Kendra, Town Hall and Sharda Sangeet Sadan.

SR MANAGER TECH. A
BHAGALPUR SMART CITYLID.
BHAGALPUR SMART CHYLID.

Open Spaces



3. Scope of Work

The scope of this study is preparation of Detailed Project Report for open spaces. The scope of work is to survey and analyse the existing situation and propose the development for the following two project:

- 1. Sandy's Compound: To design and develop Sandy's Compound into a multi-Utility Public place for every age group. On the basis of approved plan, consideration and the needs of society, the cost for the development of the park is to be estimated as a part of Detailed Project Report. The scope is to develop and achieve standards of core infrastructure such that a clean & sustainable environment and a decent quality of life can be provided to its citizens. The focus is on sustainable and inclusive development.
- 2. Lajpat Complex: Lajpat complex includes Lajpat Park, Children's Park, Kala Kendra, Town Hall and Sharda Sangeet Sadan. The aim is to propose a complex with multi-utility space which can be amalgamated within one space.



Open Spaces



4. Project Location

4.1 Sandy's Compound

Sandy's Compound is a 30-year-old park complex, opposite of police line Bhagalpur and is included in Smart City Project. It is bounded in the North-By Cleveland Road, South-By Central Jail Road, East-By Central Jail Road, West-By Beatson Road. The site has easy accesses through public transport modes such as city bus, auto rickshaw and private vehicles.

Sandy's compound is originally named after a Briton who was the Mayor of Bhagalpur and the District Judge during the British Era. The piece of land is approximately 123.34 Acres. Post fragmentation of this land, an area of 83 Acres persists with 34.25 Acres more or less in open space and the remaining covered under urban forest reserve. By the area cover, it has the potential of being a District Level Park and to serve a population of about 5 Lakhs.

4.2 Lajpath Complex

The Lala Lajpat Park which is a major part of proposed Lajpat Complex is one of the visited public place of Bhagalpur located at Adampur. This site is easily accessible through bus, auto-rickshaw and private vehicles.




Figure 4: Location of Lajpat Complex and Sandy's Compound

Page 22 of 102

Open Spaces



5. Existing Situation

5.1 Sandy's Compound

The total site area is 81.6 acres. It is a 30-year-old park and besides zoo which is located in Khanjarpur, opposite of police line Bhagalpur. It contains a Station Club, Doordarshan TV Centre, volleyball court, gym, forest area, pond, children play area and a small open stadium. It also provides state level matches and is one of the best fields in Bhagalpur.





Figure 5: Sandy's Compound

Figure 6: Mound Sandy's Compound





Figure 7: Entrance Gate, Sandy's Compound

Figure 8: Volleyball Court, Sandy's Compound



Open Spaces



Sandy's Compound is presently consisting of Green lawns, Children's Playground, Ponds, Toilet block, Concrete pathways, Full grown mature trees, Inbuilt benches, Cleveland Memorial, Park Fair Area, Open Amphitheatre, Cricket Stadium, Multipurpose ground, Parking area, Volleyball Court, Indoor Badminton Stadium, Yoga Center and Indoor Gym. It also contains one heritage mound from where the first PM of Independent India addressed Bhagalpur.

The existing site is mostly having large green patches where no activity is being done. Large part of the compound is covered with forest area that create a beautiful environment for morning walkers and evening gatherings. The cricket stadium, multipurpose ground and gym are placed in the south side of the park and devoid of appropriate environment. The Children Park does not have children friendly environment. There are few dilapidated cage structures which were used to keep herbivorous animals.

It has a General Ground which serves the political gathering, fun fair, shopping sales, music events, New Year events and Independence Day, Republic day function, Rawan and Kumbhkaran effigy burning during Dussehra organized. The compound is having boundary wall from all sides of which major portion is in good condition however the remaining portion needs to be repaired or reconstructed. The ht. of boundary wall also is an issue that needs to be catered.

5.2 Lajpat Complex

Lajpat complex contains Lajpat Park, Children's Park, Kala Kendra, Town Hall and Sharda Sangeet Sadan. The Lala Lajpat Park which is a major part of proposed Lajpat Complex is one of the visited public place of Bhagalpur. The total area of the complex is 10.7 acres. It is surrounded by many kinds of flowers and trees. Baby toys, play area and Open gym are also available.



Figure 9: Lajpat Park



Figure 10: Open Gym, Lajpat Park

SR. MANAGER I EUR.

BHAGALPUR SMART CITY LTD.

BHAGALPUR BHAGALPUR

Page 24 of 102

Open Spaces





Figure 11: Children's Park



Figure 12: Pavement Pathways, Children's Parl



Figure 13: Kala Kendra, Bhagalpur



Figure 14: Sculpture in Kala Kendra



Figure 15: Town Hall




Figure 16: Town Hall Building

Lajpat Children's Park is a functional playground for children. It has different types for play equipment's, seating area, pavement pathways, cafeteria, trees and water body. Kala Kendra is having old buildings for the art classes and the area is surrounded by sculptures. Town Hall is an indoor amphitheatre in which different types of cultural programs are conducted.

Open Spaces



6. Proposals of Work

Development of open spaces is proposed in two phases. The first phase will focus on the development of Sandy's Compound. The development of Lajpath Complex will be taken up in third phase. Development of Sandy's Compound includes development and retrofitting of existing Sandy's Compound. It carries a glory of Bhagalpur city, through old mature existing trees which will be retained in its own condition. Sandy's Compound has become a place for citizens of all age group to relax. Enhancing the character of the same environment, the design intervention will be giving city dwellers a planned space for the same purpose with segregation of activities.

The proposal envisages recreating the lost glory of Sandy's Compound through developing it as a smart urban landscape form. Sandy's Compound, the huge compound look like large patches of unused monotonous spaces that are lying underutilised. The concept would be converting the compound into different spaces with multiple activities linking through diverse medium of circulation thus creating hierarchy of open spaces. The existing public area, sports complex are to be rejuvenated to make them an integral part of the park, linking with other activities of the compound through design interventions. The other side of the park which is currently unused with deep water body to be converted into water sports and adventure zone.

The two parts of the site will be integrated with pathways and lake along with sports facilities. The sports complex, existing gym, will be developed in an exclusive environment conducive to their functional uses without intervening the compound's environment. There would be miniature/ sculpture garden with brief write up so that visitors could have better understanding about history of Bhagalpur. The proposal also takes into account the development of Station Club.

The vision for Sandy's Compound is to maintain its historic character and flourish it for future generations; to be an oasis of beauty, providing all visitors with positive and memorable experiences.

SR. MANAGER TECH. 2

SR. MANAGER TECH. 2

BHAGALPUR SMART CITY LTD.

BHAGALPUR

Open Spaces



6.1 Rejuvenation of Existing Large Open Space

The rejuvenation of existing large open space is proposed which will include redesign of stage, providing drain, laying of natural grass turf with temporary goal post and LED screen. The ground will act as an event ground for different cultural events and rallies. The ground is proposed to be encircled by hedges to mark distinction.

6.1.1 Redesign of Stage

A new stage is proposed in place of existing stage. The new stage will be 1500mm high with truss for providing shading sheet above it and fixing of light fixtures and sound boxes. The proposed stage is 20M wide and 12M deep. The finish of stage will be Kota Stone.



Figure 17 Truss for Stage

6.1.2 Landscaping and Drainage

Laying of natural grass turf is proposed in the open ground. The laying is proposed after proper surface levelling and dressing. Drainage channels is proposed on the periphery of the field which will channelize all the storm water to the water retention pond.

6.2 Development of Badminton Stadium

development existing The stadium Badminton Sandy's in proposed The size Compound. badminton of campus stadium is proposed to be expanded. The existing boundary wall will be broken and new wall will be made increasing the size of campus of Badminton Stadium. To link Badminton Stadium with Sandy's Compound, a new




Figure 18: Badminton Court

entrance is proposed from Sandy's Compound side, however the existing entrance which is directly accessible from Road will be closed and new Secondary Entrance will be made. As the current Badminton stadium is lacking basic facility and sitting spaces so a completely new badminton Stadium is proposed in place of existing Indoor Badminton Stadium. The new court will have additional 3 new Courts apart from current 4 courts, totalling 7 courts (as per requirement of BSCL). The entrance to play area will be smart entrance with card access.



Open Spaces



The proposal for new Indoor Stadium Includes:

New Indoor Stadium is proposed with seven Badminton courts with wooden floor. It will have seating space for spectators along with office spaces, storage rooms and toilet with change rooms. A small cafeteria and gym is also proposed inside the new Stadium.

The stadium will have Courts with markings for both singles and doubles play, although badminton rules permit a court to be marked for singles only. The doubles court is wider than the singles court, but both are of the same length. The exception, which often causes confusion to newer players, is that the doubles court has a shorter serve-length dimension.

The full width of the court is 6.1 metres (20 ft), and in singles this width is reduced to 5.18 metres (17 ft). The full length of the court is 13.4 metres (44 ft). The service courts are marked by a centre line dividing the width of the court, by a short service line at a distance of 1.98 metres (6 ft 6 inch) from the net, and by the outer side and back boundaries. In doubles, the service court is also marked by a long service line, which is 0.76 metres (2 ft 6 inch) from the back boundary.

The net is 1.55 metres (5 ft 1 inch) high at the edges and 1.524 metres (5 ft) high in the centre. The net posts are placed over the doubles sidelines, even when singles is played.

SR. MANAGER TECH. 2 SR. MANAGER TECHYLID. BHAGALPUR SMART CITYLID. BHAGALPUR



Open Spaces



6.3 Development of Sports Complex

Existing sports area will be redeveloped into a full-fledged sports complex. The sports complex will act as singular entity with sports area only accessible to players and sports authority. The sports complex will comprise of the following

6.3.1 Entrance and Parking

Separate entrances is proposed for Sports Complex. An Entrance Plaza of 18m X 20m is proposed as common entrance for bigger events which is accessible from Main ground of Sandy's. One direct entrance from NH 33 is proposed for sports persons with separate parking area. While 2 more general entrance is proposed for public and sports person for regular movement. One entrance is accessible from proposed food plaza which will have external access for common public.

6.3.2 Stadium

The current stadium is proposed to be developed into Cricket cum Football Stadium with drainage network. The size of playing area in the proposed stadium is 120m X 170m. The stadium is proposed to have pavilion with total capacity of around 2500 seating (covered and open seating tiers). Extension of sitting capacity can be done horizontally in future in the peripheral area of Stadium. It is also proposed to have Pavilion with all amenities comprising of



Figure 19: Stadium

rooms for administration, players, referee/ umpires, dormitory, broadcasting, commentary box, security, VIP Box, Cafeteria, first aid, Anti-Doping center, toilet facility etc. The pavilion is also proposed to house spaces for different sports federation (Cricket, Basketball, Volleyball, Lawn Tennis, Badminton, Swimming and others). The pavilion is also proposed to have space for administration who will maintain the overall working of Sports' Complex.




Figure 20: Cricket Pitch




Open Spaces



6.3.3 Basketball Court

One outdoor Basketball court is proposed inside Sports Complex but outside Stadium. In basketball, the basketball court is the playing surface, consisting of a rectangular floor, with baskets at each end. Outdoor surfaces are generally made from standard paving materials such as concrete or asphalt. Under International Basketball Federation (FIBA) rules, the court is 28 by 15 meters (91.9 by 49.2 ft). The baskets are always 10 feet (3.05 m) above the floor (except possibly in youth competition). Basketball courts have a three-point arc at both baskets. The FIBA three-point line is 2.95 ft (0.90 m) from the sideline in a zone starting at the baseline and ending when it crosses the 22.1 ft (6.75 m) arc. The 21.65 ft (6.60 m) distance exists only at the points on the three-point line that are directly to the left and right of the basket center.



2.90 m

Figure 21: Basket Dimension




Figure 22: Basketball Court Dimension

SR. MATAGER TECH. 2

SR. MATAG



Open Spaces



6.3.4 Volley Ball Court Renovation

Renovation of two existing Volley Ball Courts along with seating area is proposed in the proposed sports complex. A proposed volleyball court is 9 m \times 18 m (29.5 ft \times 59.1 ft), divided into equal square halves by a net with a width of one meter (39.4 in). The top of the net is 2.43 m (7 ft 11 11/16 in) above the center of the court for men's competition, and 2.24 m (7 ft 4 3/16 in) for women's competition, varied for veterans and junior




Figure 23: Volley Ball Court Dimension

competitions. The minimum height clearance for indoor volleyball courts is 7 m (23.0 ft), although a clearance of 8 m (26.2 ft) is recommended. The team courts are surrounded by an area called the free zone which is a minimum of 3 meters wide and which the players may enter and play within after the service of the ball. All lines denoting the boundaries of the team court and the attack zone are drawn or painted within the dimensions of the area and are therefore a part of the court or zone.

6.3.5 Gym Renovation

The existing Gym Building is proposed to be renovated with new flooring and false ceiling along with proposal of construction of one additional floor which includes construction of remaining portion on first floor and casting of roof slab. The proposal also includes façade uplifting of the building. It will be an Airconditioned Gym. It will act as an athletic and fitness centers for members and sports personnel of the sports Complex as well as other members. Toilet, change room, locker and



Figure 24: Indicative Gym Interior

drinking water facilities is proposed in the Gym with facilities of Locker. Gym is proposed with new gym equipment.







Table 2: List of Proposed Gym Equipment for each Floor

	Gym Equipment			
S.No	. Equipment/Machine	Nos		
	1 Commercial Motorised Trade Mill	7		
	2 Commercial Cross Trainer	7		
	Commercial Cycle	10		
4	Commercial Smith Machine	2		
	Commercial Cable Cross over	2		
(Commercial Lattice Set	2		
7	Big Gym Ball	10		
8	Medicine Ball 1 to 10 Kg	10		
ç	Bench Press-Inclined and declined - Both	2		
10	Flat Bench (Adjustable)	3		
11	Small Tools	6		
12	Orbit Elliptical Machine	6		
13	Generator Recumbent Bike	6		
14	Vibration Plate (Crazy Massager)	6		
15	Multi Gyms- Abdominal Crunch	6		
16	45 Degree Leg Press	2		
17	Leg Extension/Leg Curl	2		
18	Rowing Machine	5		
19	Foam roller	6		
20	Ab Wheel	6		
21	Dumble 5 Kg, 7.5 Kg, 10 Kg, 15 Kg, 20 Kg, 25 Kg, 30 Kg, 35Kg & 40 Kg	2 Pairs Each		
22	Butterfly	2		
23	Arm Curl	2		
24	Mirror (3mX 2m)	5		
25	Locker	50		
26	Steam Bath (Sauna Bath)	2		
27	Rubber Mat	50 sqm		

SR. MANNAGER TECH. 2

SR. MANNAGER TECH. 2

BHAGALPUR SMART CITY LTD.

BHAGALPUR

BHAGALPUR

Open Spaces



6.3.6 Lawn Tennis

Two outdoor Lawn Tennis court is proposed inside Sports Complex but outside Stadium. Although Tennis is played on a variety of surfaces however grass court is proposed for Sandy's Sports Complex. Tennis is played on a rectangular, flat surface. The court is 78 feet (23.77 m) long, and 27 feet (8.2 m) wide for singles matches and 36 ft (11 m) for doubles matches. Additional clear space around the court is required in order for players to reach overrun balls. A net is stretched across the full width of the court, parallel with the baselines, dividing it into two equal ends. It is held up by either a cord or metal cable of diameter no greater than 0.8 cm (1/3 in). The net is 3 feet 6 inches (1.07 m) high at the posts and 3 feet (0.91 m) high in the center. The net posts are 3 feet (0.91 m) outside the doubles court on each side or, for a singles net, 3 feet (0.91 m) outside the singles court on each side.




Figure 25: Lawn Tennis Size

6.3.7 Swimming Pool

An open swimming Pool of International size (25m X 50m) is proposed in Sports Complex.




Figure 26: Swimming Pool Dimension

(A)

DETAIL PROJECT REPORT

Open Spaces



The swimming pool is proposed with allied services; toilets, change rooms, store room, lockers, balancing tank, pump room and other administrative facility required for operation of the sports. World Championship pools must be 50 meters (160 ft) (long course) long and 25 meters (82 ft) wide, with ten lanes labelled zero to nine (or one to ten in some pools; zero and nine (or one and ten) are usually left empty in semi-finals and finals); the lanes must be at least 2.5 meters (8.2 ft) wide.

They will be equipped with starting blocks at both ends of the pool and most will have Automatic Officiating Equipment, including touch pads to record times and sensors to ensure the legality of relay takeovers. The pool must have a minimum depth of two meters.

6.3.8 Cafeteria and Food Plaza

One Cafeteria with open to sky food plaza is proposed inside Sports Complex. The food plaza will have access from common ground for general public. It will also have access from rear side from sports complex so that people from sports complex can have direct access to cafeteria. The food plaza is proposed to have permanent furniture made up of bricks and concrete with patio umbrellas.



Figure 27: Indicative Cafeteria with Food Plaza



Figure 28: Indicative Food Plaza

SR. MANAGER TECH. 2 SR. MANAGER TECHYLID. BHAGALPUR SMART CITYLID. BHAGALPUR

Open Spaces



6.4 Development of Theme Based Parks

Small theme based park and play areas are proposed inside Sandy's Compound to cater the need of people of different age groups. It will also encourage people participation in different interest/activity based events in the proposed park.

6.4.1 Kids Play Area

A Kids play area is proposed inside Sandy's Compound. This area will basically cater to Kids and teenagers. It will also have sand bed for kids to play with sitting stone benches where one can sit and enjoy the surroundings, toilet facility with feeding rooms for women and drinking water facility.



Figure 29: Representative Kids Play Area

The proposed park will have the following play equipment:

Table 3: Kids Play Equipment

Kids Play Equipment			
Sl.No.	Equipment	No	
1	Swings	4	
2	Slides	4	
3	Double Seesaw	4	
4	Trampoline with Safety Net	4	
5	Wave Slide	3	
6	Spiral Slide	3	
7	Outdoor Play Station	2	
8	Marry Go Round	2	
10	Circular Swing	4	

The area will be enclosed with wooden fencing of with single entrance. A Gazebo is also proposed in the play area.



Open Spaces



6.4.2 Sculpture Court cum Open Art Gallery

A small sculpture court is proposed where the history of Bhagalpur will be depicted through sculpture. It will also have other theme based sculptures like modern, historic, etc. The court will have sitting benches along the pathway for people to sit. The sculpture will be acquired by BSCL through public participation without incurring any cost.

It will also have open art gallery space where people can come and display (themed temporary art exhibitions) their creativity through models and paintings. The area will be enclosed with wooden fencing of 900mm height with single entrance.



Figure 30: Art Exhibition Area



Figure 31: Modern Sculpture
Representation

SR. MATAROLA TECH. 2

BHAGALPUR SMART CITY LTD.

BHAGALPUR SMART CITY LTD.



Open Spaces



6.4.3 Outdoor Gymnasium

An outdoor gym is proposed in a Sandy's Compound. The gym will have following

outdoor equipment:

- Air walker
- Sit up station
- Air Swing
- Stair Stepper/Twister
- Air Swing/Horse rider Station
- Pull Chair
- Leg Press/ Exercising bars
- Sit up/ Twister/ Arm wheel
- Dips/Chin Ups/ Pull Ups equipment
- Rowing Machine
- Double Cross Walker
- Elliptical Exerciser

Beside gym equipment, seating benches are proposed inside outdoor Gymnasium. A Gazebo is also proposed inside it as all-weather seating. It will also have a toilet block with drinking water facility. The area will be enclosed with wooden fencing of 900mm height with single entrance.

6.4.4 Yoga Park

Currently Sandy's compound is having one shaded Yoga Platform. There is proposal to develop 3 additional Yoga Platform in the proposed Yoga Park along with remodelling of existing one Yoga Platform. It will have a separate entry with access by alley having hedges on both side which will be further connected to Walkway to give it a quite environment. The area will be enclosed with wooden fencing of 900mm height with single entrance.

Figure 33: Representation of Yoga Platforn

6.4.5 Nursery

To promote habit of gardening in the people of Bhagalpur a nursery is proposed inside Sandy's Compound. It will act as interpretation center for peoples. The nursery will be responsible for maintaining the flower beds which is proposed inside Sandy's Compound at different locations. The nursery will also have retail arm which will sell seeds/plants to the general public, commercial gardeners, and private nurseries. It will also supply the needs of institutions or private estates.



Figure 34: Representation of Nursery





Open Spaces



6.4.6 Open Zoo

Earlier there was a zoo inside Sandy's Compound. Herbivorous animals were kept inside small cages for public display. However over the period of time it became redundant. Revival of the same an open Zoo is proposed inside Sandy's Compound where Herbivorous animals like Deer, Ducks, Peacock, rabbit and others. The zoo will be wire fenced from all side to restrict the movement of kept animals in the whole compound. The zoo should work under an expert zoologist so that animals gets proper care.



Figure 35: Representation of Open Zoo

6.5 Development of Linkage

Several linkages are proposed inside Sandy's Compound to connect the whole compound. The linkages will work as artery of the Sandy's compound. Based on usage following linkages are proposed inside the compound:

6.5.1 Vehicular cum Cycle Track:

A vehicular cum cycle track of 2.55km km is proposed inside Sandy's compound. It is mostly proposed on the periphery of the compound so it will also work as a maintenance road. The proposed finish of the track is Paver Block. The width of the proposed cycle track is 4.5m.

6.5.2 Joggers Track

For morning runners, a jogging track of 1.95 km is proposed. The jogging track will have shaded seating benches at 400 m interval. The track is proposed to be 2.4m wide having rammed Murram at top with concrete edging.

6.5.3 Walkways and Natural Trail

The cycle track and joggers track are proposed to be interconnected to each via. Walkways and Natural Trail. The walkways are proposed to be 3.6 m wide having Sandstone finish while the natural trials are proposed to be 1.2 m wide with rammed Murram finish. The overall length of Walkway and natural Trail are 3.98 km and 1.58 km respectively. The existing pathway on the periphery of main ground, currently of concrete, is proposed to be developed as Walkway. The walkway will have shaded seating benches at 400 m interval.

6.5.4 Drive Way

There is a proposal of revamping the existing drive way up to Station Club. A layer of Bitumen is proposed to be laid over existing concrete driveway with kerb stone and markings on both sides.

BHACHLOURS SIM PAGE 38 of 102

Open Spaces



6.5.5 Battery Operated Vehicle

No vehicular movement is to be allowed inside Sandy's Compound. However Sandy's Compound will have its own Battery Operated Vehicle which will cater to demand generated by Old age people, PH people, Ladies, Kids and others. It is proposed to be operated in PPP mode.



Figure 36: Representation of Battery Operated Car

6.6 Development of Water Bodies and Retention Pond

It is proposed to preserve every drop of rain water falling inside the Sandy's Compound. It will be done by developing 3 water bodies. Two existing water body will be developed as water retention pond and one additional retention pond will be developed in the N-E side of the compound.

Storm water will be channeled to a retention basin through a system of



Figure 37: Representative Plaza

storm drains/swale, and a network of drain channels and underground pipes. The basins are designed to allow relatively large flows of water to enter, but discharges to receiving waters are limited by outlet structures that function only during very large storm events. Depth of retention ponds is of critical importance, for removal of pollutants and the volume of water it needs to retain during the peak.

Retention pond will be landscaped with a variety of grasses, shrubs and/or wetland plants to provide bank stability and aesthetic benefits. Vegetation provides water quality benefits by removing soluble nutrients through uptake.

Out of three water retention pond, one pond is proposed to be developed for recreational purpose. The proposal includes development of Plaza, Cafeteria, Viewing deck, stepped Ghat, Toilet block along with boating facilities.

6.7 Rehabilitation of Station Club

Station Club is currently in dilapidated condition. However looking at its importance it is proposed to be rehabilitated. The current Doordarshan Kendra is proposed to be removed so that after rehabilitation the Station Club can maintain its character. There is proposal of removing the whole roof slab and casting it again as the condition of existing slab is dilapidated. The dance floor which is again in broken state is proposed to be removed as original. The proposal includes renovating interiors including plastering,



Open Spaces



painting, wall paneling, false ceiling, tiling, providing fixture in toilet, lighting and electrical works.

The proposal also includes development of water fountain outside the Station Club, External Lighting and Path development. The finish of proposed path is Granite Cubes.



Figure 39: Water Fountain



Figure 38: Cobble Stone



Figure 42: Existing Station Club Building



Figure 41: Roof Condition



Figure 43: Billiard Board



Figure 40: Broken Dance Floor

HAGALDUR SMAGALDUR Page 40 of 102



Open Spaces



6.8 Entrance

There are total 27 proposed Entrance inside Sandy's Compound, out of which 3 main entrances are proposed with parking facility, guard room along with small water fountain. Existing entrance are proposed to be demolished and new grand entrance will be made in place of that. Following is the list of entrance proposed inside Sandy's Compound.




Figure 44: Representative Fountain at Entrance

Table 4: Entrance

Main Entrance	
Main Entrance from NH33 side	1
Main Entrance from Tilkamajhi-Manali Road	1
Sports Entrance	1
Secondary Entrance	1
From Tilkamajhi-Manali Road (Fair Ground Side)	1
Near Kacheri Chowk (From NH33 side)	1
Internal Entrance	
Link Badminton Stadium to Sandy's Compound	1
Link Cleveland Memorial to Sandy's Compound	1
Link Stadium to Sandy's Compound	1 Primary + 3 Secondary
Separate Entrance	
Cleveland Memorial	1
Badminton Stadium Entrance	1
Other Entrance	2
Entrance to Parks and Open Gym	10
Emergency Exit	3

6.9 Renovation of open-air theatre

The existing Open Air Theatre which is in degraded condition is proposed to be developed into a fine place for hosting different activities including drama, musicals and others. The proposal includes landscaping, surface treatment and extension of facilities like drinking water and toilet.



Figure 45: Representation of OAT



Open Spaces



6.10 Rehabilitation of Cleveland Memorial

The existing Cleveland Memorial which is of historic importance is proposed to be developed as a separate space with all amenities. It will be developed as an open area with basic facilities like Toilet block and drinking water facility. The proposal includes:

- 1. Building renovation
- 2. Retrofitting of Boundary Wall
- 3. Special Lighting for Memorial (Indoor and Outdoor)
- 4. Ticket cum Guard Room
- 5. Cafeteria
- 6. Water Fountain

6.11 Development of Fair Ground/ Event Space

The existing Fair Ground will be developed as open landscape area. It will be developed as an open area with separate secondary entry so that it can cater any ongoing event. It will be developed for hosting events (fairs, exhibitions, etc).

6.12 Renovation of campus compound wall

The overall length of campus boundary wall around 3.5 Km of which external boundary wall is 2.5 Km and internal boundary wall is 1.0 Km. The proposal includes demolition of existing boundary wall and construction of high end boundary wall.



Figure 46: Boundary Wall

EHACALPUR Page 42 of 102



Open Spaces



6.13 Development of Adventure Zone

An Adventure zone is proposed to be developed under PPP. The proposed activity in the adventure zone include Wall Climbing, Rope Climbing, Zip line, Camping, Tunnel and Swings.

6.13.1 Zip Line

A zip line is made up of a pulley appended to a stainless-steel cable extended between fixed points of different elevations. Also known as 'zip wire', 'flying fox' and 'Tyrolean Crossing', it allows a person, fastened to the moving pulley, to 'zip' from the top to the bottom of a cable, propelled by gravity. For gravity alone to propel the user, the zip line must be inclined to a certain degree.

Besides their obvious functional value, zip lines have become a popular outdoors activity, located in adventure camps and resorts. In a professionally run recreational set-up, the user is attached to the cable by a harness, which is attached to a trolley.

The height of cables varies from 30ft (9m) to as high as 200ft (61m), and can cover distances of over 1500ft (457m). The average speed on a zip line is around 50 km/h and 60 km/h.

6.13.2 Rappelling

Rappelling also known as Abseiling, 'to recall' or 'to pull through', is a controlled descent off a vertical drop, such as a rock face, using a rope.

This technique is used by climbers, mountaineers, cavers, canyoners, search and rescue and rope access technicians to descend cliffs or slopes when they are too steep.

To descend safely, abseilers use a variety of techniques to increase the friction on the rope to the point where it can be controlled comfortably. These techniques range from wrapping the rope around their body (e.g. The Dülfersitz) to using a custom built device like a rack. Practitioners choose a technique based on speed, safety, weight and other circumstantial concerns.



Figure 47: Zip Line



Figure 48: Rappelling



Open Spaces



6.13.3 Wall Climbing

A climbing wall is an artificially constructed wall with grips for hands and feet, usually used for indoor climbing, but sometimes located outdoors. Some are brick or wooden constructions, but on most modern walls, the material most often used is a thick multiplex board with holes drilled into it. Recently, manufactured steel and aluminium have also been used. The wall may have places to attach belay ropes, but may also be used to practise lead climbing or bouldering.



Figure 49: Wall Climbing

Each hole contains a specially formed t-nut to allow modular climbing holds to be screwed onto the wall. With manufactured steel or aluminium walls, an engineered industrial fastener is used to secure climbing holds. The face of the multiplex board climbing surface is covered with textured products including concrete and paint or polyurethane loaded with sand. In addition to the textured surface and hand holds, the wall may contain surface structures such as indentions (incuts) and protrusions (bulges), or take the form of an overhang, underhang or crack.

Some grips are formed to mimic the conditions of outdoor rock, including some that are oversized and can have other grips bolted onto them.

6.13.4 Rope climbing

Rope climbing is a sport in which competitors attempt to climb up a suspended vertical rope using only their hands. Rope climbing is practiced regularly in different Games, and is enjoying a resurgence in most countries.

Figure 50: Rope Climbing

6.13.5 Paintball

Paintball is a competitive team shooting sport in which players eliminate

opponents from play by hitting them with spherical dye-filled gelatine capsules ("paintballs") that break upon impact. Paintballs are usually shot using a low-energy air weapon called a paintball marker that is powered by compressed air (nitrogen) or carbon dioxide.

SHAGALPUR SHARTCHVLTO.

BHAGALPUR SHARTCHVLTO.

BHAGALPUR SHARTCHVLTO.



Open Spaces



The game was initially developed in May 1981 for recreation, but now is frequently played at a formal sporting level with organized competition that involves major tournaments, professional teams, and players. Paintball technology is also used by military forces, law enforcement, paramilitary and security organizations to supplement military or other training. Paintball markers can play a role in riot response and nonlethal suppression of dangerous suspects.



Figure 51: Paintball

Games can be played on indoor or outdoor fields of varying sizes. A game field is scattered with natural or artificial terrain, which players use for tactical cover. Game types and goals vary, but may include capture the flag, elimination, defending or attacking a particular point or area, or capturing objects of interest hidden in the playing area. Depending on the variant played, games can last from minutes to hours, or even days in "scenario play".

6.13.6 Zorbing

Zorbing (globe-riding, sphereing, orbing) is the recreation or sport of rolling downhill inside an orb, generally made of transparent plastic. Zorbing is generally performed on a gentle slope, but can also be done on a level surface, permitting more rider control. In the absence of hills some operators have constructed inflatable, wooden, or metal ramps. Due to the buoyant nature of the orbs, Zorbing can also be carried out on water, provided the orb is inflated properly and sealed once the rider is inside. "Water walking" using such orbs has become popular in theme parks across the UK. There are two types of orbs,



Figure 52: Zorbing

harnessed and non-harnessed. Non-harness orbs carry up to three riders, while the harness orbs are constructed for one to two riders. Double-harness spheres have different slope requirements, and must only be operated in specific locations. The longer runs are approximately half a mile.



Open Spaces



6.13.7 Archery

Archery is the art, sport, practice, or skill of using a bow to shoot arrows. Historically, archery has been used for hunting and combat. In modern times, it is mainly a competitive sport and recreational activity. A person who participates in archery is typically called an archer or a bowman, and a person who is fond of or an expert at archery is sometimes called a toxophilite.

a competitive sport A person who ypically called an person who is fond sometimes called a

Figure 53: Archery

6.13.8 Mechanical Bull Ride

A mechanical bull, also known as a bucking machine, is a device that replicates the sensation of riding a bucking animal, such as a rodeo bull or horse invented and popularized by Sherwood Cryer. It is usually powered by a variable-speed electric motor. Padded flooring is often installed around the equipment in order to reduce the likelihood of injury to those thrown off it.

A "quick stop" motor allows the operator to safely control the ride and ensure safety for the



Figure 54: Mech. Bull ride

rider; this feature allows the operator to stop the ride prior to a rider being thrown. The trained operator at the variable speed control box regulates the unit's Buck-and-Spin speed, as well as spin direction. The equipment has the capability of starting rides very slowly and speeds can be advanced according to a rider's ability.

6.13.9 Human Foosball

It's the same thing as regular foosball, but life-sized! Human foosball is played with a large group, so make sure you bring enough friends or family to get the full experience. The field is about 32 feet long and 16 feet wide, with rods stretching across the field. The players (us humans) hold on to the rods in set positions. The customization of how many people can play varies, especially if you're building your own, but it generally follows the table game pretty closely. For a fun game you probably need at least 10 people, and at maximum, around 14.

Human chess is a form of chess in which people take the place of pieces. Human chess is typically played outdoors, either on a large chessboard or on the ground.

Page 46 of 102



Open Spaces










Figure 56: Human Chess

6.14 Camping Area

A camping area is also proposed inside Sandy's Compound for schools and other institutions. It will be a souce revenue generation also. Camping is an outdoor activity involving overnight stays away from home in a shelter, such as a tent or a recreational vehicle. Typically participants leave developed areas to spend time outdoors in more natural ones in pursuit of activities providing them enjoyment.



Figure 57: Representation of Camping Area

To be regarded as "camping" a minimum of one night is spent outdoors, distinguishing it from day-tripping, picnicking, and other similarly short-term recreational activities. Camping can be enjoyed through all four seasons.

6.15 Drainage

It is proposed to preserve every drop of rain water falling inside the Sandy's Compound. Storm water will be channelled to a retention basin proposed inside Sandy's Compound

at different places through a system of open storm drains/swale, and a network of drain channels and underground pipes (in case of stadium and multipurpose ground).

A swale is a shady spot, or a sunken. In particular, it is a shallow channel with gently sloping sides. Such a swale may be either natural or man-made.

Artificial swales are often infiltration basins, designed to manage water runoff, filter pollutants, and increase rainwater infiltration.

Figure 58: Swale Landform

Swales as used in permaculture are designed to slow

and capture runoff by spreading it horizontally across the landscape (along



(A)

DETAIL PROJECT REPORT

Open Spaces



an elevation contour line), facilitating runoff infiltration into the soil. This type of swale is created by digging a ditch on contour and piling the dirt on the downhill side of the ditch to create a berm.

6.16 Compost and Gray water Treatment

Two vermicomposts are proposed inside Sandy's Compound to treat organic waste which will be generated by large number of trees, shurbs, grasses and food waste. It will also be used for the treatment of Sewage generating from toilets.

Vermicomposting can also be applied for treatment of sewage. A variation of the process is vermifiltration (or vermidigestion) which is used to remove organic matter, pathogens and oxygen demand from wastewater or directly from blackwater of flush toilets.

W CHASALPIR SMART CITY LTD.

Open Spaces



6.17 CCTV Surveillance

The whole compound is proposed to have an added security of CCTV. The CCTV are proposed to be put up under MSI-ICCC project. However there will be one security video surveillance room inside the compound, which will be further connected to the Command Control Center, to monitor Sandy's Compound continuously.

6.18 Audio System

The compound is proposed to have an Audio system which can come under MSI-ICCC. Audio Bollards are proposed for the same. It can be used as an announcement system, or can be utilised to create theme by playing theme based songs. A big speaker system is also proposed for the whole compound.

6.19 Solar Roof

Solar Panels are proposed to be installed on the roof of the proposed building inside campus. However the provision of the same is to be given under Solar roof top proposal under BREDA. They will be analysing the electrical requirement of the building as well as areas where solar panels can be installed along with its support system and will give proposal based on that. The roof top solar system can be off-grid or on-grid system based on the proposal by BREDA.

6.20 Shared Bicycle System

Cycle track is proposed inside Sandy's Compound. To make it work shared bicycle system is proposed inside Sandy's Compound. 3 parking spots are proposed for bicycle stand at near general parking area at two different main entrance and one secondary entrance. An app or RFID card based bicycle sharing system is proposed. It is proposed to be developed into PPP mode.



Figure 59: App based bicycle sharing Systen

6.21 Kiosks

11 nos. of kiosks are proposed inside Sandy's Compound at 2 different location. These kiosks will be utilised as food and art and craft selling center.

6.22 Landscape Feature and Furniture

Although the whole compound is proposed to be landscaped. However certain landscape elements are proposed in Sandy's Compound like Gazebo, Mounds, Trellis Walkway, Walk and bridges. The furniture includes Sitting Benches and Dustbins. The compound is also equipped with Toilets along with Drinking water facility.





Figure 60: Mounds



Figure 62: Bridge



Figure 61: Metallic Dustbin



Figure 63: Gazeebo



Figure 64: Trellis Walkway

Page 50 of 102

Open Spaces



7. Scope of work & Specifications

7.1 Scope of Work

Scope of work includes applying the design principles, Objective and expected outcomes illustrated in drawings. The Implementing Agency shall review the design and details for betterments or improvements if any which may be incorporated to better achieve the Employer's goals and objectives. These betterments, if any, shall be submitted by the Implementing Agency to the Employer for review and for the approval before the commencement of on ground working stage.

The scope of work which shall be adhered during construction activities would include:

- The cleaning, drenching and revival of the compound, water body and surrounding.
- Civil Construction of buildings, kiosks, entrance plaza, Open Air Theater, Ghats, walkways, viewing deck, drainage and toilets.
- Installation and commissioning of light fixtures, transformers and support systems.
- Landscaping and beautification work on site.
- Installation and commissioning of aeration fountain and small fountains at entrance plaza.
- The Implementing Agency would submit a complete timeline for scope of work to be carried out.
- The Employer will supervise and monitor the progress and Implementing Agency shall provide necessary coordination.
- The details of the man power deployment for the project are to be monitored on regular basis.
- Implementing agency should ensure that there is least disturbance to the existing ecology of compound and also ensure safety of the workers while working.
- The Implementing Agency shall also prepare GFC for the project works in accordance with the design developed in DPR.

Scope of Civil, Electrical, Landscape Works and various Construction Works:

a. LANDSCAPE WORK INCLUDING IRRIGATION AND PLUMBING: Design, construct & develop Landscape for Sandy's Compound comprising execution of Architectural, Landscape work (including Softscape / Horticulture and Hardscape) complete in all respect.

The softscape works consist of works such as restoring top soil, excavation, site cleaning, Grading & drainages, mound & slope preparation, designing and



Open Spaces



planting shrub, trees & ground covers, designing and planting of lawn, Garden furniture's, dustbins, etc. as per the approved drawings by Employer.

The hardscape works consist of Site leveling of entire pathway, demolition of Peripheral railing around the pond, construction of new wall with light post all around pond, Construction of new boundary wall with light posts, Realignment of pond retaining wall, Entry gates, creating space for toilets, kiosks, new construction of steps in pond, Hardscape, pathways and sit-out spaces, dustbin, Parking areas, Painting of all the structures works etc. as per the approved drawings by Employer. Item complete in all respect to the satisfaction of engineer in charge. The work also includes plumbing and irrigation for the garden, toilets etc. as per the drawings approved by the Engineer-in-charge.

- b. CIVIL WORKS: Design, Detailed Engineering & Preparation of construction drawing for civil construction items in Sandy's Compound comprising of Architectural, Civil & Structural work complete in all respect. The civil works consist of works such as excavation, site cleaning, Plain Cement and Reinforced cement concrete works, Reinforcement steel works, centering and finishing works etc. as per the approved drawings by the Engineer-in-charge.
- c. ELECTRICAL WORKS: Design, detailed engineering, preparation of construction drawing, manufacture, acceptance testing at manufacturer's works or at any accredited agency, supply, packing, forwarding and delivery from manufacturer's works/ place of storage to erection site including transit insurance, unloading, storage at site, assembly, erection, testing, installation, commissioning & performance demonstration and handing over of electrical works as per the direction of the engineer, new wiring and illumination of entire area (Landscape Lighting) related to the landscape development within the project area as of original ratings & specifications.
- d. O&M: Comprehensive Operation and Maintenance of the above work including repair works, provision of manpower & original spares, replacement with original or better component in case one turns faulty/ damaged/ defective during the course of entire contract period in order to maintain the upkeep intact.

The Implementing Agency must be aware of general and specific site conditions, AHAGALRIK SHART CITYLID.

BHAGALRIK SHART CITYLID.

BHAGALRIK SHART LIVE Page 52 of 102 topography and any existing landscape prior to commencement of any landscape works on site.



Open Spaces



7.2 Construction Scope

The on-site execution scope of work comprises of full, final and entire installation and completion of landscape and civil works to a 'best practise standard' for such works, (inclusive of buildings, hardscape, soft-scape, site furniture, exterior signage and lighting) and associated landscape services (levelling, drainage etc.) based on the design developed by the Employer and Implementing Agency's good for construction drawings and handing over of the same in full accordance with the Employer's requirements.

Key tasks include

- The Implementing Agency should submit a complete implementation timeline along with working drawings for aspects covered in DPR.
- The Employer and/or Employer's representative will supervise and monitor the progress of the implementation of the work and solution.
- All materials/samples to be submitted to the Employer for comments and approval prior to commencement of works;
- The Implementing Agency shall prepare As-Built drawings and certify on these drawings that the drawings reflect the actual works installed.

The Implementing Agency shall ensure that this submission of As-Built drawings will not delay subsequent inspections and tests by the relevant authorities; otherwise he shall be fully responsible for any consequence due to his delay.

7.3 General Specifications

The Bihar Building construction Department (BCD) specifications must be adhered to as laid down in the schedule of rates.

Proper care must be adopted while execution to adhere to the specifications and details to preserve the ecological and historical values of the compound. Following design standards and codes shall be adhered for development of compound.

DESIGN STANDARDS & CODES

- (i) National Building Code 2016
- (ii) CPWD Specifications 2009 vol. I & II.
- (iii) Relevant IS Codes
- (iv) SP 35 Plumbing Standard
- (v) WHO standard for water quality
- (vi) TERI GRIHA



Open Spaces



APPLICABLE CODES AND STANDARDS

- IS 383 Coarse and fine aggregates from natural sources for concrete
- IS 456 Code of practice for plain and reinforced concrete
- IS 516 Methods of testing for strength of concrete
- IS 1199 Methods of sampling and analysis of concrete
- IS 1838 Performed fillers for expansion joints in concrete non-extruding and resilient type
- IS 1946 Code of practice for use of fixing devices in walls, ceiling and floors of solid Construction
- IS 2389 Methods of testing of aggregate for concrete's
- IS 2505 Concrete vibrators, immersion type
- IS 2645 Integral cement water proofing compounds
- IS 3414 Code of practice for design and installation of joints in buildings
- IS 3558 Code of practice for use for immersion vibrators for consolidating concrete
- IS 4082 Recommendation on stacking and storage of construction materials at
- IS 7861 Code of practice for extreme weather concretizing
- IS 7861 Recommended practice for hot weather (part I) concretizing
- IS 8112 Ordinary Portland Cement grade 43
- IS 12269 Ordinary Portland Cement grade 53

7.4 Civil Works specifications

The materials have been selected strategically with considerations of climate, design requirement and aesthetical value of Bhagalpur and surrounding region. The following table will explain the different types of materials used in the proposal. The specifications and approved make shall be as per latest Bihar SOR.

The list of approved makes/agency of materials will be as per latest Bihar SOR.

The general specification for building work will be as follows:

Table 7.4.1: Specifications for building works

Item No.	Description	Specification	
1.0	Foundation	(i) RCC foundation	
2.0	Super Structure		
2.1	Structure	RCC framed construction with beams & slabs with external walls in brick masonry.	
2.2	Internal Partition	The internal partitions will be in half brick masonry. The internal partitions in toilets and storage areas will be of light weight wooden panels.	
3.0	Doors & Windows	- J	
3.1	Frames	The opening will be provided with sub-base of granite stone to form a box and to support the frames.	

Page 54 of 102





Item No.	Description	Specification	
3.1.1	Doors	(i) Door frames of UPVC or polyester powder coated	
		aluminium or 2 nd Class Teakwood	
3.1.2	Windows	Polyester powder coated aluminium frames or UPVC or	
e de la companya de l		2 nd Class Teakwood	
3.1.3	Toilet & Wet Areas	Polyester powder coated aluminium frames or UPVC	
	(Doors)		
3.2	Shutters	to 51 1 1 1 1 25 11 1 1 1 1 1 1 1 1 1 1 1	
3.2.1	Doors/Cupboards	 (i). Flush door shutters 35mm thick with decorative teak ply veneering on both faces with French spirit polishing on both faces in meditation hall. (ii).Flush door shutters 35mm thick with commercial ply veneering with decorative lamination on both sides in library block and cupboards. 	
3.2.2	Toilet & Wet Areas	Shutters of compact laminated 12mm thick.	
3.3	Window Shutters	 (i) Factory made / Polyester powder coated 'Z' section aluminium shutters for windows. (ii).Double glazed hermetically sealed as per green norms for windows where there is Air Conditioning facility. 	
3.4	Fittings	Stainless steel or equivalent	
3.5	Fire check door	As per fire safety specification with GI sheet frame & shutter.	
4.0	Flooring		
4.1	General areas	Pre polished granite flooring/Italian marble stone flooring in pattern or Kota stone	
4.2	Special areas	Granite Flooring/Vitrified Tiles	
5.0	Ramps	Precast terrazzo tiles.	
6.0	Railing	Stainless steel railings with ramps.	
7.0 'ç	Toilets	Rectified glazed ceramic non-skid floor tiles, ceramic glazed tiles in dado, granite counters, stainless steel sink, Mirrors with moulded PVC frame.	
8.0	Roofing		
8.1	Roof Treatment	 (i).APP membrane sheet of STP on RCC surface and integral cement based water proofing treatment (with coba). (ii). Heat resistance tiles with SRI (Solar Refractive Index) > 78 &Solar reflection> 0.70 as per CPWD specification to meet green building norms over roof of building. 	
9.0	Finishing		
9.1	External	Texture paints, ACP cladding conforming to Energy Conservation Building code.	
9.2	Internal	Oil bound distemper/Acrylic emulsion paint/Textured paint (low VOC)	





ltem No.	Description	Specification	
9.3	Polishing	French spirit Polishing on wood works.	
10.0		Ramps & Toilets for physically challenged chequered	
	free	terrazzo tiles in ramp.	

Table 7.4.2: Details of materials and specifications for outdoor works

1.		Specifications	
• •	Entrance plaza		
	Brickwork structure	Class 1 Brick as /availability	
	Paving:		
	Red sandstone	36 mm thick rough cut as per desired size	
	Dholpur pink sandstone	36 mm thick rough cut as per desired size	
	Brick pavers	As per Design	
	PCC Kerbstone	As per Design	
	Parking tiles	Grass Pavers / As per Design	
	Cladding:		
	Red sandstone	20 mm thick as /design	
	Pink sandstone	20 mm thick as/design	
	Beige granite	12 mm thick	
	Cladding tile	As/ market	
	Coping:		
	Granite	20 mm thick	
	Sandstone	50 mm thick	
	PCC	75mm thick as/availability	
	Food court, craft plaza and We	alkway	
	Walkway1: Vehicular cum		
	Cycle Track (4.5m wide)		
	Paving:	36 mm thick rough cut as per desired size	
	Concrete Paver Block/ Red	36 mm thick rough cut as per desired size	
	sandstone	As per availability of market	
	Dholpur pink sandstone	As now Desires	
	Kerb Stone at edges	As per Design	
	Walkway2:		
	Joggers Track (2.4m wide)		
	Rammed Murram Finish		
1	Kerb Stone at edges		
	Walkway3:	As per Design	
	Walkways (3.6 m wide)	,	
	Sandstone finish		
	Kerb Stone at edges		
	Walkway 4: Natural Trail	The state of the s	
	(1.2 m wide)	As per Design	
		10x - 633	
		Page 56 of 102	





S. No.	Materials	Specifications
	Rammed Murram Finish	
	Kerb Stone at edges	
	Seats and planter walls:	
	Cast in situ seats:	
	Structure of brickwork	1st class brickwork
	Natural stone boulders	
	Coping:	
	Granite	20 mm thick
	Sandstone	50 mm thick
	Brick pavers	75mm thick as/availability
	Cladding:	
	Red sandstone	20 mm thick as /design
	Dholpur Pink sandstone	20 mm thick as/design
	Texture paint	12 mm thick
	Cladding tile	As/ market
	Shelter and food and craft	
	kiosks:	
	Structure with brick and	The structure will be brick and concrete frame structure
	concrete	as/structural design.
	Flooring	The flooring will be available tiles in the market as per
	Flooring tiles	detail
	Coping:	and the control of th
	Granite	12 mm thick Granite coping in counters and wall.
	Sandstone	20 mm thick Sandstone cladding as per design.
	Cladding:	20 mm thick as specific places and bands along with
	Red sandstone	other stones and texture paints colour as per design.
	Dholpur Pink sandstone	
	Texture paint	
3.	Ghat Area	
	The ghat area has steps of	The finish of the steps will be with 20 mm thick red
	1000 mm wide with 300 mm	sandstone blocks with 10 mm thick groves
	high at places.	The second secon
	Surface finish:	The finish of the steps will be with 20 mm thick rough
	Red Sandstone	sandstone blocks with 10 mm thick groves cut as/design
	Cladding:	
	Dholpur pink sandstone:	
	Seats and planter walls:	
	Cast in situ seats:	
	Structure of brickwork	Desired planter wall with height of 600 and 450 at
	Coping:	Raised planter wall with height of 600 and 450 at
	Sandstone	places. Structure will be of brick and coping with 30-50 mm
	Brick pavers	
	Cladding:	sandstone block or brick pavers.
	Red sandstone	



Open Spaces



S. No.	Materials	Specifications
	Dholpur Pink sandstone	The cladding will be of 20 mm thick sandstone with
	Texture paint	texture paint partly.
	rexiste paint	textore paint partly.
4.	Other linear seating areas	
	Seats and planter walls:	Raised planter wall with height of 600 and 450 at
	Cast in situ seats:	places.
	Structure of brickwork	Structure will be of brick and coping with 30-50 mm
	Coping:	sandstone block or brick pavers.
	Sandstone	
	Brick pavers	I a
	Cladding:	
	Red sandstone	
	Dholpur Pink sandstone	
	Texture paint	
5.	Open air theatre area	
	Amphitheatre steps	
	Coping with Thick brick	
	pavers.	
	<u>Cladding</u> with sandstone	
	Stage:	
	Finished with sandstone and	
	sandstone cladding with edges	Portals cast in Concrete finished with Sandstone and
	of brick pavers.	wood cladding
	Amphitheatre Frames	
	Concrete	
	Sandstone	¥
	Outdoor wood	
	O.A.T. Backdrop wall	Stage Background wall with RCC wall finished with
	RCC	stone rubble work in one side and mural mosaic on lake
	Sandstone	side
	Mosaic tiles	
6.	Other walkways	
	Sandstone	Finished in 20 mm thick sandstone partly with bands of
	Granite	brick pavers as per design
	Brick pavers	
7.	Railings and Gates	
	Iron	Hot dip galvanized iron gates and Mild steel railings
	Mild steel	along the walkway on lake side
	Stainless steel	SS 316 Grade
3.	Boundary walls Partly brick and concrete structure with plaster finish	
		texture paint finish.
·.	Fountains inside water body	Aeration fountain inside water body

O CHACALOUR SHAPFORTY






Figure 65: Typical construction specifications




Figure 66: Paving area details



Open Spaces



7.5 Details of Electrical items with specifications

The scheme covers the complete Electrification of the proposed development. All Electrical work shall be done as per code of practice for Electrical installations and meeting the requirements of Indian Electricity Rules/Act, applicable I.S. Codes/Rules and relevant I.S. Specifications as below.

- a) Indian Electricity act
- b) Indian Electricity Rules
- c) IS:732 Code of practice for Electrical Wiring Installations
- d) IS:4648 Guide for Electrical Layout in residential building
- e) CPWD Specifications for Internal Electrical Installation Works
- f) Special requirements of Bihar State Electricity board.

Outdoor Lighting:

From parks and plazas to walkways and waterfronts, open spaces are essential to city life, and the right lighting can turn them into unique visual experiences. A good Lighting scheme can clarify the layout of outdoor spaces by emphasizing walkways, focal points, gathering places and open spaces. Ample lighting also boosts safety.

The Lighting design intents to perception of safety as important criteria for park's actual safety ratings. Lighting has been used to enhance the perceptions of safety and increase park as a waterfront usage. Lighting as a strategy to ensure children and families are safe from violence in the park and waterfront.

Modern lighting technology and fixtures will be used by maximizing park resources and making it easier to adopt energy-efficient, cost-saving strategies.

Outdoor solar lights use solar cells to light areas such pathways, and they are both easy to install and almost maintenance free. Wall mounted lamps, free standing lamp posts, and security lights can be used as outdoor solar lighting. Use of LED lights and energy star rated lighting fixtures are to be used for saving energy in these criteria. Necessary indoor and outdoor lighting arrangements should be covered as per the prevailing rules within the project area.

Electric supply for the compound shall be received from Bihar on 11 KV from the nearest Grid Sub-Station through overhead line / Underground Cable upto the 11 KV HT meter room from the existing substation as decided by BSEB. 2 MLDB Substation are proposed to be installed. All Lighting, Switches, Cabling, Installation are kept under scope of Electrical Works.



Open Spaces



The types of lights proposed in the project are as below:

Table 7.5.1: Types of lights used in project

S. No.	Туре	specifications	Areas
1	L1-Post Top lights	LED light obove MS post	Along the boundary wall
2	L2-Solar Pole lights	3m high on pole with inbuilt	Along walkways
		solar panel above Led light with	1000
		star rated. Lux lavel-100	*
3	L3-Bollards	LED Bollard-20 Lux	Along Pathways and
			Plazas
4	L4-Tree Uplighters	LED lights to uplight tree	Under trees and shrubs
			Pergolas
5	L5-Step lights	LED recessed lights , LED strips	Amphitheatre steps,
		w	Ghats planter and steps,
			Seat walls
6	L6- Façade Lighting	Decorative pole, Projector light	Buildings- Station Club,
19415		& linear wall washer from	Cleveland Memorial
	-	architectural LED fixture range.	
7	L7-Stadium Lights	High Mast Lights	Stadium and open Spaces
8	L8- Indoor Lights	LED lights based, focus lights	Buildings inside the
		based on type of Space	campus





Open Spaces

professional and makes			BHAGALPUR
LOCATION	TECHNICAL SPECIFICATION	PRODUCT	PHOTOGRAPH
	到2000年的1000年 6 00%	STADIUM	
Cricket Pavilion (North South)	Width = 20 M Open Gallery .	50 nos. 4 W LED step light and 20 nos. 18 W FTL (IP 65) for building	E 3 3 3 3 3 3 3 3 3 3
Twin Volleyball court	Two nos. 9 M X 18 M court 3 mtrs apart	14 M Pole with 16 nos. 1000 W LED Flood (4 nos. light per pole)	
Open Spectator stand for volley ball		20 nos. 4 w LED step light . Security light - under general area lighting	
Old Gym area	30M X 9M . Illumination level Avg 250 lux for Task lighting .	36 nos. LED indoor decorative lighting 50 nos.	
Twin Tennis court	11 M X24 M court 5 mtrs apart . Illumination level - Avg 450 lux with uniformity Min/max = 0.4 and Min/Avg = 0.6	14 M Pole with 16 nos. 1000 W LED Flood (4 nos. light per pole)	
basketball Court	15.2 M X 28.7 M . Illumination level - Avg 350 lux with uniformity Min/max = 0.4 and Min/Avg = 0.6	14 M Pole with 12 nos. 1000 W LED Flood (3 nos. light per pole)	
Swimming pool	26 M X 52 M swimming pool with translucent cover & trust . Illumination level - Avg 350 lux with uniformity Min/max = 0.4 and Min/Avg = 0.6	32 nos. 350 W LED Flood on trust	
Changing room	37 M X 5 M Illumination level Avg 150 lux for Task lighting .	30 nos. 36 W LED indoor TL lighting / LED outdoor TL for entrance	
1	Min/max = 0.4 and	24 nos. 350 W LED Flood at 12 M High trust above court for each court - 168 nos.	. 9
	Min/Avg = 0.6		Chi.

Page 62 of 102





and the second			
Stadium Cafeteria Cleveland	Bollards for open area & Tube light for covered area	Decorative 9 W LED bollard (TETRIS - BGBOS 605 9W LED) = 10 nos. 18 W LED Tube light (IP 65) - 6 nos. Decorative post top	
memorial & stadium	3.5 M	lantern ARIAN - BCGT W4 LED WW , 45 W LED post top on 5 mtrs black pole 10 Mtrs apart in one side configuration = 40 nos.	
其中国是大学的发展。	经工程等人的 特别的自	Event/FAIR GROUND	
	(105 X 50)50 lux average considering safety and security	4 nos. 16 M Umbrala High mast with 8 nos. 350 W LED flood for adjasant area lighting	· · · · · · · · · · · · · · · · · · ·
WITH THE REAL PROPERTY.	表现实现的企业外 的企	OPEN AMPHI THEATER	
Stage		2 nos. Pole with 4 nos. 350 W LED Flood for stage lighting	
Stair & Spectator area	8 nos. stair / Top stair = 70 M ark	32 nos. 4 W step light for stair & 12 nos. 27 W Post top lantern -7 mtrs apart	
建设建筑设置设置		CLEAVELAND MEMORIAL	
Tree & Plant area		9 W Focus spike light = 16 nos. / 9W LED ground embeded light BLWUP 9W LED WW for plant = 10 for plant lighting	THE STATE OF THE S
Pathway & Memorial boundary	L = 100 M X W = 3.5 M	Decorative 9 W LED bollard (FLUTE BGBOL 605 9W LED) 10 Mtrs apart in staggered configuration = 20 nos.	
Cafeteria		18 W LED Tube light for indoor and outdoor application with cover to IP 65 protection - 6 nos.	
memorial façade		LED flood for volume light / Strip light for building edge / projection light for pillar & other area for heightling . All lights are	w.



Open Spaces



		programmable type RGB dynamic for for architechral lighting application .	
the Michael St.		NEHRU MEMORIAL	
Steps	Septs with Max radius 21 M	9 W LED Focus spike light = 20 nos. for plant / 9W LED ground embeded light BLWUP 9W LED WW for plant = 20 for tree	
Stair	12 nos. stair	4 W step light = 24 nos.	
Memorial block	L = 80 M dia	15 W LED projection light for columns = 16 nos. /Strip light for menorial structure edge = 20 mtrs / 48 W LED Flood for volume light - 1 no. All lights are RGB dynamic for architechral lighting application .	
Walk way 3.5M	L = 700 mtrs / 3.5 M wide road	Decorative post top lantern ARIAN - BCGT W4 LED WW , 45 W LED post top on 3 mtrs black pole 15 Mtrs apart in one side configuration = 50 nos.	
Open Cafeteria	Bollards for open area & Tube light for covered area	Decorative 9 W LED bollard (TETRIS - BGBOS 605 9W LED) = 10 nos. 18 W LED Tube light (IP 65) - 6 nos.	
Pathway	2.5 M road around memorial (280 M) & connection (220 M)	Decorative post top lantern 25 W LED fittings 10 Mtrs apart in one side configuration = 50 nos.	2000
	N	MUITI PURPOSE GROUND	
National Falg Vlast		100 ft Flag mast with narrow beam archi range of Natural white LED flood	
Pathway Paround ground	1.2 km long 3.5 mtrs wide pathway	5 M PU painted GI Octagonal pole with 45	The Charles
		A CONTRACTOR OF THE PARTY OF TH	11/200

ON SHAPER SHAPE SHAPE BORGE 64 of 102





		77 VI	
	. Illumination level Avg 10 lux, min/avg = 0.3	W LED Street light in 15 M distance = 80 nos	
Station club inside area	L = 32 M, W = 32 M Illumination level Avg 150 lux for Task lighting.	Decorative indoor lighting of different wattage	
Pathway around building	L = 150 M , W = 3.5 M	Decorative 3.4 Mtrs post top lantern IMAGICA ASYM with 40 W LED fittings 20 Mtrs apart in one side configuration = 6 nos.	
Main entrance walk way	L = 180 M and W = 5 M	Decorative post top lantern 25 or 40 W LED fittings 30 Mtrs apart in staggered configuration = 14 nos.	
Building Façade		15 W RGB LED projection light for pillar - 12 nos. and 48 W RGB LED Volume light for varanda - 2 nos Light are for architechral lighting application	
Stage		2 nos. Pole with 4 nos. 350 W LED Flood for stage lighting	
Stair		12 nos. 4 W step light for stair	
		RETENTION POND	
Near OAT Near Zoo	120 mtrs long 140 M X 75 M (420 Mtrs)	Decorative post top lantern ARIAN - BCGT W4 LED WW , 45 W	
Near Indoor stadium	56 M X 54 M (220 Mtrs)	LED post top on 5 mtrs black pole 15 Mtrs apart in one side configuration = 25 nos.	
		PARKING LOT	
Beside main entrance Near stadium Multipurpose ground		5 nos. 16 M Umbrala High mast with 8 nos. 350 W LED flood for adjasant area lighting	
Secondary entrance			



Open Spaces



		TOILET BLOCK	
stadium		10 nos. 18 LED TL	
		indoor and outdoor	
		application	W.
Retention pond		10 nos. 18 LED TL	
		indoor and outdoor	
		application	
Multipurpose		10 nos. 18 LED TL	
ground		indoor and outdoor	
		application	-
Kid's playing area		10 nos. 18 LED TL	
		indoor and outdoor	
7		application	
Zoo cage		12 nos. 18 LED TL	
	<i>2</i>	indoor and outdoor	
		application	
		ENTRANCE	
Main entrance		Façade lighting for	(2)
		entrance gate	
Secondary		Façade lighting for	
entry		entrance gate	
Parking lot		Façade lighting for	
entry		entrance gate	
		ROAD SURFACE	
Jogger's track	L = 2 km , 2.5 M	Will be closed at night	
2.5 M	wide track		
Cycle track 5 M	L = 2.5 km 5 M	Will be closed at night	Lighting for Security Purpose.
	wide road		Decorative 3.4 Mtrs post top
Running track	L = 1.5 km / 2.5M	Will be closed at night	lantern IMAGICA ASYM with 40 W
2.5 M	wide road	Nell I I I I I I	-
Pathway 3.5M	L=3 km / 3.5 M	Will be closed at night	
7-1-1	wide road	CITIC (10 de 11)	
Sculpture	Projector lighting	SITC of 40 nos. 15 W	
Garden	for exhibition	to 25 W Warm White	Care of the second
	object	/ White LED Narrow	Cae A
		beam Round	
		Projector with	
		accessories and	
		connection cable &	
-	C11: 11:	foundation	
2	General lighting	SITC of 4 nos. 16 M	
	for Exhibition	Umbrella mast with	
	ground	raising lowering	
		Head frame .350 W	
		LED Flood including	
		High mast lighting	
		DB, power cable and	
		all accessories &	., 9
		foundation.	· CAI

Page 66 of 102





DESCRIPTION OF THE		Others	用到了一个工作,但是是是是一个工作。
Open Gym, Children Play Area, General garden lighting & Furniture	Tree lighting	SITC of 30 nos. 54 W Warm White / White LED Narrow / medium / wide beam Flood light with accessories and connection cable & foundation	
	Bush lighting	100 nos. SITC 9W Spike light	
	Garden area lighting	SITC of 50 nos. 1.2 M Cast Iron decorative bollard with decorative LED fixture with DB and connection cable & foundation	
***	Gazebo	sitting / meditation with indirect illumination	
FAÇADE LIGHTING	Station Club	Decorative pole, Projector light & linear wall washer from architectural LED fixture range.	

Open Spaces






Figure 67: Lighting Fixtures reference images

Indoor lighting:

Indoor lighting which would be used inside Sports Building, Station Club, Cleveland Memorial, Guard house, Toilets, Pump room, Craft kiosks and food stalls would have similar specifications as above and will be of LED type. It will comprise of LED tube lights (T5 batten), LED fans, LED bulbs, LED down lights etc.

STADIUM FLOOD LIGHTING:



Poge 88 of 102



Open Spaces



REQUIREMENTS:

For lighting of a sports facility, design attitude should meet both visual performance & Visual comfort parameters of all groups of users, viz. Players, Officials, Spectators and the Media.

Players and Officials

They must be able to see clearly all the activities in the field to perform their best.

Spectators

The spectators should be able to follow the performances of the players and the action of the game with the minimum effort. Also the viewing should be agreeable and appealing i.e. not only the playing area, the immediate surrounding should also be visible in a rhythm with the game. Also the safety criteria of the spectators while entering or exiting the stadium or in case of any unwanted emergency should also be taken care of.

Media

Colour television broadcasting has become an indispensable part of any sports activity of National or International standard. The Lighting should provide conditions that guarantee of good colour picture quality because that is related to lots of commercial interest of the concerned authority. Also the lighting should be adequate for taking close-ups for both the players and spectators.

The following parameters are vital for the right lighting ambience:

- a. Quantitative: Adequate Horizontal Lighting level to create a good Visual field for Players, Spectators Good vertical lighting to meet CTV transmission requirement
- b. Qualitative
- c. Uniform lighting
- d. Glare control
- e. Horizontal Illuminance: As the illuminated playground itself forms a major part of the field of view of players and spectators it is the horizontal illumination level [Lux level] that manly serves all the important adaptation state of the eyes. It is the basic backgrounds of the playing area satisfying which the other critical visual parameters are mate.
- f. Illuminance uniformity: Good illuminance uniformity in both the horizontal and vertical planes is important as it ensures freedom of adaptability of eyes over the field by both the players and spectators. It is important to have good uniformity along with gradient, to minimize camera adjustments.



Open Spaces



U1 - Ratio of lowest to the highest illuminance.

U2 - Ratio of lowest to the average illuminance.

Even when the uniformity as defined above is acceptable for a particular design, changes in illuminance can be disturbing if they occur over too short a distance. This problem is most likely to arise when panning a television camera. Where TV/Film coverage is concerned, the illuminance uniformity at a given grid point has to be expressed as a percentage change from the average illuminance in the eight adjacent grid points. This is commonly called the uniformity gradient.

- g. Glare restriction: Glare, brightness nears or enters the field of view, has a disturbing effect on the visual comfort of both the players and spectators. Glare can be minimized by paying careful attention to the choice floodlights and by ensuring that they are properly sited and aimed bearing in mind the main directions of viewing. Glare should not only been considered for the players and spectators or who have been very close to the illuminated ground, but for also the people outside the facility who might be disturbed by the stray light from the installation. For example traffic adjacent to the playground or people living in the vicinity. A straightforward parameter to quantify the degree of such disturbances is directly related to the optical qualities of the floodlights employed and proper aiming and site of them.
- h. Modelling and shadows: Modelling is the ability of lighting to reveal form and texture and is particularly important in providing a pleasant overall impression of the players, ball and spectators all around the area. The effectiveness of modelling is dependent upon the directions from which the light comes and the number and type of light sources used. Good quality television pictures demand good modelling from the lighting.

i. Colour Appearance and Colour Rendering

- Good colour perception is important in most sports. Two most important aspects of colour have to be distinguished:
- The colour appearance of the light. This is the colour impression of the total environment as created by the lamp.
- The colour rendering of the light, this is the ability of the light to reproduce the colours of an object faithfully. Both the Colour appearance and Colour Rendering is achieved by proper spectral distribution of the lamp.

 A CHARLET RECEIVED.

 BHACKET REAL PLANTAGE 70 of 102

Open Spaces



Design Philosophy

Basic Considerations are:

Lighting equipment- Use appropriate Lamp and Luminaire combination Standard: Follow standards, Specifications for Lighting Level, Ballast –wattage delivery, etc.

Application: Use appropriate lighting design tools, and ensure that accurate data is used Usage of L: Light Regulation by selective switching for different levels of sports.

Design Requirements

The design requirements are clearly spelt out in the tender. The illumination parameters for various class of play are well defined. The quantitative as well as qualitative lighting parameters are spelt in the tender and lighting is to be designed to achieve these results at optimum Total Cost of Ownership.

Lighting should provide is visual comfort and good visibility to the players, spectators

Lighting should provide is visual comfort and good visibility to the players, spectators and TV crew for international event broadcasting.

BASIS OF DESIGN:

The design has been done on basis of the technical specification mentioned in the standard for cricket ground. Additionally, we have recommended two other switching steps for flexibility of usage of the venue i.e. for football & hockey ground.

Cricket ground lighting Specifications: -

D	Requirement
Parameters	1, 10, 10, 10, 10, 10, 10, 10, 10, 10, 1
Average Horizontal Illumination	750 Lux & 500 lux
(Lux)	44 F 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Uniformity (U1)-Min/Max	>=0.7
Uniformity (U2)-Min/Avg	>=0.6
Glare Rating	<50
Light Source Type	<=1350 W LED luminaire
Colour Temperature	5700K
Colour Rendering Index	>70
Project Maintenance Factor	0.8

Football ground lighting Specifications: -

Requirement	
500 Lux	
>=0.7	
>=0.6	
<50	
<=1350 W LED luminaire	



Open Spaces




Colour Temperature	5700K	
Colour Rendering Index	>70	
Project Maintenance Factor	0.8	

Hockey ground lighting Specifications: -

Parameters	Requirement
Average Horizontal Illumination	500 Lux
(Lux)	
Uniformity (U1)-Min/Max	>=0.7
Uniformity (U2)-Min/Avg	>=0.6
Glare Rating	<50
Light Source Type	<=1350 W LED luminaire
Colour Temperature	5700K
Colour Rendering Index	>70
Project Maintenance Factor	0.8

Typical Layout of the Stadium:



SALIN FEET FECH. 2017 I.D.

GHANNER SHIPE CHYLID.

BHACALPH SHIPE CHYLID.

BHACALPH SHIPE CHYLID.

BHACALPH SHIPE CHYLID.

(A)

DETAIL PROJECT REPORT

Open Spaces



Calculation Grid:

The lighting calculations are done at 5m x 5m grid as per CIE 169:2005.

Glare Calculations:

The glare calculation done for critical observer positions as per stated in CIE 169. The maximum glare rating achieved for the above points are less than 50.

Design Results:-

(II)luminance Calculations:						
Calculation	Switching Mode	Туре	Unit	Ave	Min/Ave	Min/Max
Football Hockey Cricket Cricket Pitch	2 1 3 3	Surface Illuminance Surface Illuminance Surface Illuminance Surface Illuminance	lux lux lux lux	537 508 592 764	0.70 0.72 0.77 0.98	0.60 0.60 0.60 0.97

Summary of Lighting Design:-

- 4 nos. 35m stadium masts at top of headframe.
- Total Lighting Load Max 213 kW

TECHNICAL SPECIFICATIONS:

Luminaires:

- The floodlight luminaires shall be of special design for sports lighting application and suitable for LED light source. Each single LED Light should have maximum 1350W system with lumen output of minimum 1,57,000 lumen.
- The Luminaire and driver unit housing, floodlight's electrical connection box and mounting bracket should be made of PDC moulded aluminium. The end caps should be made of pressure die cast aluminium. All the plastic and cables in the luminaire should be UV protected.
- Luminaire should have polycarbonate lens for dedicated rotational/symmetrical optic with reduced glare properties. Various optics should be available to meet the design criteria & optimize the design for an efficient system. (Minimum 7 symmetrical optics for optimum/efficient design from extra-narrow to extra wide (2x6° to 2x19°)) with zero ULOR (Upward Light Output Ratio). These flood lights should be suitable for operating temperature range of -40°C up to +45°C.
- The floodlight shall be a state-of-the-art design allowing easy mounting Luminaire should have a sturdy U-shaped mounting bracket with foot-print suitable for 3-point fixation by means of M20 bolts, there should be a possibility of vertical aiming from the horizontal: -90° / +90° and standing-up or hanging-down mounting. It should be supplied with electrical connection box pre-fixed enabling wiring between floodlight and driver box.
- The Floodlight fixture shall be minimum IP66 suitable for all weather outdoor application with an impact resistance of IK 08.



Open Spaces



- Luminaire should have a Class A serviceability, luminaire is equipped with serviceable parts (when applicable) be it LED board, driver, control units, surge protection device, optics, front cover and mechanical parts from serviceability of the products in future.
- The LED Light Fixture shall have UL/ENEC & CE certification and must also be certified as stated in IEC60598 for outdoor luminaires. Maintenance of lumen output L80B50 shall be 50000 Hrs at released outdoor / indoor ambient. SDCM (Standard Deviation Colour Matching) shall be maximum 5 or better. Luminaire surge protection should be 10kV standard. The power factor should be >0.95 at full power.
- The luminaire should have CRI 70, TLCI (Television lighting consistency indices) per color code should be 49. The luminaire should have percent flicker factor <1%. The corresponding lumninaire should have also ranges in CRI 80 in CRI 90.

MEASUREMENT & VERIFICATION:

One time post installation measurement and verification will be carried out as per the followings:-

- The measurement will be done after 5 burning hours of the luminaire and the power for the same needs to be provided by the customer.
- The measurement will be carried out as per 5m x5m grid as shown in our lighting design.
- Voltage and current should be measured along with lighting levels as lighting levels is dependent on the available voltage.
- Rated supply voltage should be made available during the time of measurement.
- The measurement should be carried out on a clear night sky without dust/fog and smog as all these influences the lighting levels.

SR. WANAGER TECH. 2

SR. WANAG

Open Spaces




7.6 Details of signages, Furniture's with specifications

An identity and a sense of place are created, if landscape furniture is properly integrated in the design of a public space. The furnishings of urban outdoor spaces have been designed by keeping in mind the different users like the needs of differently abled, children, and the elderly and also to enable triangulation. The furniture's has been so designed that everybody in the park can utilise well to enjoy or to relax or to gossip. A different type of "cast in situ" benches has been uses to give a natural feel of the place. This has another benefit of designing benches and seats which are robust and maintenance free.

- Signage's: The signage's will be embedded and camouflaged with surrounding materials. The signage's will be integrated into its structures like benches, pillars of kiosks or boundary walls.
- Dustbins: Dustbins are to be provided at places as required which will be harmonised with design of the areas. These will be provided more in nowhere there is more concentration of visitors such as ghat area, food and craft area.







Dust bin



Signage

Figure 68: Garden Furniture

Detail of dustbins:

The dustbins would be of Bamboo or timber made as cast in situ to be as per the landscape of the site. The samples and design shall be approved by BSCL before execution.



Open Spaces





Figure 69: Details of Dustbin and Signage

The modern signage would be metal finish cast in situ to be as per the landscape of the site. The samples and design shall be approved by BSCL before execution.

7.7 Details for fountains and specification

The aeration fountain proposed for lake shall have following specifications:

- The manufacturer of Aeration fountain will furnish a floating fountain system capable of pumping water from below the surface of water body.
- A submersible motor will have to draw water into an impeller chamber where it shall be pumped into the atmosphere in the form of a decorative fountain.
- The water droplets will become oxygen enriched and return to the surface, therefore transferring oxygen from the atmosphere into the water body. This repeated action shall effectively mix the body of the water and distribute the dissolved oxygen continuously.
- LED light fixtures of 86W would be totally enclosed with weatherproof fittings and control gear.
- Lighting system will include stainless steel lamp housings, ready to be installed in the float, sealed with clear tempered glass lenses in a stainless steel clamp ring. All lights will remain water-cooled and out of sight below the surface.
- All necessary electrical controls, including digital timer shall be pre-wired into the fountain aerator's existing UL Listed control panel.
- Glass colored lenses (amber, blue, red, green or turquoise), with optional sequencer shall be used for dramatic aquatic display.

The state of 102

Open Spaces



7.8 Details of Plants

The palette of plants chosen and displayed help create a sense of place, they evoke feelings, capture a mood, as well as beautifying and enhancing the outdoors. Among all of these hardscape work, one of the most important elements in successful public urban green space is PLANTS. Plants have the power to soften and civilize public urban space.

The proportions of structural plants including trees, evergreens, shrubs and grasses against the softer perennial plants need to be correct to give shape to the garden all year round. A focus on year-round colour and interest is a focus of all our schemes, with typical favourites in shades of Purples, Blues and Whites, or specific colour-themed planting.

Planting is designed such a way that can perform as a function of shading in hot summer, adding fragrance into the space, adding colour to the space. Different plants have been used to create sense of enclosure in some places, define boundaries and create canopies for other shade loving plants.

Hedges been created to have a soft material for dividing internal spaces within a garden. Tree and shrubs along boundary wall are proposed to create visual barrier for the surrounding settlements and chaotic areas.

The Big structured canopied trees are used to provide shade for sitting areas as no hard structures has been propped as a shading structure. Plants along the water body is very useful in maintaining dense beneficial vegetation around water which is extremely important for improving water quality, preventing erosion and controlling nuisance geese. Establishing buffer zones takes minimal effort and requires little maintenance. In the long run, it will also reduce the likelihood of excessive pond algae and other water quality issues that come from nutrient loading, thereby reducing the need for constant herbicide treatments, and lowering long-term costs associated with managing your water body.

These specific plants are proposed to have a self-maintenance and also for aesthetic purpose.







Table 2: List of Proposed Plants

	Trees									
S. No.	Ref. Pic	Botanical Name	Common Name	Height	Remarks					
1		Ailanthus excelsa	Maharukh	8'-10'						
2		Azadirachta indica	Neem	8'-10'						
3		Dalbergia sissoo	Shisham	8'-10'						
4		Peltophorum pterocarpum	Copper Pod	8'-10'						
5		Tamarindus indica	Imli	8'-10'						
		Orname	ntal Tree							
1		Lagerstroemia speciosa	Crape Myrtle	8'-10'						
2		Cassia fistula	Amaltas	8'-10'	al la					

Rage 78 of 102





3		Jacaranda mimosifolia	Neeli Gulmohar	8'-10'
4		Bauhinia variegate	Kachnar	8'-10'
		Trees for Inte	rnal Pathways	
1	<u> </u>	Plumeria alba	Safed Champa	8'-10'
2		Ficus elastica	Rubber Tree	8'-10'
3		Ficus rumphii 'variegata'	Pakur Tree	8'-10'
4		Pseudobombax ellipticum (Bombax ellipticum)	Shaving brush tree	8'-10'
	ū	Pa	lm	
1		Wodeytia bifurcate	Fox Tail Palm	10'





Open Spaces

2	Caryota urens	Fish Tail Palm	10'	
3	Washingtonia filifera	Desert Fan Palm	8'-10'	
4	Bismarckia nobilis	Silver Bismarck Palm	5'-6"	
	i.			
	 ·	rub		
	Calliandra haematocephala	Powder Puff	3'-4'	
1	Agave variety (tequilana, Americana)	blue agave, American aloe etc	,	5 years old
2	Cactus Variety			5 years old
3	Sansevieria (different varieties)	Snake Plant		5 years old
4	Adenium varieties	Desert Rose	9	5 years old

Page 80 of 102





5		Euphorbia milii	Euphorbia		5"X7" polybag
6		Cycus variety	Cycus	6 leaves	24-inch trunk height
7		Clerodendrum inerme		3'-4'	small polybag 5"x6"
8	L	Ficus panda		3'	







Table 7.8.3: List of other Trees that can be considered

S. No.	Common Name	Botanical Name	Height	Girth (mm)
Trees	3			500 VOST1
1	Fig tree	Ficus benjamina	1500	150
2	Amaltas	Cassia fistula	1500	150
3	Yellow trumpet	Tabebuia Argentea	1500	100
4	Indian willow	Salix tetrasperma	1500	100
5	Rosy trumpet tree	Tabebuia impetiginosa	1500	100
6	Madagascar almond	Terminalia mentaly	1500	100
7	Pride of India	Lagerstroemia speciosa	1500	100
8	Umbrella tree	Brassia actionophyla	1500	100
9	Neeli gulmohar	Jacaranda mimosfolia	1500	100
10	Sita Ashok	Saraca indica	1500	100
11	Kachnar	Bauhinia variegata	1500	100
12	Java ki Rani	Cassia javanica	1500	100
Shrub	S			
1	Scheflera	Scheflera arboricola	300	-
2	caliandra	, B	300	-
3	Techoma	Techoma capensis	300	-
4	Lantana	Lantana camara	300	-
5	Plumbago	Plumbago capensis	300	-
6	Crape myrtle	Lagrestroemia indica	300	-
7	Poinciana	Poinciana pulcherima	300	-
8	Draceana	Draceana colorama	300	-
9	Japanese bamboo	Pseudosasa japonica	300	-
10	Areca palm	Dypsis lutescense	300	-
11	Ixora	Ixora coccinia	300	-
12	Firebush	Hamelia patens	300	-
	Golden shrim plant	Pachystachys lutea	300	
14	Firecracker	Russelia equisetiformis	300	-
15	Fountain grass	Pennisetum setacium	300	- Lu
16	Bird of paradise	Strelizia reginae	300	VI. 120.
17	Lobster-claws	Heliconia	300	Cillia

E.R. III. Page 82 of 102





S.	Common Name	Botanical Name	Height	Girth
No.			(mm)	(mm)
18	Umbrella	Cyperus alternifolis	300	-
	papyrus			
19	Adam's needle	Yucca	300	-
20	Sago palm	Cycus revoluta	300	-
21	Canna lily	Canna indica	300	-
22	Lily	Hymenocalis littoralis	300	-
23	Ipomea	Ipomea alba	300	-
24	Alpinia	Alpinia zerumbet	300	-
25	Lily	Lily amhyrilis	300	-
26	Lily	Hymenocalis littoralis	300	-
27	Sider lily	Crinum lily		
1	Alpinia	Setcresia purpurea	200	-
2	Ruellea	Ruellea rosea	200	-
3	Rhoheo	Rheo	200	-
4	Iresene	Iresene herbstii	200	-
5	Alternenthra	Alternenthra red	100	-
6	peace lilies	Spathyphylum	200	-
7	Blue flax-lily	Dianella tasmanica	200	-
8	Mondo grass	Ophiopogon japonicus	200	-
9	Fern	Nephrolepis exaltata	200	-
10	Liriope	Liriope mascari	200	-
11	Elephent ear	Caladium	200	-
12	Philodendron	Philodendron	200	-
13	Syngonium	Syngonium	200	
List of	creepers			
1	Madhumalti	Quisqualis indica	300	-
2	flamevine	Bignonia venusta	300	-
3	Rakhi creeper	Passiflora violacia	300	-
Į.	Sehra bel	Thunbergia mysorensis	300	
5	Garlic creeper	Adenocalyma	300	-
,	glory tree	Clerodendron splendens	300	-

Open Spaces





Tabebuia impetiginosa



Tabebuia argentea



Terminalia mentalis



Jacaranda mimosifolia

Figure 70: Proposed trees on site

CR MANUA SWAFT CITY LTD

BHAGALPUR SWAFT CITY LTD

Page 84 of 102



Open Spaces



8. Financial Viability

The financial viability of the project was ascertained with the intention of understanding the sustainability of the project in terms of meeting the O&M expenses. A critical requirement of this approach is estimation of the revenues generated from user charges, which is assumed to be the case (i.e. levying of user charges) for the project. Accordingly, the financial viability of the project has to be ascertained.

In order to determine the financial viability of the project, the following approach needs to be adopted

- Estimation of capital cost (CAPEX) of the project
- Identification of operation and maintenance (O&M) expenses that would be incurred under the project and estimation of the same.
- Identification of revenue streams for the project and estimation of the same, in the event that BSCL decides to generate revenues from the project.
- Financial analysis i.e. O&M expenses v/s revenues analysis

8.1 Estimated Project Cost:

A detailed cost estimate has been prepared at this DPR stage for the proposed project of Sandy's Compound which includes all the components for bringing project into reality. The purpose is to provide a detailed cost breakup and estimate which will be guiding factor during project execution.

This detailed estimate will give an insight into the cost of the project before working can start on site and it will form as a base for RFP for the developer. This is based on the specifications of materials, Lighting, planting as proposed in DPR. The item rates and specifications are mostly based on Bihar SOR. The rates which are not available in SOR have been taken from market through quotation from reputed vendors and GEM portal and rate analysis has been done to arrive at the cost for estimate purpose. The total cost of project for comprehensive development comes to Rs. 93.36 Crore. Abstract cost of same is provided below. The detailed cost estimate is provided in VOL II.

100000	ABSTRACT	OF COS	T OF SANDYS	S PARK AT B	HAGALPUR	
SL.NO.	DESCRIPTION OF WORK	UNIT	ITEM RATE	QUANTITY	AMOUNT	REFERENCE
1	Cycle Track	No.	₹ 2,65,72,008	1.00	₹ 2,65,72,008	Appendix 1
2	Jogging Track	No.	₹ 33,84,554	1.00	₹ 33,84,554	Appendix 2
3	Walk Way	No.	₹ 3,36,25,605	1.00	₹ 3,36,25,605	Appendix 3
4	Toilet (SMALL)	No.	₹ 7,55,291	10.00	₹ 75,52,914	Appendix 4



Open Spaces



Suard Room Cum Ticket Counter Recurrence Recurr	- APP - 1 - 1	₩ ₂ 1 + 1 (x)					Veril Section Bridge Bridge
6 Romm ₹ 75.731 8.00 ₹ 6,05,848 Appendix Append	5		No.	₹ 3,37,391	8.00	₹ 26,99,126	Appendix 5
8 Drain 0.5 x 0.75 No. ₹ 9,69,83,413 1.00 ₹ 9,69,83,413 Appendix 19 9 Drain 0.75 x 0.9 No. ₹ 8,40,97,919 1.00 ₹ 8,40,97,919 Appendix 8 10 RCC NP 3 Pipe for SWD No. ₹ 13,85,177 1.00 ₹ 13,85,177 Appendix 9 11 Landscaping No. ₹ 14,16,5726 1.00 ₹ 13,85,177 Appendix 11 2 Kiosk No. ₹ 3,54,579 11.00 ₹ 3,900,364 Appendix 12 13 Kids Play Area No. ₹ 24,43,883 1.00 ₹ 24,43,883 Appendix 13 14 Outdoor Gym No. ₹ 19,69,225 1.00 ₹ 19,69,225 Appendix 14 15 New Yoga Platform No. ₹ 40,94,652 1.00 ₹ 19,69,225 Appendix 14 16 Voga Platform No. ₹ 40,94,652 1.00 ₹ 40,94,652 Appendix 16 17 New Stage No. ₹ 1,38,45,42 1.00 ₹ 13,84,542 Appendix 18 18 Nehru Memorial No. ₹ 6,90,760 1.00 ₹ 6,90,760 Appendix 19 19 Station Club No. ₹ 1,32,87,508 1.00 ₹ 1,32,87,508 Appendix 20 20 Entry/ Exit Gate No. ₹ 8,85,625 1.00 ₹ 1,32,87,508 Appendix 22 21 Entrance gate No. ₹ 8,85,625 1.00 ₹ 2,33,75,713 Appendix 23 22 Swimming Pool Mech and Other ₹ 2,33,75,713 1.00 ₹ 2,33,75,713 Appendix 23 23 and Other ₹ 2,33,75,713 1.00 ₹ 2,33,75,713 Appendix 24 24 Cricket Pavillion No. ₹ 1,96,43,511 1.00 ₹ 1,63,20,985 Appendix 25 25 Pavillion Longe No. ₹ 1,36,320,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 8,76,1104 3.00 ₹ 2,62,83,313 Appendix 25 27 Open Air Theatre No. ₹ 3,37,764 1.00 ₹ 3,33,77,64 Appendix 27 29 Pond 1 No. ₹ 6,95,5448 1.00 ₹ 3,33,77,64 Appendix 27 20 Pond 3 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 1,56,882 1.00 ₹ 1,54,6828 Appendix 29 31 Basket Ball Court No. ₹ 1,56,882 1.00 ₹ 1,54,68,89 Appendix 29 32 Trellis walkwway No. ₹ 1,12,7421 1.00 ₹ 1,18,31,450 Appendix 34 35 Renovation of Existing No. ₹ 1,81,450 1.00 ₹ 2,23,79,515 Appendix 37 36 Lawn Tennis Court No. ₹ 1,56,80,937 1.00 ₹ 1,88,60,937 Appendix 37 38 Water Fountain No. ₹ 1,68,60,937 1.00 ₹ 1,89,753 Appendix 39 39 Cleaveland Memorial No. ₹ 1,55,25,256 1.00 ₹ 7,52,5,256 Appendix 39 40 Tollet (BIG) No. ₹ 1,99,7533 1.00 ₹ 1,99,7553 Appendix 41	6		No.	₹ 75,731	8.00	₹ 6,05,848	Appendix 5 A
8	7	Cafeteria (PROPOSED)	No.	₹ 1.18.16.245	4.00	₹ 4.72.64.978	
9		Drain 0.5 x 0.75	No.				50
10 RCC NP 3 Pipe for SWD No. ₹13,85,177 1.00 ₹13,85,177 Appendix 9		Drain 0.75 x 0.9	No.				
11		RCC NP 3 Pipe for SWD	No.				
12 Kiosk No. ₹3,54,579 11.00 ₹39,00,364 Appendix 12 13		Landscaping	No.				
13 Kids Play Area No. ₹ 24,43,883 1.00 ₹ 24,43,883 Appendix 13 14		Kiosk	No.		1		
14 Outdoor Gym No. ₹19,69,225 1.00 ₹19,69,225 Appendix 14 15 New Yoga Platform No. ₹40,94,652 1.00 ₹40,94,652 Appendix 16 Renovation of Existing Yoga Platform No. ₹8,45,625 1.00 ₹8,45,625 Appendix 17 17 New Stage No. ₹13,84,542 1.00 ₹13,84,542 Appendix 18 18 Nehru Memorial No. ₹6,90,760 1.00 ₹6,90,760 Appendix 19 19 Station Club No. ₹1,32,87,508 1.00 ₹1,32,87,508 Appendix 20 20 Specific/ Emergency Entry/ Exit Gate ₹7,28,670 13.00 ₹94,72,712 Appendix 21 21 Entrance gate No. ₹85,01,469 3.00 ₹2,55,04,408 Appendix 22 22 Swimming Pool No. ₹1,56,28,608 1.00 ₹1,56,28,608 Appendix 23 A Swimming Pool Mech and Other ₹2,33,75,713 1.00 ₹2,33,75,713 Appendix 24 24 Cricket Pavillion No. ₹1,63,20,985 1.00 ₹1,63,20,985 Appendix 25 25 Pavillion Longe No. ₹1,63,20,985 1.00 ₹1,63,20,985 Appendix 26 26 Parking No. ₹8,761,104 3.00 ₹2,62,83,313 Appendix 26 27 Open Air Theatre No. ₹33,37,764 1.00 ₹3,33,75,448 Appendix 27 28 Pond 1 No. ₹69,55,448 1.00 ₹3,37,58,574 Appendix 29 29 Pond 2 No. ₹3,79,58,574 1.00 ₹3,79,58,574 Appendix 29 29 Pond 2 No. ₹3,79,58,574 1.00 ₹3,79,58,574 Appendix 29 20 Pond 3 No. ₹5,75,9,855 1.00 ₹7,59,855 Appendix 29 20 Pond 3 No. ₹3,79,58,574 1.00 ₹3,79,58,574 Appendix 29 21 Rentrance for No. ₹3,79,58,574 1.00 ₹3,79,58,574 Appendix 29 22 Pond 1 No. ₹6,95,5448 1.00 ₹3,79,58,574 Appendix 29 23 Pond 1 No. ₹6,95,548 1.00 ₹1,64,628 Appendix 29 24 Pond 2 No. ₹3,79,58,555 1.00 ₹7,59,855 Appendix 30 25 Pond 3 No. ₹3,79,58,574 1.00 ₹3,79,58,574 Appendix 29 26 Pond 3 No. ₹3,79,58,574 1.00 ₹3,79,58,574 Appendix 29 27 Cricket Field and its No. ₹1,46,828 1.00 ₹1,48,161 Appendix 30 30 Pond 3 No. ₹3,79,58,574 1.00 ₹7,54,8,161 Appendix 30 31 Basket Ball Court No. ₹1,40,1,500 5.00 ₹7,0,7,500 Appendix 37 32 Trellis walkwway No. ₹1,1,57,525 56 Appendix 37 33 Water Fountain No. ₹1,68,60,937 1.00 ₹1,68,60,937 Appendix 37 34 Oricket Field and its No. ₹1,50,57,53,14 No. ₹1,99,7,553 Appendix 39 35 Cleaveland Memorial No. ₹3,59,75,314 1.00 ₹3,59,75,314 Appendix 41 36 Cleaveland Memorial No. ₹3,59,75,314		Kids Play Area	No.				
15 New Yoga Platform Renovation of Existing Yoga Platform Renovation of Existing Yoga Platform No. ₹ 40,94,652 1.00 ₹ 40,94,652 Appendix 16 Renovation of Existing Yoga Platform No. ₹ 13,84,542 1.00 ₹ 8,45,625 Appendix 17 New Stage No. ₹ 13,84,542 1.00 ₹ 6,90,760 Appendix 19 Station Club No. ₹ 1,32,87,508 1.00 ₹ 6,90,760 Appendix 19 Specific / Emergency Specific / Emergency Specific / Emergency Entry / Exit Gate Symming Pool No. ₹ 1,56,28,608 1.00 ₹ 1,56,28,608 Appendix 22 Swimming Pool Mech and Other Symming Pool Mech and Other Symming Pool Mech and Other Symming Pool Mech Appendix 23 Appendix 24 Swimming Pool Mech Appendix 25 Pavillion Longe No. ₹ 1,96,43,511 1.00 ₹ 2,33,75,713 Appendix 24 Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 26 Parking No. ₹ 87,61,104 3.00 ₹ 2,62,83,313 Appendix 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 33,37,764 Appendix 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 29 Pond 2 No. ₹ 3,75,98,855 1.00 ₹ 57,59,855 Appendix 29 Pond 3 No. ₹ 3,75,98,855 1.00 ₹ 11,27,421 Appendix 34 Renovation of Existing No. ₹ 11,27,421 New Badminton Court No. ₹ 15,46,828 Renovation Renovation ₹ 2,47,39,515 No. ₹ 2,47,39,515 Appendix 34 New Badminton Court No. ₹ 2,47,39,515 No. ₹ 2,47,39,515 No. ₹ 2,47,39,515 No. ₹ 2,47,39,515 No. ₹ 1,68,60,937 No. ₹							
Renovation of Existing Yoga Platform							
16 Yoga Platform ₹ 8,45,625 1.00 ₹ 8,45,625 Appendix 17 17 New Stage No. ₹ 13,84,542 1.00 ₹ 13,84,542 Appendix 18 18 Nehru Memorial No. ₹ 6,90,760 1.00 ₹ 6,90,760 Appendix 19 19 Station Club No. ₹ 1,32,87,508 1.00 ₹ 1,32,87,508 Appendix 20 20 Entry/ Exit Gate - ₹ 7,28,670 13.00 ₹ 94,72,712 Appendix 21 21 Entrance gate No. ₹ 8,501,469 3.00 ₹ 2,55,04,408 Appendix 22 22 Swimming Pool Mech No. ₹ 1,56,28,608 1.00 ₹ 1,56,28,608 Appendix 23 24 Cricket Pavillion No. ₹ 1,96,43,511 1.00 ₹ 1,96,43,511 Appendix 24 25 Pavillion Longe No. ₹ 7,61,104 3.00 ₹ 2,62,83,313 Appendix 23 26 Parking No. ₹ 8,76,1,104 3.00 ₹ 2,62,83,313 Appendix 25 27 Open Air Theatre	15			(40,94,032	1.00	(40,94,032	Appendix 16
17 New Stage No. ₹ 13,84,542 1.00 ₹ 13,84,542 Appendix 18 18 Nehru Memorial No. ₹ 6,90,760 1.00 ₹ 6,90,760 Appendix 19 19 Station Club No. ₹ 1,32,87,508 1.00 ₹ 6,90,760 Appendix 19 20 Entry/ Exit Gate No. ₹ 7,28,670 13.00 ₹ 94,72,712 Appendix 21 21 Entrance gate No. ₹ 85,01,469 3.00 ₹ 2,55,04,408 Appendix 23 22 Swimming Pool Mech No. ₹ 1,56,28,608 1.00 ₹ 1,56,28,608 Appendix 23 24 Cricket Pavillion No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 8,61,104 3.00 ₹ 2,63,37,764 Appendix 25 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 3,379,58,574 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30	16		140.	₹ 8,45,625	1.00	₹ 8,45,625	Appendix 17
18 Nehru Memorial No. ₹ 6,90,760 1.00 ₹ 6,90,760 Appendix 19 19 Station Club No. ₹ 1,32,87,508 1.00 ₹ 1,32,87,508 Appendix 20 20 Entry/ Exit Gate No. ₹ 7,28,670 13.00 ₹ 94,72,712 Appendix 21 21 Entrance gate No. ₹ 85,01,469 3.00 ₹ 2,55,04,408 Appendix 22 22 Swimming Pool Mech and Other No. ₹ 1,56,28,608 1.00 ₹ 1,56,28,608 Appendix 23 A 24 Cricket Pavillion No. ₹ 1,96,43,511 1.00 ₹ 1,96,43,511 Appendix 22 25 Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 87,61,104 3.00 ₹ 2,62,83,313 Appendix 25 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 33,37,764 Appendix 22 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 29			No.				
Station Club		Nehru Memorial	No.				1
Specific Emergency Entry Exit Gate		Station Club	No.				1
20 Entry/ Exit Gate ₹ 7,28,670 13.00 ₹ 94,72,712 Appendix 21 21 Entrance gate No. ₹ 85,01,469 3.00 ₹ 2,55,04,408 Appendix 22 22 Swimming Pool No. ₹ 1,56,28,608 1.00 ₹ 1,56,28,608 Appendix 23 A 23 Swimming Pool Mech and Other No. ₹ 2,33,75,713 1.00 ₹ 2,33,75,713 Appendix 23 B 24 Cricket Pavillion No. ₹ 1,96,43,511 1.00 ₹ 1,96,43,511 Appendix 24 25 Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 8,61,104 3.00 ₹ 2,62,83,313 Appendix 25 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 3,79,58,574 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 5,59,9855 1.00 ₹ 5,59,955 Appendix 30 31	17	Specific/ Emergency	No.	(1,02,07,000	1.00	(1,02,07,000	Appendix 20
21 Entrance gate No. ₹ 85,01,469 3.00 ₹ 2,55,04,408 Appendix 22 22 Swimming Pool No. ₹ 1,56,28,608 1.00 ₹ 1,56,28,608 Appendix 23 A 23 Swimming Pool Mech and Other No. ₹ 2,33,75,713 1.00 ₹ 2,33,75,713 Appendix 23 B 24 Cricket Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 87,61,104 3.00 ₹ 2,62,83,313 Appendix 25 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 69,55,448 Appendix 27 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 57,59,855 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 30 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 32	20		92 10	₹ 7,28,670	13.00	₹ 94,72,712	Appendix 21
22 Swimming Pool No. ₹ 1,56,28,608 1.00 ₹ 1,56,28,608 Appendix 23 A 23 and Other and Other and Other ₹ 2,33,75,713 1.00 ₹ 2,33,75,713 Appendix 23 B 24 Cricket Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 8,61,104 3.00 ₹ 2,62,83,313 Appendix 26 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 33,37,764 Appendix 27 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 37,95,85,74 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 30 31 Basket Ball Court No. ₹ 11,27,421 1.00 ₹ 15,46,828 Appendix 32 32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 11,27,421 Appendix 34 34	21	Entrance gate	No.	₹ 85,01,469	3.00	₹ 2,55,04,408	
23 Swimming Pool Mech and Other No. ₹ 2,33,75,713 1.00 ₹ 2,33,75,713 Appendix 23 B 24 Cricket Pavillion No. ₹ 1,96,43,511 1.00 ₹ 1,96,43,511 Appendix 24 25 Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 87,61,104 3.00 ₹ 2,62,83,313 Appendix 26 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 3,33,7,764 Appendix 27 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 30 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 32 32 Trellis walkwWay No. ₹ 1,127,421 1.00 ₹ 78,48,161 Appendix 34 <	22	Swimming Pool	No.	₹ 1,56,28,608	1.00		
24 Cricket Pavillion No. ₹ 1,96,43,511 1.00 ₹ 1,96,43,511 Appendix 24 25 Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 87,61,104 3.00 ₹ 2,62,83,313 Appendix 26 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 33,37,764 Appendix 27 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 29 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 30 31 Trellis walkwWay No. ₹ 15,46,828 1.00 ₹ 11,27,421 Appendix 33 33 Badminton Court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34	23		No.	-/8 1:-	0.000		
25 Pavillion Longe No. ₹ 1,63,20,985 1.00 ₹ 1,63,20,985 Appendix 25 26 Parking No. ₹ 87,61,104 3.00 ₹ 2,62,83,313 Appendix 26 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 33,37,764 Appendix 27 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 29 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 30 32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 11,27,421 Appendix 33 Renovation of Existing Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34 Building renovation ₹ 1,18,31,450 1.00 ₹ 7,18,31,450 Appendix 34 B 35 L			No.				
26 Parking No. ₹ 87,61,104 3.00 ₹ 2,62,83,313 Appendix 26 27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 33,37,764 Appendix 27 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 30 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 32 32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 78,48,161 Appendix 33 33 Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34 Building No. ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court		Pavillion Longe	No.				
27 Open Air Theatre No. ₹ 33,37,764 1.00 ₹ 33,37,764 Appendix 27 28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 37,79,58,574 1.00 ₹ 37,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 30 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 32 32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 11,27,421 Appendix 33 Renovation of Existing Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 34 Building Suilding renovation ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 36 37 Orainage		Parking	No.				
28 Pond 1 No. ₹ 69,55,448 1.00 ₹ 69,55,448 Appendix 28 29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 30 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 32 32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 11,27,421 Appendix 33 33 Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34 Building ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 36 37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 75,25,2		Open Air Theatre	No.				
29 Pond 2 No. ₹ 3,79,58,574 1.00 ₹ 3,79,58,574 Appendix 29 30 Pond 3 No. ₹ 57,59,855 1.00 ₹ 57,59,855 Appendix 30 31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 32 32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 11,27,421 Appendix 33 33 Renovation of Existing Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34 Building Gym Building renovation ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39			No.				
Pond 3		Pond 2	No.				
31 Basket Ball Court No. ₹ 15,46,828 1.00 ₹ 15,46,828 Appendix 32 32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 11,27,421 Appendix 33 33 Renovation of Existing Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34 Building Gym Building renovation № ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 2,47,39,515 Appendix 36 Cricket Field and its Drainage No. ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 3,59,75,314 Appendix 41							•
32 Trellis walkwWay No. ₹ 11,27,421 1.00 ₹ 11,27,421 Appendix 33 33 Renovation of Existing Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34 New Badminton Court Building Sulding renovation No. ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 1,401,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41 <							
Renovation of Existing Badminton court No. ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A 34 New Badminton Court Building Gym Building Renovation No. ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41							
33 Badminton court ₹ 78,48,161 1.00 ₹ 78,48,161 Appendix 34 A New Badminton Court No. 1.00 ₹ 1,18,31,450 Appendix 34 B 34 Building No. ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 Cricket Field and its No. ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41	32			₹ 11,27,421	1.00	< 11,27, 4 21	Appendix 33
34 New Badminton Court Building No. ₹ 1,18,31,450 1.00 ₹ 1,18,31,450 Appendix 34 B 35 Gym Building renovation No. ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41	33		INO.	₹ 78.48.161	1.00	₹ 78.48.161	Appendix 34 A
Gym Building renovation No. ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 Cricket Field and its No. ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41			No.		2.00	(10)10)101	ripperial 54 ft
35 renovation ₹ 2,47,39,515 1.00 ₹ 2,47,39,515 Appendix 35 36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 Cricket Field and its No. 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41	34			₹ 1,18,31,450	1.00	₹ 1,18,31,450	Appendix 34 B
36 Lawn Tennis Court No. ₹ 23,18,576 1.00 ₹ 23,18,576 Appendix 36 37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41			No.			T 0 4 T 00 T 4 T	
Cricket Field and its No. 37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41			No				1000
37 Drainage ₹ 1,68,60,937 1.00 ₹ 1,68,60,937 Appendix 37 38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41	36			₹ 23,18,576	1.00	₹ 23,18,576	Appendix 36
38 Water Fountain No. ₹ 14,01,500 5.00 ₹ 70,07,500 Appendix 38 39 Cleaveland Memorial No. ₹ 75,25,256 1.00 ₹ 75,25,256 Appendix 39 40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41	37		No.	₹ 1.68.60 937	1.00	₹1.68.60 937	Annendiy 27
39 Cleaveland Memorial No. ₹75,25,256 1.00 ₹75,25,256 Appendix 39 40 Toilet (BIG) No. ₹19,97,553 1.00 ₹19,97,553 Appendix 40 41 Multipurpose ground No. ₹3,59,75,314 1.00 ₹3,59,75,314 Appendix 41			No.				
40 Toilet (BIG) No. ₹ 19,97,553 1.00 ₹ 19,97,553 Appendix 40 41 Multipurpose ground No. ₹ 3,59,75,314 1.00 ₹ 3,59,75,314 Appendix 41			Section Control of the Control of th				
41 Multipurpose ground No. ₹3,59,75,314 1.00 ₹3,59,75,314 Appendix 41							
The composite the control of the con						1	7
42 CPCH 200 100 ₹ 3,05,79,017 1.00 ₹ 3,05,79,017 Appendix 42							
	42	Open 200	140.	₹ 3,05,79,017	1.00	< 3,U3,79,U17	Appendix 42

BHAGALFUR SMART CHI TAPPETRALE
BHAGALFUR SMART CHI TAPPETRALE
BHAGALFUR SMART CHI TAPPETRALE



Open Spaces



43	Adventure Zone	No.	₹ 63,04,918	1.00	₹ 63,04,918	Appendix 43
44	Scuplture court	No.	₹ 28,39,915	1.00	₹ 28,39,915	Appendix 44
45	Open Art Gallery	No.	₹ 19,31,459	1.00	₹ 19,31,459	Appendix 45
46	Dismantelling of Boundary Wall	No.	₹ 19,60,462	1.00	₹ 19,60,462	Appendix 46
47	Boundary wall EXTERNAL	No.	₹ 11,792	2,550.00	₹ 3,00,69,600	Appendix 47
48	Boundary Wall Internal	No.	₹ 6,039	1,010.00	₹ 60,99,791	Appendix 48
49	Compost Pit Plant Nursary	No.	₹ 20,00,000	2.00	₹ 40,00,000	Appendix 49
50	Estimate Sports Complex Electrical	No.	₹ 6,67,48,241	1.00	₹ 6,67,48,241	Additional Sheet
51	Estimate of General Lighting Electrical	No.	₹ 3,27,94,472	1.00	₹ 3,27,94,472	Additional Sheet
52	SUB TOTAL				₹ 83,93,01,104	
53	Operation and Maintenance costs for three year (Included in RFP)			6%	5,03,58,066	y 8
54	Centage (7%- 0 to 10 Cr & 5%-10 to 100 cr)	v Jun 1 Jun 1 Jun 1 June	The state of the s	The Control of the Co	4,39,65,055	
55	Total Project Cost	1.0	A Company of the Comp	To see the see the see that the see the see that the see the see the see that the s	₹ 93,36,24,226	The State of the S

^{*} O&M expenses have been estimated over an O&M period of 3 years. This O&M is apart from DLP of 1 Year.

An approach similar to life-time costs is adopted over the construction period and 3 year O&M period, in arriving at the project cost.

Note: O&M expenses can be recovered from the revenue streams envisaged for the project.

The total project cost including O&M expenses over a 3 year maintenance period is estimated as Rs. 93.36 Crore /- which includes all the project components as stated in DPR and shall be used as base for tender purpose. The funding would be from funds of smart city proposal. The detailed cost estimates with BOQ of all the items are attached with the report as Volume 2.

8.2 Funding

The proposed cost for Open Space as per SCM is Rs. 37.8 Crore, out of which SCM fund is Rs. 30.2 Crore. The breakup is provided below:

- 1. Rejuvenation of existing Large open spaces with added activities: Rs. 25.2 Crore
- 2. Recreation & Entertainment: Rs. 12.6 Crore

Table 8.2.1: Funding Availability as per SCM





Open Spaces



Activity	Project Precinct	Indicative Cost (in lacs)	Gol Funding	GoB Funding	ULB- Own Source	PPP Funding	Gol Amrut
Activity group 5	Rejuvenation of existing Large open spaces with	2520	880.00	880.00	360.00	300.00	100.00
Activity group 6	Recreation &Entertainment	1260	630.00	630.00			

The Scm fund consisting of GoI and GoB funds sums up to Rs. 30.2 Crore. Additional Rs. 3.6 Crore funding is by ULB. So the total available fund for this project equals Rs. 33.8 Crore. However in the review meeting with Chairperson BSCL on 18th October 2019, it was directed to phase the project according to the availability of funds. The items for development under Phase 1 was taken based on direction given by BSCL.

BSCL has directed us not to take up drainage works in the whole campus under Phase 1 but as per best engineering practice its requirement in landscape related project is must. However in reference to the available funds and after discussions from BSCL, in line to their suggestions drain development is not taken in Phase 1 of the project.

The total cost of Project along with O&M and Centage comes to Rs. 35.88 Crore under Phase1 of development. Under phase 1 of the development following activities are proposed by BSCL:

Table 8.2.2: Abstract of Detailed Cost estimate of the project (Phase I)

	ABSTRACT OF COST OF SANDYS PARK AT BHAGALPUR (PHASE 1)						
SL.NO.	DESCRIPTION OF WORK	UNIT	ITEM RATE	QUANTITY	AMOUNT		
1	Walk Way	No.	3,24,32,853	1.00	₹ 3,24,32,853		
2	Guard Room Cum Ticket Counter	No.	3,33,619	4.00	₹ 13,34,475		
3	Electrification of Guard Room	No.	75,731	4.00	₹ 3,02,924		
4	Cafeteria (PROPOSED)	No.	1,18,16,245	1.00	₹ 1,18,16,245		
5	Landscaping	No.	1,41,65,726	1.00	₹ 1,41,65,726		
6	Kids Play Area	No.	24,43,883	1.00	₹ 24,43,883		
7	Nehru Memorial	No.	6,90,760	1.00	₹ 6,90,760		
8	Station Club	No.	1,50,24,091	1.00	₹ 1,50,24,091		
. 9	Specific/Emergency Gate	No.	7,28,670	13.00	₹ 94,72,712		
10	Entrance gate	No.	85,01,469	1.00	₹ 85,01,469		
11	Swimming Pool	No.	1,56,28,608	1.00	₹ 1,56,28,608		
12	Swimming Pool Mech and Other	No.	2,33,75,713	1.00	₹ 2,33,75,713		
13	Parking	No.	87,61,104	1.00	₹ 87,61,104		
14	Open Air Theatre	No.	33,37,764	1.00	₹ 33,37,764		

SR. MANAGER TECH. 2



Open Spaces



1.5	Basket Ball Court	No.	15,46,828	1.00	₹ 15,46,828
15	Trellis walkway	No.	11,27,421	1.00	₹ 11,27,421
16	Renovation of Existing Badminton court	No.	78,48,161	1.00	₹ 78,48,161
17	New Badminton Court Building	No.		Var. 0500	₹ 1,18,31,450
18			1,18,31,450	1.00	
19	Gym Building renovation	No.	1,76,52,741	1.00	₹ 1,76,52,741
20	Lawn Tennis Court	No.	12,16,407	1.00	₹ 12,16,407
21	Cricket Field and its Drainage	No.	1,68,60,937	1.00	₹ 1,68,60,937
22	Cleveland Memorial	No.	24,70,690	1.00	₹ 24,70,690
23	Toilet (BIG)	No.	19,97,553	1.00	₹ 19,97,553
24	Multipurpose ground	No.	3,59,75,314	1.00	₹ 3,59,75,314
25	Sculpture court	No.	28,39,915	1.00	₹ 28,39,915
26 /	Dismantling of Boundary Wall	No.	19,60,462	1.00	₹ 19,60,462
27	Boundary wall EXTERNAL	No.	11,792	2,550.00	₹ 3,00,69,600
28	Boundary Wall Internal	No.	6,039	1,010.00	₹ 60,99,791
	ESTIMATE of SPORTS COMPLEX	No.			
	LIGHTING				
29	(Proposed Item only)		1,57,93,523	1.00	₹ 1,57,93,523
	ESTIMATE of GENERAL	No.			
	LIGHTING				
30	(Proposed Item only)		1,88,42,125	1.00	₹ 1,88,42,125
31	SUB TOTAL				₹ 32,14,21,245
	Operation and Maintenance costs for				*
32	three year (Include this in RFP)			6%	1,92,85,275
	Centage (7%-0 to 10 Cr & 5%-10 to 100 cr)				
33					1,80,71,062
34	Total Project Cost				₹ 35,87,77,581

Under in Phase 1, change in quantity in following proposed items are done.

- 1. Under Phase 1 four Guard Rooms are proposed instead of 8.
- 2. One Cafeteria is proposed instead of 3.
- 3. 4 Specific/Emergency gates are proposed instead of 11.
- 4. 1 Main Entrance is proposed instead of 3.
- 5. 1 Parking development is proposed instead of 3.
- 6. Under Phase 1 in Cleveland Memorial, drain development is excluded due to constrain of fund however it is kept for under comprehensive development of compound and can be taken up in further phase of development.
- 7. Under Phase 1 in Lawn Tennis Court, drain development is excluded due to constrain of fund however it is kept for under comprehensive development of compound and can be taken up in further phase of development.

Note: Additional fund requirement can be procured from savings of SCM fund from other projects after approval from Board and other competent body for fund mobilization.



Open Spaces



8.3 Operation and maintenance:

During the design stage and stakeholder discussions, various components of operation and maintenance aspects were set in place for the design proposal. Following aspects are identified and provided for smooth operation and maintenance of the project.

- 1. Urban facilities and on street parking
- 2. Regular maintenance Finishes of the pathway.
- 3. Public safety & water front activities
- 4. Lighting adequacy and maintenance.
- 5. Replacement of dilapidated structure
- 6. Maintaining of public Toilets.
- 7. Maintenance of water body.
- 8. Maintenance of Open air theatre.
- 9. Lake aeration & lake illumination for which a pump house will be provided with Toilet blocks.
- 10. Maintenance of Parks, Cafeteria and Landscape
- 11. Maintenance of Sports Complex.
- 12. Maintenance of Open Zoo.

In order to facilitate the project with above mentioned aspects, regular manpower and equipment cost has to be taken into consideration for maintenance purpose. For the first three year this work has to be carried by Contractor and BSCL will only look after its administrative part.

8.4 Institutional Arrangements:

In order to run the activities in the proposed project, institutional arrangements would be essential which will include the human resources, funding, equipment and supplies, effectiveness, and the communication links between and among them. The tables below describe the institutional arrangements required to efficiently run the project.

Manpower requirement:

Table 8.4.1: Manpower requirement

Sl. No.	Manpower	No	
1	Park Manager		1
2	Accountant		1
3	Maintenance Manager	_	1
4	Zoologist	alf. Je	1
5	Botanist	LEP. 110.	1

SR HIP CHANGE ROUSE 90 of 102







6	Security Officer	1
7	Computer Operator	5
8	Security guard	20
9	Curator	1
10	Gardner	5
11	Ticket Collector	4
12	Technician (Electrical, Lighting, Pump operator)	5
13	Sweeper/Cleaner	10
14	Life guard	2
15	Office Boy	3
16	Doctor	1
17	Compounder/Nurse	1
18	Game Experts/ Trainer	6
19	Support Staff	18
	Total	87

A total of 87 persons are estimated to be required for all the operation and maintenance activities under the project. Based on requirement BSCL can increase or decrease the no. of employees.

Equipment required:

Table 8.4.2: Equipment requirement

Sl. No.	Equipment	Nos.
1	Lawnmower	5
2	Forks	20
3	Powered edger	5
4	Leaf blower	10
5	Pressure washer	10
6	Powered chainsaw	10
7	Shears	20
8	Wheel barrow (double)	10
9	Garden spade	20
10	Shovel	20
11	Pickaxe	10
12	Ное	10
13	Pond Pliers	5
14	Pond Scissors	. 5
15	Pond Cleaning Clearing/Catching Landing Net	10

The equipment cost and manpower cost to be included in O&M expenses. A separate agency can be hired for O&M of the whole compound. However for the first three year



Open Spaces



contractor will be solely responsible for the maintenance of the compound. The equipment and manpower shall be deployed as per requirement and may change as direction of BSCL/engineer in charge.

8.5 Project Revenue

Projected revenue refers to the estimated money a project will generate during a specific period. The projections often refer to monthly, quarterly or annual accounting periods. For financial sustainability of the project there must be revenue sources through which finance can be generated on a regular basis. In case of this project as per the design intent the revenue sources available in this project as described below:

Table 8.5.1: Revenue Estimation

Revenue Head	Charges per person (Rs)/ Bulk Charges	Users/ Nos.	Total (monthly)*	Total (Rs. p.a.)
Entry Ticket Cost	₹ 20/day	5000/day	₹ 30,00,000.00	₹ 3,60,00,000.00
Monthly Pass (morning walkers)	₹150/month	3000/month	₹ 4,50,000.00	₹ 54,00,000.00
Membership (Gym)	₹500/month	100	₹ 50,000.00	₹ 6,00,000.00
Membership (Sports)	₹500/month	100	₹ 50,000.00	₹ 6,00,000.00
Membership (Club)	₹1000/month	100	₹ 1,00,000.00	₹ 12,00,000.00
Water Front/ Boating	₹ 20/15mins	500/day	₹ 3,00,000.00	₹ 36,00,000.00
Art and Craft Kiosk	₹10,000/month/ kiosk	5 Kiosk	₹ 50,000.00	₹ 6,00,000.00
Food Kiosks	₹15,000/month/ kiosk	5 Kiosk	₹ 75,000.00	₹ 9,00,000.00
Cafeteria	₹ 50,000/ Cafeteria	3	₹ 1,50,000.00	₹ 18,00,000.00
Events	₹ 50,000/month	-	₹ 50,000.00	₹ 6,00,000.00
Advertising revenues**	₹1,00,000/month	-	₹ 1,00,000.00	₹ 12,00,000.00
		Total	₹ 43,75,000.00	₹ 525,00,000.00

^{*} assuming 30 days per month

The total revenue from ticketing, rentals and advertising, under the project is thus estimated as Rs.5.25 Crore p.a. Table below illustrates the revenues from the project over a 5 year period, with an annual escalation of 5%.

SR MARINE SHEET Ridge 92 of 102

^{**} In arriving at advertising revenues, the following sources are made: (1) Around 400 Nos. of light poles, each with two faces for Backlit advertising. (2) Cafeteria Ads (3) Plaza and Parks



Open Spaces



Table 8.5.2: Annual Revenues (Rs.)

Year 1	Year 2	Year 3	Year 4	Year 5	Total
525,00,000.00	551,25,000.00	578,81,250.00	607,75,312.50	638,14,078.13	2900,95,640.63

The EBITDA (Earnings before Interest, Tax, Depreciation and Amortization) is observed to be positive in all the operating years, clearly indicating that revenues estimated for the project, in the event BSCL decides to charge user fees for the project, is sufficient to cover the operating and maintenance (O&M) expenses of the project.

Further, the IRR (internal rate of return) for the project was calculated and found to be negative, indicating that the capital cost incurred under the project cannot be recovered from its cash inflows.

Socio-Economic Benefits

The project once developed would be a place for public realm and would give a much needed green recreational zone to the city of Bhagalpur. The economic benefits of the project has to be looked upon in terms of environmental and social aspects rather than in financial terms as the project would emerge as a model for open space development. Benefits are also expected to accrue with the rejuvenation of an old waterbody in the heart of ABD area in the form of a green space for social gatherings and thereby contributing to the enhancement of the liveability of citizens.

The project would directly impact 4 lacks person living in the ABD area as well as the city (source: census 2011). The project is also expected to generate employment opportunities, especially 87 manpower directly employed under the project and 44 persons expected to find employment through the commercial activities proposed in the project. Therefore, it is estimated that the project is expected to impact lives of 131 person directly and indirectly which in turn would affect 655 families altogether.

The socio-economic benefit of the project in terms of health benefits to the users of the project is of high value and thus increases the overall economic benefit of the project. At least 10,000 persons are estimated to use the project facility on a daily basis for recreational and physical activities such as walking, jogging etc.



Open Spaces



8.6 Risks and Allocation of Risks

Identification of Risks

For the purpose of identification and analysis, risks can be categorized into

- Risks encountered during the pre-operative stage of the project
- Risks prevailing during the construction stage of the project
- Risks arising during the Operations Stage of the project
- Risks faced during the Handing-Back Stage of the project and
- Risks prevalent throughout the project.

Table below describes the typical risks associated with an infrastructure project

Table 8.6.1: Typical Risks

Risk type	Description
	Risks During Pre-Operative Stage
Delays in land	Refers to the risk that the project site (or sites) will be
acquisition	unavailable or unable to be used within the required time,
	or in the manner or the cost anticipated or the site will
	generate unanticipated liabilities due to existing
	encumbrances and native claims being made on the site.
	This risk is most relevant to greenfield projects.
External linkages	Refers to the risk that adequate and timely connectivity to
	the project site is not available, which may impact the
	commencement of construction and overall pace of
	development of the project. An example of connectivity
	could be approach roads.
Financing risks	Refers to the risk that sufficient finance will not be available
**	for the project at reasonable cost (e.g. because of changes in
)e	market conditions or credit availability) resulting in delays
	in the financial closure for a project.
Planning risks	Refers to the risk that the pre-development studies
	(technical, legal, financial and others) conducted are
	inadequate or not robust enough resulting in possible
	deviations from the outcomes that were planned or
	expected.
Approvals risks (other	The risk is that the needed approvals will either be delayed
than for construction)	or will not be granted, resulting in additional cost or threat
=	to the project. Such approvals may include transport
	permits, relevant environmental permits etc.
	Risks During Construction Stage

SR MARINE SHART COLL THE STATE OF 102





Risk type	Description
Design risk	Refers to the risk that the proposed design will be unable to
(885)	meet the performance and service requirements in the
	output specification. It can result in additional costs for
20	modification and redesign.
Construction risk	Refers to the risk that the construction of the assets required
	for the project will not be completed on time, on budget or
	to specification. It may lead to additional raw materials and
	labour costs, additional financing costs, increase in the cost
	of maintaining existing infrastructure or providing a
	temporary alternative solution due to a delay in the
,	provision of the service.
Approvals risk	Refers to the risk that delays in approvals to be obtained
11	during the construction phase will result in a delay in the
	construction of the assets as per the construction schedule.
	Such delays in obtaining approvals may lead to cost
	overruns.
	Risks During Operations Stage
Operations and	Refers to the risks associated with the need for increased
maintenance risk	maintenance of assets or machinery over the term of the
	project in order to meet performance requirements.
Volume risk	Refers to the risk that demand for a service will vary from
	the initial forecast, such that the total revenue derived from
	the project over the project life will vary from initial
	expectations.
Payment risk	Refers to the risk that fees for services are not collected in
,	full or are not set at a level that allows recovery of costs.
	Who bears the payment risk depends on whether the fees
	for services are paid directly by users.
Financial risk	Refers to the risk related to high financial stress on a project
	due to an inappropriate financial structure planned for the
	project. It can result in additional funding costs for
	increased margins or unexpected refinancing costs.
	Currency risk can also impact on financial risk if the project
	includes funding denominated in foreign currency.
Environmental health	Refers to the risk of environmental damage in excess of
and safety risk	what is planned for in the environmental impact mitigation
	plan and the risk to employee health and safety from
	operations.
	operation.





Risk type	Description			
	Risks During Hand-Over Stage			
Handover risk /	Refers to the risk that the operator will default in the			
Terminal value risk	handover of the asset at the end of the project life, or that it			
	will fail to meet the minimum quality standard or realisable			
	value of the asset that needs to be handed back to the public			
	entity.			
R	isks Arising Throughout the Project			
Change in law	Refers to the risk that the current legal / regulatory regime			
	will change, having a material adverse impact on the			
	project.			
Force Majeure	Refers to the risk that events beyond the control of either			
	entity may occur, resulting in a material adverse impact on			
	either party's ability to perform its obligations under the			
	PPP contract. These events are sometimes also called "Acts			
	of God", to indicate that they are beyond the control of			
	either contracted party.			
Contractor/operator	Refers to the risk that the contractor/operator will prove to			
risk	be inappropriate or unsuitable for delivery of the project,			
V.	for example due to failure of their company.			
Sponsor risk	Refers to the risk that the Sponsor will prove to be an			
	unsuitable partner for the project, for example due to poor			
	project management or a failure to fully recognise the			
	agreed terms of the contract agreement.			
Government event of	Refers to the risk that the public Sponsor will not fulfil its			
default	contractual obligations and that the contractor/operator			
,	will be unable to either enforce those obligations against the			
-	Sponsor, or recover some form of compensation or remedy			
	from the Sponsor for any loss sustained by it as a result of			
	the breach.			

Risk Allocation

For the purpose of analysis and association of risks, the project is divided into

- 1. Construction phase that includes planning and
- 2. Operations phase that includes hand-over of the project

The project is structured such that it may be tendered on EPC basis, with and O&M contract of 5 years, during which revenue may be collected by BSCL/Authority. Tables below provide the details of risk allocation, during each Phase of the project.

SR. MARKER TECH. 2.

SR. MARKE



Open Spaces



Table 8.6.2: Risk Allocation during Construction Phase

Risk Type	Construction Phase
Pre-operative T	ask Risks
Delays in Land Acquisition	Public Sector
External Linkages	Public Sector
Financing Risks	Public Sector
Planning Risks	Public Sector
Approval Risks	Public Sector
Construction Pl	nase Risks
Design Risk	Public Sector
Construction Risk	Private Sector
Approvals	Public Sector
Additional Site Risk	Public Sector

Table 8.6.3: Risk Allocation during Operating Phase

Risk Type	O&M Phase		
Operations Phase R	isks		
Technology Risk	Not Relevant		
Operations & Maintenance Risk	Private Sector		
Volume Risk	Public Sector		
Payment Risk	Public Sector		
Financial Risk	Public Sector		
Handover Risk Eve	ents		
Handover Risk	Private Sector		

Table 8.6.4: Risk Allocation of Other Risks

Risk Type	Construction Phase	O&M Phase
Change in Law	Public Sector	Public Sector
Force Majeure	Public Sector	Public Sector
Sponsor Risk	Private Sector	Private Sector
Operator Event of Default	Not Relevant	Not Relevant
Government's Event of Default	Not Relevant	Not Relevant

Open Spaces



8.7 Project Phasing

Financing Milestones are drawn in alignment with the project milestones during construction, prescribed for the project. Table below illustrates the milestones.

Table 8.7.1: Milestones

Sl.	Project Milestone (Phase I)
No.	
1	Demolishing Dilapidated Structure, Cleaning of site
2	Construction of Boundary Wall
3	Pathways and Links along-with site drainage
4	OAT and other civil works (construction of toilets, kiosk, entrance, guard room,
	parking)
5	Play Courts development, Cafeteria
6	Development of Theme Parks, City Gym, Nehru memorial
7	Renovation of Station Club, Gym, Cleveland Memorial and other remaining Structures
8	Multipurpose Ground, Plumbing work, Mechanical works, and drainage works.
9	Electrical works (high-mast, bollards, street lights etc.)
10	Landscaping work, signage

MANAGER TECH. 2 SR. MANAGER TECH. 2 BHACALPUR SMART CITYLID.

Open Spaces



9. Environmental Proposals

9.1 Environmental considerations:

The main intent of providing open spaces is to have a healthy living for the city dwellers. The main purpose of this development is to upgrade the existing condition of Sandy's Compound with establishing natural ecosystem with all types of flora and fauna. There is a cultural ecosystem in urban areas which can be seen through the park, playground, water body and others in an urban context. The purpose of development is to create a sustainable urban open space with creating microclimate for the locality of Sandy's Compound area which has a scope to become an important landmark of smart city. Proposal of growing plants in the compound is an important environmental action. Cleaning and desalting of water body is important for establishing a balanced ecosystem.

Proposal of aeration fountain:

Oxygen serves as the most essential component to the health of a body of water. Pond aeration is the simple, yet effective, process of increasing oxygen levels in a pond and can not only greatly enhance the aesthetic beauty of a pond, but can also improve the natural systems taking place beneath the water's surface. Aeration creates desertification of the water column, as lakes and ponds typically consist of stratified layers separated mainly by different temperature and oxygen levels. Natural resource and environmental managers are often challenged by problems caused by lake and pond stratification. The main purpose of aeration is to increase and stabilize the amount of dissolved oxygen in the entire water column and this has a widespread effect on many different aspects of pond and lake health.

Planting of Native trees:

Planting native species of trees and shrubs helps to re-establish the original eco-system of the region. Native species crate natural corridors or islands in the urban landscape for migrating wildlife. Many species of wildlife do not recognize non-native species and cannot use them for food or shelter. The native trees are adapted to the region's soil, hydrology, and climate and have evolved defences to many diseases and insect pests. It also creates deep and extensive root systems, which help to stabilize the soil column and create an environment favourable to building fertile soils rich in organic matter. It is beneficial because it absorbs excess nutrients from runoff, enhancing infiltration during periods of heavy rain as well as drought and also provide habitat for butterflies, birds, songbirds, and beneficial insects.



Open Spaces



Also the site is full of Eucalyptus Trees. The plantations, mainly of E. globulus and sometimes its clones, are also controversial. They are accused of a gamut of sins: depleting groundwater, fostering fires, encouraging erosion, vitiating watersheds, deterring native flora with voracious roots and allelopathy, etc.

Eucalyptus depletes the nutrients and moisture reserves of the soil and inhibits the undergrowth due to allopathic properties. Furthermore the decomposition of the dead plant parts is very slow which adversely affects the nutrient cycling. Owing to these adverse effects, Eucalyptus is often referred as "Ecological Terrorist". Taking this into consideration these trees can be removed from site after taking approval from Forest and Environmental Departments.

City microclimate:

Water bodies creates a microclimate for the area by decreasing the temperature by 0.5 to 2 degrees. Water bodies affect the overall microclimate of an area by increasing the humidity in the area. The water body has its own micro watershed. Selection of trees and shrubs has been done in such a manner that the carbon sequestration is high and it becomes an absorbent for pollution thus reducing the chances of Urban Heat Island.

Anticipated Environmental Impacts and Mitigation Measures:

CONSTRUCTION PHASE

Table 2: Anticipated Environmental Impacts and Mitigation Measures

SL.	COMPONENT	IMPACTS IDENTIFIED	SUGGESTED MITIGATION		
NO.	And the second		MEASURES		
1	AMBIENT AIR QUALITY	The location is close to the river Ganges. The river has receded from the existing location creating a large area of sedimentation and due to that there is presence of large amount of particulate matter in the surrounding ambient air quality and may cause to be a threat in maintaining the	spraying and sprinkling of water regularly		
		prescribed standards.			
2	SOCIO	The following points are	Optimal water		
	ECONOMIC	considered under socio-	conservation measures		
		economic condition: to be adopted along			

SHAGALPUR SMART CITY LIVE Page 100 of 102





and agreement			BHAGALPUR			
SL.	COMPONENT	IMPACTS IDENTIFIED	SUGGESTED MITIGATION MEASURES			
NO.		 pressure on local water resources Problem of disposal of solid and liquid waste Contamination of surface and groundwater Sediment runoff 	with adequate awareness programs for the people of the area Restriction on random disposal of wastewater Adequate drains and collection sumps need to be provided Sufficient nos. of slopes and drainage channels are to be provided for disposal of liquid wastes All waste to be handled as per applicable regulations Waste to be segregated in biodegradable and non-biodegradable parts and to be handled and disposed off in accordance with the regulatory requirements			
3	Landscape and Topography	Construction of pathways and landscape area.	 Land surface contours to be made in an aesthetic manner Greenbelt and green buffers may be developed to improve the landscape and beautification 			
4	Water Resources and Quality	 Change in topography and alteration of drainage pattern Additional pressure on local water resources 	 Water for construction phase to be sourced from existing sources allocated to project Proponent 			





SI COMPONENT IMPACTS IDENTIFIED SUCCESTED MITICATION						
NO. MEASURES						
SL. NO.	COMPONENT	due to water requirement for construction work and labour camps Sediment run off from construction area Disposal of sewage from construction camps Contamination of surface and groundwater	supplem authorize Optimal conserva at camp s with adea awareness programs organized workers Adequate toilets (at toilets per with sept soak pit at to be provided campsites Adequate collection provided campsites Sludge from water treat systems to off proper Regular redebris from constructing practiced	tion measures sites along quate as mes to be disposal of er from donies to be around om waste atment to be disposed of the dis		
			away from water drai	n the storm n.		
			VII and gr	ease geffluents to		
away from the storm water drain. Oil and grease Cit containing effluents to Page 102 of 102 BHASH PIRSH PIRSH PAGE 102 of 102						





SL.	COMPONENT	IMPACTS IDENTIFIED	SUGGESTED MITIGATION MEASURES
			be pre-treated before discharge. • Silt traps and bunds to be set up around construction sites. • Adequate slopes and drainage channels to be provided across the project site.
5	Soil Resources	 Soil Erosion and compaction Soil contamination 	 Top soil to be preserved and relocated after construction activities. Clearance of vegetative cover to be minimized to the extent possible and redeveloped later on. Site grading and excavation to be undertaken during dry season. Dikes, berms, drainage swales or ditches to be provided to divert surface run-off. A retention wall or bund to be provided around the storage areas for excavated soil and other construction material. Completed earth work to be sealed and/or revegetated at the earliest with the help of landscape expert.





SI. COMPONENT IMPACTS IDENTIFIED SUGGESTED MITIGATION MEASURES Stacking of excavated soil material will be made only in earmarked areas. Excavated soil to be used/transported at the earliest for filling low lying areas. Proper routing and adequate capacity of the storm water runoffs drains to be provided. Movement and parking of heavy machinery and vehicles to be restricted to identified areas. Area used for parking purposes to be restored immediately after completion of each project activity. All storage facilities to be designed with paved surface, provided with covered shed and adequate containment facility at the construction. All waste to be handled as per applicable regulations. Hazardous waste to be handled and disposed off in accordance with the requirements of Hazardous Waste
soil material will be made only in earmarked areas. Excavated soil to be used/transported at the earliest for filling low lying areas. Proper routing and adequate capacity of the storm water runoffs drains to be provided. Movement and parking of heavy machinery and vehicles to be restricted to identified areas. Area used for parking purposes to be restored immediately after completion of each project activity. All storage facilities to be designed with paved surface, provided with covered shed and adequate containment facility at the construction. All waste to be handled as per applicable regulations. Hazardous waste to be handled and disposed off in accordance with the requirements of Hazardous Waste
All on Lazardous waste





SL. NO.	COMPONENT	IMPACTS IDENTIFIED	SUGGESTED MITIGATION MEASURES
			Management Rules2016. Portable spill containment and cleanup equipment to be made available at construction site and training for use of such equipment to be imparted. Provision of covered bins at camp sites. Waste to be segregated in biodegradable fraction. Biodegradable waste to be used for animal feed/vermin- compost/manure. Contaminated sand/soil shall be prevented during construction activities. Trainings to be imparted to all workers and subcontractors regarding hazardous waste storage and disposal procedures. On completion of construction activities, septic tanks for camp sites to be abandoned and filled with earth.





Traffic and Transport Increased traffic volume Damage to existing urban roads Disruption of traffic and increased cases of road related hazards Traffic and heavy machinery movement schedule to be communicated clearly to the local inhabitant's Prior consultation with local authorities to be undertaken. Movement of heavy vehicles to be taken up only during day time in the construction site near habitation areas. Providing dedicated path within the site for entry and exit of the construction vehicles. Roads damaged due to project vehicles will be continuously repaired. Provision of adequate training to drivers. Dedicated parking area to be provided area for project vehicles. Parking along footpaths, single lane roads shall be prohibited. Detailed plan for signage around the construction areas to be prepared to the properties of the construction areas to be prepared to the provided area for project vehicles.
movement.





and the second						
SL. COMPONE	OMPONENT IMPACTS IDENTIFIED			SUGGESTED MITIGATION MEASURES		
7 Ambient N	Ioise • N	Voise due to		Inventory of vehicles used and construction equipment of their PUC's maintained.	ed in project ction along with to be	
quality	e e p	onstruction ctivities(such as xcavation, grading, recting equipment, viling, etc) Noise due to operation of heavy equipment and machinery Movement of vehicles		avoid high is activities to undertaken. Acoustic en noise barries provided in high noise grounds. Movement of during night limited. Construction to use ear implugs in the potential for generation. Regular main of vehicles as of equipment of vehicles are receptors. Restriction of equipment grounds high noise dinight time. Working how construction	noise be nclosures, rs to be areas of generating of vehicles t time to be n workers uffs/ear areas with high noise ntenance nd repair nt. rs will be tween the d the on use of generating uring urs and	



Open Spaces



NO. MEASURES	man de fano.		BHAGALPUR
8 Labour camp management • Location of labour camps • Domestic solid waste generation • Firewood for cooking and burning of garbage • Indoor air quality issues • Waste water generation • Health and hygiene issue • Waste water generation • Health and hygiene issue • Random disposal of wastewater from labour colonies to be restricted • Adequate drains and collection sumps to be provided around campsites • Regular removal of debris from construction site to be practiced • Integrated solid waste management plan will be developed for		IMPACTS IDENTIFIED	A secretary measurement of the secretary
transportation,	NO. 8 Labour camp	 Location of labour camps Domestic solid waste generation Firewood for cooking and burning of garbage Indoor air quality issues Waste water generation Health and hygiene 	to be aligned and works to be prohibited during night. Optimal water conservation measures at camp sites along with adequate awareness programmes to be organized for the workers Adequate number of toilets (at least 8-10 toilets per 100 labours) with septic tanks and soak pit arrangements to be provided onsite. Random disposal of wastewater from labour colonies to be restricted Adequate drains and collection sumps to be provided around campsites Regular removal of debris from construction site to be practiced Integrated solid waste management plan will be developed for collection,

W OF WARANASER FECH, LTD.

BHAGALPUR SWARTCHY LTD.

BHAGALPUR SWARTCHY LTD.





Open Spaces

SL.	COMPONENT	IMPACTS IDENTIFIED	SUGGESTED MITIGATION MEASURES
9	Occupational Health and Safety	 Injury due to improper handling, operation and execution Trip and fall, inadequate fall safe arrangements Exposure to hazardous substances 	 Workers to be provided with health and safety training. Safety measures, including use of temporary fall protection and out edges of elevated work surfaces, such as hand rails and to be boards to prevent materials from being dislodged shall be done for workers while working at heights. First aid and essential medical services to be provided at site. Manual transfer of heavy loads to be minimized by proper work site lay out. Good housekeeping practices to be exercised. Measures such as job rotations and stretch breaks to be adopted. Proper signage to be provided around construction site. Use of personal protection Equipment (PPEs) to be mandated at worksite. Workers to be provided with health and safety training.



Open Spaces



SL. NO.							
			 Use of temporary fall protection measures in scaffolds and out edge of elevated work surfaces, such as hand rails and toe boards to prevent materials from being dislodged shall be done. Safety harness to be ensured for workers while working at heights. First aid and essential medical services to be provided at site. 				
10	Employment and local Economy	 Increased employment opportunities Contracting opportunities for locals Better avenues for small scale service providers 	 Project to utilize the facilities available from the local market to support the local economy to the extent possible Wherever possible, labour from local community will be employed for project 				
11	Ecology	Loss of trees and ground vegetation	 Original soil profile shall be retained by storing each excavated layers separately and restoring it later. Tree felling to be minimized to the 				
	extent possible. Contractors shall be instructed to practice instructed to practice SHAMARIER OF TO THE SAME. Page 110 of 102						



Open Spaces



SL. NO.	COMPONENT	IMPACTS IDENTIFIED	SUGGESTED MEASURES	MITIGATION
			away fro bodies , run off a • Standard to be ma	be stored om water streams and reas. I noise levels intained onstruction

9.2 Resettlement proposals

Legislations applicable

As the construction has been proposed mostly along the existing government land, the extent of potential impact in terms of land and structure is expected to be minimal. Notwithstanding, the necessity of a framework to ensure mitigation of any negative impacts, as well as compliance with the state and national legal policy cannot be overstated.

The Legislations of State / National acts, policies and rules applicable for Sandy's Compound Development Project regarding land acquisition (if required) and Resettlement and Rehabilitation (R&R) are summarized in the following sections.

In case of Land acquisition (if applicable/Required)

- Bihar Raiyati Land Lease policy 2014.
- Bihar Right to Fair Compensation and Transparency in Land Acquisition, Rehabilitation and resettlement rules 2014.
- The Right to Fair Compensation and Transparency in Land Acquisition,
 Rehabilitation and Resettlement Act, 2013 (LARR act 2013)

Open Spaces




10. Conclusions and recommendations

- i. The park is designed with the purview of the cultural context of the city.
- ii. The proposal has been modified and designed in order to cater the local population of Bhagalpur along with emphasis on local tourism sector.
- iii. The design has focus on sustainable use of existing Landscape while keeping in view the surrounding areas and their relation with their users.
- iv. For development of Play courts permission with related sports authority should be taken beforehand.
- v. Water bodies and Landscape will have to be periodically checked and cleaned for a sustainable ecosystem.

As per direction we will submit RFP and after the approval of this DPR, then tender shall be floated. The work will be executed by the successful bidder under the supervision of implementing agency. The smart city proposals are to be completed in 3 years, but for this project the contractor will complete all works within 24 months only. The same contractor will operate and maintain this park for 3 year under the direction of BSCL/Bhagalpur Nagar Nigam.


SR WANAGER TECH 2 SR WANAGER TECH 2D.







0 \bigcirc \bigcirc



























 \bigcirc \bigcirc \bigcirc \bigcirc







 \bigcirc
















0 \bigcirc () \bigcirc \bigcirc 0 0 \bigcirc U 0 \bigcup






















CITY GYM & DOORDARSHAN KENDRA SANDY'S COMPOUND 3 Project code : 00 DEVELOPMENT OF SANDY'S PARK CALL MANAGEMENT REPORT LAND SP/LA/AR-01 THENT PATNASMART CITY LTD DRAWING TITLE: 0098 TOILET 3000 X 1500 K jeans ch. room 3350 X 1800 3350 Ladies Changang Room PASSAGE 15053 X 1300 CAR PARKING Toilet 2000 x 3000 STORE 3630 X 3000 DOORDARSHAN KENDRA 0919 7150 OFFICE 5200 X 4500 Ground Floor Plan 2800 2200 OFFICE 4350 X 4500 ENT LOBBY 14050 X 6850 CITY GYM GYM 21500X7900 ENTRY 0099 25450 OFFICE 4800 X 4500 14050


ENTRY 3000 OFFICE 4100 X 4030 0064 Store Room 3540 X 1760 GYM Office 3550 X2500 STORE ROOM 3700 X5430 4140 CAR PARKING Store 0098

SR MAANDER TECH. 2
BHAGALPUR SMART CITY LTD. BHAGALPUR





























 \cap \cap \bigcirc \bigcirc \bigcirc \bigcirc \bigcirc 0 \bigcirc \cup \bigcirc

PROJECT MANAGEMENT COPE
SANDYS PARK

CHEST
PATRA SAMPT CITY LTD

ROBELT MANAGEMENT CITY LTD

THORET MANAGEMENT CITY LTD

THORET MANAGEMENT CITY LTD

THORET MANAGEMENT CITY LTD

THORET MANAGEMENT CITY WARTH CITY CHEST
THORET MANAGEMENT CITY CHEST
THORET CHEST
THORE



SR. MANAGER TECH. 2
SR. MANAGER TECH. 2
SHAGALPUR SMART CITY LTD.
BHAGALPUR
BHAGALPUR

SCALE



SL.NO	DESCRIPTION OF WORK	UNIT	ITEM RATE	QUANTITY	AMOUNT
1	Walk Way	No.	32,432,853	1.00	₹ 32,432,853
2	Guard Room Cum Ticket Counter	No.	333,619	4.00	₹ 1,334,475
3	Electrification of Guard Romm Cafeteria (PROPOSED)	No.	75,731	4.00	₹ 302,924
4	, , , , , , , , , , , , , , , , , , , ,		11,816,245	1.00	₹ 11,816,245
5	Landscaping	No.	14,165,726	1.00	₹ 14,165,726
6	Kids Play Area	No.	2,443,883	1.00	₹ 2,443,883
7	Nehru Memorial	No.	690,760	1.00	₹ 690,760
8	Station Club	No.	15,024,091	1.00	₹ 15,024,091
9	Specific/Emergency Gate	No.	728,670	13.00	₹ 9,472,712
10	Entrance gate	No.	8,501,469	1.00	₹ 8,501,469
11	Swimming Pool	No.	15,628,608	1.00	₹ 15,628,608
12	Swimming Pool Mech and Other	No.		1.00	
	Parking	No.	23,375,713		₹ 23,375,713
13	Open Air Theatre	No.	8,761,104	1.00	₹ 8,761,104
14	Basket Ball Court	No.	3,337,764	1.00	₹ 3,337,764
15	Trellis walkwWay	No.	1,546,828	1.00	₹ 1,546,828
16			1,127,421	1.00	₹ 1,127,421
17	Renovation of Existing Badminton court	No.	7,848,161	1.00	₹ 7,848,161
18	New Badminton Court Building	No.	11,831,450	1.00	₹ 11,831,450
19	Gym Building renovation	No.	17,652,741	1.00	₹ 17,652,741
20	Lawn Tennis Court	No.	1,216,407	1.00	₹ 1,216,407
21	Cricket Field and its Drainage	No.	16,860,937	1.00	₹ 16,860,937
22	Cleaveland Memorial	No.	2,470,690	1.00	₹ 2,470,690
23	Toilet (BIG)	No.	1,997,553	1.00	₹ 1,997,553
	Multipurpose ground	No.			₹ 35,975,314
24	Scuplture court	No.	35,975,314	1.00	
25	Dismantelling of Boundary Wall	No.	2,839,915	1.00	₹ 2,839,915
26	Boundary wall EXTERNAL	No.	1,960,462	1.00	₹ 1,960,462
27	Boundary Wall Internal	No.	11,792	2,550.00	₹ 30,069,600
28	Estimate of Sports Complex Lighting	INO.	6,039	1,010.00	₹ 6,099,791
20	(Proposed Item only)	No.	15,793,523	1.00	₹ 15,793,523
29	ESTIMATE of GENERAL LIGHTING	No.			
30	(Proposed Item only) SUB TOTAL		18,842,125	1.00	₹ 18,842,125
31					₹ 321,421,245
32	Operation and Maintenance costs for three year (Include this in RFP)			6%	19,285,27
	Total DPR Cost			070	-
33	Centage (7%- 0 to 10 Cr & 5%-10 to 100 cr)	-	ana VID	TED TED	340,706,519.4 18,071,06
34	Total Project Cost		X	MADE!	14/10.
			all "	BHAGALPUR	``₹ 358,777,582



		Cons	structi	Construction of Walk Way	lk Way					
S.No	Code	Description	Unit	Ž	Longit	147: 351				
	RCD 2019	Cutting of Trees, including Cutting of Trunks, Branches and Removal (Cutting of trees, including cutting of trunks, branches and removal of stumps, roots, stacking of sequing of stumps, roots,				Width	Height	Quantity	Rate (Rs)	Amount (Rs)
1	2.1.1	depression/pit.) Girth from 300 mm to 600 mm	Nos.	65	ı	3	1	65	250	₹ 16,250.00
3		Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well es 10 sqm on plan)								
7	2.6.1	including disposal of excavated earth, lead upto 50 m and lift upto 1.5 m; disposed earth to be levelled and	Cum	Н	3980	3.8	0.3	4537.2	279.1	₹1,266,332.52
		uressed upplying and Filling in plinth with local sand and								
3	2.28	under floors including, watering, ramming consolidating and dressing complete.	Cum	1	3980	3.8	0.075	1134.3	238.6	₹ 270.643 98
		Providing designation 100 A one brick flat soling joints								
4	11.72	filled with local sand including cost of watering from	(*		
		complete as	Sqm	ı	3980	3.8		15124	277.5	₹ 4,196,910.00
		Providing and laying in position cement concrete of								
D.	4.1.5	specified grade exluding the cost of centring and shuttering-all work upto plinth level. 1:3:6 (1 Cement: 3 coarse sand: 6 graded stone	Cum	1	3980	3.8	0.15	2268.6	3461.4	₹7,852,532.04
		40 11:11								
9	11.29.1	**O IIIII UNCK rough chised dressed stone flooring over 20 mm (average) thick base including pointing with C.M 1:2 (1 cement :2 stone dust) with an admixture of pigment to match								
ca.N		the shade of the stone with base 1:1:1 (1 lime : 1surkhi : coarse sand or 1:5 (1 cement : 5 coarse sand) Rend Sand Stone	Sqm	1	3980	3.6		14328	753.1	₹ 10,790,416.80

CR NANACE PROCHED.

BHACALPUR SMART CITYLID.

BHACALPUR

		Con	tructio	Construction of Walk Way	k Way					
S.No	Code	Description	Unit	No	Length	Length Width	Height	Ouantity	Rate (Rs)	Amount (Re)
7	4.1.3	Providing and laying in position cement concrete of specified grade exluding the cost of centring and shuttering-all work upto plinth level. 1:2:4 (1 Cement: 2 coarse sand: 4 graded stone aggregate 20 mm nominal size)	Cum	2	3980	0.1	0.15	119.4	4151.4	₹ 495,677.16
00	Gem Portal	Gem Sitting Arrangements Portal Product id: 5116877-58242510321	Nos.	50				20	13500	₹ 675,000.00
		Sub Total								₹ 25,563,763
		Carriage Cost								₹ 6,869,090
		Total Cost of Walk way								₹ 32,432,853

	1	ESTIMATE OF GUARD ROOM Cum	Ticket Count	er		
S.No	BCD SOR 2018	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT (Rs.)
1	2.6	Earth work in excavation over areas (exceeding 30 cm is depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m; disposed earth to be levelled and neatly dressed.	g			
	2.6.1	All kinds of soil	cum	22.50	279.10	6280.00
2	2.26	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers no exceeding 20cm in depth: consolidating each deposited layer by ramming and watering lead.	t d	14.46	103.30	1493.00
3	2.28	Supplying and filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete.	d cum	4.39	238.60	1047.00
4	4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work upto plinth level.				
	4.1.6	1:3: 6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40 mm nominal size)	cum	2.66	3307.00	8805.00
5	BCD SOR 6.1.12C+6.3C	complete as per building specification and direction of E/I (with fly ash Brick).				
	6.1.14A	Cement mortar 1:4 (1 cement : 4 coarse sand)	cum	13.59	4799.20	65231.00
7	Item no. 5.33A.1	Reinforced Cement Concrete Works Providing and laying in position machine batched, machine mixed and machine vibrated design mix cement concrete of specified grade for reinforced cement concrete structural elements, excluding the cost of centring, shuttering, finishing and reinforcement, M-20 grade reinforced cement concrete				
		All work upto plinth level Reinforcement for RCC work including straightening.	cum	1.86	4924.00	. 9164.00
8	5.22	Cutting, bending, placing in position and binding all complete.				
	5.22.7B	Thermo-Mechanically Treated bars TMTC-500-10 mm dia.	kg	146.09	76.70	11205.00
	5.90	Centring and shuttering including strutting, propping etc.		110.07	70.70	11205.00
9		and removal of form for: Walls (any thickness) including attached pilasters.	oam.	17.49	321.30	5(10.00)
	5.9.2 Item no. 4.1.8	Butteresses, plinth and string courses etc. Providing and laying in position cement concrete of	sqm	17.49	321.30	5618.00
10		specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	cum	0.73	2940.80	2150.00
		Flooring Work				
11	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer -in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Motar 1:3 (1cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	Sqm	28.50	739.80	21084.00
2	11.27	Kota stone slabs 25 mm thick in risers of steps, skirting, dado and pillars laid on 12 mm (average) thick cement mortar 1:3 (1 cement : 3 coarse sand) and jointed with grey tement slurry mixed with pigment to match the shade of the slabs, including rubbing and polishing complete.	Sqm	1.52	1133.90	1724.00
3	12.11	Plaster & Finishing Works			\wedge	
3		2 mm cement plaster of mix :4 (1 cement : 4 coarse sand)	sqm	67.99	139.90	9512.00
4	13.12	5 mm cement plaster on rough side of single or half brick vall of mix.	1			PER TEN
	13.12.2 1	:4(1 cement: 4 coarse sand)	sqm	39.26	161.90	6356.00
5 L	13.24 6	mm cement plaster to ceiling of mix.			F. 180 10	· Will Children

		ESTIMATE OF GUARD ROOM Cum Ti	icket Counter	r		Ţ
S.No.	BCD SOR 2018	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT (Rs.)
10	13.24.2	1:4 (1 cement : 4 coarse sand)	sqm	9.99	110.90	1107.0
16	13.79	Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade				
	13.79.1	New work (three or more coats)	sqm	117.24	68.30	8007.00
17	22.8	Waterproofing Providing and laying integral cement based water proofing treatment including preparation of surface as required for treatment of roofs, balconies, terraces etc consisting of following operations:				
	22.8.1	With average thickness of 120mm and minimum thickness at Khurra as 65 mm.	sqm	9.99	2553.30	25496.00
18	9.20	Providing and fixing ISI marked flush door shutters decorotive type core of block board construction with frame of 1st class hard wood and well matched teak ply veneering with vertical grains or cross or cross bands and face veneers on the both faces venears on the both face of shutters.				
	9.20.2	30mm thick including stainless steel butt hinges with necessary screws	sqm	3.72	2474.40	9205.00
19	9.1	Providing wood work in frames of doors, windows, clearstory windows and other frames, wrought framed and fixed in position				
-	9.1	Second Class teak wood	cum	0.20	95749.10	19389.00
20	9.53	Providing 40 x 5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size)	each	18.00	106.60	1919.00
21	9.96	Providing and fixing aluminium sliding door bolt anodised (anodiccoating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with nuts and screws etc.				
	9.96.1	300 x 16 mm	each	1.00	220.40	220.00
22	9.100	Providing and fixing aluminium handles anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete:				
	9.100.1	125 mm	each	6.00	54.00	324.00
23	9.101	Providing and fixing aluminium hanging floor door stopper anodized (anodic coating not less than grade AC 10 as per IS :1868) transparent or dyed to required colour and shade with necessary screws etc. complete.				
	9.101.2	Twin rubber stopper	each	2.00	40.40	81.00
24	9.97	Providing and fixing aluminium sliding tower bolt anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with nuts and screws etc.				
	9.97.1	300 x 10 mm	each	1.00	67.80	68.00
25	9.9	Providing and fixing glazed shutters for doors, windows and clerestory windows using 10kg/square meter (4mm thick) glass panes including black enamlled M.S butt hindge with necessary screws.				
		30 mm thick	sqm	0.90	1975.90	1778.00
26	10.18 s i	Providing and fixing circular cast iron box for ceiling fan clamp 140 mm internal dia, 73 mm height, 5 mm thick rim bottom and top lids, 1.5 mm thick M.S sheet with its top surface hacked for proper bonding top lid shall be screwed into the cast iron box by means of 3.3 mm dia round headed screws, one pcf at the corners. Clamps shall be made of 12mm dia M.S. bar bent to shape as per standard drawing.	each	2.00	141.30	283.00
27	13.81.1 k	With ready mixed pink or grey primer of approved brand and manufacture on woodwork (hard and soft wood)	sqm	8.78	32.20	283.00
28	13.93 a	Painting with synthetic enamel paint of approved brand and manufacture to give an even shed. Two or more coats on new work	sqm	8.78	70.40	618.00

 \cap

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc


 \bigcirc

		ESTIMATE OF GUARD ROOM Cum T	icket Counte	or		
S.No.	BCD SOR 2018	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT (Rs.)
29	18.48	providing and placing on terrace (at all floor levels) polytheline water storges tank, ISI:12701 marked, with cover and sutaible loking arrangment and making necessary holes for inlet, Outlet and over flow pipes but without fittings and the base support for tank.	Litre	1000.00	7.90	7900.00
	17.32	Providing and fixing mirror of superior glass (of approved quality) and of required shapes and size with plastic moulded frame of approved make and said with 6mm thick hard.				
30	17.32.3	Oval shape 450 x 350 mm Mirror	Nos.	4.00	744.60	2978.00
		Sub Total				229,325
		Carriage Cost				28,563
31		Internal electrification				75,731
entren de marco			GRA	ND TOTAL		333,619
	Analysis	Carriage				
	А	Brick	Per Thousand	5832.79	767.08	4474.22
33	В	Local Sand	Cum	4.58	262.05	1200.84
33	С	Coarse Sand	Cum	8.62	1030.3	8876.35
	D :	Stone Chips	Cum	4.10	2701.3	11071.92
[Е	Cement	Cum	8.93573496	328.25	2933.16
	F	Steel	Cum	0.02	328.25	6.23
	Water water and the same		GRA	ND TOTAL		28,562.72

SR. MANAGER TECH. 2

BHAGALPUR SMART CITY LTD.

BHAGALPUR SMART CITY LTD.



		APPENDIX-5 A	D BC	017		
	T	ELECTRIC work Wiring and Light of GUAR			T	Amour
S.No	SOR Coo	de Description	Un	it Qty	. Rate (R	(Rs.
1	BCD Ele SOR 2018 Item 1.3.	single core cable in surface/ recessed medium class PV conduit, with modular switch, modular plate, suitable size G.	or C	s. 10	72	
2	BCD Ele SOR 2018 Item 1.5	recessed medium class PVC conduit alongwith 1 No 4 sq. mi	C / n		200	
3	BCD Ele. SOR 2018 Item 1.7.2	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FR PVC insulated copper conductors single core cable in surface/ recessed medium class PVC conduit as required, 2 X 2.5 sq. mm + 1 X 2.5 sq. mm eart	h :,		163	
4	BCD Ele. SOR 2018	conduit along with accessories in surface/ recess including		30	16.	8,030.00
5	Item 1.21.2 BCD Ele. SOR 2018,	conduit as required. 25 mm Supplying and fixing following modular switch/socket on the	Mete	r 20	79	1,580.00
	Item 1.24.1	excluding modular plate etc. as required. 5/6 amps switch	Each	2	81	162.00
6	BCD Ele. SOR 2018, Item 1.24.4	lovely ding modular plate at an annial 2 F/	t	2	122	244.00
7	BCD Ele. SOR 2018, Item 1.24.6	Supplying and fixing following modular switch/socket on the existing modular plate & switch box including connection but excluding modular plate etc. as required. Telephone socket		4		
8	SOR 2018,	outlet Supplying and fixing stepped type electronic fan regulator on the existing modular plate/ switch box including connections but excluding modular plate etc. as required.			359	108.00 359.00
9	BCD Ele. SOR 2018, Item 1.31	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess including providing and fixing 3 pin 5/6 A modular socket outlet and 5/6 A			337	337.00
10	SOR 2018, Item 1.32	modular switch, connections, painting etc. as required. Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess including providing and fixing 6 pin 5/6 & 15/16 Aampsmodular socket outlet and 15/16 amps modular switch, connections, painting etc. as			362	362.00
	BCD Ele.	required. Supplying and fixing 2 pin, 6 amp ceiling rose on the existing junction box/ wooden block including connection etc as required.	Each Each	7	413	826.00 294.00
12	BCD Ele. 5OR 2018, Item 2.8.7	Supplying and fixing following way, single pole and neutral, sheet steel, MCB distribution board, 240 V, on surface/ recess, complete with tinned copper bus bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator), 2+6 way. Double door	Fach	1	1081	1 081 00
3 5	BCD Ele. 6 6OR 2018, ftem 2.12.1	Supplying and fixing following rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. 6/32	Each	MAN 5. 10	GERTES	H. 2 MYLTD. 960.00

amps, Single pole

LOOD THE COLUMN

				Tota	al Amount	75,731.00
		and terminal sealing, including making connection,testing etc. as required. up to 60 ampere three phase meter	Each	1	5156	5,156.00
24	2017, Item	meterology, electromechanical counter, cover plate for body				
24	RUIDP	1/ 0.5 accuracy class, LED indicators for tamper operation (Reverse &/or earth connection), pulsating LED indicator for				
		static watt-hour meter (kwh) having resolution 0.1/ 0.01 kwh,				
	67.40.2	P&F of IP51 direct or CT operated, 1x240/ 3x240 volts, 50 Hz	Nos.	1	204/	4,047.00
23	Ele. SOR 2017, Item	including the cost of fixing with nut, bolts etc as required. 5		1	2647	2,647.00
	12	of loop, all as per standard design complete. Providing and fixing charged ABC type fire extingusher	Each	1	124.45	124.00
22	DSR Civil SOR 2014,	Providing and fixing M.S. fan clamp type I or II of 16 mm dia M.S. bar bent to shape with hooked ends in R.C.C. slabs, beams during laying including painting the exposed portion		1	124.45	124.00
21	BCD Ele. SOR 2018, Item 2205	3.5 core, 25 sq. mm, XLPE/PVC insulated PVC. sheathed (Heavy duty) Armoured electric cable with aluminium	MTR	<i>7</i> 0	126	8,820.00
20	BCD Ele. SOR 2018, Item 8.11.2	Supply and installation of Regular/ standard model A.C ceiling fan of 1200 mm sweep including wiring the down rods of standard length (upto 30 cm) with 1.5 sq. mm FR PVC insulated copper coductor etc. as required.		1	1618	1,618.00
19	SOR 2018,	Laying of one number PVC insulated and PVC sheathed/ XLPE power cable of 1.1 KV grade of following size direct in ground including excavation, sand cushioning, protective covering and refilling the trench etc as required. Upto 35 sq. mm	mtr	70	144	10,080.00
18	1	Supplying and fixing single 40/45 watt LED type street light with die cast aluminium housing for ingress protection of IP65 and complete with all accessories etc, on pole/building including connection with FR PVC insulated copper conductor cable and earthing the body etc. as required.		1	4056	4,056.00
17	BCD Ele. SOR 2018,	Supplying and fixing single wall/ ceiling mounted 20/22 watt LED type batten fitting complete with electronic driver and LED tube etc directly on wall/ ceiling including connection with 1.5 sq. mm FR PVC insulated copper conductor cable and earthing the body etc. as required.	Each	5	684	3,420.00
16	BCD Ele. SOR 2018, Item 3.15	Providing and fixing 25 mm X 5 mm G.I strip on surface or in	Meter	10	150	1,500.00
15	BCD Ele. SOR 2018, Item 3.2	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/coke and salt as required.	set	1	5125	5,125.00
14	BCD Ele. SOR 2018, Item 2.30	Supplying and fixing TPN sheet steel enclosure on on surface/recess along with 63 amps 415 volts, "C" curve TPN MCE complete with connections, testing and commissioning etc. as required.	Each	1_	1919	1,919.00

 \cap

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

0

0

Û

APPENDIX- 6

<u></u>	т	Cafeteria in San	dys PARI	K (Civil)			
SL. NO		DESCRIPTION	UNIT	QTY.	Rate	AMOUNT	Ref.
I	15.3	Demolishing R.C.C. work including stacking of stee bars and disposal of unserviceable material withing 50 metres lead:		93.80	1172.70	109999.26	SOR Item
2	15.5	work (Payment shall be made on the cross sectional area of R.C.C. or R.B. work)	per RCC	40.00	406.20	16248.00	SOR Item
3	15.7	Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead:					
4	15.7.4 15.60			619.724	685.10	424572.91	SOR Item
5	2.29	Surface dressing of the ground including removing vegetation and inequalities not exceeding 15 cm deep and disposal of rubbish, lead upto 50 m and lift upto 1.5 m		713.524	142.50	101677.17	SOR Item
)	2.29.1	All kinds of soil.	100sqm	3.46	1126.90	3900.31	SOR Item
6	2.8	Earth work in excavation in foundtion trenches or drains (not exceeding 1.5m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift up to 1.5m, including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50m.	,				
-	2.8.1	All kinds of soil	Cum	328.56	319.60	105008.93	Quoted Rate
7 8	2.26	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth, consolidating each deposited layer by ramming and watering lead. Extra for every additional lift of 1.5 m or part thereof in	Cum	193.74	103.30	20013.41	SOR Item
7	2.27.1	All kinds of soil	Cum	28.85	41.00	1182.95	SOB Item
9	2.28	Supplying and Filling in plinth with local sand and under floors including watering, ramming consolidating and dressing complete.	cum	252.22	238.60	60180.81	SOR Item Quoted Rate
20	2.35	Supplying chemical emulsion in sealed containers including delivery as specified. Chlorpyriphos/Lindone emulsifiable concentrate of 20%					
))1		Providing and laying in position cement concrete of specified grade excluding the cost of centering and	litre	485.84	199.40	96876.21	SOR Item
ــــــــــــــــــــــــــــــــــــــ	4.1.3	shuttering-All work up to plinth level: 1:2:4(1 Cement:3 coarse sand: 6 graded stone aggregate					
)	4.1.8	20mm nominal size) 1:4:8(1 Cement: 4 coarse sand:8 graded stone aggregate	cum	22.16	4151.40	92009.26	SOR Item
2	4.3	40 mm nominal size) Centering and shuttering including strutting, proping etc. and removal of form work for:	cum	26.10	2940.80	76766.16	Quoted Rate
	4.3.1	Foundations, footings, bases for columns	Sqm	74.90	185.90	13923.82	SOR Item
3		Providing and laying damp-proof course 50mm thick with cement concrete 1:2:4(1 cement: 2 coarse sand: 4 graded stone aggregate 20mm nominal size).	Sqm	22.65	245.50	5560.24	SOR Item SOR Item SOR Item SOR Item
)		Page	1 of 9			RHAGALTUR	MCALPUR
į.		. ugo				P. D.	V

14	4.12	Extra for providing and mixing water profing material in					
		cement concrete work in the proportion recommended	1				con t
		by the manufacturers.	cement	7.25	52.35	379.41	SOR Item
15	4.17	Making plinth protection 50mm thick of cement				11	
		concrete 1:3:6(1 cement:3 coarse sand:6 graded stone					
		aggregate 20mm nominal size) over 75mm bed dry brick					
		ballast 40mm nominal size well rammed and					
		consolidated and grouted with fine sand including				2:0=2 =:	0 10
		finishing the top smooth.	sqm	64.35	417.60	26872.56	Quoted Rate
16	5.33	Providing and laying in position machine batched and					
		machine mixed design mix M-25 grade cement concrete					
		for reinforced cement concrete work, using	1				
		cementcontent as per approved design mix, including					
		pumping of concrete to site of laying but excluding the					
		cost of centering, shuttering, finishing and including					
		retard setting of concrete.					
		improve workability without impairing strength	1				
		andadmixtures in recommended proportions as per IS:					
		9103 to accelerate, reinforcement, durability as per					
		direction of Engineer-incharge. Note:- Cement content					
		considered in this item is @ 330 kg/cum. Excess or less					
		cement used as per design mix is payable or recoverable					
		separately.					
	5.33.1	All work up to plinth level	cum	78.20	5192.50	406032.57	SOR Item
	5.33.2	All work from plinth level upto floor V level	cum	83.14	5859.00	487098.10	SOR Item
17	5.35	Add for using extra cement in the items of design mix					
		over and above the specified cement content therein.	20 80				
			quintal	129.07	732.40	94528.06	SOR Item
18	5.9	Centering and shuttering including strutting, propping					
		etc. and removal of form for:					
	5.9.1	Foundations, footings, bases of columns, etc. for mass			10620	2120711	COPIL
		concrete.	Sqm	114.25	186.30	21285.11	SOR Item
	5.9.2	Walls (any thickness) including attached pilasters.					
		Butteresses, plinth and string courses etc.	approximate and	0.00	221.20	0.00	SOR Item
			sqm	0.00	321.30	0.00	SOR Item
	5.9.3	Suspended floors, roofs, landings, balconies and access		225.55	362.60	81785.03	SOR Item
		platform.	sqm	12.11	362.60	4390.25	SOR Item
	5.9.4	Shelves (Cast in situ) Lintels, beams, plinth beams, girders, bressumers and	sqm	12.11	302.00	4370.23	30K Item
	5.9.5		sqm	388.84	335.30	130376.84	SOR Item
	-06	cantilevers. Columns, Pillars, Piers, Abutments, Posts and Struts.	Sqiii	300.04	333.30	130370.01	Soft item
	5.9.6	Columns, Piliars, Piers, Aduthents, Posts and Struts.	sqm	285.27	425.80	121466.18	SOR Item
	507	Stairs, (excluding landings) except spiral-staircases.	3qiii	203.27	123.00	121100.10	0011110111
	5.9.7	Stairs, (excluding landings) except spiral-staircases.	sqm	0.00	384.70	0.00	SOR Item
	5015	Small lintels not exceeding 1.5m clear span, moulding	Sqiii	0.00.	301.70	0.00	0011110111
	5.9.15	as in cornices, window sills, string courses, bands,					
		copings, bed plates, anchor blocks and the like.					
		copings, ocu piates, anchor biocks and the fike.	sqm	102.95	198.50	20435.29	SOR Item
	5.9.16	Edges of slabs and breaks in floors and walls.	- N			0.00	
	5.9.16.1	Under 20cm wide	Metre	45.80	100.90	4621.22	SOR Item
	5.9.17	Cornices and mouldings	sqm	3.34	502.00	1678.44	SOR Item
	5.9.17	Weather shade, Chajjas, corbels, etc. including edges.	1				
	.7.17	camer smart, company construction, site mentaling congress	sqm	36.06	468.40	16891.54	SOR Item
19	5.11	Extra for additional height in centring, shuttering where					
. /	5.11	ever required with adequate bracing, propping etc.					
		including cost of de-shutering and de centring at all					
		levels over a height of 3.5 m ,for every additional height					
		of 1 metre or part thereof (Plan area to be measured)					
	5.11.1	Suspended floors, roots, laning, beams and balconies					
		(Plan area to be measured)	sqm	249.50	146.20	36476.75	SOR Item
20	5.22	Reinforcement for R.C.C work including straightening,	-				
20	J.44	cutting, bending, placing in position and binding all					
		complete.					
-+	5.22.1	Mild steel 6.00mm dia	Kg	0.00	86.00	0.00	SOR Item
	J 1						

 \bigcirc

()

S227 Thermo-Mechanically Treated bars TMTC-500-10mm Kg 7568.94 77.40 558335.77 SOR Item	4000						-p	
Sec. 2.718 dis	1,	5.22.7.		· Kg	7568.94	77.40	585835.77	SOR Item
Security		5.22.71	3 dia	Kg	1376.17	76.70	105552.28	SOR Item
S.22.70 Thermo-Mechanically Treated bars TMTC-500-20mm Sg. 5015.96 76.00 38.3492.84 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 5016.88 76.00 418355.82 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 5016.88 76.00 418355.82 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 5016.88 76.00 76.00 0.00 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 76.00 0.00 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 Sor Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 Sor Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 Sor Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 SOR Item Soc. 7 Thermo-Mechanically Treated bars TMTC-500-25mm Sg. 50.00 SOR Item Soc. 7 Thermo-Mechanical TmC-500-25mm Sor Item	-	5 22 70			3440 43	75.20	258720.05	SOR Item
			Thermo-Mechanically Treated bars TMTC-500-16mr	n.				
S.2.2.7F dis			Thermo-Mechanically Treated bars TMTC-500-20mr		3043.96	/6.00	383492.84	SOR Item
22 6.13		5.22.7E			5504.68	76.00	418355.82	SOR Item
Solidation and plinth in: Court Solidation Court Solidation Court Solidation Sol	1 21		dia	Kg	0.00	76.00	0.00	SOR Item
23 6.33	1, 21	6.1A		וו				
23 6.13A Brick work rom thick with FPS brick of class designation 100A in cement mortar 1:3(1 cement: 3 course sand) in superstructure: 3cm 18.24 471.10 8590.56 SOR Item 100A in Dundations and pluth in: 3cm	22				28.86	4799.20	138485.40	SOR Item
designation 100A in cement mortar 1:3(1 cement: 3 cm	L		upto floor V Level	cum	0.00	702.20	0.00	SOR Item
24 6.18A Half brick masonry with bricks of class designation 100A in foundations and plinth in: 100A in foundations and plinth level up to floor V level. 100A in foundations and plinth level up to floor V level. 100A in foundations and plinth level up to floor V level. 100A in the second to floor in the second plinth level up to floor V level. 100A in the second plinth level up to floor V level. 100A in the second plinth level in cement mortars 1:6(1 cement: 6 cores sand) 100A in exposed brick work including making horizontal and vertical invoves florm wide 12mm deep complete from ground level up to plinth level in cement mortars 1:6(1 cement: 6 cores sand) 100A in exposed brick work in superstructure above plinth level and upto floor level. 0.75 x 1.5 = 1.13 100	23	6.13A	designation 100A in cement mortar 1:3(1 cement: 3	3	18.24	471.10	8590.56	SOR Item
6.18-4A Cement mortar 1-14 Lement: 4-coarse send 25 6.19A Extra for half Brisk masonry in superstructure above pinth level upto floor V level. 26 6.21A Extra for providing and placing in position 2 nos. 6mm dai. MS bars at every third course of half brick masonry (with F.P.S bricks) 27 6.41A Brick work with selected bricks of class designation 100A in exposed brick work including making horizontal and vertical irooves 10mm wide 12mm deep complete from ground level up to plinth level in cement mortars 1.6(1 cement: 6 corse sand) 28 6.45A Extra for exprosed brick work in superstructure above plinth level and upto floor level. 0.75 x 1.5 = 1.13 Cum 64.36 889.40 57240.37 SOR Item 29 9.1 Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position 9.20 Providing and fixing 151 marked flush door shutters conforming to 15: 2202 (Part 1) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 151 marked Stainless Steel butt hinges with necessary screws. 9.20.1 35mm thick including 150 marked	1 24	6.18A	Half brick masonry with bricks of class designation					
25 6.19A Extra for half Brick masonry in superstructure above pinth level upto floor V level. 26 6.21A Extra for providing and placing in position 2 nos. 6mm dia, M5 bars at every third course of half brick masonry (with E.P.S bricks) 27 6.41A Brick work with selected bricks of class designation 100A in exposed brick work including making horizontal and vertical irroves 10mm wide 12mm deep complete from ground level up to plinth level in cement mortars 1.6(1 cement: 6 corse sand) 28 6.45A Extra for exprosed brick work in superstructure above plinth level and upto floor level. 0.75 x 1.5 = 1.13 29 9.1 Providing wood work in frames of doors, windows, excretely windows and other frames, wrought framed and fixed in position 9.9.1 Second class teak Wood Cum 0.21 95749.10 19954.71 SOR Item 10 9.20 Providing and fixing ISI marked flush door shutters conforming to 15 :2202 (Part I) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply venering with vertical grains or cross bands and face veneres on both faces of shutters (over all area of door shutter to be measured) 9.20 Symm thick including ISI marked Stainless Steel butt hinges with necessary serves. Symm 7.91 2598.90 20561.85 SOR Item 30 9.23 Extra for providing lipping with 2nd class teak wood batters 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) Symm 7.91 392.30 3103.78 SOR Item 31 9.23 Extra for providing lipping with 2nd class teak wood batters 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) Symm 7.91 392.30 3103.78 SOR Item 32 9.53 providing and fixing aluminium sliding door botts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and serves etc. complete: Each 0.00 220.40 0.00 300.00 300.00 300.)—	6.18.4A		sqm	83.37	596.80	49752.60	SOR Item
27 6.21A Extra for providing and placing in position 2 nos 6mm dia, MS bars at every third course of half brick masonry (with F.P.S bricks) 27 6.41A Brick work with selected bricks of class designation 100A in exposed brick work including making horizontal and vertical irrooves 10mm wide 12mm deep complete from ground level up to plinth level in cement mortars 1:6(1 cement: 6 corse sand) 28 6.45A Extra for exprosed brick work in superstructure above plinth level and upto floor level. 0.75 x 1.5 = 1.13 Cum 64.36 4887.00 314519.54 SOR Item 29 9.1 Providing wood work in frames of doors, windows, clerostory windows and other frames, wrought framed and fixed in position 9.1.1 Second class teak Wood Second class teak Wood Providing and fixing 1SI marked flush door shutters conforming to 1S :2202 (Part I) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.20.1 35mm thick including ISI marked Stainless Steel butt lininges with necessary screws. sqm 7.91 2598.90 20561.85 SOR Item 9.23 Extra for providing lipping with 2nd class teak wood batters 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) sqm 7.91 392.30 3103.78 SOR Item 33 9.23 Extra for providing Ipping with 2nd class teak wood batters 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) sqm 7.91 392.30 3103.78 SOR Item 39.60 For iding and fixing aluminimum sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: Each 0.00 220.40 0.00 0	25	6.19A			82 27	74.70		
Cwith EP-S bricks) Sqn 83.37 87.70 7311.16 SQR Item	26	6.21A	Extra for providing and placing in position 2 nos. 6mm		83.37	74.70	0227.41	SOR Helli
27 6.41A Brick work with selected bricks of class designation 100A in exposed brick work including making horizontal and vertical frooves 10mm wide 12mm deep complete from ground level up to plinth level in cement mortars 1:6(1 cement: 6 corse sand) 28 6.45A Extra for exprosed brick work in superstructure above plinth level and upto floor level. 0.75 x 1.5 = 1.13 29 9.1 Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position 9.1.1 Second class teak Wood 9.2.0 Providing and fixing 1SI marked flush door shutters conforming to IS: 2202 (Part I) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.2.0.1 35mm thick including ISI marked Stainless Steel butt hinges with necessary screws. 31 9.2.3 Extra for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) 9.5.3 providing 40x5 mm flat iron hold fast 40 cm long including fisting to frame with 10 mm diameter bots, auts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:36 mix (1 cement 3 coarse sand 6 graded stone agergeate 20 mm nominal size) 9.9.6 Providing and fixing aluminium sliding door botts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.9.6.1 300x16mm Each 0.00 220.40 0.00 30x6, file minute and screws etc. complete:	,			1	83 37	87.70	7311.16	SOR Item
horizontal and vertical frooves 10mm wide 12mm deep complete from ground level up to plinth level in cement mortars 1:6(1 cement: 6 corse sand) Cum 64.36 4887.00 314519.54 SOR Item Cum 64.36 4887.00 314519.54 SOR Item Cum 64.36 889.40 57240.37 SOR Item 29 9.1 Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position 9.1.1 Second class teak Wood Providing and fixing ISI marked flush door shutters conforming to IS :2202 (Part I) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.2.0 35mm thick including ISI marked Stainless Steel butt hinges with necessary screws. 9.2.1 Strar for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) 9.2.3 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:35 cm ix (1 cement 3 coarse sand 36 graded stone aggregate 20 mm nominal size) 9.9.6 Providing and fixing aluminium sliding door botts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.9.6.1 300x16mm Each 0.00 220.40 0.00 80x.6mm	27.	6.41A	Brick work with selected bricks of class designation		65.57	87.70	7511.10	30K Item
Cum 64.36 4887.00 314519.54 SOR Item Cum 64.36			horizontal and vertical irooves 10mm wide 12mm deep complete from ground level up to plinth					
28 6.45A Extra for exprosed brick work in superstructure above plinth level and upto floor level. 0.75 x 1.5 = 1.13 Cum 64.36 889.40 57240.37 SOR Item 29 9.1 Providing wood work in frames of doors, windows elerestory windows and other frames, wrought framed and fixed in position 9.1.1 Second class teak Wood Second class teak Wood Second class teak Wood Providing and fixing ISI marked flush door shutters conforming to IS :2202 (Part I) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.20.1 35mm thick including ISI marked Stainless Steel butt hinges with necessary screws. Sqm 7.91 2598.90 20561.85 SOR Item 31 9.23 Extra for exprosed brick wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) sqm 7.91 392.30 3103.78 SOR Item 32 9.53 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) each 30.00 106.60 3198.00 SOR Item 33 9.96 Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS;1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm Each 0.00 220.40 0.00 SOR Item 9.96.2 250x16mm Each 3.00 195.50 586.50 300R Item 9.96.2 250x16mm Each 3.00 195.50			instruction of the same of the		<1.0×		2 0 0000 100	
Second class teak Wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position Second class teak Wood	28	6.45A	Extra for exprosed brick work in superstructure above		64.36	4887.00	314519.54	SOR Item
9.1 Providing wood work in frames of doors,windows, clerestory windows and other frames, wrought framed and fixed in position 9.1.1 Second class teak Wood 9.20 Providing and fixing ISI marked flush door shutters conforming to IS :2202 (Part I) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.20.1 35mm thick including ISI marked Stainless Steel butt hinges with necessary screws. 9.20.2 Extra for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) 9.53 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots,nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) 9.96 Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm Each 0.00 220.40 0.00 50R feeting the frame of the face o)	8	plinth level and upto floor level. $0.75 \times 1.5 = 1.13$	Cum	64.36	889.40	57240 37	SOP Itam
9.1.1 Second class teak Wood 9.20 Providing and fixing ISI marked flush door shutters conforming to IS :2202 (Part I) decorative type, core of block board construction with frame of I st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.20.1 35mm thick including ISI marked Stainless Steel butt hinges with necessary screws. 9.20.2 Extra for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) 9.31 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) 9.96 Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm	3.9	9.1	clerestory windows and other frames, wrought framed	Cum	01.30	007.40	31240.31	SOK IICIII
conforming to IS:2202 (Part I) decorative type, core of block board construction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both faces of shutters. 9.20.1 35mm thick including ISI marked Stainless Steel butt hinges with necessary screws. 9.23 Extra for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) 9.53 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots,nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) 9.96 Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm Each 0.00 220.40 0.00 SOR ftem Each 3.00 195.50 586.50 SOR ftem)—		Second class teak Wood	Cum	0.21	95749.10	19954.71	SOR Item
9.20.1 35mm thick including ISI marked Stainless Steel butt hinges with necessary screws. Sor Item 9.21 Extra for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) 9.53 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm Each 0.00 220.40 0.00 SOR frem Sor frem Sor frem Fach 0.00 195.50 586.50 Sor frem	30	9.20	conforming to IS:2202 (Part I) decorative type, core of block board construction with frame of I st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both			30		5
31 9.23 Extra for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters (over all area of door shutter to be measured) 32 9.53 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots,nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) 33 9.96 Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm Each 0.00 220.40 0.00 SOR Item 9.96.2 250x16mm Each 3.00 195.50 586.50 SOR Item		The second secon	Name and the state of the stat		7.01	2500.00	20761.07	gop t
9.53 providing 40x5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) 9.96 Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm Each 0.00 220.40 0.00 SOR feem 9.96.2 250x16mm Each 3.00 195.50 586.50 SOR feem 1.3.50 Each 3.00 E	31	9.23	Extra for providing lipping with 2nd class teak wood battens 25mm minimum depth on all edges of shutters	sqm	7.91	2398.90	20361.83	SUK Item
including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand :6 graded stone aggregate 20 mm nominal size) Providing and fixing aluminium sliding door bolts ISI Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm Each 0.00 220.40 0.00 SOR frem 9.96.2 250x16mm Each 3.00 195.50 586.50 SOR frem 1.3.00 frem 1.	ز			sqm	7.91	392.30	3103.78	SOR Item
9.96.1 300x16mm 9.96.2 250x16mm 9.96.1 30.0x16mm 9.96.2 250x16mm 9.96.2 250x16mm 9.96.1 30.0x16mm Each 30.00 106.60 3198.00 SOR Item 10.00 220.40 0.00 SOR Item 20.00 220.40 0.00 SOR Item 20.00 195.50 SOR Item 20.00 SOR Item	32) J		including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement :3 coarse sand					
Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with nuts and screws etc. complete: 9.96.1 300x16mm				each	30.00	106.60	3198.00	SOR Item
9.96.1 300x16mm Each 0.00 220.40 0.00 SOR frem 9.96.2 250x16mm Each 3.00 195.50 586.50 SQR frem	33		Marked anodised (anodic coating not less than grade AC 10 as per IS:1868) transparent or dyed to required		,		CO	V CERTECKIZ
9.96.2 250x16mm Each 3.00 195.50 586.50 SQR Item	J			D. L	0.00	220.10		HALL STREET CITY
	J+							
	١		Page	3 of 9			BA	WON'S BHYONE

34	9.97	Providing and fixing aluminium tower bolts ISI Marked					
		anodised (anodic coating not less than grade AC 10 as					
		per IS:1868) transparent or dyed to required colour or					
		shade with necessary screws etc. complete:					
	9.97.1	300x10mm	Each	0.00	105.20	0.00	SOR Item
	9.97.1	150x10mm	Each	10.00	67.80	678.00	SOR Item
35	9.100	Providing and fixing aluminium handles anodised ISI		1		0,010	
22	2.100	Marked (anodic coating not less than grade AC 10 as per					
		[S:1868) transparent or dyed to required colour or shade					
		with necessary screws etc. complete:					
				-			
	9.100.1	125mm	Each	10.00	54.00	540.00	SOR Item
36	9.101	Providing and fixing aluminium hanging floor door					
		stopper ISI Marked anodised (anodic coating not less					
		than grade AC 10 as per IS:1868) transparent or dyed to required colour and shade with necessary screws etc.					
	-	complete.					
	9.101.2	Twin rubber stopper	Each	5.00	40.40	202.00	SOR Item
37	9.103	Providing and fixing bright finished brass 100mm					
,	,,,,,,	mortice latch and lock with six levers and a pair of					
		anodised (anodic coating not less than grade AC 10 as					
		per IS:1868) aluminium lever handles with necessary					
		screws etc. complete (Best make of approved quality).	2000 2000			2 of 12 M San # F100 (2020) (12)	
			Each	3.00	642.90	1928.70	SOR Item
38	21.1	Providing and fixing aluminium work for doors,					
		windows, ventilators and partitions with extruded built				45	
		up standard tubular sections/ appropriate Z sections and					
		other sections of approved make conforming to IS: 733					
		and IS:1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at					
		junctions, i.e. at top, bottom and sides with required					
		EPDM rubber/ neoprene gasket etc. Aluminium sections					
		shall be smooth, rust free, straight, mitred and jointed					
		mechanically wherever required including cleat angle,					
		Aluminium snap beading for glazing / aneling, C.P. brass					
		/ stainless steel screws, all complete as per architectural					
		drawings and the directions of Engineer-in-charge.					
		(Glazing, paneling and dash fasteners to be paid for					
		separately):					
	21.1.1	E. C. J. adia					-
-		For fixed portion Anodised aluminium (anodised transparent or dyed to					
	21.1.1.1	required shade according to IS: 1868, Minimum anodic	¥.				-
		coating of grade AC 15)	Kg	379.10	369.20	139964.75	SOR Item
	21.1.2	For shutters of doors, windows & ventilators including					
		providing and fixing hinges/ pivots and making					
		provision for fixing of fittings wherever required					
		including the cost of EPDM rubber / neoprene gasket					
		required (Fittings shall be paid for separately)					
					- '		
		Anodised aluminium (anodised transparent or dyed to					
		required shade according to IS: 1868, Minimum anodic	V~	190 55	423.90	80350.84	SOR Item
20		coating of grade AC 15) Providing and fixng glazing in aluminium door,	Kg	189.55	423.90	00330.84	30K Item
39		window, ventilator shutters and partitions etc. with					
		PVC/neoprene gasket etc. complete as per the					
		architectural drawings and the directions of engineer-in-					
		charge. (Cost of aluminium snap beading shall be paid					
		in basic item):					
+		With glass panes of 4.0mm thickness (weight not less					
	1	than 10.0 kg/sqm)	Sqm	53.71	735.60	39506.30	SOR Item
十	21.3.2	With glass panes of 5.50 mm thickness(weight not less					
	1	thar 13.75 kg/sqm)	Sqm	0.00	1017.30	0.00	SOR Item

0

17	() Amele	is Esten for using Touchand at 12					
1 40		is Extra for using Toughened glass 12 mm thickness to single of glass pages of 1.0 mm thickness to sight p					
	as per BCD		ot				CODI
T	SOR-1		0	22.71	2012.00	10010172	SOR Item with
41		Providing and fixing double action hydraulic floo	Sqm	53.71	2012.89	108104.73	Analysis
1 41	21.4	spring of approved brand and manufacture conforming					
1		to IS: 6315, having brand logo embossed on the body					
1		plate with double spring mechanism and door weigh			1		
I		upto 125 kg, for doors, including cost of cuttin					
4		floors.embedding in floors as required and making goo					
1		the same matching to the existing floor finishing an					
1		cover plates with brass pivot and single piece M.S. shee					
1		outer box with slide plate etc. complete asper th					
L		direction of Engineer-in-charge.					
1	21.4.1	With stainless steel cover plate minimum 1.25 mm		-			
L	21.4.1	thickness	Each	2.00	2162.50	1227.00	CODI
42	21.8	Filling the gap in between aluminium frame & adjacen		2.00	2163.50	4327.00	SOR Item
1 42	21.0	RCC/Brick/Stone work by providing weather silicon					
		sealant over backer rod of approved quality as pe					
		architectural drawings and direction of Engineer-in-					
		charge complete.	1				
	21.8.1	Upto 5mm depth and 5mm width.	Mater	134.14	72.00	0770.01	CODI
43	21.16	Providing and fixing aluminium round shape handle of	Metre	134.14	72.90	9778.81	SOR Item
13	21.10	outer dia 100mm with SS screws etc. complete as per					
)		direction of Engineer-in-charge					
	21.16.1	Anodized (AC 15) aluminium	each	4.00	66.20	264.80	SOD II
44	21.18	Providing and fixing 12 mm thick frameless toughened		4.00	00.20	204.80	SOR Item
	21.10	glass door shutter of approved brand and manufacture,					
1		including providing and fixing top & bottom pivot &					
		spring type fixing arrangement and making necessary					
1.	1	holes etc. for fixing required door fittings, all complete					
		as per direction of Engineer-in-charge (Door handle,	1				
1		lock and stopper etc.to be paid separately).			1		
1		province of para separately).	sqm	4.47	4779.90	21343.21	SOR Item
15	10.5	Providing and fixing in position collapsible steel	Sqiii	1.17	4777.20	21343.21	30K Itelli
		shutters with vertical channels 20x10x2mm and braced					1
1		with flat iron diagonals 20x5mm size with top and					1
1		bottom rail of T-iron 40x40x6mm with 40mm dia, steel					
		pulleys complete with bolts, nuts, locking arrangement,					
, , , , , , , , , , , , , , , , , , ,		stoppers, handles, including applying a priming coat of					
		approved steel primer.					
,			sqm	0.00	5089.50	0.00	SOR Item
46	10.18	Providing and fixing circular/hexagonal cast iron or M.S	1		70,000,000,000		SOIL ILEM
. 2		sheet box for ceiling fan clamp 140 mm internal dia, 73					
		mm height, 5 mm thick rim bottom and top lids, 1.5 mm					
1		thick M.S sheet with its top surface					
		hacked for proper bonding top lid shall be screwed into					
1		the cast iron box by means of 3.3 mm dia round headed					
		screws, one lock at the corners. Clamps shall be made of			1		
)		12 mm dia M.S. bar bent to shape as per standard					
		drawing.					
ال			Each	12.00	141.30	1695.60	SOR Item
47		Providing and fixing 18 mm thick gang saw cut, mirror					
	Įŧ	polished, premoulded and prepolished, machine cut for					
	1	citchen platforms, vanity counters, window sills, facias					
)		and similar locations, of required size, approved shade,					
		colour and texture laid over 20 mm thick base cement					
_)	1	nortar 1:4 (1					
		ement: 4coarse sand), joints treated with white cement,					
	-	nixed with matching pigment, epoxy touch					
		sps,including rubbing, curing, moulding and polishing				Col	2 40
		o edges to give high gloss finish etc. complete at all					JECH.
	le	evels.				XXX	68 12 WILD.
	1000					- CONTRACTOR	3 pa. 22 C/1/1 2
		Granite of any colour and shade				- Miller	CARRIE
ــــــر	8.2.2.1 A	area of slab upto 0.50 sqm	sqm	0.00	3741.20	0.00	SOR Item
550		o parameter country	_			MAGRILI	MAGALI
)		Page	5 of 9			Bur	Plu

			,				
	8.2.2.2		sqm	14.99	3699.10	55458.76	SOR Item
48	8.4	Extra for fixing marble/granite stone over and above					
		coresponding basic ite. in facia and drops of width upto					
		150 mm with expoxy resin based (Araldite or					
		equivalent) adhesive including cleaning etc. complete.	m	17.11	236.30	4043.09	SOR Item
49	8.5	Extra for providing opening of required size & shape for		17.11	230.30	1013.07	3010 Item
49	0.5	wash basins/kitchen sink in kitchen platform. Vanity					
		counters and similar location in marble/stone work		11			
		including necessary holes for pillar taps etc. including	1				
		rubing and polishing of cut edges etc. complete.					
		Tuesting and personning or our region of	each	2.00	355.80	711.60	SOR Item
50	8.12	Providing and laying flamed finish Granite stone					
		flooring in required design and patterns, in linear as well					
		as curvilinear portions of the building all complete as					
		per the architectural drawings with 18 mm thick stone					
		slab over 20mm(avearage) thick base of cement mortar					
		1:4(1 cement : 4 coarse sand) laid and jointed with					
		cement slurry and pointing with white cement slurry					
		admixed with pigment of matching shade including					
		rubbing, curing and polishing etc. all complete as					
		specified and as directed by the Engineer-in-Charge:					
	(a)	Flamed finish granite stone slab Jet Black, Cherry		27.107	2070 20	01017 = 7	SOD It
		Red, Elite Brown, Cat Eye or equivalent.	sqm	27.497	2979.20	81917.57	SOR Item
51	11.41	Providing and laying vitrifed(Unpolished) floor tiles in					
		different sizes (thickness to be specified by the manufactruer) with water absorption's less than 0.08 %					
		and conforming to IS: 15622 of approved make in all					
		colours and shades, laid on 20 mm thick cement mortar					
		1:4 (1 cement: 4 coarse sand) including grouting the					
		joint with white cement and matching pigments etc.,					
	22	complete.					
	11.41.2	Size of Tile 60x60 cm	sqm	181.99	1520.90	276790.49	SOR Item
52	11.46	Providing and laying Vitrified tiles in different sizes					
		(thickness to be specified by manufacturer), with water					
		absorption less than 0.08 % and conforming to I.S.					
		15622, of approved make, in all colours &					
		shade, in skirting, riser of steps, over 12 mm thick bed					
		of cement mortar 1:3 (1 cement: 3 coarse sand),					
		including grouting the joint with white cement &					
		matching pigments etc. complete.					
	11.46.2	Siza of Tila 60v60 cm	sam	140.75	1141.60	160674.83	SOR Item
52		Size of Tile 60x60 cm Providing and fixing 1st quality ceramic glazed wall	sqm	140.73	1171.00	100077.03	JOIC ROIII
53		tiles conforming to IS:15622(thickness to be specified					
		by the manufacture) of approved make in all colours,					
		shades except burgundy, bottle green, black of any size	1				W
		as approved by Engineer-in-Charge in skirting, risers of	1				
		steps and dados over 12mm thick bed of cement Mortar					
		1:3(1 cement: 3 coarse sand) and jointing with grey					
		cement slurry @ 3.3 kg per sqm including pointing in					
		white cement mixed with pigment of matching shade					
		complete.	sqm	31.62	739.80	23394.25	SOR Item
54	11.26	Kota stone slab flooring over 20mm (average) thick base					
		laid over and jointed with grey cement slurry mixed with					
		pigment to match the shade of the slab including					
		rubbing and polishing complete.					
		20 to 25mm thick	sqm	34.41	1119.60	38527.82	SOR Item
55		Kota stone slab 20 mm thick in risers of steps skirting.					
		Dado & pillars laid on 12mm (average thick cement					
		mortar 1:3(1 cement: 3 coarse sand) and jointed with					
		grey cement slurry mixed with pigment to match the					
	100	shade of the slab including rubbing and polishing	2000	0.00	1133.90	0.00	SOR Item
	1.	complete.	sqm	0.00	1111190	UUU	NUR HEID

 \circ

55	5 11.72		1				
		filled with local sand including cost of watering, taxes	-1				
-		royalty all complete as per building specification and	d				
		direction of E/I.	sqm	430.46	277.50	119454.03	SOR Item
5	7 12.39						
Ĭ		thickness of 5 cm cement concrete 1:2:4(1 cement: 2	2				
1.		coarse sand: 4 graded stone aggregate of 20mm nomina					
1		size) over P.V.C sheet 1mx1mx400 micron, finished					
7		with 12mm cement plaster 1:3(1 cement: 3 coarse sand					
1		and a coat of neat cement rounding the edge sand	1				
		making and finishing the outlet complete.	Each	4.00	172.30	689.20	SOR Item
1 58	13.11	12mm cement plaster of mix:	- Butil	1	1	007.20	0011110111
	13.11.4		sqm	231.35	126.20	29196.91	SOR Item
1 59	13.12	15mm cement plaster on the rough side of single or half					
1		brick wall of mix:	1				
1)	13.12.4	1:6(1 cement: 6 course sand)	sqm	231.35	145.50	33662.05	SOR Item
60	13.13	20mm cement plaster of mix:	1				
)	13.13.2	1:4(1 cement: 4 course sand)	sqm	302.46	194.30	58768.02	SOR Item
61	13.24	6mm cement plaster to ceiling of mix:					
)	. 13.24.2	1:4(1 cement: 4 coarse sand)	sqm	254.00	110.90	28168.70	SOR Item
62	13.36	Extra for providing and mixing water proofing material					
,)		in proportion recommended by the manufacturers.					
)	13.36.6	20mm cement plaster 1:4(1 cement: 4 sand)	sqm	302.46	9.20	2782.63	SOR Item
63	13.56	Pointing on brick work with cement mortar 1:3(1					
)		cement:3 coarse sand):					
		Ruled pointing	sqm	272.25	100.40	27333.52	SOR Item
54	13.51	Painting with silicon & acrylic emulsion based water					
	DSR	thinnable sealer of approved brand and manufacture on					
)		wet or patchy portion of plastered surfaces:					
	10.41.0						
)		Two coats	sqm	597.88	129.05	77156.13	SOR Item
65	13.80A.2	Providing and applying white cement based putty of					
()		average thickness 2 mm, of approved brand and manufacturer, over the plastered wall surface to prepare					1
			121 (212)	000.24	117.60	105070 75	CODI
1 66	13.78	the surface even and smooth complete Applying one coat of cement primer of approved brand	sqm	900.34	117.60	105879.75	SOR Item
00	13.76	and manufacture on wall surface:				-	
	13.78.1	Cement primer	sqm	597.88	31.00	18534.21	SOR Item
67	13.46A	Finishing walls with Premium Acrylic Smooth exterior	Sqiii	397.00	31.00	18334.21	SOK Item
.)	13.40/1	paint with Silicone additives of required shade.					
		paint with Streetle additives of required stade.					
J	13.46A.1	New work (Two or more coats applied @ 1.43 ltr/10					
		sqm over and including base coat of water proofing					
		cement paint applied @ 2.20 kg/10 sqm).	sqm	302.46	90.10	27251.66	SOR Item
68		Applying priming coat:	12.5		70.7		
j		With ready mixed pink or Grey primer of approved					
		brand and manufacture on wood work (hard and soft					
)		wood)	sqm	22.24	32.20	716.04	SOR Item
69	13.101	French spirit polishing:					
.)	13.101.1	Two or more coats on works including a coat of wood					
		filler.	sqm	141.07	346.90	48936.80	SOR Item
. 30		Forming groove of uniform size from 12x12mm and			4		
7.5		upto 25x15mm in plastered surface as per approved				>=	
)		pattern using wooden battens, nailed to the under layer					
4		including removal of wooden battens, repairs to the					
(ر		edges of plaster panel and finishing the groove complete					
7'		as per specifications and direction of the Engineer-in-	.			955 1155 cm 1500	
		Charge.	Metre	0.00	40.80	0.00	SOR Item

with proprietary water proofing compound conforming to IS: 2645 and finally finishing the surface with trovel with neat cement slurry and making of 300 x 300 mm square. (e) The whole terrace so finished shall be flooded with water for a minimum period of two weeks for curing and for final test. All above operations to be done in order and as directed and specifed by the Engineer-in-Charge. 22.8.1 With average thickness of 120mm and minimum thickness at khurras point to be 65. Sqm 242.14 2253.30 545621.91 SOR Item Carriage of Materials with loading & unloading: Cement 41.25 328.25 13540.31 Cement 5150 Steel MT 23.03 328.25 7359.60 Sortion of Steel MT 25.00 Sort	71	22.8	Providing and laying integral cement based water proofing treatment including prepatation of surface as required for treatment of roofs, balconies, terraces etc. consisting of following operations. (a) Applying and grouting a slurry coat of neat cement using 2.75 kg/sqm of cement admixed with proprietary water -proofing compound cleaning the surface before treatment. (b) Laying cement concrete using broken bricks / brick bats 25 mm to 100 mm size with 50 % of cement mortar 1:5 (1 cement: 5 coarse sand) admixed with proprietary water proofing compound conforming to IS: 2645 over 20 mm thick layer of cement mortar of mix 1:5 (1 cement: 5 coarse sand) admixed with proprietary water froofing compound conforming to IS 2545 to reuired slope and treating similary the adjoining walls upto 300 mm height including rounding of junctions, or walls ad slabs. (c) After two days of proper curing applying a secoung coat of cement slurry admixed with proprietary water proofing compound conforming to IS: 2645. (d) Finishing the surface with 20 mm thick jointless cement					
thickness at khurras point to be 65. Sqm 242.14 2253.30 545621.91 SOR Item			to IS: 2645 and finally finishing the surface with trowel with neat cement slurry and making of 300 x 300 mm square. (e) The whole terrace so finished shall be flooded with water for a minimum period of two weeks for curing and for final test, All above operations to be done in order and as directed and specifed by the					
Carriage of Materials with loading & unloading:		22.8.1			242.14	2253 30	545621 91	SOR Item
Cement Steel MT 23.03 328.25 13540.31	70		Couriege of Metariele with leading & unleading.	Sqiii	242.14	2233.30	343021.71	Soft item
Steel	70				41.25	328.25	13540.31	
Bricks 100A(local lead 1K+7P) Coarse sand 55 km(p) from Koilwar Stone chips 185 KM(P) from Koderma Cum 158.40 1030.30 163195.40 SOR Stone chips 185 KM(P) from Koderma Cum 184.16 2701.30 497474.75 SOR Local Sand (Lead local 1K+2P) Cum 258.81 262.05 67821.37 SOR 2.37.31 Diluting and injecting chemical emulsion for Pre-Constructional/Post Constructional Anti-termite treatment and creating a continuous chemical barrier under and alround the column pits,wall trenches,basement excavation,top surface of plinth filling, junction of wall and floor along the external perimeter of building,expansion joints,over the top surface of consolidated earth on which apron is to be laid surrounding of pipes and conduits etc. complete as per specifications Chlorpyriphos Emulsifiable concentrate of 20% with 1% concentration. 73 7029 Providing and fixing glavanised chicken wire mesh in 5" wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC Column-with Brick work before plaster work.				MT		328.25	7559.60	
Stone chips 185 KM(P) from Koderma cum 184.16 2701.30 497474.75 SOR Local Sand (Lead local 1K+2P) cum 258.81 262.05 67821.37 SOR 72 2.37.31 Diluting and injecting chemical emulsion for Pre-Constructional/Post Constructional Anti-termite treatment and creating a continuous chemical barrier under and alround the column pits,wall trenches,basement excavation,top surface of plinth filling, junction of wall and floor along the external perimeter of building,expansion joints,over the top surface of consolidated earth on which apron is to be laid surrounding of pipes and conduits etc. complete as per specifications Chlorpyriphos Emulsifiable concentrate of 20% with 1% concentration. 73 7029 Providing and fixing glavanised chicken wire mesh in 5" wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC Column-with Brick work before plaster work.				‰ No.	65332	767.08	50115.11	SOR
Local Sand (Lead local 1K+2P) Local Sand (Lead local 1K+2P) cum 258.81 262.05 67821.37 SOR 237.31 Diluting and injecting chemical emulsion for Pre- Constructional/Post Constructional Anti-termite treatment and creating a continuous chemical barrier under and alround the column pits,wall trenches,basement excavation,top surface of plinth filling, junction of wall and floor along the external perimeter of building,expansion joints,over the top surface of consolidated earth on which apron is to be laid surrounding of pipes and conduits etc. complete as per specifications Chlorpyriphos Emulsifiable concentrate of 20% with 1% concentration. 7029 Providing and fixing glavanised chicken wire mesh in 5" wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC Column-with Brick work before plaster work.			Coarse sand 55 km(p) from Koilwar	cum	158.40	1030.30	163195.40	SOR
72 2.37.3.1 Diluting and injecting chemical emulsion for Pre- Constructional/Post Constructional Anti-termite treatment and creating a continuous chemical barrier under and alround the column pits,wall trenches,basement excavation,top surface of plinth filling, junction of wall and floor along the external perimeter of building,expansion joints,over the top surface of consolidated earth on which apron is to be laid surrounding of pipes and conduits etc. complete as per specifications Chlorpyriphos Emulsifiable concentrate of 20% with 1% concentration. 73 7029 Providing and fixing glavanised chicken wire mesh in 5" wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC Column-with Brick work before plaster work.				cum	184.16	2701.30	497474.75	SOR
Constructional/Post Constructional Anti-termite treatment and creating a continuous chemical barrier under and alround the column pits,wall trenches,basement excavation,top surface of plinth filling, junction of wall and floor along the external perimeter of building,expansion joints,over the top surface of consolidated earth on which apron is to be laid surrounding of pipes and conduits etc. complete as per specifications Chlorpyriphos Emulsifiable concentrate of 20% with 1% concentration. 7029 Providing and fixing glavanised chicken wire mesh in 5" wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC Column-with Brick work before plaster work.		W	Local Sand (Lead local 1K+2P)	cum	258.81	262.05	67821.37	SOR
concentrate of 20% with 1% concentration. sqm 242.92 218.50 53077.86 SOR BCI 73 7029 Providing and fixing glavanised chicken wire mesh in 5" wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC Column-with Brick work before plaster work.	72	2.37.3.1	Constructional/Post Constructional Anti-termite treatment and creating a continuous chemical barrier under and alround the column pits,wall trenches,basement excavation,top surface of plinth filling, junction of wall and floor along the external perimeter of building,expansion joints,over the top surface of consolidated earth on which apron is to be laid surrounding of pipes and conduits etc. complete as					
wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC Column-with Brick work before plaster work.	73	7029	concentrate of 20% with 1% concentration. Providing and fixing glavanised chicken wire mesh in 5"	sqm	242.92	218.50	53077.86	SOR BCD
Julii 03.72 200.71 24002.32 30K BCI			wide strip with average width of aperture 1.18mm and nominal dia of wire 0.556mm at junctionsof RCC	Sqm	85.72	280.71	24062.32	SOR BCD

 \ominus

 \bigcirc

 \bigcirc

74	Analysis	Providing & Applying Nitocote SN522 or approved equivalent Colourless silicone water repellent Protective coating on brick work, all complete as per manufacturer's instructions / recommendations.					
			Sqm	272.25	214.29	58339.64	Analysis
		SUB Total of Civil Work				8073267	
		SUB Total of PHE Work				632290	
		SUB Total of Electrical Work				978524	
		SUB Total of AC Work				2132164	
)		Grand Total of CAFETERIA				11816245	
			-				



1		Cafeteria in Sandys PARK (PHE)				
						VARD
NC	BCD SOR		UNIT	QTY.	Rate	AMOUNT
	Α	SANITARY INSTALLATION				
1	SOR 17.80	Providing and fixing white vitreous china battery based infrared senso operated urinal of approx. size 610 x 390 x 370 mm having pre &pos flushing with water (250 ml & 500 ml consumption), having water inle from back side, including fixing to wall with suitable brackets all as pe manufacturers specification and direction of Engineer-in-charge.	t t	1.00	5407.30	5407.30
2	SOR 17.10	Providing and fixing Stainless Steel A ISI 304 (18/8) kitchen sink as per IS 13983 with C.I brackets and stainless steel plug 40mm including painting of fittings and brackets, cutting and making good the walls wherever required:	B			
	SOR	Kitchen sink with drain board				
	17.10.1.					
)	SOR	510x1040mm bowl depth 178mm	1			
	17.10.1.4	2	Each	1.00	3781.80	3781.80
3	SOR 17.31	Provding and fixing 600X450mm beveled edge mirror of superior glass complete with 6mm thick hard board ground fixed to wooden cleats with CP brass screws & washers complete.		3.00	741.90	2225.70
	SOR 17.28	Provding and fixing PVC waste pipe for sink & wash basin including PVC				
)4		waste fittings complete				
1	17.28.1	Semi rigid pipe				
)		32 mm dia	Each	1.00	86.20	86.20
1	В	WATER SUPPLY				
,	SOR 18.7	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC)pipes, having				
,		thermal stability for hot & cold water supply, including all CPVC plain &				1
5	1 0	brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC				-
		solvent cement and testing of joints complete as per direction of Engineer in Charge.				
)						
-		Internal work - Exposed on wall				
)		20 mm Nominal outer dia pipes				
	18.7.2	25 N	Metre	5.00	165.90	829.50
)		25 mm Nominal outer dia pipes				
	18.7.3		Metre	25.00	204.70	5117.50
)		32 mm Nominal outer dia pipes				
	18.7.4		Metre	38.00	279.10 -	10605.80
)	1	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC)pipes, having thermal stability for hot & cold water supply, including all CPVC plain &				
6		brass threaded fittings, including fixing the pipe with clamps at 1.00 m spacing. This includes jointing of pipes & fittings with one step CPVC				
1	34.0	solvent cement and testing of joints complete as per direction of Engineer				
		in Charge.				
/		Concealed work, including cutting chases and making good the				
)	18.8.2		Metre	13.00	255.70	3324.10
)	18.8.3		Metre	7.00	308.00	2156.00
5		Providing and fixing Chlorinated Polyvinyl Chloride (CPVC)pipes, having				
/	16.	hermal stability for hot & cold water supply, including all CPVC plain &				
7		orass threaded fittings This includes jointing of pipes & fittings with one				
1	s	tep CPVC solvent cement trenching refilling & testing of joints complete				
		s per direction of Engineer in Charge.		in h		
	E	external work		45CH		
			Vetre	10.00	249.30	2493.00
)——		W M	Make	661	100	

SR MANAGER SMART CHAIR

	SOR 18.9					
		thermal stability for hot & cold water supply, including all CPVC plain &				
8		brass threaded fittings This includes jointing of pipes & fittings with one				
		step CPVC solvent cement trenching refilling & testing of joints complete				
		as per direction of Engineer in Charge.				
	SOR	Providing and fixing brass stop cock of approved quality				
9	18.16					
	SOR	20 mm Nominal bore				
	18.16.2		Each.	1.00	303.00	303.00
	SOR 18.17	Providing and fixing gun metal gate valve with C.I. wheel of approved			Y	
10		quality.				
	SOR	25 mm Nominal bore				
	18.17.1		Each.	3.00	461.80	1385.40
	SOR	32 mm Nominal bore				
	18.17.2		Each.	4.00	540.00	2160.00
	SOR 18.21	Providing and fixing uplasticised PVC connection pipe with brass unions.				
11						
	18.21.2	45 cm length				
		15 mm Nominal bore	Each.	3.00	76.10	228.30
	SOR	Providing and fixing G.I. union in G.I.pipe including cutting and threading				
12	18.46	the pipe and making long screws etc.				,
	SOR	20 mm dia. Nominal bore				
	18.46.2		Each.	1.00	155.20	155.20
	SOR	25 mm dia. Nominal bore				
	18.46.3	25 11111 4141 1141 1141 1141	Each.	3.00	192.60	577.80
	SOR	32 mm dia. Nominal bore				
	18.46.4	32 mm dia. Nomina sore	Each.	4.00	230.00	920.00
-	10.40.4	C.P. BRASS FITTINGS				
	COP 19 50	Providing and fixing C.P. brass long nose bib cock of approved quality				
13	301/10.30	conforming to IS standards and weighing not less than 810 gms.				
13		Comorning to 13 standards and weighing not less than 525 gives				
	18.50.1	15 mm Nominal bore	Each	4.00	599.50	2398.00
1.1		Providing and fixing PTMT grating of approved quality and colour.	20011			
14						
		Circular type 100mm nominal dia.	Each	2.00	36.20	72.40
		Providing and placing on terrace polythethylene water storage tank ISI.		2.00	30.20	72.10
		:12701 marked with cover and suitable locking arrangement and making				
15		necessary holes for inlet, outlet and overflow pipes but without fittings				
		and the base support for tank. (2000x1=2000)	Dar litr	2000.00	7.90	15800.00
_			er nur	2000.00	7.30	13800.00
_		RAIN WATER SPOUT AND PIPE				
		Providing and fixing on wall face unplasticised Rigid PVC rain water pipes				
16		conforming to IS: 13592 Type A including jointing with seal ring				
		conforming to IS: 5382 leaving a 10 mm gap for thermal expansion.(i)				
		Single socketed pipes.			222.22	1766.00
		110 mm didiriosi e	Metre	20.00	238.30	4766.00
		Providing and fixing on wall face unplasticised Rigid PVC moulded fittings/				
		acessories for unplasticised Rigid PVC rain water pipes conforming to IS:				
17	1	13592 Type A including jointing with seal ring conforming to IS: 5382				
		leaving a 10 mm gap for thermal expansion.				
	12.79.2	Single pushfit Coupler				
1	12.79.2.2		Each	5.00	354.90	1774.50
		Bend 87.5 ⁰		1	1.5-1-5-1	
+		110 mm bend	Each	5.00	124.70	623.50
+		Shoe (Plain)				
-		110 mm Shoe	Each	5.00	108.52	542.60
	12.73.0.2	TTO HITH SHOC				

 \cap

 \cap

 \bigcirc

 \bigcirc

 \bigcirc

0

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

0

 \bigcirc

 \bigcirc

1	1000 100	0				
	SOR 12.80	Providing and fixing unplasticised - PVC pipe clips of approved design t				
		unplasticised - PVC rain water pipes by means of 50 x 50 x 50 mm har				
18		wood plugs, screwed with M.S. screws of required length cutting bric	k			
		work and fixing in cememt mortar 1:4 (1 cement : 4 coarse sand)and	d			
\		making good the wall etc. complete.				
	12.80.2	110 mm	Each	15.00	157.37	2360.55
	SOR 12.81	Providing and fixing to the inlet mouth of rain water pipe cast iron grating	100000000000000000000000000000000000000			
19		15 cm diameter and weighing not less than 440 grams.	Each	5.00	44.90	224.50
	Е	DRAINAGE	Lacin	3.00	44.50	224.30
-	SOR	Excavating trenches of required width for pipes, cables, etc including		-		-
			-1			
	2.10	excavation for sockets, and dressing of sides, ramming of bottoms, depth	1			
_		up to 1.5m including getting out the excavated soil, and then returning the				1
20		soil as required, in layers not exceeding 20cm in depth including				
		consolidating each deposited layer by ramming, watering, etc. and	4			
		disposing of surplus excavated soil as directed, within a lead of 50m:				
	2.10.1	All kinds of soil				
	2.10.1.2	Pipes, cables etc. exceeding 80mm dia but not exceeding 300mm dia				
			Metre	53.60	326.40	17495.04
	SOR 19 01	Providing, laying and jointing glazed stoneware pipes class SP-1 'A' with		33.00	320.40	17433.04
21	3011 13.01	stiff mixture of cement mortar in the proportion of 1:1(1 cement: 1 fine				
21						1
-	10.1.3	sand) including testing of joints etc. complete.	24	2.00	245	4125 1
	19.1.2	150mm diameter	Metre	3.60	315.40	1135.44
- 1	SOR 19.02	Providing and laying cement concrete 1:5:10(1 cement: 5 coarse sand:10				
22		graded stone aggregate 40mm nominal size) all-round S.W pipes including				
		bed concrete as per standard design.				
	19.2.2	150mm diameter S.W pipe	Metre	3.60	479.30	1725.48
	SOR 19.4	Providing and fixing square mouth SW gully trap grade A complete with CI				
		grating brick masonry chamber with water tight CI cover with frame of				
23		300X300mm size(inside) the wt. of cover to be not less than4.50kg. And				
		frame to not less than 2.70 kg. as/standard design				
	1					
-	SOR	180x150mmsize p type				
	encore contract	180X130ITIITISIZE p type				221
+	19.4.3	W. 1				
		With F.P.S. bricks designation 75				
	19.4.3.1		Each	3.00	1639.90	4919.70
S	SOR 19.6	Providing and laying non -pressure NP2 class R.C.C. pipes with collars			1	
4	j	ointed with stiff mixture of cement mortar in the proportion of 1:2			l	
	li	ncluding testing of joints etc.				
		L50 mm dia R.C.C. pipe				
	19.6.2	5-10-10-10-10-10-10-10-10-10-10-10-10-10-	Metr.	50.00	359.30	17965.00
				00	333,30	1,505.00
\top	SOR I				1	
	Acceptance of the second secon	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4				
	19.7	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 oarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4				
	19.7	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8				
	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal				
5	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3)				
5	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal ize) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making				
5	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded)				
5	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal ize) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making				
5	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded)				
5	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded tone aggregate 20mm nominal size) finished with a floating coat of neat				
	19.7 c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded tone aggregate 20mm nominal size) finished with a floating coat of neat ement complete as per standard design:				
	19.7 c 8 r s c c c s c c 19.7.1 lr	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded tone aggregate 20mm nominal size) finished with a floating coat of neat cement complete as per standard design:				
	19.7 c g g r s c c c c s c c c c c c c c c c c c c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded tone aggregate 20mm nominal size) finished with a floating coat of neat cement complete as per standard design: Inside size 90x80cm and 45cm deep including C.I cover with frame (light out) 455x610mm internal dimensions total weight of cover and frame to				
	19.7 c g g r s c c c c s c c c c c c c c c c c c c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded tone aggregate 20mm nominal size) finished with a floating coat of neat cement complete as per standard design:				
	19.7 c g g r s c c c s c c c c s c c c c c c c c c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 mix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making thannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded tone aggregate 20mm nominal size) finished with a floating coat of neat tement complete as per standard design: Inside size 90x80cm and 45cm deep including C.I cover with frame (light cuty) 455x610mm internal dimensions total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg)				
	19.7 c g g r s c c c s c c c c s c c c c c c c c c	Constructing brick masonry manhole in cement mortar 1:4(1 cement: 4 coarse sand) R.C.C top slab with 1:2:4 mix (1 cement:2 coarse sand: 4 graded stone aggregate 20mm nominal size), foundation concrete 1:4:8 nix (1 cement: 4 coarse sand:8 graded stone aggregate 40mm nominal size) inside plastering 12mm thick with cement mortar 1:3(1 cement: 3 coarse sand) finished with floating coat of neat cement and making hannels in cement concrete 1:2:4 (1 cement: 2 coarse sand:4 graded tone aggregate 20mm nominal size) finished with a floating coat of neat cement complete as per standard design: Inside size 90x80cm and 45cm deep including C.I cover with frame (light uty) 455x610mm internal dimensions total weight of cover and frame to be not less than 38 kg (weight of cover 23 kg and weight of frame 15 kg) With common burnt clay F.P.S (non modular) bricks of class designation			S. 147.2	15321.60

SR. MANAGER SMART CITY LTD.

26	SOR 19.8	Extra for depth for manholes				
	19.8.1	Size 90x80cm				2
	19.8.1.1	With F.P.S bricks class designation 75	Metre	0.40	5635.50	2254.20
27	SOR 19.30	Constructing brick masonry chamber for underground C.I inspection chamber and bends with 75 class designation bricks in cement mortr 1:4(1 cement: 4 coarse sand) C.I cover with frame (light duty) 455x610mm internal dimensions, total weight of cover with frame to be not less than 38 kg(weight of cover 23 kg and weight of frame 15 kg) R.C.C top slab ith 1:2:4 mix (1 cement: 2 coarse sand:4 graded stone aggregate 20mm nominal size) foundtion concrete 1:5:10(1 cement: 5 fine sand:10 graded stone aggregate 40mm nominal size), inside plastering 12mm thick with cement mortar 1:3 (1 cement: 3 coarse sand) finished smooth with a floating coat of neat cement on walls and bed concrete etc. complete as per standard design:				
	19.30.1	Inside dimensions 455x610mm and 45cm deep for single pipe line:				
		With F.P.S bricks	Each	4.00	4194.20	16776.80
28		Extra for depth beyond 45cm of brick masonry chamber:			0	
	19.31.1	For 455x610mm size				
	19.31.1.1	With F.P.S bricks	Metre	0.60	3932.40	2359.44
29	SOR 19.32	Making soak pit 2.5 m diameter 3.0 meter deep with 45x45 cm dry brick honey comb shaft with brick of class designation 75 and S.W. drain pipe 100 mm diameter, 1.8 m long complete as per standard design.				
	19.32.1	With F.P.S. bricks	Each	1.00	32412.70	32412.70
	F	SEPTIC TANK (Size: 5.0 m x 1.4m x1.8m)				
30		Earth work in excavation in foundation trenches or drains(not exceeding 1.5 m in width or 10 sqm on plan) including dressing of sides and ramming of bottoms, lift upto 1.5 m . including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.	- 1			
	SOR 2.8.1	All kinds of soil	Cum	32.88	319.60	10508.45
31	SOR, 2.28	Supplying and Filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete.	Cum	1.68	238.60	400.85
32		Providing and laying in position cement concrete of specified grade exluding the cost of centring and shuttering-all work upto plinth level.				
		1:2:4 (1 Cement : 2 coarse sand: 4 graded stone aggregate 20 mm	Cum	2.32	4151.40	9631.25
		nominal size) Providing designation 100 A one brick flat soling joints filled with local	Culli	2.32	4131,40	3031.23
33	11.72	sand including cost of watering, taxes royalty all complete as per specification and direction of E/I.	Per M²	13.44	277.50	3729.60
34		Brick work with bricks of class designation 100A in foundations and plinth in :			1705 22	2002: 25
		Cement mortar 1:6 (1 cement: 6 coarse sand)	Cum	7.56	4799.20	36281.95
35		Half brick masonry with bricks of class designation 100A in foundations and plinth in :		2.55	500.00	4507.10
	6.18.4A	Cement mortar 1:4 (1 cement: 4 coarse sand)	Sqm	2.66	596.80	1587.49
36	SOR 13.18	15 mm cement plaster 1:3 (1 cement: 3 coarse sand) finished with a floating coat of neat cement on the rough side of single or half brick wall.	Sqm	44.41	215.50	9570.36

 \bigcirc

 \bigcirc

 \cup

 \cup

_	500.53			1	Т	
ĺ	SOR 5.2	I was a market to the control of the	g			
\		attached pilasters, buttresses, plinth and string courses, fillets,				
37		columns, pillars, piers, abutments, posts and struts, etc. upt floor five leve	21			
		excluding cost of centring, shuttering, finishin and reinforcement.				
	5.2.3	1:2:4 (1 cement: 2 coarse sand: 4 graded stone aggregate 20 mm nomina				
_		size)	Cum	0.23	5166.40	1188.2
	SOR 5.3	Reinforced cement conrete work in beams, suspended floors, roofs having	-1			
		slope upto 15, landings,balconiec, shelves, chajjas, lintels, bands, plain	1			
1202		window sills, staircases and spiral stair cases upto floor five leve				
38		excludingthe cost of centring, shuttering, finishing and reinforement with				
		1:2:4(1 cement:2 coarse sand:4 graded stone aggregate 20 mm nomina	1			
		size).				
	500.50		Cum	1.82	5258.20	9569.9
39	SOR 5.9	Centring and shuttering including strutting, propping etc. and removal o	f			
	F 0.4	form for.				
	5.9.1	Foundations, footings, bases of columns etc. for mass concrete.	Sqm	2.40	186.30	447.12
	5.9.5	Lintels, beams, plinth beams, girders, bressumers and cantilevers.	Sqm	2.38	335.30	798.01
	5.9.6	Columns, Pillars, Piers, Abutments, Posts and Struts	Sqm	1.40	425.80	596.12
	5.9.3	Suspended floors, roofs, landings, balconies and access platform.	Sqm	8.44	362.60	3060.34
40	SOR 5.22	Reinforcement for R.C.C. work including straightening, cutting, bending,				
	F 22 74	placing in position and binding all complete.	14	100.00	77.40	12222
	5.22.7A	Thermo-Mechanically Treated bars TMTC-500-8mm dia.	Kg	180.00	77.40	13932.0
11		Thermo-Mechanically Treated bars TMTC-500-10mm dia.	Kg	120.00	76.70	9204.00
41		Supplying and fixing C.I. cover without frame for manholes				
	19.18.2	500 mm diameter C.I cover (medium duty) the weiht of he cover to be not	37	4.00	2027.20	44740.0
	COR 10 1F	less than 58 kg.	Each	4.00	2937.30	11749.20
	30K 19.13	Providing M.S. foot rests including fixing in manholes with 20x20x10 cm				
42		cement concrete blocks 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) as per standard design				
		aggi egate 20 mm nommai size) as per standard design				
	19.15.1	With 20x20mm square bar	Each	10.00	240.90	2409.00
	F	TUBEWELL				
	SOR	Boring/drilling bore well of required dia for casing/strainer pipe, by				
	24.1	suitable method prescribed in IS: 2800 (part I), including collecting				
		samples from different strata, preparing and submitting strata chart/bore				
13		log, including hire & running charges of all equipments, tools, plants &				
		machineries required for the job, all complete as per direction of Engineer			8	
1		in-charge, upto 90 metre depth below ground level.				
+	24.1.1	All types of soil				
			Mtrs.	90.00	388.70	34983.00
4	SOR .					
4	24.2					
	24.2.1					
T	24.2.1.1 E	Boring/drilling bore well of required dia for casing/strainer pipe, by	Mtrs.			
		uitable method prescribed in IS: 2800 (part I), including collecting				
	s	amples from different strata, preparing and submitting strata chart/bore				
4	The second secon	og, including hire & running charges of all equipments, tools, plants &			12	
+		nachineries required for the job, all complete as per direction of Engineer				
	I	n-charge, beyond 90 metre & upto 150 metre depth below ground level				
		all types of soil 300 mm dia		-		
				30.00	453.50	13605.00
					1111	

SR. MANAGER TECH.

SR. MANAGER T

	COR	Supplying, assembling, lowering and fixing in vertical position in bore well,				Γ
	SOR 24.3	unplasticized PVC medium well casing (CM) pipe of required dia,				
4.5	24.3	conforming to IS:12818, including required hire and labour charges,				
45		fittings & accessories etc. all complete, for all depths, as per direction of				
		Engineer -in-charge.				
	24.3.1	100 mm nominal size dia	Mtrs.	45.00	309.90	13945.50
		150 mm nominal size dia	Mtrs.	30.00	612.80	18384.00
_	24.3.2	Supplying, assembling, lowering and fixing in vertical position in bore well	0.000,000,000			
	SOR	unplasticized PVC medium well screen (RMS) pipes with ribs, conforming				
10	24.4.1	to IS: 12818, including hire & labour charges, fittings & accessories etc. all				
46		complete, for all depths, as per direction of Engineer-in-charge. 100 mm				
		nominal size dia		30.00	479.50	14385.00
	SOR	Gravels packing in tubewell construction in accordance with IS 4097			.IT	
	24.8	including providing graval fine/medium/coarse,in required grading & sizes				
47	24.0	as per actual requirement, all complete as per direction of Engineer-in				
		charge.	cu_m	7.08	1225.10	8673.71
	SOR	Development of tube well in accordance with IS: 2800 (part I) and IS:				
	24.12	11189, to establish maximum rate of usable water yield without sand		20		
	24.12	content (beyond permissible limit), with required capacity air compressor,				
		running the compressor for required time till well is fully develo ped,				
		measuring yield of well by V notch method or any other approved				
48		method, measuring static level & draw down etc. by step draw down				
40		method, collecting water samples & getting tested in approved laboratory,				
		i/c disinfection of tubewell, all complete, including hire & labour charges of				
		air compressor, tools & accessories etc., all as per requirement and				
		direction of Engineer-in-charge.				
		direction of Engineer in Charge.	Hrs	36.00	594.60	21405.60
	SOR	Providing & fixing suitable size threaded mild steel cap or spot welded	each			
		plate to the top of borewell housing/ casing pipe ,removable as per				
49	24.13.2	requirement, all complete for borewell of, 150 mm dia				
		requirement, an complete for bottoments, 250 mm and		1.00	196.10	196.10
	SOR	Providing & fixing MS clamp of required dia to the top of housing/casing				
-	24.14	pipe of,removable as pe tubewell as per IS;2800(part-I), including				
50		necessary bolts & nuts of required size complete				
	24.14.2	150 mm dia	each	1.00	1190.00	1190.00
	SOR	Providing & fixing Bail plug/ bottom plug of required dia to the bottom of				
51	24.15	pipe assembly as per IS;2800(part-I),				
	24.15.1	100mm dia	each	1.00	198.80	198.80
52		Add Carriage of Materials with Loading & Unloading				
		Bricks lead of (1K+7P)	‰ No.	4441.00	767.08	3406.60
		Stone chips (200KM P) from Koderma	cum	3.89	2701.30	10508.06
-		Coarse sand 50KM (1K+49P)) from Koilwar	cum	4.78	1030.30	4924.83
		Local sand(1K+2P)	cum	1.89	262.05	495.27
7		Cement (5kmP)	Tone	2.09	328.25	686.04
		Steel (5kmP)	Tone	0.30	328.25	98.48
		Sub TOTAL				454433.98
	GeM	Providing & fixing wall wall hung w.c with UF soft close set over hinges				
		assecerries set size 360x500x380 mm,Jaquar ,cat.no -LYS - WHT -38951. &				
		Concealed Single piece slim concealed cistern cat.no -JCS - WHT -				
1		2400WS.with Flusing Control plate cat.no -JCP -CHR -372415.all complete.				
		specification and direction of Engineer-in-charge.				
		Product ID - 511 6877 - 5920 65766 18				
			Each	2.00	17400.00	34800.00
	GeM	Urinal partitions Jaquar cat.no- JSE-CHR-810US450X SIZE- H: 900 W: 450				
- 1	,,	- Control Control - Control Co	1			
2		Product ID - 511 6877 - 32280 746 868	1			


 \bigcirc

 \bigcup

 \bigcup


7		TOTAL				632290.14
		Sub TOTAL (Gem Portal + SOR)				177856.16
	1	make, an outspecte as per specimental and satisfactory or eyr	each	1.00	48285.00	48285.00
11	3	make, all complete as per specification and satisfactory of e/I				
10		Establishment of -2HP of submersible pump set of approved brand and	Lucii	4.00	750.40	2321.00
10		110 mm dia cp jali	Each	4.00	730.40	2921.60
9		CP brass 2-way bib cock with wall flange(Kubix-F) 15mm	Each	2.00	599.50	1199.00
5		Soap dispenser	Each	3.00	122.10	366.30
7		Providing Towel Ring	Each	2.00	402.40	804.80
6	17.34.1	Providing Paper holder	Each	2.00	363.00	726.00
	18.92.50	40 mm plain tee	Each	8.00	850.50	6804.00
)	18.90.5	40 mm elbow	Each	10.00	144.40	1444.00
	1900	110 X110 mm dia p-trap	Each	6.00	97.17	583.04
\	12.78.2	110 mm pipe clip	Each	3.00	238.30	714.90
2	5.20	110 X 110 mm dia plain tee	Each	2.00	124.70	249.40
5	4.2	110 mm door bend	Each	6.00	183.10	1098.60
,	4.2	110 mm plain bend	Each	7.00	183.10	1281.70
	BCD.1896	110 mm vent cowel	Each	1.00	293.18	293.18
)	12.79	Provding and fixing fittings all complete as/specification & direction of E/I			·	
,	12.78.2	40 mm dia	metre	8.00	147.40	1179.20
4	12.78.1	110 mm dia	metre	28.00	238.30	6672.40
)	12.78	Provding and fixing PVC Soil , Waste & vent pipes all complete				0.010.01
		all complete. Product ID - 511 6877 - 6672 8291 253	Each	3.00	21457.68	64373.04
3		trap,32 mm size-300X190 long wall connection pipe(jaguar - ald -769)etc				
3		CP brass Pillar cock with base flange(jaguar-KUP-35001PM) CP bottle	2			
		angular stop cock with wall flange(kubix-f) 15mm(jaguar KUP- 35053PM)			
1	GeM	Poviding & fixing under counter basin (Jaquar, FLS-WHT-5701), CP brass	5			





		APPEND					
AR ELEC	CTRICAL SO	Cafeteria in Sandy	s PARK (E	LE)	1		
						AWARD	
SI. No	-1	Item of work	Unit	Quantity	Rate	AMOUNT	Ref.
		WIRING Wiring for Light plug and circuit with 2x2.5 sq.mm FF					
1	1.7.2	PVC insulated copper conductor single core cable insurface/ recessed PVC conduit/casing capping along with 1 No.2.5 sq mm FR PVC insulated copper conductor single core cable for loop earthing as required	e g r s Meter	410	161.00	66010.00	SOR Item
2	1.6	Wiring for power plug with 4x4 sq.mm FR PVC insulated copper conductor single core cable in surface recessed PVC conduit along with 2 No.4 sq mm FF PVC insulated copper conductor single core cable for loop earthing as required	/ R	40	225.00	12100.00	SOD It-
3	1.5	Wiring for power plug with 2x4 sq.mm FR PVC insulated copper conductor single core cable in surface, recessed PVC conduit along with 1 No.4 sq mm FR PVC insulated copper conductor single core cable for	/ R	40	335.00	13400.00	SOR Item
4	1.7.11	loop earthing as required Wiring for submain with 4x6 sq.mm +1X6 sq mm earth wire FR PVC insulated copper conductor single core cable in recessed PVC conduit as required.		280	200.00	56000.00	SOR Item
			Meter	80	410.00	32800.00	SOR Item
5	1.7.12	Wiring for submain with 4x10 sq.mm +1X10 sq mm earth wire FR PVC insulated copper conductor single core cable in recessed PVC conduit as required.		120	593.00	71160.00	SOR Item
6		Supplying & fixing following size ISI marked PVC conduit with accessories in recess including cuting of wall and making good the same as required.					
	1.21.1	(a) 20 mm dia	Meter	20	68.00	1360.00	SOR Item
	1.21.2	(b) 25 mm dia	Meter	40	79.00	3160.00	SOR Item
7		Supplying and fixing metal box of following size in recess with suitable size of phenolic laminated sheet cover in the front including painting etc. as required.					
	1.22.1	(a)75mmX75mmX50mm	Each	2	93.00	186.00	SOR Item
	1.22.6	(b)200mmX150mmX60mm Supplying and fixing following size/modules, GI box	Each	2	193.00	386.00	SOR Item
8		along with modular base & cover plate for modular fitting in recess etc. as required.				• •	
	1.27.1	(a)75mmX75mm :	Each	31	180.00	5580.00	SOR Item
9	1.3.3	Wiring for light point/ fan point/ exhaust fan point / call bell point with 1.5 Sq.mm FR PVC insulated copper conductor cable in recessed PVC conduit with modular switch modular plate suitable GI box earthing the point with 1.5 sq mm FR PVC insulated copper conductor single core cable etc as required.			9		
		Supplying and fixing suitable size GI box with modular	Point	137	724.00	99188.00	SOR Item
10	1.31	plate and cover in recess including providing and fixing modular type 3 pin 5/6 amps socket outlet & 6A switch connection etc. as required.					
_		Supplying and fiving of suitable size OI have with	Point	20	362.00	7240.00	SOR Item
11	1.32	Supplying and fixing of suitable size GI box with modular plate and cover in recess including providing and fixing modular 6 pin 15/16 amp socket outlet &15/16 amp modular switch including connection, painting etc as required	Set	9	413.00	3717.00	SOR Item
12	1.24.4	Supplying and fixing modular type 5/6 amp, 5 pin socket outlet on the existing modular plate & box including making connection but excluding moduler plate etc. as required. (For Bracket fan only)	250	ŭ.		201100	SOR Item
			Each	28	122.00	3416.00	SOR Item

BHAGALPUR BHAGALPUR



13	2.30	Supplying and fixing TPN sheet steel enclosure of surface or in recess along ,with 63 amp 415 volts '0 series, TPN, MCB, complete with connections testing	2'				
		and commissioning etc. as required.(For ODU)					
14	2.29	Supplying and fixing TPN sheet steel enclosure of surface or in recess along ,with 32 amp 415 volts 'C series, TPN, MCB, complete with connections testing and commissioning etc. as required.(For ODU)	9	3	1919.00	5757.00	SOR Item
-		Supplying and fixing modular type telephone socke	Each	1	1392.00	1392.00	SOR Item
15	1.24.6	outlet on the existing modular plate & box including connections, excluding moduler plate etc. as required.		1	108.00	108.00	SOR Item
16	1.16.2	Supplying and drawing 2 pair 0.5 sq mm. FR PV0 insulated annealed copper conductor unarmoured telephone cable in the existing surface / recessed	d		108.00	108.00	30K ICH
		PVC concuit etc. as required.	Meter	25	18.00	450.00	SOR Item
17	1.17	Supplying and drawing co-axial T.V cable RJ-6 grade copper conductor PE insulated with PVC sheath in the existing PVC concuit etc. as required.		40	20.00	1160.00	COD Itom
	+	Supplying and fixing modular T.V socket on the		40	29.00	1160.00	SOR Item
18	1.24.7	existing modular plate and metal box including making connection, etc. as required. Supplying and fixing modular blanking plate on the	Each	2	102.00	204.00	SOR Item
19	1.26	existing modular plate & box excluding moduler plate etc. as required.	1	10	26.00	260.00	SOR Item
	-	MAIN PANEL & D.B.s Supplying and fixing 6 way(4+12) double door			-		
20	2.9.5	horizontal type Three pole and Neutral sheet steel M.C.B. D.B, 415 Volts in surface/ recess, complete with tinned copper busbar, neutral bus bar, earth bar, din bar, detachable gland plate, interconnection phosphatised and powder painted including, earthing etc. as required(But without MCB/RCCB/ Isolator)			ā		
			Each	2	2905.00	5810.00	SOR Item
21		Supplying and fixing following ways TPN vertical Loadline distribution board suitable for upto 160 Amp four pole MCCB as incomer and MCBs as outgoing in surface/ recess, ,inclusive of tinned copper busbar, common neutral link , earth bar, din bar , for mounting MCB's etc. as required, (but without MCCB & MCB's)				,	
	2.31.6	6 way Double door	Each	1	10538.00	10538.00	SOR Item
22	2.32.7.	Supplying and fixing cable end box (Loose wire box, IP 43) suitable for TPN sheet steel vertical M.C.B. Distribution board, on surface/ recess, complete with testing commissioning etc. as required					
		Supplying and fixing of following rating electrical items	Each	1	861.00	861.00	SOR Item
23		in the existing Verticle DB as incomer including drilling holes in cubicle panel making connections etc. as required.					20
	2.4.3	(i)125 Amp 16 KA FP 415 volt MCCB.	Each	1	4004.00	4004.00	SOR Item
24		Supplying and fixing of following rating C series MCB suitable for inductive and other loads of following poles in the existing Verticle/ MCB DB complete witth connections ,testing and commissioning etc. as required.					
	2.12.1	6 Amp. To 32 Amp. SP MCB 240 Volt	Each	36	192.00	6912.00	SOR Item
	2.12.5	32 Amp TPN MCB 415 Volt	Each	4	1108.00	4432.00	SOR Item
	2.12.5	63 Amp TPN MCB 415 Volt	Each	4	1108.00	4432.00	SOR Item
25		Supplying and fixing cable end box (Loose wire box, IP 43) suitable for following three pole and Neutral sheet steel M.C.B. Distribution board, on surface/ recess, complete with testing commissioning etc. as required					., 9
	2.32.5	(i) For 6 way Double door TPN MCB DB	Each	2	1034.00	2068.00	SOR Item
26	8.10.2	Supplying and fixing of wall/floor mounted cubicle panel board fabricated with 16 guage iron sheet suitable for panel mounted switch disconnector, including busbar chamber, insulator, nut-bolt painting			Ø	2068.00	SMARTCHYLIA
		etc as required. (But without busbar copper strip)	Sft	20	1382.00	27640.00	SOR Item



		Supplying and fixing of following rating electrical item in the existing cubical panel board including drilling					
27		holes in cubicle panel making connections etc. a	9				
	=	required .					
	2.4.4	(i) 160 Amp 35 KA FP 415 volt MCCB.	Each	1	9787.00	9787.00	SOR Item
	2.7.5	(ii) 160 Amp, 4 pole changeover switch.	Each	1	7903.00	7903.00	SOR Item
	2.4.3	(iii) 125 Amp 16 KA FP 415 volt MCCB.	Each	1	4004.00	4004.00	SOR Item
	2.12.5	(iv) 32 Amp TPN MCB 415 Volt	Each	5	1108.00	5540.00	SOR Item
	2.12.2	(v) 32 Amp SPN MCB 240 Volt	Each	4	511.00	2044.00	SOR Item
	8.10.6	(vii) Digital ammeter three phase (viii) Digital Voltmeter three phase	Each	1 1	1643.00	1643.00	SOR Item
	8.10.4	Providing and fixing MV danger notice plate of	Each	1	1337.00	1337.00	SOR Item
		200mmX150mm made of mild steel at least 2mm thick					
28	2.20	and vitreous enamelled white on both sides, and with	*1				
		inscription in single red colour on front side etc as	S				
		required.	Each	1	178.00	178.00	SOR Item
		SUPPLY & INSTALLATION OF FIXTURES					
		Supply and Installation of regular / standard mode					
		A.C. ceiling fan of 1200 mm sweep including wiring the down rod of standard length (upto 30cm) with 1.5					
29	8.11.2	sq.mm FR PVC insulated copper conductor, single core					
		cable etc. as required.					
			Each	1 -	1618.00	1618.00	SOR Item
		Supplying and fixing stepped type electronic fan					
30	1.25	regulator on the existing switch box including					
50	1.20	connections excluding modular plate etc. as required.					
	-	Supply and Installation of 200mm augus 220 A.C.	Each	1	359.00	359.00	SOR Item
		Supply and Installation of 300mm sweep 230 A.C. exhaust fan in the existing opening including making					
31	8.11.4	good the damage connection testing commissioning					
		etc. as required.	Each	2	1483.00	2966.00	SOR Item
		Supply and installation of 400 mm, 230 V AC wall /				2,33,133	
32	8.11.7	cabin fan including fixing the bracket, making					
02	0.11.7	connection, testing, commissioning etc as required.					
	-	Cumplying and fiving 40 wett LED surface recention	Each	26	2427.00	63102.00	SOR Item
		Supplying and fixing 40 watt LED surface mounting luminiare provides soft light and glare free symmetrical					
		illumination fitting and all accessories including ball					
		and socket arrangement, 2 no down rods of 20 mm dia					
34	5.14	x1.6 mm thick G.I. pipe upto 30 cm length painting and					
34	5.14	wiring the down rods and connections with 1.5 sq.mm					
		FR PVC insulated, copper conductor single core cable			1		
		land earthing etc. as required					1
		and earthing etc. as required.					
		and earthing etc. as required.	Fach	4	4949.00	19796.00	SOP Itam
		and earthing etc. as required. Supplying and fixing single wall mounted 20/22watt	Each	4	4949.00	19796.00	SOR Item
		Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver	Each	4	4949.00	19796.00	SOR Item
		Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including	Each	4	4949.00	19796.00	SOR Item
35	5.9.3	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper	Each	4	4949.00	19796.00	SOR Item
35	5.9.3	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc.	Each	4	4949.00		SOR Item
35	5.9.3	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper		Scarce Scarce		T.	
35	5.9.3	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required.	Each	3	4949.00 684.00		SOR Item
	5.9.3	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the		Scarce Scarce		T.	
		Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required.		Scarce Scarce		T. 2052.00	SOR Item
		Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection	Each	3	684.00	T.	
35	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper	Each	3	684.00	T. 2052.00	SOR Item
		Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including	Each Each	3	684.00 42.00	2052.00 126.00	SOR Item
36	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required.	Each	3	684.00	T. 2052.00	SOR Item
36 37	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing	Each Each	3	684.00 42.00	2052.00 126.00	SOR Item
36	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required.	Each Each	3 3 5 .	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item
36	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing	Each Each	3	684.00 42.00	2052.00 126.00	SOR Item
36	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast	Each Each	3 3 5 .	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item
36	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with	Each Each	3 3 5 .	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item
36 37 38	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling	Each Each	3 3 5 .	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item
36 37 38	1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC	Each Each	3 3 5 .	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item
36 37 38	1.33 1.34 6.1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and	Each Each	3 3 5 .	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item
36 37 38	1.33 1.34 6.1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC	Each Each	3 5 5	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item SOR Item
36	1.33 1.34 6.1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required.	Each Each	3 3 5 .	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item SOR Item
36 37 38	1.33 1.34 6.1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing decorative wall bracket fixture in chrome finish with glass diffuser suitable for 2x15 watt	Each Each	3 5 5	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item SOR Item
337 388 399	1.33 1.34 6.1.33	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing decorative wall bracket fixture in chrome finish with glass diffuser suitable for 2x15 watt CFL/ LED lamp directly on wall including connections	Each Each	3 5 5	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item SOR Item
36 37 38	1.33 1.34 6.1.33 5.15	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing decorative wall bracket fixture in chrome finish with glass diffuser suitable for 2x15 watt CFL/ LED lamp directly on wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor swith 1.5 sq.mm FR PVC insulated, copper conductor	Each Each	3 5 5	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item SOR Item
337 388 399	1.33 1.34 6.1.33 5.15	Supplying and fixing single wall mounted 20/22watt LED type batten fitting complete with electronic driver and LED tube etc. directly on ceiling / wall including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing 2 pin 5 Amp ceiling rose on the existing junction box/ PVC box including connection etc as required. Supplying and fixing batten / angle holder including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable etc. as required. Supplying and fixing following types lamp in existing electrical fitting/ fixture etc as required. (i) 12 watt LED lamp Supplying and fixing surface mounted 10/12 watt LED type bulkhead fitting comprising of pressure die cast housing with acrylic diffuser(IP 65)and complete with integrated electronic driver etc directly on wall/ ceiling including connections with 1.5 sq.mm FR PVC insulated, copper conductor single core cable and earthing the body etc. as required. Supplying and fixing decorative wall bracket fixture in chrome finish with glass diffuser suitable for 2x15 watt CFL/ LED lamp directly on wall including connections	Each Each	3 5 5	684.00 42.00 46.00	2052.00 126.00 230.00	SOR Item SOR Item



		9					
		SUPPLY & LAYING OF UNDER GROUND CABLE				T	
42	2	Laying of one number PVC insulated and PVI sheathed/ XLE power cable of 1.1 KV grade of followin size direct in ground including excavation, san cushionig, protective covering and refilling the trenc etc. as required.	g d				
	7.1.2	(a) Above 35 sq. mm. and upto 95 sq.mm	Meter	95	151.00	14345.00	SOR Item
43	3	Laying and fixing of one number PVC insulated an PVC sheathed aluminium conductor cable of1.1 KV grade of following size on surface etc. as required.					
	7.4.2	(a) Above 35 sq. mm. and upto 95 sq.mm (Clamped with 25/3 mm MS flat clamp)	Meter	15	68.00	1020.00	SOR Item
44	9.2	Excavating for cable trenches of depth upto 1.2M in soft soil including getting out the excavated soil and disposal of surplus excavated soil directed within lead of 50 metres.	d Cum	12	155.00	1860.00	SOR Item
45	9.3	Filling available excavated earth (excluding rock) in tenches, sides of foundations etc. in layers no exceeding 20 cm in depth, consolidating each deposited layer by ramming and watering, lead upto 50 metres.	t	6	99.00	594.00	SOR Item
46		Providing and laying following size NP2 (Non pressure) RCC pipe complete with RCC collar etc. as required .					7:
	9.14.2	(a)150 mm dia	Meter	10	369.00	3690.00	SOR Item
47	DSR 2018	Laying of one number PVC insulated and PVC sheathed aluminium conductor cable of1.1 KV grade of following size in the existing RCC/ HUME/METAL pipe etc. as required.	-				
	7.5.2	(a) Above 35 sq. mm. and upto 95 sq.mm	M	10	47.00	470.00	SOR Item
48		Supplying and making end termination with brass compression gland and aluminium lugs for following size of PVC insulated and PVC sheathed/XLPE aluminium conductor cable of 1.1 KV grade as reguired.					
	9.1.22	(a) 3.5 Core 50 sq mm	Set	2	329.00	658.00	SOR Item
	9.1.24	(b) 3.5 Core 95 sq mm	Set	2	473.00	946.00	SOR Item
		EARTHING					
49	3.2	Earthing with G.I earth pipe 4.5 mt. long 40mm dia including accessories and providing masonary enclosure with cover plate having locking arrangement and watering pipe etc. with Charcoal/coke and salt as required.		2	5125.00	10250.00	SOR Item
50	3.12	Providing and laying earth connections from earth electode with 6 SWG dia G.I. wire in 15 mm. Dia G.I.pipe from earth electrode including connection with G.I. thimble excavation and refilling etc. as required.				×	
		Providing and fixing 6 SWG dia G.I. wire on surface or	Meter	40	192.00	7680.00	SOR Item
51	3.16	in recess for loop earthing etc as required.	Meter	30	38.00	1140.00	SOR Item
		SUB TOTAL A (Schedule Item)				634710.00	
27		Supplying and fixing of following rating electrical items in the existing cubical panel board including drilling holes in cubicle panel making connections etc. as required.				F) 2	
	MR	vi) Copper strip of all sizes.	Kg	10	788.80	7888.00	Quotation
	MR	(ix)Pilot lamp for indicator	Each	3	40.60	121.80	Quotation
33	0.000,000.00	Supplying and fixing of Model JNL-CHR-SL800WPAGE 27 glass & wood pendant with albaster finish E-27 9W x 1 LED light of Jaquar Make including all accessories and connection with 1.5 sq mm FR PVC insulated copper conductor single core cable and earthing the body etc as required.	Each	70	4172.52	292076.40	Quotation
41	MR	Supply of PVC insulated PVC sheathed aluminium conductor armoured under ground cable of graded 1.1 KV for working voltage upto 1100 volts conforming to ISI 1554 (Part-I) of 1964 with upto date amendment as detailed below.					Quotation
						1.000	

100

389.76

38976.00

Meter

(a) 3.5 Core 95 sq mm

Quotation

Quotation



(b) 3.5 Core 50 sq mm	Meter	20	237.57	4751.36	Quotation
SUB TOTAL B				343813.56	
 TOTAL for ELECTRICAL				978523.56	

ON 1000 SPRINGER TECH. 2 SPRINGER SMART CHYLID. SHACALPUR SMART CHYLID.



APPENDIX- 6 C

	Cafeteria in Sandys	s PARK (.	AC)			
No.No	Description	T		T .		
		1		Su	bmitted	
	SUPPLY PART (HIGH SIDE WORK)	Unit	Qty.	Rate	Amount	-
A	Sett Et Takt (mon side work)	Cinc	Qiy.	(incld. Taxes)	Amount	Ref.
1						
5-1.0	Air-conditioning System					
4	Supply of Ductable air conditioners with Single Indoor & Single/Twir	n				
	Outdoor Unit of minimum 12000 BTU/Hr. cooling capacity per Tr. fitted	1				
1	with 3 Ph. scroll compressor, Hi & LO Pressure switch, Microprocessor	r				
71	control with Hi & LO voltage cutout, single phase protection and	i				
	programmable handset & with factory charged R-22 Refrigerant.					
)						1
	AC should be fitted with Microprocessors based control includes features	5				
1	of Hi/Lo voltage protection, single phase protection, Phase reversal	1				
	protection, Compressor On/Off delay for compressor protection, Auto					
	restart function, Fault detection LP/HP/Sensor fail. LED handset, Filter				.55	1
	clean time stting, Fault logger to view 100 fault, Total run time veiwing,					
	password protected menu and parameter setting, 6 prog timer with 24			40		
	Hrs. time mode for defferent event setting in a day, weekly off. (2 days),					
	etc. Make: Carrier, Mitshubishi Heavy, Midea		1			
ì						
a	4.0 Tr. (1:1) Ductable air conditioners.	Nos.	1.00	113557.90	113557.90	
	11 Tr. (1:2) Ductable air conditioners.	Nos.	3.00	248615.05	745845.15	
	INSTALLATION PART:					
	Installation, Testing and commissioning of ductable/cassette air					
	conditioners. The rates shall be inclusive of the following:					
$\neg \uparrow$	a) Indoor unit mounting with all items.					1
	b) Minor Civil work like opening in the walls for piping & cables &					
	finishing the same. Pipes & cables between through wall shall be taken					
	through sleeves & plugged to avoid leakages.	9				
	and against the set pringger to arrow terminger.			1		1
	c) Outdoor unit mounting with all accessories vibration mounting pads					
	etc			1 1		
	d) Pressure Testing & Commissioning.					
	4.0 Tr. Carrier Make Ductable air conditioners.	Nos.	1.00	7475.00	7475.00	
	11 Tr. Carrier Make Ductable air conditioners.	Nos.	3.00	20700.00	62100.00	
	Supply & fixing of Copper cable laying in 2.0 MM thick PVC conduit	1103.	3.00	20700.00	02100.00	
5 2000	suitable for:					
_	4.0 Tr. Ductable air conditioners	Rmt.	18.00	862.50	15525.00	
	11.0 Tr. Ductable air conditioners	Rmt.	55.00	1380.00	75900.00	
	Supply, fabrication and fixing of painted MS plateform with all required	Kiiit.	33.00	1380.00	73900.00	-
		Van	200.00	102.50	20700.00	
	naterials & labour to be fixing of outdoor units.	Kgs.	200.00	103.50	20700.00	
	Supply, installation & testing of Factory fabricated Round/Oval GSS					1
	ducts with flanges, joints etc. in accordance with the approved drawings					
	and as per specifications.	C .	177.00	1427.50	251562.50	
	44 gauge galvanized sheet steel (0.63mm)	Sqmt.	175.00	1437.50	251562.50	
	22 gauge galvanized sheet steel (0.80mm)	Sqmt.	75.00	1638.75	122906.25	
	Supply,installation,testing & balancing of fixed bar extruded aluminium			1		
-6 p	owder coated round supply air Diffusers with all sides flange.		22.55	1500		
		Nos.	32.00	4600.00	147200.00	
	Supply,installation,testing & balancing of fixed bar extruded aluminium					
7 1	owder coated Louvered return air Grills with all sides flange.				Name and American Control of State of S	
-/ P	- I	0	8.00	9749.70	77997.60	
	* *	Sqmt.		3143.10		
S	supply & installation of thermal insulation with 9 mm thick closed cell	Sqmt.		9749.70		
-8 e	lastomeric nitrile rubber insulation pasted from inside of the duct with					\$-
-8 e	lastomeric nitrile rubber insulation pasted from inside of the duct with elf adhesives.	Sqmt.	150.00	690.00	103500.00	
-8 e se	lastomeric nitrile rubber insulation pasted from inside of the duct with elf adhesives. upplying & fixing of 12 mm accoustic lining of duct with open cell					
S e so S	lastomeric nitrile rubber insulation pasted from inside of the duct with elf adhesives. upplying & fixing of 12 mm accoustic lining of duct with open cell litrile Rubber density 140-180 Kg/Cu.Mtr. Applied by adhesive					
-8 e so S	lastomeric nitrile rubber insulation pasted from inside of the duct with elf adhesives. upplying & fixing of 12 mm accoustic lining of duct with open cell litrile Rubber density 140-180 Kg/Cu.Mtr. Applied by adhesive onfirming to standard specification.					al.
-8 e so S	lastomeric nitrile rubber insulation pasted from inside of the duct with elf adhesives. upplying & fixing of 12 mm accoustic lining of duct with open cell litrile Rubber density 140-180 Kg/Cu.Mtr. Applied by adhesive	Sqmt.	150.00	690.00	103500.00	TON S
S e e so	lastomeric nitrile rubber insulation pasted from inside of the duct with elf adhesives. upplying & fixing of 12 mm accoustic lining of duct with open cell litrile Rubber density 140-180 Kg/Cu.Mtr. Applied by adhesive onfirming to standard specification.	Sqmt.	150.00	690.00	103500.00	O TECH!
S e e so S N co	lastomeric nitrile rubber insulation pasted from inside of the duct with elf adhesives. upplying & fixing of 12 mm accoustic lining of duct with open cell litrile Rubber density 140-180 Kg/Cu.Mtr. Applied by adhesive onfirming to standard specification.	Sqmt.	150.00	690.00	103500.00 113850.00	A TEN



NS-12	Pressure flushing of all refrigerant piping System with Dry nitrogen & leak testing.	Nos.	7.00	2070.00	14490.00	
	Supply, Installation, testing & commissioning of 32 mm/25 mm PVC		1.00	20,000	.,,,,,,,,,,	
S-13	medium class pipes for the water drainage from IDU duly insulated with					
	6 mm thick close cell elastometric nitrile rubber.	Rmt.	50.00	276.00	13800.00	
	Supplying & Installation of interconnecting of Refrigerant Copper Piping					
	work of required outer diaMeter, insulated with 19/13 mm thick closed					
.)	cell electrometric nitrile rubber tubular insulation (or as per	1				
	manufacturer's standard) between Each set of indoor & outdoor units	1				
S-14	shall be properly fixed/supported with suitable size of clamp/ M.S.					
5 11	hanger.Refrigerant Copper Pipe Makes: Rajco/Mandev Tubes/Mehta					
)	Tubes/Totaline/Camipro etc. Protective coating over insulation					
,	Make:Paramount Polytreat/K-Flex/A-Flex/Armacell etc. suitable for:					
	4.0 Tr. Ductable air conditioners					
NS-14.1	4.0 11. Ductable all conditioners	Rmt.	15.00	1380.00	20700.00	
. —	11.0 Tr. Ductable air conditioners	IXIII.	13.00	1500.00	20700.00	
NS-14.2	Tr. o Tr. Ductable an Conditioners	Rmt.	45.00	2530.00	113850.00	
NO.15	Vaccumisation of the system and charging of Refrigerant in the system as			1		
NS-15	required.	Kgs.	14.00	1207.50	16905.00	
	Supply, Installation & commissioning of 200 mm x 75 mm x 1.6 MM					
NS-16	thick GI Cable tray with Cover for the laying of Copper pipes outside of					770
)	the building.	Rmt.	40.00	1092.50	43700.00	
)	TOTAL				2132164.4	

SR. MANAGER TECH. 2 SR. MANAGER TECH. 2 BHAGALPUR SMART CITY LTD. BHAGALPUR



		APPENDIX 11: LA	ANDSCA	APING		
S.No.	Ref	Description of Work	Unit	Qty	Rate (Rs.)	Amount (Rs.)
	A	SOIL AND SITE PREPARATION				
1	23.1	Making up the trenched area upto proper levels b filling with earth or earth mixed with manure befor and after flooding trench with water (including cps of imported earth, sludge or manure.	e cum	3600.00	37.20	1,33,920.00
2	23.2	Supplying and stacking of good earth at site including royalty but excluding carriage (earth measured in stacks will be reduced by 20 % for payment)		3600.00	119.40	4,29,840.00
3	23.4.3	Supplying and stacking at site dump manure from approved source, excluding carriage (manure measured in stacks will be reduced by 8% for payment) Screened through sieve of I.S. designation 4.75 mm	e			
		Screened through sieve of i.s. designation 4.75 hun	cum	900.00	64.30	57,870.00
4	23.9	Mixing earth and sludge or manure in proportion specified or directed.	cum	4500.00	17.40	78,300.00
5	23.8	Spreading of sludge, dump manure or/and good earth in required thickness (Cost of sludge, dump manure or/and good earth to be paid separately)		4500.00	25.00	1,12,500.00
6	23.6	Uprooting rank vegetation and weeds by digging the area to a depth of 60 cm removing all weeds and other growth with roots by forking repeatedly, breaking clods, rought dressing, flooding with water, uprooting fresh growths after 10 to 15 days and then fine dressing for planting new grass, including disposal of all rubbish with all leads and lifts.	100 sqm	40	235.7	9,428.00
7	23.7	Fine dressing the ground	100 sqm	40.00	173.40	6,936.00
8	23.1	Grassing with 'Doob' grass including watering and maintenance of the lawn for 30 days or more till the grass forms a thick lawn free form weeds and fit for moving including supplying good earth if needed.				
9	23.10.3	In rows 5 cm apart in either direction.	100 sqm	34.21	855.40	29,263.23
10	23.14	TREE, SHRUB, CREEPER PLANTATION Digging holes in ordinary soil and refilling the same with the excavated earth mixed with manure or sludge in the ratio of 2:1 by volume (2 parts of stacked volume of earth after reduction by 20 % 1 part of stacked volume of manure after reduction by 8 %) flooding with water, dressing including removal of rubbish and surplus earth, if any with all leads and lifts (cost of manure sludge or extra good earth if needed to be paid for separately)				
		Holes 60 cm dia. and 60 cm deep.	each	1000.00	57.80	57,800.00
		- source of the time of the thep.	cucit	200.00	07.00	37,000.00

AMANAGER PECH. 2 SR. MANAGER PECH. TO. BHACALPUR SHART CITY LTD.



The Cressing, revening etc. Intuitions stating and disposal of materials declared unserviceable and surplus earth by spreading and levelling as directed, within a lead of 50 m lift upto 1.5 m complete (cost of sludge, manure or extra earth to be paid for separately) Supplying and Plantation as per the direction of engineer incharge inc. carriage cost of	S.No.	Ref	Description of Work	Unit	Qty	Rate (Rs.)	Amount (Rs.)
A A EVERGEN TREES for Boundary wall (Ht-3000mm) A Allanthus Excelsa / Maharukh Nos. 190.00 500 95.000.0 A Azadarichata indica Nos. 110.00 500 55.000.0 Azadarichata indica Nos. 500.00 500 1.00.000.0 Azadarichata indica Nos. 300.00 500 1.00.000.0 Azadarichata indica Nos. 300.00 500 1.00.000.0 Peltophorum pterocarpum Nos. 300.00 500 1.50.000.0 Famarindus indica Nos. 300 500 1.50.000.0 Lagerstroemia speciosa Nos. 150 750 1.12.500.0 Cassia fistula Nos. 150 570 1.12.500.0 Basulnia variegate Nos. 150 500 75.000.0 Basulnia variegate Nos. 150 500 75.000.0 Basulnia variegate Nos. 150 500 75.000.0 Ficus elastica Nos. 500 750 3.75.000.0 Ficus elastica Nos. 500 750 3.75.000.0 Ficus elastica Nos. 500 500 25.000.0 Pseudobmbax ellipticum (Bombax ellipticum) Nos. 50 2500 1.25.000.0 C Palm Wodeyta bifurcate Nos. 75 800 60.000.0 Caryota urens Nos. 75 800 60.000.0 Bismarckia nobilis Nos. 50 2500 1.25.000.0 C SHRUBS (Ht-300 to 1000 mm) C C C C C C C C C	11	23.13	excavating 60 cm deep and trenching the excavated base to a further depth of 30 cm refilling the excavated earth after breaking clods and mixing with sludge of manure in the ratio of 8:1 (8 parts of stacked volume of earth after reduction by 8%) flooding with water filling with earth if necessary, watering and finally fine dressing, leveling etc. including stacking and disposal of materials declared unserviceable and surplus earth by spreading and levelling as directed, within a lead of 50 m lift upto 1.5 m complete (cost of sludge, manure or extra earth to be paid for	d d r c c cum	1944.00	105.50	2,05,092.00
A	12						
Azadrachta indica		A				,	
Azadrachta indica			Ailanthus Excelsa / Maharukh	Nos.	190.00	500	95,000.00
Azadirachta indica							55,000.00
Dalbergia sissoo							2,50,000.00
Peltophorum pterocarpum							1,00,000.00
Tamarindus indica						500	1,50,000.00
Lagerstroemia speciosa Nos. 150 750 1,12,500.0							1,50,000.00
Cassia fistula			Lagerstroemia speciosa	Nos.		750	1,12,500.00
Jacaranda mimosifolia Nos. 150 500 75,000.0			Cassia fistula	Nos.	150	750	1,12,500.00
Bauhinia variegate			Jacaranda mimosifolia			500	75,000.00
Plumeria alba			Bauhinia variegate	Nos.	150	600	90,000.00
Plumeria alba		В	Tree for Internal Pathway				
Ficus elastica Nos. 100 600 60,000.0 Ficus rumphii 'variegata' Nos. 50 500 25,000.0 Pseudobombax ellipticum (Bombax ellipticum) Nos. 50 2500 1,25,000.0 C Palm			Plumeria alba	Nos	500	750	3 75 000 00
Ficus rumphii 'variegata' Nos. 50 2500 25,000.00 Pseudobombax ellipticum (Bombax ellipticum) Nos. 50 2500 1,25,000.00 C Palm							
Pseudobombax ellipticum (Bombax ellipticum) Nos. 50 2500 1,25,000.00						7000000	
C Palm Nos. 75 800 60,000.00 Caryota urens Nos. 75 750 56,250.00 Washingtonia filifera Nos. 50 2500 1,25,000.00 Bismarckia nobilis Nos. 50 2500 1,25,000.00 C SHRUBS (Hf- 300 to 1000 mm) SHRUBS (Hf- 300 to 1000 mm) 200 250.00 50,000.00 Calliandra haematocephala Nos. 200 250.00 30,000.00 Agave variety (tequilana, Americana) Nos. 5000 600.00 30,00,000.00 Cactus Variety Nos. 100 750.00 75,000.00 Sansevieria (different varieties) Nos. 400 600.00 2,40,000.00 Adenium varieties Nos. 500 300.00 1,50,000.00 Euphorbia milii Nos. 500 150.00 75,000.00 Cycus variety Nos. 100 2500.00 2,50,000.00 Clerodendrum inerme Nos. 100 60.00 6,000.00 D <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>							
Wodeytia bifurcate		С		1105.	- 50	2500	1,23,000.00
Caryota urens			Wadaytia hifurcata	Noc	75	900	60,000,00
Washingtonia filifera Nos. 50 2500 1,25,000.00 Bismarckia nobilis Nos. 50 2500 1,25,000.00 C SHRUBS (Ht- 300 to 1000 mm) SHRUBS (Ht- 300 to 1000 mm) 200 250.00 50,000.00 Calliandra haematocephala Nos. 5000 600.00 30,00,000.00 Agave variety (tequilana, Americana) Nos. 5000 600.00 30,00,000.00 Cactus Variety Nos. 100 750.00 75,000.00 Sansevieria (different varieties) Nos. 400 600.00 2,40,000.00 Adenium varieties Nos. 500 300.00 1,50,000.00 Euphorbia milii Nos. 500 150.00 75,000.00 Cycus variety Nos. 100 2500.00 2,50,000.00 Clerodendrum inerme Nos. 100 15.00 1,500.00 D GROUND COVERS (Ht-200mm) 8 100 50.00 50.00 1,250.00 Alternenthra red sqm 50.00 50.00 <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td></t<>							
Bismarckia nobilis							
C SHRUBS (Ht- 300 to 1000 mm) Nos. 200 250.00 50,000.00 Agave variety (tequilana, Americana) Nos. 5000 600.00 30,00,000.00 Cactus Variety Nos. 100 750.00 75,000.00 Sansevieria (different varieties) Nos. 400 600.00 2,40,000.00 Adenium varieties Nos. 500 300.00 1,50,000.00 Euphorbia milli Nos. 500 150.00 75,000.00 Cycus variety Nos. 100 2500.00 2,50,000.00 Clerodendrum inerme Nos. 100 15.00 1,500.00 Ficus panda Nos. 100 60.00 6,000.00 D GROUND COVERS (Ht-200mm) sqm 25.00 50.00 1,250.00 Alternenthra red sqm 50.00 50.00 2,500.00							
Calliandra haematocephala Nos. 200 250.00 50,000.00 Agave variety (tequilana, Americana) Nos. 5000 600.00 30,00,000.00 Cactus Variety Nos. 100 750.00 75,000.00 Sansevieria (different varieties) Nos. 400 600.00 2,40,000.00 Adenium varieties Nos. 500 300.00 1,50,000.00 Euphorbia milii Nos. 500 150.00 75,000.00 Cycus variety Nos. 100 2500.00 2,50,000.00 Clerodendrum inerme Nos. 100 15.00 1,500.00 Ficus panda Nos. 100 60.00 6,000.00 D GROUND COVERS (Ht-200mm) 100 60.00 1,250.00 Alternenthra red sqm 25.00 50.00 2,500.00				1403.	30	2500	1,23,000.00
Agave variety (tequilana, Americana) Nos. 5000 600.00 30,00,000.00 Cactus Variety Nos. 100 750.00 75,000.00 Sansevieria (different varieties) Nos. 400 600.00 2,40,000.00 Adenium varieties Nos. 500 300.00 1,50,000.00 Euphorbia milii Nos. 500 150.00 75,000.00 Cycus variety Nos. 100 2500.00 2,50,000.00 Clerodendrum inerme Nos. 100 15.00 1,500.00 Ficus panda Nos. 100 60.00 6,000.00 D GROUND COVERS (Ht-200mm) Iresene herbstii sqm 25.00 50.00 1,250.00 Alternenthra red sqm 50.00 50.00 2,500.00				Nice	200	250.00	50,000,00
Cactus Variety							
Sansevieria (different varieties) Nos. 400 600.00 2,40,000.00 Adenium varieties Nos. 500 300.00 1,50,000.00 Euphorbia milii Nos. 500 150.00 75,000.00 Cycus variety Nos. 100 2500.00 2,50,000.00 Clerodendrum inerme Nos. 100 15.00 1,500.00 Ficus panda Nos. 100 60.00 6,000.00 D GROUND COVERS (Ht-200mm) Iresene herbstii sqm 25.00 50.00 1,250.00 Alternenthra red sqm 50.00 50.00 2,500.00							
Adenium varieties							
Euphorbia milii						The second secon	
Cycus variety			Adelliditi varieties				15 - A. LWS 97 / 709 - 5 / 75 - 100 / ASS - 5
Clerodendrum inerme Nos. 100 15.00 1,500.00 Ficus panda Nos. 100 60.00 6,000.00 D GROUND COVERS (Ht-200mm)			Euphorbia milii		500		75,000.00
Ficus panda Nos. 100 60.00 6,000.00				Nos.	100	2500.00	2,50,000.00
D GROUND COVERS (Ht-200mm) Iresene herbstii			Clerodendrum inerme	Nos.	100	15.00	1,500.00
Iresene herbstii sqm 25.00 50.00 1,250.00 Alternenthra red sqm 50.00 50.00 2,500.00			Ficus panda	Nos.	100	60.00	6,000.00
Alternenthra red sqm 50.00 50.00 2,500.00		D	GROUND COVERS (Ht-200mm)				
Alternenthra red sqm 50.00 50.00 2,500.00			Iresene herbstii	sam	25.00	50.00	1 250 00
3411 30.00 30.00 2,300.00							
			Dianella tasmanica	sqm	75.00	20.00	1,500.00

SR. MANAGER TECH. 2 SR. MANAGER TECH. 2 BHAGALPUR SMART CITYLTD. BHAGALPUR SMART CITYLTD.



S.No.	Ref	Description of Work	Unit	Qty	Rate (Rs.)	Amount (Rs.)
13		Carriage of Materials				
	A	Earth (1 km kutcha + 2 km pucca)	cum	3600.00	262.05	9,43,380.00
	В	Manure (1km kutcha + 5 km pucca)	cum	900.00	301.36	2,71,221.73
14		Supplying and installation of precast cc dustbins a per approval of PSCL.	no.	65.00	1500.00	97,500.00
15		Supplying and installation of precast cc bollards provision of bollards at minor junctions, plot entry points and pedestrian crossing with a minimum spacing of 1.2m c/c or as directed by enginee incharge, pv and fixing of concrete bollards of m30 grade and size 1000 mm (ht-1000m dia 150mm complete inclusive of all consumables, t&p and labours as/requirement	y n r no.	200.00	2000.00	4,00,000.00
16		Supplying and installation of FRP seating benches of 3 person capacity with cast iron side support as per approval of PSCL.		110.00	12000.00	13,20,000.00
17	RCD SOR, 8.19	Fencing with welded steel wire Fabric 75 mm x 50 mm (Suggestive) (Providing 1.20 metre high fencing with angle iron posts 50 mm x 50 mm x 6 mm at 3 metre center to center with 0.40 metre embedded in M15 grade cement concrete, corner, end and every 10th post to be strutted. provided with welded steel wire fabric of 75 mm x 50 mm mesh or 75 mm x 25 mm mesh and fixed to iron posts by flat iron 50 x 5 mm and bolts etc. complete in all respects.)	m m	1800.00	557.00	10,02,600.00
		Provision of Water Supply for the Park				
18	UD HD MEWS 250 M	Cost for constructiom of 150mm x 100mm x 120 m deep high yeild tube well. All complete as per specification, site condition and as per direction of e/I UD & HD Approved Estimate	Set	1.00	224670.00	2,24,670.00
19		5 HP Pump motor with Starter pannel, all complete as per specification and direction of E/I UD & HD Approved Estimate	Set	1.00	104000.00	1,04,000.00
20	ME WS 250	110 mm to 63 mm HDPE Pipe distribution of 2020 Mtr for Hrticulture and Irrigation purposeall complete. UD & HD Approved Estimate	Set	1.00	1294025.00	12,94,025.00
22	LS	Stone sculptures	Nos.	9.00	50000.00	4,50,000.00
		Cost of landscaping				1,32,22,346
		Carriage of Materials				9,43,380.00
100		Total Cost of landscaping			4	1,41,65,726





-	T		T			T	T	T	T
	Amount (Rs)	₹3,000.00	₹3,51,666.00	₹1,50,318.00	₹1,16,550.00	₹ 8,010.18	₹ 72,649.50	₹ 1,48,500.00	₹ 48,000.00
	Rate (Rs)	250	279.1	238.6	277.5	131.53	4151.4	13500	12000
	Quantity	12	1260	630	420	6.09	17.5	11	4
	Height		0.3	0.15		0.15			15
æ	Width		09	09	9	5.8			
endix 13 : Kids Play Area	Length		70	70	20	70			
: 13 : Kids	No	12						11	4
pendix	Unit	Nos.	Cum	Cum	Sqm	Cum.	Cum	Nos.	Nos.
App	Description	Cutting of Trees, including Cutting of Trunks, Branches and Removal (Cutting of trees, including cutting of trunks, branches and removal of stumps, roots, stacking of serviceable material with all lifts and up to a lead of 1000 mtrs and earth filling in the depression/pit.) Girth from 300 mm to 600 mm	Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well es 10 sqm on plan) including disposal of excavated earth, lead upto 50 m and lift upto 1.5 m; disposed earth to be levelled and neatly dressed	upplying and Filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete.	Providing designation 100 A one brick flat soling joints filled with local sand including cost of watering, taxes, royalty all complete as per building specification and direction of E/I.	M Granular Material or hard murrum for GSB works at Quarry	Providing and laying in position cement concrete of specified grade exluding the cost of centring and shuttering-all work upto plinth level. 1:2:4 (1 Cement: 2 coarse sand : 4 graded stone aggregate 20 mm nominal size)	Sitting Arrangements Product id: 5116877-58242510321	Wide Slide :Product id: 5116877-53479918813
	Code	RCD 2019	2.6.1	2.28	11.72	RCD M - 010	4.1.3	Gem S Portal	Gem Portal
	S.No	1	74	ю	4	5	9	7	SE W

EHACALPUR SMART CITY I



		App	pendix	: 13 : Kids	endix 13: Kids Play Area	-				
S.No	Code	Description	Unit	°N N	Length	Width	Height	Quantity	Rate (Rs)	Amount (Rs)
6	Gem Portal	Wave Slide , Product id: 5116877-76117636819	Nos.	8				c	24700	7 100 00 ± 74 ± 74 ± 74 ± 74 ± 74 ± 74 ± 74
10	Gem Portal	Spiral Slide, Product id: 5116877-42863169742	Nos.	ю				c	00840	* 7 ±,100.00 * 7 00 E20 00
11	Gem	Double see saw, Product id: 5116877-14551277238	Nos.	4				, 4	25000	00.0000000000000000000000000000000000
12	-Gem Portal	Merry go Round;, Product id: 5116877-30759744505	Nos.	2				71	24000	₹ 48.000 00
13	Gem Portal	Swing for Children Gem Portal Product id: 5116877-14066115194	Nos.	4				4	38000	₹1,52,000.00
14	Gem Portal	Children Round Swing GeM Product id: 5116877-8698111099	Nos.	4				4	13899	₹ 55 506 00
15	Gem	Artificial Grass (Artificial Grass) GeM Product id: 5116877-36166393221	Sqm		15	7.		205	1500 40	
16	Gem	TRAMPOLINE FOR PARK Product id: 5116877-44763654480	, No.	4				C-1	1392.40	00.808,508.00
	1 Ortal	Advance Multi Play Station (SHUBHAM) (MIII TI COMBO		-				4	7670	₹ 30,680.00
17	Gem	MODULED) Product id: 5116877-18391069021	Nos.	7				2	87000	₹ 1,74,000.00
A		Sub Total								
В		Carriage Cost								₹ 21,90,898
С		Total Cost of Kids Play Area								₹ 2,52,986
										₹ 24,43,883
							30			

SR. MANAGER TECH. 2 SR. MANAGER TECH. 2 BHAGALPUR SMART OTTY LTD. BHAGALPUR



		Appendix 19 : Estimate of Nel	hru Memorial Re	novation			
S.No	SOR 2018	Description	Unit	No	Quantity	Rate (Rs)	Amount (R
1 /	2.1.1	Cutting of Trees, including Cutting of Trunks, Branches and Removal (Cutting of trees, including cutting of trunks, branches and removal of stumps, roots, stacking of serviceable material with all lifts and up to a lead of 1000 mtrs and earth filling in the depression/pit.)					
		Girth from 300 mm to 600 mm	Nos.	10	10	248	2,480.00
2	2.33	Clearing grass and removal of the rubbish upto a distance of 50 m outside the periphery of the area cleared.	Sqm	1	1390	2.96	4,114.40
3	4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centering and shuttering - All work upto plinth level.					
	4.1.6	1:3: 6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40 mm nominal size)	cum	1.00	4.17	3307.00	13,791.84
4	11.29	40 mm thick rough chisel dressed stone flooring over 20 mm (average) thick base including pointing with C.M 1:2 (1 cement :2 stone dust) with an admixture of pigment to match the shade of the stone with base 1:1:1 (1 lime : 1surkhi : coarse sand or 1:5 (1 cement : 5 coarse sand)					-
	11.29.1	Red sand stone	Sqm	1	109.56	753.1	82,509.64
5	10.32	Steel work welded in built up sections/framed worK including cutting hoisting, rixing in position and applying a priming coat of approved steel primer using structural steel, etc. as required.					el el
	10.32.2	In gratings, frames, guard bar, ladders, railings, brackts. Gates & similar works.	Kg	1	100	88.8	8,880.00
6	13.48.3	Painting Steel work with Deluxe Multi Surface Paint to give an even shade. Two or more coat applied @ 0.90 ltr/ 10 sqm over an under coat of primer applied @ 0.80 ltr/ 10 sqm of approved brand and manufacture.					2
		Steel Struture Steel Struture	Sqm	1.00	10	37.8	378
7	10.36	Providing and fixing stainless steel (Grade 304) railing made of Hollow tubes, channels, plates etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners, stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-incharge, (for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).	Kg	1	1093.20	496.00	5,42,227.20
8	13.79	Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade					
		New work (three or more coats)	Sqm	1.00	300	68.3	20,490.00
9	13.80	Removing dry or oil bound distemper by scrapping, sand paper and preparing the surface smooth including necessary repari scratches tec.Gmplete	Sqm	1	300.00	8.10	2,430.00
10		CARRIAGE					
		Coarse Sand	Cum			1030.3	2041.05
		Stone Chips Cement	Cum ` MT			2701.25	10578.36
F			1411		0.95	472.68	447.63
	D 19	Steel	MT		1.19	328.25	391.67

GR. MANAGER TECH. 2 GR. MA



	BCD	STATION CLUB		T	T	
S.No.	SOR 2018	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT (Rs
		Desmantiling				
	15.7	Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead:				
1	15.7.2	In lime mortar with old mugnal bricks	Cum	888.6	587	521608.2
	15.7.4	In cement mortar	Cum	2692.00	685.10	1844289.2
		Desmantiling doors windows and clerestory windows (steel or wood) shutters				
	15.12	including chowkhats, architrage, holdfasts etc. complete and stacking within 50				
2		metres lead:		_		
	15.12.1	Of area 3 sqm and below	Each	21	125.8	2641.8
	15.12.2	Of area beyond 3 sqm Dismantling wood work in frames, trusses, purlins and rafters upto 10 metres span	Each	33	173.1	5712.3
3	15.14	and 5 metres height including stacking the material within 50 metres lead:				
-	15.14.1	Of sectional area 40 cm* and above	Cum	5.6	1528.1	8576
		Brick work		-	100011	00.0
4	6.1A	Brick work with bricks of class designation 100A in foundation and plinth in :				
-	6.1.12 /1	Cement mortar 1:4 (1 cement : 4 coarse sand)	Cum	30.25	5037.20	152375.30
		Reinforced Cement Concrete Works				
		Providing and laying in position machine batched, machine mixed and machine				
	5.33A	vibrated design mix cement concrete of specified grade for reinforced cement				
5	3.33A	concrete structural elements, excluding the cost of centring, shuttering, finishing and reinforcement. M-20 grade reinforced cement concrete				
	E 22 A 2 2	Beams, planth beams, girders, bressumers, contilevers, Suspended floors lintels roofs		244.50	F (00 00	100111010
	5.33A.2.2	and staircases including spiral staircases, shelves etc.	cum	244.59	5689.80	1391668.18
		Reinforcement for RCC work including straightening. Cutting, bending, placing in				
6	5.22	position and binding all complete.				
	5.22.7B	Thermo-Mechanically Treated bars TMTC-500-10 mm dia.	1	40001	77.70	2212404.26
			kg	43201	76.70	3313494.36
7	5.9	Centring and shuttering including strutting, propping etc. and removal of form for:				
	5.9.3	Suspended floors, roots, landings, balcnies and access platform.	sqm ,	985.20	362.60	357,233.
		Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S.				
8	9.48	flats, square or round bars etc. including priming coat with approved steel primer all				
	9.48.2	Fixed to openings/ wooden frames with rawl plugs	И-	1/20 00	122.0	207 172
	7.40.2	Flooring Work	Kg	1680.00	122.9	206,472.
		Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622		+		
		(Thickness to be specified by the manufacture) of approved make in all colours,			Ú.	
		shades except burgundy, bottle green, black of any size as approved by Engineer -in-			017000000000000000000000000000000000000	
9	11.36	Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Motar	Sqm	26.25	739.80	19,419.
		1:3 (Icement : 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm				
		including pointing in white cement mixed with pigment of matching shade complete.				
		Providing and laying Vitrified tiles in different sizes (thickness to be specified by the				
		manufacturer), with water absorption less than 0.08% and conforming to IS: 15622,				
		of approved brand & manufacturer, in all colours and shade, in skirting, riser of				
10		steps, laid with cement based high polymer modified quick set tile adhesive (water				
		based) conforming to IS: 15477, in average 6 mm thickness, including grouting of			1	
		joints (Payment for grouting of joints to be made separately).		1 1		
	11.47.3	Size of Tile 800 x 800 mm.	C	920.75	15(0.50	121 (002 07
		40 mm thick rough chisel dressed stone flooring over 20 mm (average) thick base	Sqm	839.65	1568.50	1316983.97
	2000 E20	including pointing with C.M 1:2 (1 cement :2 stone dust) with an admixture of				
11		pigment to match the shade of the stone with base 1:1:1 (1 lime : 1surkhi : coarse		1 1		•
		sand or 1:5 (1 cement : 5 coarse sand)				
		Red sand stone	Sqm	51.00	753.10	38408.10
		Plaster & Finishing Works				
		12 mm cement plaster of mix				
12	13.11.2	1:4 (1 cement : 4 coarse sand)	Sqm	1950.00	139.90	272805.00
12	12.12	15 mm cement plaster on rough side of single or half brick wall of mix.		1	1(1.00	120120.00
13			C	742.00		120129.80
	13.12.2	1:4(1 cement: 4 coarse sand)	Sqm	742.00	161.90	
	13.12.2 13.24	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix.				79177 11
13	13.12.2 13.24 13.24.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand)	Sqm Sqm	742.00 663.65	117.80	78177.44
13	13.12.2 13.24 13.24.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix.				78177.44
13 14	13.12.2 13.24 13.24.1 13.79	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and				
13 14	13.12.2 13.24 13.24.1 13.79	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing	Sqm	663.65	117.80	78177.44 50,678.6
13 14 15	13.12.2 13.24 13.24.1 13.79 13.79.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies, terraces etc,	Sqm	663.65	117.80	
13 14	13.12.2 13.24 13.24.1 13.79 13.79.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies , terraces etc, consisting of following operations. Applying and grouting a slurry coat of neat	Sqm	663.65	117.80	
13 14 15	13.12.2 13.24 13.24.1 13.79 13.79.1 22.8 22.8.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies , terraces etc, consisting of following operations. Applying and grouting a slurry coat of neat With average thickness of 120mm and minimum thickness at Khurra as 65 mm.	Sqm	663.65	117.80	50,678.6
13 14 15	13.12.2 13.24 13.24.1 13.79 13.79.1 22.8 22.8.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies , terraces etc, consisting of following operations. Applying and grouting a slurry coat of neat With average thickness of 120mm and minimum thickness at Khurra as 65 mm. Providing wood work in frames of doors, windows, clearstory windows and other	Sqm	663.65 742.00	117.80	50,678.6
13 14 15	13.12.2 13.24 13.24.1 13.79 13.79.1 22.8 22.8.1 9.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies , terraces etc, consisting of following operations. Applying and grouting a slurry coat of neat with average thickness of 120mm and minimum thickness at Khurra as 65 mm. Providing wood work in frames of doors, windows, clearstory windows and other frames, wrought framed and fixed in position	Sqm sqm sqm	742.00 985.20	117.80 68.30 2253.30	50,678.6 2,219,951.1
13 14 15	13.12.2 13.24 13.24.1 13.79 13.79.1 22.8 22.8.1 9.1 9.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies , terraces etc, consisting of following operations. Applying and grouting a slurry coat of neat with average thickness of 120mm and minimum thickness at Khurra as 65 mm. Providing wood work in frames of doors, windows, clearstory windows and other frames, wrought framed and fixed in position Second Class teak wood	Sqm	663.65 742.00	117.80	50,678.6 2,219,951.1
13 14 15 16 17	13.12.2 13.24 13.24.1 13.79 13.79.1 22.8 22.8.1 9.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies , terraces etc, consisting of following operations. Applying and grouting a slurry coat of neat with average thickness of 120mm and minimum thickness at Khurra as 65 mm. Providing wood work in frames of doors, windows, clearstory windows and other frames, wrought framed and fixed in position Second Class teak wood Providing 40 x 5 mm flat iron hold fast 40 cm long including fixing to frame with 10	Sqm sqm cum	985.20 8.36	117.80 68.30 2253.30 95749.10	
13 14 15	13.12.2 13.24 13.24.1 13.79 13.79.1 22.8 22.8.1 9.1 9.1	1:4(1 cement: 4 coarse sand) 6 mm cement plaster to ceiling of mix. 1:3(1 cement: 3 coarse sand) Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade New work (three or more coats) Waterproofing prepatation of surface as required for treatment of roofs, balconies , terraces etc, consisting of following operations. Applying and grouting a slurry coat of neat with average thickness of 120mm and minimum thickness at Khurra as 65 mm. Providing wood work in frames of doors, windows, clearstory windows and other frames, wrought framed and fixed in position Second Class teak wood	Sqm sqm sqm	742.00 985.20	117.80 68.30 2253.30	50,678.6 2,219,951.1

BR. MENACETR SHART CITY LTD.
BRAGALPUR SHARALPUR
BHAGALPUR

	Т	Providing and fixing aluminium handles anodised (anodic coating not less than		T	Т	
19	9.10	grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade with necessary screws etc. complete:	1			
	9.100.1	125 mm	Each	174.00	54.00	9,396.00
20	9.10	Providing and fixing aluminium hanging floor door stopper anodized (anodic coating not less than grade AC 10 as per IS :1868) transparent or dyed to required	1			
	9.101.2	colour and shade with necessary screws etc. complete. Twin rubber stopper	Each	66.00	40.40	2,666.40
	7.101.2			00.00	10.10	2,000.10
21	10.18	Providing and fixing circular cast iron box for ceiling fan clamp 140 mm internal dia, 73 mm height, 5 mm thick rim bottom and top lids, 1.5 mm thick M.S sheet with its top surface hacked for proper bonding top lid shall be screwed into the cast iron box by means of 3.3 mm dia round headed screws, one ;pcf at the corners. Clamps shall be made of 12mm dia M.S. bar bent to shape as per standard drawing.	Each	40.00	141.30	5,652.00
22	13.81.1	With ready mixed pink or grey primer of approved brand and manufacture on woodwork (hard and soft wood)	Эчи	196.00	32.20	6,311.20
	13.82	Painting with ready mixed paint of approved brand and manufacture in all shades				
23	13.82.1	to give an even shade: New steel work (two or more coats)	Sqm	20.79	74.50	1,548.86
	13.82.2	New wood work (two or more coats)	Sqm	196.00	74.50	14,602.00
		Painting with synthetic enamel paint of approved brand and manufacture to give an		170.00	7 2,00	11/002.00
24	13.93	even shed.				
	13.93.1	Two or more coats on new work	Sqm	1,950.00	70.40	137,280.00
25	17.1	Providing and fixing water closet squattting pan (Indian Type WC pan) with 100mm sand cast iron P or S trap, 10 liter low fixture complete, including cutting and making good the wall and level white PVC flushing cistern, including flush pipe, manully control device(handle lever) confiming to IS:7231, with all fiftings and floors where ever required.				
	17.1.1	white Vitreous china, Orissa, Pattern WC pan of size 580x440 mm with integral type	Nos.	1.00	3390.90	3,390.90
26	17.3	footrest. Providing and fixing white vetreous china pedestal type water closet. (European type) with seat and lid, 10 ltr flow level white vitreous china flushing cistren and C P flush bend with fitting and CI brackest, 40mm flush bend, over flow arrangment with special of standreds make and mosqutoues proof coupling of approved municipal complete design complete, including painting of fittings and brackets,				
	17.3.1	cutting and making good the walls. W.C. Pan with ISI marked white solid plastic seat.	Nos.	1.00	4554.00	4,554.00
27	17.4	Providing and fixing white vitreous china flat back or wall corner type leaped urinal basin of 430x260x350 mm and 340x410x265 mm size repectively with automatic flushing cistren with standred flush pipe and CPP brass spreaders with brass union and GI claim complte, including painting of fittings and brackets, cutting and	1103.	1.00	1301.00	1,001.00
		making good the wall and floor whenever required.				<u> </u>
	17.4.2	Range of Two Urinal Basin with 5 ltr white PVC automatic flushing cistren.	Nos.	2.00	5121.70	10,243.40
	17.7	Providing and fixing wash basin with CI Brackest, 15mm CP brass pillar taps, 32mm CP brass waste of standred pattren including painting of fittings and brackets, cutting and making good the wall whereever required.				
28	17.7.1	White virterous China wash basin size 630x450mm with a pair of 15mm CP brass pillar taps	Nos.	4.00	2307.10	9,228.40
	17.7.7	White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps.	Nos.	4.00	1520.00	6,080.00
29		Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore.				
29		15 mm Nominal Bore	Nos.	9.00	512.90	4,616.10
		Providing and fixing CP Brass long body bib cock of approved quality conferming to				
30	18.51	IS: standreds and weighinf not less than 690 grams				
		15 mm Nominal Bore	Nos.	3.00	531.60	1,594.80
31	18.48	providing and placing on terrace (at all floor levels) polytheline water storges tank, ISI :12701 marked, with cover and sutaible loking arrangment and making necessary holes for inlet, Outlet and over flow pipes but without fittings and the base support for tank.	Litre	1000.00	7.90	7,900.00
32	17.32	Providing and fixing mirror of superior glass (of approved quality) and of required shapes and size with plastic moulded frame of approved make and said with 6mm thick hard.				
		Oval shape 450 x 350 mm Mirror	Nos.	4.00	744.60	2,978.40
33	Analysis	Septic tank as per Specification and dorection of E/I. all complete as per the Specification,Note: 1) Effluent from septic tank to be taken to nearby manhole/ sump/STP through shallow sewers. If this option is not available then it is to be disposed off	Nos.	1.00	188113.00	188,113.00
0.40						13,154,916.21
34	Analysis	Internal plumbing and electrification			7%	920,844.13
35	Analysis	Carriaga				14,075,760.34
33	Analysis A	Carriage Brick	Per Thousand	13849.01	767.08	10623.30
	В	Coarse Sand	Cum	193.68	1030.3	199545.45
		Stone Chips	Cum	248.49	2701.25	671224.27
		Cement	MT	110.45	472.68	52205.37
	E	Steel	MT	44.88	328.25	14732.09
					TOTAL	15,024,091

 \bigcirc

 \odot

 \bigcirc

 \bigcup

()

4			APPENDIX 21: ESTIMAT	E OF SEC	CONDARY/E	MERGENC	GY ENTRA	NCE GA	TE		
	SL. NO	BCD SOR	DESCRIPTION OF ITEM	UNIT	No.	Length	Width	Depth	QTY.	RATE (Rs.) AMOUNT
1	1	20.3A.1	Making 25cm (10") dia bore up to 5 M depth below ground with hand auger of approved quality is ordinary soil (vide classification of sol item-A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50 M lead including all lifts, all complete as per approved design and direction of E/I./	f Rmt	6	5			30	148.6	4458
1,1,-	2	20.3A.2	Making 63 cm (25") dia under-ream at required depth with hand auger of approved quality ir ordinary soil (vide classification of soil item-A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50M lead including all lifts, all complete as per approved design and direction of E/I.	Each	12					158.60	1903.2
	3	2.8.1	Earth work in excavation in foundation trenches or drains(not exceeding 1.5 M in width 10 sqm on plan)including dressing of sides and ramming of bottoms lift upto 1.5 m including getting out the excaveted soil and disposal of surplus excaveted soil as directed, within a lead of 50.0m	cum							
					1	16.2	1.5	0.75	18.225		
	4	- 2.28	Supply and filling in plinth with local sand and under floors including	cum					18.225	319.6	5824.71
1			watering,ramming,consolidating and dressing complete								
)_					1	16.2	1.5	0.075	1.8225		
-		4.1.8	Providing and laying in position cement concrete of			-			1.8225	238.60	434.85
	5		specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	cum							
-			beam		1	16.2	0.5	0.1	0.81		
É			gate path in slope		2	6 1.2	5	0.15	4.5 1.8		
)						1.2	3	0.13	7.11	2940.8	20,909.09
L			R.C.C WORKS								
	6	BCD SOR, 5.1.1	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement-All work up to plinth level.1:1:2 (1 cement:1 coarse sand:2 graded stone aggregate 20mm nominal size)	cum						*	
			Beam		1	16.2	0.8	0.6	7.776		
)			pile @ .250 mm radiuds		6	4.4	0.25	2.2	0.65		
6.	-		pergola top		1	9.9	0.8	0.6	12.672 1.3365		
-/-					8	0.9	0.4	0.3	0.864		
)-		9	Security Room		1	2.7	2.4	0.15	0.972		
					1	10.2	0.25	0.15	0.3825 22.43	6434.4	1,44,337.27
1									22.43	0434.4	1,44,337.27
	7	6.1A f	Brick work with bricks of class designation 100A in oundation and plinth in :	cum							
		6.1.12 A	Cement mortar 1:4 (1 cement : 4 coarse sand)			2.7		0.05			
1					2 2	2.7	4.4	0.25	5.94 5.28		
_						4.4	7.4	0.23	11.22	5037.2	56,517.38
)	8		Providing 20mm thick cement plaster 1:6(1cement:6 oarse sand)	Sqm							6/
)_					4	2.7	4.4		47.52		4.14.5
-					4	2.4	4.4		42.24 89.76	173.00	15,528.48
J	9	o re	inishing walls with water proofing cement paint fapproved brand and manufacture and of equired shade to give an even shade	Sqm					de CO	173.00	13,328,48
		N	lew work(three or more coats)						~	P. (4.17)	3. Cillhan

Solling.

BHBE



		Plaster area		1				89.76	68.3	6,130.61
10	7.30	Providing and laying Red Sand Stone as pe approved sample 30 mm thk (only cladding)	r sqm							
				1	2.7	1		2.7		
								2.7	949	2,562.30
12	5.22.7B	Reinforecment for R.C.C work including straightening, cutting, bending, placing in position and binding all complete	,	4,262.10				4,262.10	76.7	3,26,903.36
13	10.32.2	Steel work welded in built up sections/framed work including cutting hoisting, rixing in position and applying a priming coat of approved steel primer using structural steel, etc. as required			19					
		In gratings, frames, guard bar, ladders, railings, brackts. gates & similar works.								
		@ 40 kg /Sqm(Gate grill)	Kg	1	1.2	2.4		2.88		
				1	6	2.4		14.4		
								17.28		
								864	88.8	76,723.20
14		Carriage of Materials								
		Steel	MT.					4.26	290.27	1,237.16
		bricks	per thousand				94	5.542	767.08	4,251.16
		stone	cum.					25.4	1576.82	40,051.23
		cement	Mt.					16.3	290.27	4,731.40
		Sand	cum.					18.03	896.66	16,166.78
									Total Cost	7,28,670

ON ONE FIECH. 2 SR. MANAGER TECH. 2 BHACALPUR SMART CITY LTD. BHACALPUR BHACALPUR



Annendix	77.	ESTIM	ATE	OF F	NTRA	VCF GATE	


SL. NO.	BCD SOF 2018		UNIT	No.	Length	T		QTY.	RATE (Rs.)	AMOUNT
	2018 20.3A.1	Making 25cm (10") dia bore up to 5 M depth belo ground with hand auger of approved quality	w					-	None None	
1		ordinary soil (vide classification of sol item-A) to to plumb and without eccentricity in any stage operation and disposal of the excavated earth up 50 M lead including all lifts, all complete as p	of to Rmt	12	5			60	148.6	8916
		approved design and direction of E/L/								
2	20.3A.2	Making 63 cm (25") dia under-ream at require depth with hand auger of approved quality is ordinary soil (vide classification of soil item-A) truto plumb and without eccentricity in any stage coperation and disposal of the excavated earth up to 50M lead including all lifts, all complete as peapproved design and direction of E/I.	n e of e Each	24					158.60	3806.4
3	2.8.1	Earth work in excavation in foundation trenches of drains(not exceding 1.5 M in width 10 sqm or plan) including dressing of sides and ramming of bottoms lift upto 1.5 m including getting out the excaveted soil and disposal of surplus excaveted soil as directed, within a lead of 50.0m	n if e cum							i
		4		2	17.3	1.5	0.75	38.925		
				6	3	1.5	0.75	20.25	240.5	*****
4	2.28	Supply and filling in plinth with local sand and under floors including watering,ramming,consolidating and dressing complete	, cum					59.175	319.6	18912.33
				2	17.3	1.5	0.075	3.8925		
				6	3	1.5	0.075	2.025		
5	4.1.8	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:4:8 (I Cement: 4 coarse sand: 8 graded stone aggregate 40 mm nominal size)	cum	3 10 10 10 10 10 10 10 10 10 10 10 10 10				5.9175	238.6	1,411.9
		beam		2	17.3	0.5	0.1	1.73		
		and with in along		6	3	0.5	0.1	0.9		
		gate path in slope		2	6.3	6	0.15	5.67 5.94		
								14.24	2940.8	41,876.9
6	BCD SOR, 5.1.1	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement-All work up to plinth level.1:1:2 (1 cement:1 coarse sand:2 graded stone aggregate 20mm nominal size)	cum							
		Beam		2	17.3	0.8	0.6	16.608		
-		Beam		6 2	3 17.3	0.8	0.6	8.64		
				6	3	0.8	0.6	16.608 8.64		
		pile @ .250 mm radiuds		12		0.25	2.2	1.30		
		colum colum pedastal main gate		10	0.75	0.8	0.6	19.2 0.75		
	s	security cabin		1	2.2	2.2	0.125	0.605		
		electrical control room		1	2.2	2.2	0.125	0.605		
		pergola main gate beam & colum		2	17.3 9	0.45 1.45	0.6	4.671		
		g		2	17.3	1.45	0.5	17.30		
								107.97	6434.4	6,94,736.65
	- In	Brick work with bricks of class designation 100A in								
7	6.1A fo	oundation and plinth in :	cum							
	6.1.12 A	Cement mortar 1:4 (1 cement : 4 coarse sand)		4	2.6	3	0.25	7.8		
				2	2.5	3	0.25	3.75		, 9.
				2	1.15	3	0.25	1.725		C.Y.
							1	13.28	5037.2	66,868.83
0	13.13.4 P	Providing 20mm thick cement plaster 1:6(1cement:6	Ca							CO.000,00
8		Providing 20mm thick cement plaster 1:6(1cement:6 oarse sand)	Sqm							1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
8			Sqm	4	2.6	3		31.2	000	
8			Sqm	4 2 2	2.6 2.5 1.15	3 3 3		31.2 15 6.9		



								Total Cost of 3nos gate.	85,01,469.42
				-			 	Total Cost	28,33,823.14
		Sand	cum.				 50.71	896.66	45,469.63
		cement	Mt.				67.42	290.27	19,570.00
		stone	cum.				91.77	1576.82	1,44,704.77
		8	per thousand				6.56	767.08	5,032.04
		bricks	MT.				 20.51	290.27	5,954.81
14		Carriage of Materials Steel) (T						
							1256	88.8	1,11,532.80
							31.4		
				2	1.25	2	5		
		7	0	1	6	2.4	14.4		
		brackts. gates & similar works. ® 40 kg /Sqm(Gate grill)	Kg	2	3	2	12		
		In gratings, frames, guard bar, ladders, railings,				-			
13	10.32.2	Steel work welded in built up sections/framed work including cutting hoisting, rixing in position and applying a priming coat of approved steel primer using structural steel, etc. as required							
12	5.22.7B	Reinforecment for R.C.C work including straightening, cutting, bending, placing in position and binding all complete		20,514.73			20,514.73	76.7	15,73,479.60
							19.8	2236.8	44,288.6
				1	1	6	6		
				2	1.15	6	13.8		
	7.37.1 A	Dressing of sandstone in veneer work	sqm				-		
11	7.37	Stone work for wall lining etc.(Veneer work) over 12 mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry 3.30 kg/sqm including rubbing and polishing complete.(to be secured to the backing by means of cramps which shall be paid seperately)	3						
							36.3	949	34,448.
				1	6	0.6	3.6		
	-		-	2 2	1.45 3.3	9	26.1		
10	7.30	Providing and laying Red Sand Stone as pe approved sample 30 mm thk (only cladding)	sqm	1 2	1.45		254		
		Plaster area		1			53.1	68.3	3,626.
		New work(three or more coats)							
		of approved brand and manufacture and c required shade to give an even shade	of Sqm						



		Appendix 23A: Estimat	te of Sw	imming Po	ool	T
SL.No.	BCD SOR 2018	DESCRIPTION OF ITEM	UNIT	RATE	QTY.	AMOUNT (Rs.)
1	2	3	4	5	6	7
1	2.6	Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m; disposed earth to be levelled and neatly dressed.				
	2.6.1	All kinds of soil	cum	279.1	1787.26	498824.266
2	2.26	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth: consolidating each deposited layer by ramming and watering lead.	cum	103.30	442.68	45728.844
3	11.41	Providing and laying vitrifed floor tiles in different sizes {thickness to be specified by the manufactruer) with water absorption's less than 0.08 % and conforming to IS: 15622 of approved make in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joint with white cement and matching pigments etc., complete.	SQM			
	11.41.1	Size of Tile 50x50 cm.		1377.1	1338.35	1843041.785
4	2.28	Supplying and filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete.	cum	238.6	267.67	63866.062
		CONCRETE WORK				
5	4.1.8	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	cum	2940.8	136.85	402448.48
6	BCD SOR, 5.1.2	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement-All work up to plinth level. 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stone aggregate 20 mm nominal size)	cum	4902.3	488.08	2392714.584
		REINFORCEMENT				
7	5.22.7B	Reinforcement for R. C. C work including straightening, cutting, bending, placing in position and binding all complete.	KG	76.7	47471.56	3641068.652
		Shuttering			all	Carrie C
					<u> </u>	GR MARKEN SIMET



8	BCD SOR,	Walls (any thickness) including attached plas	Sqm	321.3	92.52	29726.676
9	5.9.2	Foundations, footings, bases Columns	SQM	185.9	639.32	118849.588
)	4.5.1	Masonry work	JQIVI	103.3	039.32	118843.388
10	6.1A	Brick work with bricks of class designation 100A in foundation and plinth in :				
)	6.1.12 A	Cement mortar 1:4 (1 cement : 4 coarse sand)	cum	5037.2	33.96	171063.312
		Finishing				
) 11	13.11	12 mm cement plaster of mix	22			
	13.11.2	1:4 (1 cement : 4 coarse sand)	sqm	139.9	290.47	40636.753
12	13.26	Neat cement punning	sqm	38.60	290.47	11212.142
		Flooring				
13	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer -in-Charge in skirting, risers of steps and dados over 12 mm thick bed of cement Motar 1:3 (1cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	Sqm	739.8	220	162756
14	11.37	Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of ist quality conforming to IS: 15622 of approved make in colours such as white, Ivory, Grey, Fume Red, Brown, laid on 20 mm thick Cement motar 1:4 (1 cement: 4 coarse sand) including pointing the joints with white cement and matching pigment etc., complete	SQM	671	1250	838750
15	11.26 r	Kota stone slab flooring over 20 mm (average) thick base laid over and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete . Base with 1:1:1 (1 lime : 1 surkhi: L coarse sand) / 1:4	-			
	11.26.1	20 to 25 mm thick -	SQM	1119.6	181.98	203744.808





16	8.2	Providing and fixing 18 mm thick gang saw cut, mirror polished, premoulded and prepolished, machine cut for kitchen platforms, vanity counters, window sills, facias and similar locations, of required size, approved shade, colour and texture laid over 20 mm thick base cement mortar 1:4 (1 cement: 4coarse sand), joints treated with white cement, mixed with matching pigment, epoxy touch ups, including rubbing, curing, moulding and polishing to	SQM			
<u> </u>	r	edges to give high gloss finish etc. complete at all levels.				
	8.2.2	Granite of any colour and shade				
	8.2.2.1	Area of slab upto 0.50 sqm	SQM	3741.2	181.98	680823.576
))))))))))		Providing and laying integral cement based treatment for water . proofing on horizontal surfaces at all levels as directed by Engineer-in-charge and consisting of: 1) 1st layer of 20 mm thick approved and specified rough stone slab over a 25 mm thick base of cement mortar 1:3 (1 cement:3 coarse sand) mixed with water proofing compund conforming to IS: 12645 in the recommnded proportion. Joints sealed and grouted with cement slurry mixed with water proofing compound conforming to IS: 12645 in proportions recommended by the manufacturer. II) 2nd'c!ass layer of mm thick cement mortar 1:3 (1 cement:3 coarse sand) mixed water proofing compound in recommended proportions. III) Finishing top with stone aggregate of 10 mm to 12 mm nominal size spreadidng @ 8 cudm/sqm thoroughly embedded in the 2nd layer.				
	22.1.1	using rough kota stone	SQM	1304.3	1377.26	1796360.218





		Bricks Stone Cement Sand	per thousand cum. Mt. cum.	16.776 535 242.27 331.1	767.08 1576.82 290.27 896.66 Total Cost	12868.53408 843598.7 70323.7129 296884.126 1,56,28,608
		Stone Cement	thousand cum. Mt.	535 242.27	1576.82 290.27	843598.7 70323.7129
		Stone	thousand cum.	535	1576.82	843598.7
			thousand			
		Bricks		16 776	767.08	12868.53408
		Steel	MT.	47.471	290.27	13779.40717
22		Carriage of Materials				
		anchor brackets				
21	MR	providing and suppling lane ropes with anchor brackets	each	1680	9	15120
	9.48.2	welding Fixed to openings/ wooden frames with rawl plugs	kg	122.9	2373.7	291727.73
20	9.48	complete. Providing and fixing M.S. grills of required pattern in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all				
19	11.43	Fixing glazed/ Ceramic/ Vitrified floor tiles with cement based high polymer modified quick-set tile adhesive (Water based) conforming to IS: 15477, in average 3 mm thickness.	SQM	380.6	1470	559482
	22.2.1	using rough kota stone	SQM	1627.8	358.28	583208.184
18	22.2	Providing and laying integral cement based treatment for water proofing on the vertical surface by fixing sspecified stone slab 20 mm thick with cemm slurry mixed with water proofing compound conforming to IS: 2645 in recommended proportion with a gap of 20 mm (minimum) between stone slabs and the receiving surfaces and filling the gaps with neat cement slurry mixed with water proofing compound and finishing the exterior of stone slab with cement mortar1:4 (1 cement:4 coarse sand) 20 mm thick with neat cement punning mixed with water proofing compound in recommended proportion complete at all levels and as directed by Engineer-in-charge.				

HAGALPUR SMART CITY LTD.

BHAGALPUR SMART CITY LTD.

BHAGALPUR SMART CITY LTD.



Appendix 23B - Electro-Mechanical BOQ for Swimming Pool

Type of Swimming Pool : Over Flow Type Surface Area for Main Pool Approx : 1250.0 M₂ Depth for Main Pool Approx : 2.0 M Volume for Main Pool Approx : 2500.0 M3 Volume for Balancing Tank : 125.0 M3 Total Volume for Main Pool + Balancing tank Approx : 2625.0 M3 Turnover Period : 5.0 Hrs. Flow Rate : 525.0 M³/Hr. Nos. of Pump Provided : 5 Working + 1 Standby Flow of Each Pump Approx : 105.0 M3/hr. Filtration Velocity : 35.0 M³/Hr/M² Filter Offered Nos. : 5.0 Cross Sectional Area Required for Each Filter : 3.00 M^2 Suggested Filter Dia : 2000 mm Provided Cross Sectional Area per Filter M² : 3.140

SI. No.	Description	Qty.	Unit	Unit Rate (In Rs.)	Total
1	EQUIPMENT PART				
) /1(a)	Supply of Bobbin Wound Side Mount Sand Filter manufactured with fiber glass and polyester resin, UV resistance surface, fitted with collector arms and diffuser made from unplasticised PVC and Polypropylene with lid in polyester resin and fibre glass, manual air purge and 6" PVC flanged connection for inlet and outlet, Pressure gauge, water drain/empty drain for filter etc. Complete in all respects.				
7	Capacity 105000 ltrs/hr				
	Design @ 35000 ltrs/sqm/hr.				
)	Diameter 2000 mm Working Pressure 2.5 kg/cm²	5	Nos.	9,50,000.00	47,50,000.00
)	Model: GD-301925				
(b)	Valve Battery				
,)	Supply of Valve Battery Manifold made in PVC with flanges for connecting to filters Consists of set of 5 - butterfly valves for carrying out filtration, backwashing, rinsing and shut down of the filters. Size: 160mm	5	Nos.	1,50,000.00	7,50,000.00
.)	Model: GD-301935				
(c)	Corse & Fine Sand media for filter	22500	Kg	15.00	3,37,500.00
)2	Supply of Self Priming pumps with plastic body, in built strainer basket, Impeller in PPO, Motor shaft in stainless steel AISI-420, Mechanical seal in SIC/graphite and steatite, Motor housing in aluminium, with motor -2800rpm, F class insulation, protection IP-55. (5W+1S)				
	Capacity 105000 ltrs/hr				
)	Head 16 mtr				
	Hp 10.0, Three Phase	6	Nos.	2,25,000.00	13,50,000.00
,	Model: GSP-3020-7.5				
~					. 0

GR. MANAGER TECH. 2

GR. MANAGER SMART CITY LTD.

BHAGALPUR SMART CITY LTD.

3	Swimming Pool U.V. Sterlizer				
	Supply of U.V. Sterlizer with S.S. Housing outside, U.V. Lamp, glass tube and				
	all other accessories with cleaning arrangement, supports, inlet outlet				
	connection with bypass arrangement including S.S. Cabinet with glass door of				
	suitable size to house the U.V. Sterlizer complete with required accessories.				
	Flow rate = 100000 Ltr/Hr				
	working Pressure = 2.5 Kg/Sqm	6	Nos.	6,50,000.00	39,00,000.00
	Model: UV-3010240W				
	Desire Desire	3	Nos.	48,000.00	1,44,000.00
4	Dosing Pump Supply of Chemical dosing Pump for Chlorination with 200 Ltrs. Sintex tank		1103.	40,000.00	1,11,000.00
	and Accessories				
######################################					
	Capacity 0-20 litres/hr. Head 35 M				
	Model: DP-301004				
	Niodel. Dr-301004				
5	Stainless Steel Drain				
	Supply of Stainless steel drain grating plate made out of 316 quality S S	10			
	plates with suitable supporting frame and of following sizes and				
	having holes of required size for drainout chamber.		- 4		
- 3			Nee	32,000.00	64,000,00
	Size 500X500 MM	2	Nos.	32,000.00	64,000.00
	Model: DG-SS-316-04				
6	Inlet Nozzle	100	Nos.	714.00	71,400.00
0	Supply of Flow adjastable ABS inlet nozzles UV treated with S.S. screws to fit				
	in the 2" PVC pipes				
	Model: IN-301201				
	1				
7	Suction Inlets (Vacuum points)	6	Nos.	485.00	2,910.00
	Supply of ABS white plastic suction port / Vacuum nozzle with 2 inch solvent				
	cement connection				
	Model: VC-301301				
8	Ladder				
0	Supply of Stainless Steel 316 ladders, width: 500mm wide, handrails dia			71 - 1	
	43mm stainless steel, non-slip steps provided with anchoring Socket.				
	Tolling Grant Gran				
a	6 Step Standard Ladder with Anti-skid Steps	4	Nos.	48,000.00	1,92,000.00
	Model: LD-ST-316-6				

0

 \cup

		,			
9	Underwater LED Lights				
	Supply of 24Volt 54 W under water stainless steel 316L LED light				
	fixture (IP 68) including all required assessories & making	20	Nos.	45,000.00	9,00,000.00
)	connection as required, with 2 Mtr power cord.				
	Model: UWL-301615	-			
10	Power Supply	2	Nos.	15,000.00	30,000.00
	Supply of Transformer for LED Lights 24V DC, 30 amp	<u> </u>	1100.	10,000.00	30,000.00
	Model: PS24-301605				
11	Deck Box	20	Nos.	1,071.00	21,420.00
	Supply of ABS white plastic deckbox.		1,00.	1,011.00	21,420.00
)	Model: JB-301101				- Company of the comp
12	Cleaning Accessories				
	Extensive telescopic Handle, (2.4 - 4.8) metres long &1.1mm thick for				
a	cleaning attachment in anodized almunium.	1	Nos.	3,648.00	3,648.00
	Model: GD-TP224A				
/	Middel. GD-11 224A		_	 	
b	Transparent Blue Polyethylene hose 40mm(1-1/2") dia 30 m length.	1	Nos.	10,580.00	10,580.00
)	Model: GD-H3815PE		1103.	10,500.00	10,360.00
С	Surface net skimmer made in polypropylne	1	Nos.	884.00	884.00
	Model: GD-LS301				
d	Deep bag net Skimmer made in polypropylne			700.00	
\u	Model: GD-LS201	1	Nos.	702.00	702.00
	Model. GB-E3201				
) e	Curved polybristle wall brush 450 mm	1	Nos.	642.00	642.00
	Model: GD-BR401		1100.	042.00	042.00
)					
f	Test kit for PH and chlorine.	1	Nos.	618.00	618.00
)	Model: GD-TK907				
g	Hi-grade Stainless Steel Algae Brush - 10"	1	Nos.	1,067.00	1.007.00
)	Model: GD-BR404		1105.	1,067.00	1,067.00
h _	Vacuum head with SS-body, 1 1/2" connection size 900 mm long	1	Nos.	58,000.00	58,000.00
	Model: GD-SS-VH01				
)					
i	Deluxe large Vacuum head with 4 wheels, alu-body, plastic handle, 1 1/2"	1	Nos.	6,100.00	6,100.00
)	connection size 445x130 mm		1103.	0,100.00	0,100.00
ı i	Polybristle wall brush 10" (26cm)	1	Nos.	275.00	275.00
,	Model: GD-BR402	- 1	INOS.	375.00	375.00
)					
k	Chemical TCCA 90 (50 kg.) & ALUM (30 kg.)	1	Set	18,000.00	18,000.00
	Model: GD-301921		200	10,000.00	10,000.00
1	nylon rope	100	Mtr	85.00	8,500.00

- 10	To the Full west	Τ	T		
13	Competition Equipment				
i	Starting Blocks	10	Nos.	1,86,125.00	18,61,250.00
1	Supply of Fixed Diving Starting Block 700mm height	1		.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
	Make: GADS/DGM				
ii	Float Lines	11	Nos.	1,76,420.00	19,40,620.00
	Supply of Roma model lane separator 50mt complete				
	Make: GADS/DGM				
iii	Anchoring Sockets	22	Nos.	14,230.00	3,13,060.00
	Supply of Stainless steel separator anchor.				
	Make: GADS/DGM				19
				4 04 500 00	2 22 222 24
iv	Float Line Roller	2	Nos.	1,81,500.00	3,63,000.00
	Supply of Separator collection wheel 1.8m				16
	Make: GADS/DGM				
		2	Nos.	90,430.00	1,80,860.00
٧	Backstroke turn indicators		NOS.	90,430.00	1,60,600.00
	Supply of backstroke indicator for pools up to 25m wide (posts are complete				
	with cords with floats)/ pair				
-	Make: GADS/DGM				
:	Anchoring Sockets	4	Nos.	14,230.00	56,920.00
vi	Supply of Stainless steel separator anchor.	· ·	1100.	, ,,200,00	55,025.5
	Make: GADS/DGM				
	Make, GADS/DGM				
vii	False start post indicator	1	Nos.	95,940.00	95,940.00
VII	Supply of false indicator for pools up to 25m wide (posts are complete with				
	cords with floats)/ pair				
	Make: GADS/DGM				
viii	Anchoring Sockets	2	Nos.	14,230.00	28,460.00
	Supply, of Stainless steel separator anchor.			49	E
	Make: GADS/DGM				
	Supply of Lifeguard chair with wheels made in S/S AISI 304, dia 43mm tube.				
ix	Treads, platform, chair including parasol holder made of polypropylene fibre -	2	Set	85,000.00	1,70,000.00
	glass . Complete with wheeled base				
,	Make: GADS/DGM				
14	Life Saving Equipment				
	I I I I I I I I I I I I I I I I I I I	2	Nos.	6,000.00	12,000.00
i	J Hook / Safety Hook		1103.	0,000.00	12,000.00
	Make: GADS/DGM				
11	Life inelat	6	Nos.	5,500.00	33,000.00
ii	Life jacket		1103.	0,000.00	00,000.00
	Make: GADS/DGM				
iii	Oxygen Cylinder with trolley	1	Nos.	45,000.00	45,000.00
111	Make: GADS/DGM			,	.3,000.00
	INIANG. CADO/DOM				
iv	Single fold Stretcher	1	Nos.	8,500.00	8,500.00
17	Make: GADS/DGM				3,000.00
	mano. Onborbom				
v	First Aid Kit	1	Nos.	3,500.00	3,500.00

0

 \bigcirc

 \cap

 \bigcirc

 \bigcirc

 \bigcirc

0

 \ominus

0

Ö

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

0

 \bigcirc

	Make: GADS/DGM				
vi	Artificial Respirator / Ambu bag	1	Nos.	6,500.00	6,500.00
	Make: GADS/DGM				
vii	Life buoy ring	6	Nos.	8,550.00	51,300.00
	Make: GADS/DGM				
7					
ATT OF	Total Price in Rupees		建设工程		1,77,92,256.00

OR MANAGER TECH. 2 SR. MANAGER TECH. 2 SR. MANAGER TECH. 2 BHAGALPUR SMART CITY LTD. BHAGALPUR SMART CITY LTD.

	PLUMBING & ELECTRICAL PART				
15	uPVC pipes Providing and fixing uPVC pressure Pipes (10kg/cm2) with plain socket suitable for solvent cement jointing conforming to IS:4985/2000 & fittings conforming to IS 7834/87. Cut to required lengths including all necessary fittings and specials such as bends, tees, unions, reducers, flanges and plugs etc. The pipes & fittings shall be tested to a pressure of 10 Kg/Sq.cm.				
i)	32 mm dia	30	RM	130.00	3,900.00
ii)	50 mm dia	RO	RM	198.00	
iii)	63 mm dia	78	RM	295.00	23,010.00
iv)	75 mm dia	6	RM	415.00	2,490.00
v)	90 mm dia	132	RM	582.00	76,824.00
vi)	110 mm dia	6	RM	865.00	5,190.00
vii)	160 mm dia	312	RM	1,826.00	5,69,712.00
viii)	200 mm dia	270	RM	2,817.00	7,60,590.00
vii)	250 mm dia	282	RM	4,810.00	13,56,420.00
viii)	315 mm dia	12	RM	7,858.00	94,296.00
16	Ball Valve				
	Providing and fixing Pvc lever operated ball valve of full flow with setting and gland of superior quality having minimum working pressure of 10 kg/cm ² with union, flanges where as required.				
i)	32mm dia	10	Nos.	567.00	5,670.00
ii)	40mm dia	RO	Nos.	848.00	
——————————————————————————————————————	50mm dia	RO	Nos.	1,426.00	
iv)	63mm dia	RO	Nos.	2,084.00	
v)	75mm dia	1	Nos.	5,503.00	5,503.00
vi)	90mm dia	RO	Nos.	8,047.00	
			- 03		
17	Butterfly Valve Providing and fixing uPVC butterfly valves. Tested to a pressure not less than 10 Kg/Sq.cm. Including rubber gasket, flanges, nuts, bolts, washers complete as required.				
i)	90 mm dia	12	Nos.	9,132.00	1,09,584.00
	110 mm dia	1	Nos.	11,168.00	11,168.00
iii)	160 mm dia	7	Nos.	17,617.00	1,23,319.00
iv)	200 mm dia	10	Nos.	28,360.00	2,83,600.00
iv)	250 mm dia	3	Nos.	66,994.00	2,00,982.00
			*		
18	Non return valve				
а	Providing and fixing Pvc ball Type Or Spring Loaded Non Return valve with setting and gland of superior quality having minimum working pressure of 10 kg/cm ² with union, flanges where as required.				
	E0mm dia	RO	Nos.	2,703.00	
i)	50mm dia 63mm dia	RO	Nos.	3,910.00	
	75mm dia	RO	Nos.	6,900.00	
iii)	7 Jillili ula	1.0	1100.	3,000.00	

 \bigcirc

 \cap

 \bigcirc

 \bigcirc

 \bigcirc

 \cup

 \bigcirc

 \cup

)					
b	Providing and fixing of uPVC Wafer Check Valve non-return valves (PN 10)	T			
	complete with matching flanges, rubber insertion, nuts, bolts and washer etc	2.			
	of following sizes.				
7		1			
i)	75mm dia	RO	Nos.	4,280.00	
- ii)	90 mm dia	RO	Nos.	5,168.00	
iii)	110 mm dia	RO	Nos.	6,009.00	
_ iv)	160 mm dia		Nos.		00.004.00
_	200 mm dia	6		11,034.00	66,204.00
(v)	250 mm dia	2	Nos.	16,421.00	32,842.00
vi)	250 mm dia	3	Nos.	24,641.00	73,923.00
19	Puddles Sleeve	-			
19	Fudules Sieeve	-			
	Const. 9 fining of fallowing since of house data DVO LH. 9 / DVO	-			
	Supply & fixing of following sizes of heavy duty PVC puddle flanges (uPVC				
)	pipe(10 kg/cm2) fixed with flanges, length 400 to 600 mm length) on the wall			1	
	of plantroom, balancing tank and the water body walls & Slab (As required).				
)	To be laid in between the steel reinforcement before RCC. Does not include				
	any civil work.				***
7)					
i)	32 mm dia	2	Nos.	300.00	600.00
ii)	50 mm dia	RO	Nos.	405.00	
iii)	63 mm dia	RO	Nos.	675.00	
iv)	75 mm dia	1	Nos.	900.00	900.00
v)	90 mm dia	RO	Nos.	1,080.00	
vi)	110 mm dia	1	Nos.	1,530.00	1,530.00
vii)	160 mm dia	1	Nos.	3,150.00	3,150.00
viii)	200 mm dia	2	Nos.	3,800.00	7,600.00
ix)	250 mm dia	7	Nos.	4,800.00	33,600.00
	230 mm dia		1105.	4,000.00	33,000.00
71	Supply, laying, testing and commissioning of SS 304 Grade 400MM DIA			ļ	
	Pump Suction Header with 2 Nos 250mm Dia Flange Connection For				
	Balancing Tank to Pump Suction Header, 1 No. 90 mm Dia Flange				
20		1	Nos.	2,65,000.00	2,65,000.00
	Connection For Vacuum Pipe & 1 No. 250 mm Dia Flange Connection For			_,_,_,	2,00,000.00
)	Pool Drain Pipe & 6 No. 200mm Dia Flange Connection For Pump Suction.				
	· ·				
-					
2	Supply, laying, testing and commissioning of SS 304 Grade 300MM DIA				
	Pump Delivery Header with 2 Nos 200mm Dia Flange Connection For Filter				
21	Inlet Header, 1 No. 160 mm Dia Flange Connection For Drain Pipe & 6 No.	1	Nos.	2,10,000.00	2,10,000.00
	160mm Dia Flange Connection For Pump Delivery.			* **	AV 18840 01 07 07 07
)					4.
)	Supply, laying, testing and commissioning of following size PVC insulated				
22	sheathed copper conductor 1100 V grade unarmoured cable with required				
	size of sleeves complete as required.				
i	4 x 16 sq.mm	RO	RM	745.00	
√ii	4 x 6 sq.mm	100	RM	292.50	29,250.00
iii	4 x 4 sq.mm	RO	RM	149.00	20,200.00
√i i	4 x 2.5 sq.mm	RO	RM	130.00	
v	4 x 1.5 sq.mm	RO	RM	108.00	
√ i	3 x 6 sq.mm	RO	RM		
	3 x 4 sq.mm			267.00	
vii		RO	RM	133.00	
<u>)iii </u>	3 x 2.5 sq.mm	RO	RM	125.00	
ix	3 x 1.5 sq.mm	RO	RM	98.00	
X	2 x 6 sq.mm	200	RM	157.00	31,400.00

SR. MANAGER TECH. 2

SR. MANAGER TECH. 2

SR. MANAGER TOTY LTD.

SR. MANAGER SIMART CITY LTD.

BHAGALPUR SIMART CITY LTD.

Page 7

		T BO	DM	105.00	
xi	2 x 4 sq.mm	RO	RM	70.00	7,000.00
xii	2 x 2.5 sq.mm	100		55.00	5,500.00
xiii	2 x 1.5 sq.mm	100	RM	35.00	5,500.00
23	Supply, laying, testing and commissioning of following size PVC insulated sheathed copper conductor flexible multistand wire complete as required.				
	1.5 sqmm	RO	RM	28.00	
i		RO	RM	40.00	
ii	2.5 sqmm	RO	RM	50.00	
iii	4 sqmm	110	TXIVI	00.00	
24	Supply, laying, testing and commissioning of following size PVC electrical conduit complete as required.				
i	20 m	RO	RM	55.00	
ii	25 m	720	RM	60.00	43,200.00
25	G.I. earthing wire 8 gauge from all motor and M.C.C panel to be connected in as approved manner to the general earthing system complete.		r		
i	8 Gauge GI Wire	100	RM	115.00	11,500.00
26 i	Providing and fixing M.S. slotted cable tray supported from ceiling at intervals of 60 cms on both ends including cable clips with nuts and bolts welding of support rods with ceiling inserts or through dash fasteners cutting and making good complete. 300mm wide	30	RM	650.00	19,500.00
		50	RM	450.00	22,500.00
ii	150mm wide	30	IXIVI	430.00	22,300.00
27	Providing and fixing M.S. support with nuts and bolts welding of support rods with ceiling inserts or wall through dash fasteners cutting and making good complete	300	kg	170.00	51,000.00
28	ELECTRICAL CONTROL PANEL				
3	Supply, installation, testing and commissioning of following swimming pool panel 415 V, 1 / 3 Phase and 50 Hz power distribution system. The panel shall be free standing floor mounting sheet metal enclosed dust and vermin proof confirming to IP-54, compartmentalized design fabricated out of 16 SWG sheet Steel, painting earthing numbering, danger plate as per specifications and drawings. Flush front with aluminium busbars, seperate earth bus bars to be provided throughout the length of the panel the incoming and outgoing feeder breakers, fuses, indicating lamps etc shall be accomadated in a modular multilier arrangement. The panel shall be provided forcable termination. The outgoing feeders inside shall be connected through bus bars/ flexible cable links.	1	Set	3,85,000.00	3,85,000.00
	Bus bars shall be provided with heat shrinkable sleeves and shall be colour coded. The panels shall be suitable for cable entry from top to bottom. The panels shall be fabricated after the approval of drawings.				

()

0

 \bigcirc

 \bigcap

 \bigcirc

 \cap

 \bigcirc

 \bigcirc

 Θ

0

 \circ

 \bigcirc

 \bigcirc

0

 \bigcirc

0

	Starter shall be provided with MCB/MCCB. Suitable for the specified Kw of motor AC 3 power contractors. Single phasing preventer, on-off indication Lamps, start stop push buttons. Auto manual selector switch, ammeter with suitable auxillary contact remote control, interlocking etc starter shall be Type 2 coordinated. "c" curve MCB's 10 KA shall be used wherever required.	n h			
a	Incoming:	-	1		
	One (1) no. 200A TP 25 KA MCCB with thermomagnetic based overload and	d	1		
)	short circuit release.				
	Digital flush mounted 0-200A ammeter with 3 way and OFF selection switch	h			
.)	with 3 Nos. 200/5 Amp CT.				
	1 set (3 Nos.) of phase indication lamps	1			
7	200A 25 KA TPN Aluminium bus bar. It shall be insulated with heat shrinkable	e			
	sleeves and shall be color coded.				
∖ b	Outgoing:				
/	Recirculation pump				
)	Six (6) Nos. DOL starter complete with separate single phasing protection feature. ON/OFF indicating lamps, relay, contractors, start/stop push button, auto/manual selector switch, sufficient nos of potential free spare contacts, etc for suitable HP	,			
	3 Nos. 6AMP DP MCB of suitable rating with correct thermal range suitable	,			
)	for chemical dosing	1			
	3 Nos. Toggle switch for LED Pool Lights				
)	6 Nos. 6AMP DP MCB of suitable rating with correct thermal range suitable for UV				
7	6 Nos. Toggle switch for LED Pool Lights				
)——	1 Nos.16AMP DP MCB of suitable rating with correct thermal range suitable for Underwater Lights				
)	1 Nos. Toggle switch for LED Pool Lights				
28	Designing, Installation, testing & commissioning of Equipments	1	Job	6,50,000.00	6,50,000.00
					0,00,000.00
	Total Price in Rupees		The Property		55,83,457.00
	Civil Item				1,45,28,117.91
	GRAND TOTAL IN INDIAN RUPEES				2,33,75,713.00
)			DESCRIPTION OF THE PROPERTY OF		
				1	

ms & Conditions

Taxes and freight shall be claimed extra as actual.

F yment Terms: 50 % advance along with the LOI / PO

10% Submission Of Shop Drawing 30% Before Dispatch of material 10% Against the commissioning

Contract Validity: 6 Month

E blusions List:


- 1 Water Supply at the Plant room with adequate pressure.
- 2 Backwash connection from the Filter to the Storm water drain.
- 3 Water and Electricity for Construction, Testing and Commissioning.
- 4 All Civil Work.
- 5 Plant room construction along with pump base, balancing tank, drains, lighting etc.
- 6 Suitable Power supply at Plant room for running all electrical equipments.
- 7 All Civil works, waterproofing, finishes.

SR. MANAGER TECH. 2

SR. MANAGER TECH. 2

BHAGALPUR SMART CITY LTD.

BHAGALPUR



		Append	ix 26 : Es	timate of	Parking					
-S.No.	Ref. SO 2018		Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
$\overline{\gamma_1}$	2.28	Supply and filling in plinth with local sand and under floors including watering, ramming, consolidating and dressing complete	Cum							
		Complete		1	125	30	0.075	281.25		
				1	45	5	0.075	16.875		
				1	59	22	0.075	97.35		
)	RCD 4.1	2 Providing and laying Wet Mix macadam in layers with all lead and lifts etc. Complete as per drawings, Technical Specificatio 406 and as directed by the Engineer, With Vibratory Roller						395.48	238.60	94,360.34
``)		50% of total area		0.5	125	30	0.25	468.75		
				0.5	45 59	5 22	0.25	28.125 162.25		
)				1 0.5	37		0.23	659.13	1005.00	6,62,420.63
2	4.1.8	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:4:8 (I Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	Cum						¥	
)		20% of total area		0.2	125	30	0.15	112.5		
-		1 7		0.2	45 59	5 22	0.15	6.75		
)				0.2	39	44	0.15	38.94 158.19	2940.8	4,65,205.15
)))))	11.79.1	Providing and laying factory made chamfered edge Cement Concrete paver blocks of required strength, thickness & size/shape, made by table vibratory method, to attain superior smooth finish using PU or equivalent moulds, laid in required Grey colour & pattern over 50mm thick compacted bed of coarse sand, compacting and proper embedding / laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with jamuna sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand In footpath, parks, lawns, drive ways or light traffic parking etc. all complete as per manufacturer's specifications & direction of Engineer-in Charge (a) 80 mm thick c.c. paver block of M-35 grade with approved colour design and pattern.	Sqm				.00			
)		30% of total area	Sqm	0.3	125	30		1125		
				0.3	45	5		67.5		
)				0.3	59	22		389.4 1581.9	812.70	12,85,610,13
)4	11.45	Providing and laying 500x500x40 mm thick Turf paver (Turfpave XD) on 150 mm thick sub grade of compacted bed of 20 mm thick nominal size stone aggregate and base course and filling with 150 mm thick jamuna sand, including spreading, well ramming, consolidating and finishing smooth etc. all complete as per direction of Engineer-in-charge.	Sqm					9		
		50% of total area on the top of wmm area	Sqm	0.5	125	30	-	1875		
)—		one of the second of the secon	34111	0.5	45	5		112.5		
				0.5	59	22		649		
								2636.5	894.8	23,59,140.20
) 5)	16.69	Providing and laying at or near ground level factory made kerb stone of M-25 grade cement concrete in position to the required line, level and curvature, jointed with cement mortar 1:3 (1 cement: 3 coarse sand), including making joints with or without grooves (thickness of joints except at sharp curve shall not to more than 5mm), including making drainage opening wherever required complete etc. as per direction of Engineer-in-charge (length of finished kerb edging shall be measured for payment). (Precast C.C. kerb stone shall be approved by Engineer-in-charge).	Cum	1	230	2.5	0.2	115	5180.8	5,95,792.00
	RCD constant of the second sec	Retro- reflectorised Traffic signs (Providing and fixing of retro- reflectorised cautionary, mandatory and informatory sign as per RC :67 made of encapsulated lens type reflective sheeting vide clause 801.3, fixed over aluminium sheeting, 1.5 mm thick supported on a mild steel angle iron post 75 mm x 75 mm x 6 mm firmly fixed to the ground by means of properly designed oundation with M15 grade cement concrete 45 cm x 45 cm x 60 cm, 60 cm below ground level as per approved drawing.) 60 cm equilateral triangle	each	12			d	MANAGE STATE OF THE STATE OF TH	RHAGA PIN	37,224.00
J								BHBA	BHHA	




		Cum.	405.33	Total Estimated	87,61,104
	Sand	cum.	469.35	1030.3	4,83,571.31
	cement	Mt.	26.89	328.28	8,827.45
	stone	cum.	1010.67	2701	27,29,819.67
	Paver block	per thousand	51.02	767.08	39,133.56
7	Steel	MIT.	0	328.28	
7	Carriage of Materials				
à					

SR MANAGER TECH. 2 SR MANAGER TECH. 2 BHAGALPUR SMART CITY LTD. BHAGALPUR SMART CITY LTD.



No.	Τ	Арре	endix 27 : (I neat		1)	17 1 1 1 1 1 1 1 1		Rate	Me The	Amount
$\overline{\gamma_1}$	Ref.No	. Description	Numbers	C. 1972 C. Store			Unit	Total	2-47 (3-2-7)	1 3.46.5	Ls./	Amount
$\overline{\gamma_1}$				Length	Breadt	Height	1	Quantity	Agreement	SoR	Market	
1	-	Describing a second second including disposal of material within 50	-		-	-	-					-
	15.2	Demolishing cement concrete including disposal of material within 50 metre lead of seating and boundary										
2	15.2.1			2531.25		0.05	cum	126.5625		807.2		102161.25
3		Carriage upto 5km						0				
4												
5		Staircase and steps seating	1		-							
7	13.11	12 mm thick cement plaster of mix: 1:3 (1 cement:3 coarse sand)	-	585	-	-	sgm	585	-	153.6	-	89856
	13.11.1	Supplying sand stone 40 mm thick for flooring ,carriage to site and roug	h	783			Sqrii	303		133.0	-	0
- 8	11.28	chisel dressing on Open Air theater (STEPS SEATING) under engineer										1000
		incharge										
9	11.28.1.	1 Red sand stone	-	491.4	-	-	sqm	491.4		373.7		183636.18
)		40 mm thick rough chisel dressed stone flooring over 20 mm (average)thick base with joint base 1:1:1 (1lime:1surkhi:1coarse sand) or 1:5										
10	11.28A	(1:cement :5coare sand) finished flush.all the work going under the										
	200000000	supervision of engineer incharge										
)	19											
_	11.28A.1	Red sand stone	-	491.4			sqm	491.4		659.3		323980.02
12		Staircase Providing and fixing 10x10x7.50 cm Granite stone block hand cut and	-	-	-							
1		chisel dressed on top, for paving in floors, drains etc. laid over 20mm										
		thick base mortar 1:4 (1 cement : 4 coarse sand) with joints										
13	16.92	10mm wide filled with same mortar including ruled pointing etc.	1	93.5			sqm	93.5		1309.1		122400.85
		complete as per direction of engineer-in-charge.	1									
							1					
4		platform area										
15	4.4	Providing and faying cement concreate in platform area .										
13	4.4											
16	4.4.1	1:2:4 (1 Cement : 2 coarse sand : 4 grade stone aggregate 20 mm nominal		508.68		0.15	cum	76.302		4151.4		316760.1228
	4.4.1	size)		300.00		0.13	Cum	70.302		4131.4		310700.1228
\7	13.11	12 mm thick cement plaster of mix:										
18	13.11.1	1:3 (1 cement:3 coarse sand)		508.68			sqm	508.68		153.6		78133.248
1.9	11.28	Supplying sand stone 40 mm thick for flooring, carriage to site and rough chisel dressing on Open Air theater (STEPS SEATING) under engineer									1	
)	11.20	incharge									1	
20	11.28.1.1	Red sand stone		508.68	WALL CO.		sqm	508.68		373.7		190093.716
× 1		40 mm thick rough chisel dressed stone flooring over 20 mm (average										
21	11.28A)thick base with joint base 1:1:1(1lime :1surkhi:1coarse sand)or									1	
	11.20/	1:5(1:cement:Scoare sand) finished flush.all the work going under the supervision of engineer incharge										
1				500.50								
23	11.28A.1	Red sand stone Stage		508.68			sqm	508.68		659.3		335372.724
23		Providing Cement concrete on tap face 1:2:4(1cement :2coarse sand										
)4	4.4.1	:4grade stone aggregate 20mm nominal size)		10	6	0.15	cum	9		4151.4	- 1	37362.6
		Providing and fixing 10x10x7.50 cm Granite stone block hand cut and										
\ \		chisel dressed on top, for paving in floors, drains etc. laid over 20mm										
25		thick base mortar 1:4 (1 cement : 4 coarse sand) with joints		86		- 1	sqm	86		1309.1	- 1	112582.6
		10mm wide filled with same mortar including ruled pointing etc. complete as per direction of engineer-in-charge.			1	- 1			1			02000304000
3	.	3	ll s		- 1			1 1				
26		Boundary Wall										
27	13.13.2	20 mm cement plaster of mix 1: 4(1 cement: 4 coarse sand)	2	151.2		5	sqm	1512		194.3		293781.6
)		Finishing with Deluxe Multi surface paint system for interiors and									-	
28	13.40	exteriors wall of boundary							1			
		using Primer as per manufacturers specifications.										
		Two or more coats applied on walls @ 1.25 ltr/10 sqm over and including	2	CHIPPERSON				0.00-187097				
29 1	13.48.1	one coat of special primer applied @ 0.75 ltr /10		151.2		5	sqm	1512		92.2		139406.4
		Providing and fixing M.S. grills of required pattern in frames of windows etc.								-	-+	
	9.18	with M.S. flats, square or round bars etc. including priming coat with										
1	3.46	approved steel primer all		1						- 1		1
30							27001 10-10				-	
+							Kg	6000		114.2		685200
+	9.48.1	Fixed to steel windows by										
1 9	12 92 F	Painting with ready mixed paint of approved brand and manufacture in				10		- 1	F.	1	- 1	1
)	13.82 F	Painting with ready mixed paint of approved brand and manufacture in ill shades to give an even shade:					-					
) 3 1	13.82 F 3.82.1 N	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade: New steel work (two or more coats)					Sqm	250		74.5		18625
) 3 1	13.82 F a.3.82.1 N nalysis	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade: New steel work (two or more coats) Carriage	Per Thousand				Sqm	250				18625
) 3 1	13.82 F a.3.82.1 N nalysis	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade: New steel work (two or more coats)	Per Thousand				Sqm	250		74.5		18625
) 3 1 4 A	13.82 F a 3.82.1 M nalysis A B L	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade: New steel work (two or more coats) Carriage Brick Local Sand	Cum				Sqm					
3 1 4 A A 6 5	13.82 F a a	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade: New steel work (two or more coats) Carriage Brick Local Sand Coarse Sand	Cum Cum				Sqm	79.023326		767.08 262.05 1030.3		0 0 31417.73226
3 1 4 A 6 5 8	13.82 F a a 3.82.1 M nalysis A B L C C C D S	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade: New steel work (two or more coats) Carriage Brick Local Sand Coarse Sand Itone Chips	Cum Cum Cum				Sqm	79.023326 76.76327	2	767.08 262.05 1030.3 2701.25	2	0 0 31417.73226 207356.7825
3 1 4 A A 6 5	13.82 F a 3.82.1 N nalysis A B L C C C D S E C	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade: New steel work (two or more coats) Carriage Brick Local Sand Coarse Sand	Cum Cum				Sym	79.023326	2	767.08 262.05 1030.3	2	0 0 31417.73226

SR. MANASER TECH 2 SR. MANASER TECH ITO. BHAGALPUR SMART CITY LTD.



$\overline{}$		Appendix 32 - Estimate of Basketball Court										
SL.No.	BCD SOR 2018	DESCRIPTION OF ITEM	UNI	RATE	QTY.	AMOUNT (Rs.)						
1	2	3	4	5	6	7						
1.0	2.6	Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m; disposed earth to be levelled and neatly dressed.										
	2.6.1	All kinds of soil	cum	279.1	94.00	26235.4						
)2.0	2.26	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth: consolidating each deposited layer by ramming and watering lead.	cum	103.3	30.00	3099						
		CONCRETE WORK										
3.0	4.1.8	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	cum	2940.8	33.00	97046.4						
4.0		Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement-All work up to plinth level. 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stone aggregate 20 mm nominal size)	cum	4902.3	61.00	299040.3						
5.0		Reinforcement for R. C. C work including straightening, cutting, bending, placing in position and binding all complete.	KG	76.7	4880	374296						
6.0	6 1 4 1	Brick work with bricks of class designation 100A in foundation and plinth in :										
)		Cement mortar 1:4 (1 cement : 4 coarse sand)	cum	5037.2	35.00	176302						
J J7.0 J	11.40	52 mm thick cement concrete flooring with metallic concrete hardener topping under layer 40 mm thick cement concrete 1:2:4(1 cement:2 coarse sand:4 graded stone aggregate 20 mm nominal size) and top layer 12 mm thick metallic concrete hardener consisting of mix 1:2 (1 cement hardener mix:2 stone aggregate 6 mm nominal size) by volume @ 2 liter per 50 kg of cement or as per manufacture specification. This includes cost of cement slurry, etc. but excluding the cost of nosing of steps etc. complete.	SQM	450.8	608.00	274086.40						
8.0		Providing and fixing glass strips in joints of terrazo/cement concrete floors, 40mm wide and 4mm thick	Meter	49.60	300.00	14880.00						
) .b.0 .)	Gem (Providing and Fixing One pair of Basketball Pole (made of minimum 5.0 mm thick 8" round pipe), Acrylic Backboard with angle iron frame (180mm x 105mm x x25mm), Ring (20mm solid Rod) and Net (regulation size) Movable type as per standards. Contractor shall get approved the make and design of the pole and acessories from the engineer-in charge. Approved make - STAG, RIDO, ESSKAY, KHALSA SPORTS, VINEX or equivilant.		240000.00	1.00	240000.00 CH. 2 NAMES ART OF LT HAGALPUR SMART OF LTD BHAGALPUR						
)					8	HACHLE BHACHLOUR						




1		Total				₹ 15,46,828
10.0	BCD 13.82B.2	Finishing with Epoxy paint (two or more coats) at all locations prepared and applied as per manufacture's specifications including appropriate priming coat, preparation of surface, etc. complete. On Concrete work	SQM	106.10	180.00	19098.00
10.0	BCD 13.98.1	Floor painting with floor enamel paint of approved brand and manufacture of required colour to give an even shade, Providing and laying 50mm wide x 52 mm thick White Cemnet Border line(Boundary Luine, Base Line, Side line and internal lines) including the cost of centering and shittering required to create Curves, D's, Circles etc. complete as per drawing.	SQM	140.40	162.00	22744.80

SR MANAGER TECH. 2 SR MANAGER TECH. 2 BHAGALPUR SMART CITYLITO. BHAGALPUR SMART CITYLITO.




	Appendix 33 - Trellis Walkway								
Sr. No.	Ref. No.	Description	Unit	Quantity	Rate As.	Amount			
7		Earth Work Excavation in foundation							
		trenches or drains(not exceeding 1.5 m in							
		width or 10 sqm on plan) including							
		dressing of sides and ramming of							
	2.8	bottoms, lift upto 1.5 m . including getting							
1	2.8	out							
		the excavated soil and disposal of surplus							
		excavated soil as directed,							
		within a lead of 50 m.				=1			
	2.8.1	All Kinds of Soil	Curr	05.6	210.0	27257.76			
<u> </u>	4.19.1	All Work Up To Plinth Level	Cum	85.6	319.6	27357.76			
	4.19.1	Provide PCC Layer of M-15 grade plain		-					
2	11011			2 2 2 4	17101				
1	4.19.1.1	cement concrete (cement content	Cum	2.304	4719.1	10872.8064			
		considered @ 240 kg/cum)							
	1	Providing and laying in position specified							
		grade of reinforced cement concrete							
	5.1	excluding the cost of							
	3.1	centring, shuttering, finishing and							
3		reinforcement-All work puto plinth level	¥						
1 .									
		1:1:5:3(1 cement: 1.5 coarse sand:3							
1	5.1.2	graded stone aggregate 20 mm nominal	Cum	12.1	4902.3	59317.83			
)	*	size)							
		Centring and shuttering including							
2		strutting, propping etc. and removal of							
4	5.9	from for							
	5.9.1	Foundations, footings, bases of columns	Sqm	81.12	186.3	15112.656			
	5.9.5	Lintels, beams, plinth bams, griders,	Sqm	57	335.3	19112.1			
		bressumers and contilevers.		3,	333.3	13112.1			
5	13.11	12 mm cement plaster of mix:							
	13.11.2	1:4(1 cement :4 coarse sand)	Sqm	70	139.9	9793			
		Reinforcement for R.C.C. work including							
	5.22	straightening, cutting, bending, placing in				(A)			
	5.22	position and binding all complete			1				
6						91			
	5.22.7B	Thermo-Mechanically Treated bars TMTC-	Va	1000	76.7	145720			
	3.22.76	500-10mm dia.	Kg	1900	76.7	145730			
	5.22.7A	Thermo-Mechanically Treated bars TMTC-	Va	215	.77.4	15544			
	5.22.7A	500-8mm dia.	Kg	215	77.4	16641			
		Providing wood work in france of door							
		Providing wood work in frames of doors,							
		windows, clerestory windows and other				1			
	0.1	frames, wrought framed and fixed in							
7	9.1	position with hold fast lugs or with dash							
		fasteners of equired dia & length (hold							
		fast lugs ordash fastener shall be paid for		20					
		separately).				2/10			
	9.1.2	Sal Wood	Cum	7.92	37862.5	69587			
	27.5	L	000/27/2012	M	^	1 Vr. Paling			

SR. MANAGARIR SHART CITY IN BHAGALPUR




8	7.42	Providing and Fixing, adjustable with stainless steel nuts, bolts and asher (total weight not less than 260 gms), for dry stone cladding fixed on rame work at suitable location, including making necessary recesses in stone slab, drilling required holes etc complete as per direction of the Engineer-in-charge.	Each	112	204.4	22892.8
9	13.48.2	Painting wood work with Deluxe Multi Surface Paint of required shade. Two or more coat applied @ 0.90 ltr/ 10 sqm over an under coat of primer applied @ 0.75 ltr/ 10 sqm of approved brand and manufacture.	Sqm	290.4	81.9	23783.76
	13.46A	Finishing walls with Premium Acrylic Smooth exterior paint with Silicone additives of required shade :		-		
10	13.46A.1	New work (Two or more coat applied @ 1.43 ltr/ 10 sqm over and including priming coat of exterior primer applied @ 2.20 kg/ 10 sqm)	Sqm	70	90.1	6307
11	13.80 A .2	Providing and applying white cement based putty of average thickness 2 sqm 117.60 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	Sqm	70	117.6	8232
12	13.82	Painting with ready mixed paint of approved brand and manufacture in all shades to give an even shade:	,			
	13.82.2	New wood work (two or more coats)	Sqm	290.40	74.50	21,634.80
13	Analysis	Carriage				
	В	Coarse Sand	Cum	7.22	1030.3	7436.88
)	С	Stone Chips	Cum	12.48	2701.25	33709.90
	D	Cement	MT	6.18	472.68	2921.51
	Е	Steel	MT	2.12	328.25	694.25
J					TOTAL	11,27,421





Sl.No.	Ref.BCD SOR 2018	Description Of work	Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
1	SOR 2018	DISMANTLING AND								
		DEMOLISHING								
	15.2	Demolishing cement concrete including disposal of material within 50 metre lead:								
	15.2.1	1:3:6 or richer mix	Cum	1	35.3	8	0.1	28.24	807.20	22795
		Dismantiling doors windows and								
9	15.12	clerestory windows (steel or wood) shutters including chowkhats, architrage, holdfasts etc. complete and stacking within 50 metres lead:				8.0				
	15.12.1	Of area 3 sqm and below	Each	50				50	125.80	6290
2	15.7	Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead:								
t	15.7.4	In cement mortar	Cum	1	24	8	0.25	48	685.10	32884.8
	15.14	Dismantling wood work in frames, trusses, purlins and rafters upto 10 metres span and 5 metres height including stacking the material within 50 metres lead:								
	15.14.1	Of sectional area 40 cm* and above	Cum	1	35.3	16	0.025	14.12	1528.10	21576.8
	15.28	Dismantling roofing including ridges, hips valleys and gutters etc. and stacking the material within 50 metres lead of:		41						
	15.28.1	G.I. Sheet	Sqm	1	35.55	24		853.2	56.00	47779.2
2		CONCRETE WORK								
	4.1	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level.								
		1:3:6 (1 Cement: 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)	Cum	1	8	35.55	0.15	42.66	3461.4	1,47,663.3
3		BRICK WORK								
		Brick work with bricks of class designation 100A in foundation and plinth in :								F
	61121	Cement mortar 1:4 (1 cement : 4 coarse sand)	Ćum	1	45.28	0.25	3	33.96	5037.2	1,71,063.3
4	12.11	Plaster								
		12 mm cement plaster of mix 1:4 (1 cement : 4 coarse sand)	Sqm	1	18.34	4.9		89.87		
	15.11.2	2.1 (2 centert : 2 coarse sand)	Sqm	2	45.28	3		271.68		
			oqiii		73.20	Tota	1 +	361.55	139.9	50580.29
5		REINFORCED CEMENT CONCRETE WORK								00000.2
	5.2 f	Reinforced cement concrete in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts, etc. up to floor five level, excluding the cost of centring, shuttering, finishing and reinforcement.								
	5.2.2	1:1.5:3 (1 Cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size)	Cum	1	18.34	4.9	0.15	13.48	5723.30	77150

OR HANDER TELLINITO



							·			
SI.No.	Ref.BCD SOR 2018	Description Of work	Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
6	-	SHUTTERING		-	-	-				
100		Centring and Shuttering including strutting, propping etc. and removal of form for								
	5.9.1	Suspended floors, roofs, landings, balcnies and access platform.	Sqm	1	18.34	4.9		89.87	362.60	32,585.41
7		REINFORCEMENT								
		Reinforcement for R.C.C work including straightening, cutting, bending, placing in position and binding all complete.								
	5.22.7 B	Thermo - Mechanically Treated bars TMTC - 500-10mm dia	Kg	1				1058.2	76.70	81162
8		ROOF SHEET								
,	12.1	Providing corrugated G.S. sheet roofing fixed with G.I.J. or hooks, bolts and nuts 8 mm diameter with bitumen and G. I. limpet washers or with G.I. limpet washers filled with white lead and including a coat of approved steel primer and two coats of approved paint on over lapping of sheets complete (upto a pitch of 60°) excluding the cost or purlins, rafters and trusses.			2					5
	12.1.3	1.00 mm thick with zinc coating not less than 275 gm/m z	Sqm	1	36	27		972.0	1121.40	1090000.8
9		FLOOR								
	26.1	Providing & fixing in position Phenol bonded Bamboowood flooring with planks of sizes 14mm thick, 1800mm length (minimum) and 130 mm wide(minimum), in approved colour, texture and finish, having Performance Appraisal Certificate (PAC) issued by Building Materials & Technology Promotion Council (BMTPC). The flooring shall be fixed with tongue and groove interlocking system, with underlayment of 4mm thick expanded poly ethylene foam sheets having density 40kg/cum, over prepared surface with necessary quarter round planks of size 1900mm x 18mm and door reducer of size 1900mm x 44mm, wherever required. The bomboo wood planks shall have minimum density of 1000 Kg/cum & minimum Hardness 1000 Kgf. with Eco friendly UV coating, all complete as per direction of the Engineer in-charge.	Sqm	1.00	35.55	16		568.8	5314.30	30,22,773.84
10	11.37 E	Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of ist quality conforming to IS: 15622 of approved make in colours such as white, wory, Grey, Fume Red, Brown, laid on 80 mm thick Cement motar 1:4 (1 cement: a coarse sand) including pointing the points with white cement and matching sigment etc., complete PAINT	Sqm	1.00	8	35.55		284.4	671.00	1,90,832,40° Lander of the state of the stat



Sl.No.	Ref.BCD SOR 2018	Description Of work	Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
1	13.93	Painting with synthetic enamel paint of approved brand and manufacture to give an even shed.								
-,	13.93.1	Two or more coats on new work	Sqm	1.00				2741.28	70.40	1.92,986.11
	13.40A	Providing and applying plaster of paris putty of 2 mm thickness over plastered surface to prepare the surface even and smooth complete.	Sam					2741.28	105.20	2,88,382.66
,	13.74	Removing white or colour wash by scrapping and sand paper in and preparing the surface smooth including necessary repair scratches etc. complete	Sqm	1.00				2469.6	6.40	15,805,44
)	13.48.3	Painting Steel work with Deluxe Multi Surface Paint to give an even shade. Two or more coat applied @ 0.90 ltr/ 10 sqm over an under coat of primer applied @ 0.80 ltr/ 10 sqm of approved brand and manufacture.	Sqm	1.00				384	37.80	14,515.20
11		DOORS AND WINDOWS								
		Providing and fixing steel glazed doors, windows and ventilators of standard rolled steel sections, joints mitered and welded with 15x3 mm lugs 10 cm long with steel lugs embedded in cement concrete blocks 15x10x10 cm of 1:3:6(1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size) or with wooden plugs and screws or rawl plugs and screws or with fixing clips or with bolts and nuts as required, including providing and fixing of glass panes with glazing clips and special metal-sash putty of approved make complete including applying a priming coat of approved steel primer; excluding the cost of metal beading and other fitting except necessary hinges or pivots as required.	Sqm	65.00	1.5	1		97.5	2,973.30	2,89,896.75
)		SANITARY INSTALLATION								
2	17.80	Providing and fixing white vitreous china battery based infrared sensor operated urinal of approx. size 610 x 390 x 370 mm	Each	1.00					5407.30	5,407.30

SR. MANAGER TECH. 2 SR. MANAGER TECH. 2 BHAGALPUR SWART CITY LTD.




						·			·	
SI.No	Ref.BCD SOR 2018	Description ()t work	Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
5	SOR 17.1	Providing and fixing Stainless Steel A IS 304 (18/8) kitchen sink as per IS 1398 with C.I brackets and stainless steel plu 40mm including painting of fittings an brackets, cutting and making good th walls wherever required:	3 19 1d							-
<u> </u>	SOR 17 10 1	Kitchen sink with drain board	1							-
-1	SOR 17.10.1	4 510x1040mm bowl depth 178mm	Each	1.00					3781.80	3,781.80
6	SOR 17.31	Provding and fixing 600X450mr beveled edge mirror of superior glas complete with 6mm thick hard board	n s	3.00					741.90	2,225.70
7	SOR 17.28	B Provding and fixing PVC waste pipe for sink & wash basin including PVC waste fittings complete. Semi rigid pipe	ır							-
	17.20.1	Semi rigid pipe								-
7	17.28.1.1	32 mm dia	Each	1.00					86.20	86.20
)	В	WATER SUPPLY								
) 10	SOR 18.7	Providing and fixing Chlorinated Polyviny Chloride (CPVC)pipes, having therma stability for hot & cold water supply Internal work - Exposed on wall								-
	SOR 18.7.2									829.50
	SOR 18.7.3	25 mm Nominal outer dia pipes	Metre	5.00					165.90	5,117.50
}	SOR 18.7.4	32 mm Nominal outer dia pipes	Metre	25.00					204.70	10,605.80
)	SOR 18.8	Providing and fixing Chlorinated Polyvinyl	Metre	38.00					279.10	
)	SUR 10.0	Chloride (CPVC)pipes, having thermal stability for hot & cold water supply Concealed work, including cutting								-
)		chases and making good the								-
) 12		20 mm Nominal outer dia pipes	Metre	13.00					255.70	3,324.10
.)		25 mm Nominal outer dia pipes	Metre	7.00					308.00	2,156.00
13	SOR 18.9	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC)pipes, having thermal stability for hot & cold water supply External work			-					-
, D	18.9.4	32 mm Nominal outer dia pipes	Metre	10.00					249.30	2,493.00
14	SOR 18.9	Providing and fixing Chlorinated Polyvinyl Chloride (CPVC)pipes, having thermal stability for hot & cold water supply, including all CPVC plain & brass threaded		.0,00					£10.00	
15	SOR 18.16	Providing and fixing brass stop cock of approved quality								-
J	SOR 18.16.2	20 mm Nominal bore	Each.	1.00					303.00	303.00
16		Providing and fixing gun metal gate valve with C.I. wheel of approved quality.								-
		25 mm Nominal bore	Each.	3.00					461.80	1,385.40
	SOR 18.17.2	32 mm Nominal bore	Each	4.00						2,160.00
17		Providing and fixing uplasticised PVC connection pipe with brass unions.	Each.	4.00					540.00	/ -
)	18.21.2	45 cm length								-
						1				




Sl.No.	Ref.BCD SOR 2018	Description Of work	Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
Ĺ	18.21.2.1	15 mm Nominal bore	Each.	3.00					76 10	228.3
18	SOR 18.46	Providing and fixing G.I. union in G.I.pipe including cutting and threading the pipe and making long screws etc.		3.00					76.10	
	SOR 18.46.2	2 20 mm dia. Nominal bore								155.20
)	SOR 18.46.3	3 25 mm dia. Nominal bore	Each.	1.00					155.20	577 80
<u> </u>	SOR 18.46.4	32 mm dia. Nominal bore	Each.	3.00					192.60	920.00
		C.P. BRASS FITTINGS	Each.	4.00					230.00	920.00
24	SOR 18.50	Providing and fixing C.P. brass long nose bib cock of approved quality conforming to IS standards and weighing not less than 810 gms.								-
	18.50.1	15 mm Nominal bore	Each	4.00					599.50	2,398.00
25	SOR 18.58	Providing and fixing PTMT grating of approved quality and colour.								-
	18.58.1	Circular type 100mm nominal dia.		0.00						
26	18.58.1.1 SOR 18.48	Providing and placing on terrace	Each	2.00					36.20	72.40
		nolythethylene water storage tank ISI	Per litre	2000.00					7.90	15,800.00
27	SOR 12.78	RAIN WATER SPOUT AND PIPE Providing and fixing on wall face unplasticised Rigid PVC rain water pipes conforming to IS: 13592 Type A including jointing with seal ring conforming to IS: 5382 leaving a 10 mm gap for thermal expansion.(i) Single socketed pipes.	+						-	
	12.78.2	110 mm diametre	Metre	20.00					238.30	4,766.00
28		Providing and fixing on wall face unplasticised Rigid PVC moulded fittings/			8					14
)	12.79.2	Single pushfit Coupler								-
)	12.79.2.2	110 mm	Each	5.00					354.90	1,774.50
ί	12.79.5	Bend 87.5 °								
.)	12.79.5.2	110 mm bend	Each	5.00					124.70	623.50
.)	12.79.6	Shoe (Plain)							121110	
1		110 mm Shoe	Each	5.00					108.52	542.60
)))		Providing and fixing unplasticised - PVC pipe clips of approved design to unplasticised - PVC rain water pipes by means of 50 x 50 x 50 mm hard wood plugs, screwed with M.S. screws of required length cutting brick work and fixing in cememt mortar 1:4 (1 cement: 4 coarse sand) and making good the wall etc. complete.								-
_)		110 mm	Each	15.00					157.37	2,360.55
30	r	Providing and fixing to the inlet mouth of rain water pipe cast iron grating 15 cm diameter and weighing not less than 440 grams.	Each	5.00					44.90	224.50
12		GYM EQUIPMENTS								
)	Gem Portal	Commerciat Motorised Trade Mill Product id: 5116877-20575903247	No.	2.00					229000.00	4,58,000.00
		Commerciat Elliptical Cross Trainer	No.	2.00					175000.00	3,50,000.00
)	Gem Portal	Coomercial Gym S R Electronic Cycle	No.	2.00					24500.00	49,000.00
2		Commercial Smith Machine for Gym	No.	2.00			D		24900.00	49,800.00
1		Commercial Cable Cross over for Gym	No.	2.00			*	1	99996.00	1,99,992.00
		Big Gym Ball 95 CM Medicine Ball for 1 to 10 Kg. for the Gym	No.	5.00					1399.97 599.00	6,999.85
)		Kg	No.	5.00				**	1580.00	2,995.00 7,900.00



SI.No.	Ref.BCD SOR 2018	Description Of work	Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
5	Gem Porta	3 Kg Product id: 5116877-60249516699	No.	5.00					865.00	4,325.00
	Gem Porta	Bench press inclined MULTIPURPOSE ADJUSTABLE BENCH PRESS Product id: 5116877-80463679018	No.	2.00					22500.00	45,000.00
	Gem Portal	Flat Bench (Adjustable) Olympic Flat Bench Product id: 5116877-27292292784	No.	2.00			- 50		24993.00	49,986.00
	Gem Portal	Orbit Elliptical machine/ELLIPTICAL EXERCISE MACHINE Product id: 5116877-62699339198	No.	1.00					24990.00	24,990.00
	Gem Portal	Generator Recumbent Byke (Fitness World) Product id: 5116877-89056790453	No.	0.00		e)			175000.00	
5	Gem Portal	Multi Gyms - Abdominal Crunch VIVA FITNESS Multi Abdominal Bench, DFT-637 Product id: 5116877-45115314272	No.	2.00					34425.00	68,850.00
	Gem Portal	45 Degree leg Press LEG PRESS (PREMIER) Product id: 5116877-49383134578	No.	2.00					24990.00	49,980.00
	Gem Portal	Leg Extention / Leg Curl - LEG SHAPER / LEG PRESS Product id: 5116877-78800892782	No.	1.00					37000.00	37,000.00
	Gem Portal	Rowing Machine - ROWING MACHINE OUTDOOR Product id: 5116877-49654170141	No.	0.00					16300.00	-
)	Gem Portal	Foam Roller for Gym IRIS Interlocking Gym EVA Foam Floor Mat Tiles (80 sqft) (Off white) Product id: 5116877-12475246144	No.	2.00					3999.00	7,998.00
[) [Gem Portal	AB wheel for zym AB 75LTR MS WITH WHEEL HAND CART Product id: 5116877-66621574466	No.	2.00					11190.00	22,380.00
	Gem Portal	Dumbles Set of 2 5kg Product id: 5116877-79020905998	No.	2.00					1139.00	2,278.00
	Gem Portal	2.5 Kg Product id: 5116877-77263178090	No.	2.00					610.00	1,220.00
)	Gem Portal	10 Kg,	No.	2.00					1870.00	3,740.00
	Gem Portal	7.5 Kg Product id: 5116877-2865259899	No.	2.00					2900.00	5,800.00
)	Gem Portal	17.5 Kg Product id: 5116877-25743480835	No.	2.00					4375.00	8,750.00
ر. ر	Gem Portal	Product id: 5116877-43525639692 8 Station Multi Gym (NA) (Fitness World Multi Station Gym 8)	No.	2.00					124900.00	2,49,800.00
)		Mirror (3 m x 2 m) Product id: 5116877-10155089109	No.	2.00					5050.00	10,100.00
) ,) ,)	Gem Portal	Locker for gym (GODREJ 6 DOOR PLU BASE UNIT LOCKER WITHOUT STAND / PERSONAL LOCKER UNIT / COLLEGE / GYM) Product id: 5116877-51600775039	No.	1.00					15109.00	15,109.00
)		Steam Bath	No.	0.00			A	63	200000.00	-
))		Rubber Mat for Gym Product id: 5116877-55066733872 Per Piece of 1.53 Sqm	No.	10.00			eg.	W 3/18	MARTIN SAS.00	1,450.00
			L				01/2	John (Total	76,00,485
1			400000000000000000000000000000000000000				Δ,		Carriage Cost	2,47,676



7.7		Appendix 34B: Estimate of N	ew Extensi	on of Inc	loor Bad	minton	Court B	uilding		//
i N	o Code	Description	Unit	No	Length	Width	Height	Quantity	Rate (Rs)	Amount (Rs)
1	2.6	Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well as 10 sqm on plant including disposal of excavated earth, lead upto 50m and lift upto 1.5m; disposed earth to be levelled and neatly dressed.	cum	1	95	1.5	0.5	71.25	279.1	19885.875
	2.6.1	All kinds of soil Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth: consolidating each deposited layer by ramming and watering lead.	cum	1	95	1	0.2	19	103.30	1962.7
3	2.28	Supplying and filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete.	1	1	95	1.5	0.075	10.69	238.60	2550.0375
4	11.72	Providing designation 100 A one brick flat soling joints filled with local sand including cost of watering, taxes, royalty all complete as per building specification and direction of E/	Sqm	1	31	24.25		751.75	277.5	208610.625
5	4.1.5	Providing and laying in position cement concrete of specified grade exluding the cost of centring and shuttering-all work upto plinth level. 1:3:6 (1 Cement: 3 coarse sand : 6 graded stone aggregate 20 mm nominal size)	Cum	1	31	24.25	0.15	112.76	3461.4	390316.1175
6	20.3A.1	Making 25cm (10") dia bore up to 5 M depth below ground with hand auger of approved quality in ordinary soil (vide classification of sol item-A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50 M lead including all lifts, all complete as per approved design and direction of E/I./	Rmt	20	5	,		100.00	148.6	14860
-)- -) 7)	20.3A.2	Making 63 cm (25") dia under-ream at required depth with hand auger of approved quality in ordinary soil (vide classification of soil item-A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50M lead including all lifts, all complete as per approved design and direction of E/I.	Each	40				40.00	158.6	6344
1		brick work.								
8	6.1A	Brick work with bricks of class designation 100A in foundation and plinth in :	cum							
	6.1.12 .1	Cement mortar 1:4 (1 cement : 4 coarse sand) wall		1	95	0.2	6.5	105.25		
-		Wall		1	93	0.3	6.5	185.25 185.25	5037.2	933141.3
	BCD SOR, 5.1.2	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of centring, shuttering, finishing and reinforcement-All work up to plinth level. 1:1.5:3 (1 cement: 1.5 coarse sand: 3 graded stone aggregate 20 mm nominal size)	cum							
$ \downarrow$		beam		1	95	0.3	0.3	8.55		
2		Lintel colum @5m interval		20	95 11	0.3	0.2	5.7 13.75	-	
)		Gate ramp		1	4	0.2	2	1.6		
- 1		Shuttering						29.60	4902.3	145108.08
10		Walls (any thickness) including attached pilasters, buttresses, plinth and string courses etc.	Sqm		004100					21
1		beam		3	95		0.3	85.5		
)		intel colum ·		80	95		0.2	120	410.	
لاء	1	ramp path		4	2		0.15	1.2	24,	
		REINFORCEMENT			19	1	4/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1/1	244.7	321.3	78622.11
)	0	Reinforcement for R. C. C work including straightening, cutting, bending, placing in position and binding all complete.				Xes	CHACA!	BHASA	TA.	




OR, dia Thermo - Mechanically Treated bars TMTC - 500-10mi	n kg	5920					76.7	454064
Plaster				1				
3.11 12 mm cement plaster of mix								
.11.2 1:4 (1 cement : 4 coarse sand)	sqm	2	95		6	1140		
		2	6		0.3	3.6		
rid					-	1143.6	139.9	159989.64
Providing & fixing in position Phenol bonder	.1	-	-	-	-	-	-	
Bamboowood flooring with planks of sizes 14mm thick, 1800mm length								
(minimum) and 130 mm wide(minimum), in approved colour, texture and finish, having	d							
Performance Appraisal Certificate (PAC) issued by Building Materials & Technology Promotion Council (BMTPC). The	1							
flooring shall be fixed with tongue and groove interlocking system, with								
underlayment of 4mm thick expanded poly ethylene foam sheets	s sqm	1	31	15		465	5314.30	2471149.5
having density 40kg/cum, over prepared surface with necessary quarter round planks of size 1900mm x 18mm and door reducer of size		7						
1900mm x 44mm, wherever required. The bomboo wood planks								
shall have minimum density of 1000 Kg/cum & minimum Hardness 1000 Kgf.								
with Eco friendly UV coating, all complete as per direction of the Engineer in-charge.	5							×
Providing and laying Ceramic glazed floor tiles 300x300								
mm (thickness to be specified by the manufacturer) of ist quality								
conforming to IS : 15622 of approved make in colours such as	LACS	1	21	10		210	<i>(7</i> 1.00	22224
white , Ivory , Grey , Fume Red , Brown , laid on 20 mm thick	SQM	1	31	10		310	671.00	208010
Cement motar 1:4 (1 cement: 4 coarse sand) including pointing								
the joints with white cement and matching pigment etc., complete								-
Roofing								
Providing and installing of pre painted Galvanized								10
Trapezoidal profiled sheet of approved make								
1060mm width (1000mm cover width), 28-30 mm				~				
crest height with crest distance of 200mm c/c with								
Construction of the Constr								
2 ribs at the center for stifening. The total coated								
thickness (TCT) of the sheet will be 0.47mm +/-						-1		
. 1	sqm	1	32	26		832	770	640640
Igain as per Astivi 1337/A733-330 lilpa steel							18	
grade,5-7 microns epoxy primer on both sides of								
the sheet and polyester top coat 20-22 microns								
using self drilling/self tapping screws of of 25mm	1	1						
The state of the s	+1							
indicate and the children putility, latters.					1	1		
00 no- 0	0.02mm tolerance zinc-alu alloy coating AZ150 gsm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns	0.02mm tolerance zinc-alu alloy coating AZ150 sqm gsm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of of 25mm	0.02mm tolerance zinc-alu alloy coating AZ150 sqm 1 gsm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of of 25mm	0.02mm tolerance zinc-alu alloy coating AZ150 sqm 1 32 gsm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of of 25mm	0.02mm tolerance zinc-alu alloy coating AZ150 sqm 1 32 26 gsm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of of 25mm	0.02mm tolerance zinc-alu alloy coating AZ150 sqm 1 32 26 gsm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of of 25mm	0.02mm tolerance zinc-alu alloy coating AZ150 sqm 1 32 26 sqm 1 32 26 sqm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of of 25mm	0.02mm tolerance zinc-alu alloy coating AZ150 sqm 1 32 26 832 770 gsm as per ASTM 1397/A755-550 mpa steel grade,5-7 microns epoxy primer on both sides of the sheet and polyester top coat 20-22 microns using self drilling/self tapping screws of of 25mm

ON CHARLER FECH. A. SHARLOW ID.



	Windows				MA	1	100	100	
							23840	8/88	2116992
	Iron Steel Sitting Chair @40kg/Sqm	Kg	1	52	11		22880	11)	
	@ 40 kg /Sqm(Gate grill)	Kg	1	4	6		960		
	In gratings, frames, guard bar, ladders, railings, brackts. gates & similar works.								
	Steel work welded in built up sections/framed work including cutting hoisting, rixing in position and applying a priming coat of approved steel primer using structural steel, etc. as required								
		sqm	2	6	1.5		18	2,236.80	40262.4
7.37.1 A	be paid seperately) Dressing of sandstone in veneer work (in gate Area)	sam	2	6	1 5		10	2 224 90	40363.4
7.37	mm thick bed of cement mortar 1:3 (1 cement: 3 coarse sand) and jointing with grey cement slurry 3:30 kg/sqm including rubbing and polishing complete.(to be secured to the backing by means of cramps which shall								
	Stone work for wall lining etc.(Veneer work) over 12								
13.93.1	brand and manufacture to give an even shed. Two or more coats on new work	sqm					1143.6	70.40	80509.44
13.93	Painting with synthetic enamel paint of approved								
10.19	Providing and fixing M.S. round holding down bolts with nuts and washer plates complete.	Kgs	В				60	71.50	4290
							29742.5	113.10	3363876.75
	beam @40 kg /Sqm	Kgs	3	24.5	0.4		1176	462.55	
-	beam @40 kg /Sqm	Kgs	4	31	0.4		1984		
	Truss @35 kg/Sqm	Kgs	1	31	24.5		26582.5		
	per specifications								
	all lead and lift, transportation etc., complete as								
	the members including cost of all materials, welding, grinding and erection equipments, with								
	applying one coat of redoxide primer coat to all								
10.16.3	angle and welding whenever necessary and		1	-					
10.16.3	cutting, straightening, placing in position of M.S		4						
	with base plate and shoe plate. the work includes					1		3	
	using 4nos of M.S. anchor bolts at each support	-							
	trusses for all spans as per approved drawing and design. The entire trusses is anchoredSuitably by								
	Fabrication supplying and errecting M.S Angular								
		34III	1	32	0.5		28.8	740.00	21312
-	Ridges Gutters	sqm sqm	2	32	0.3		19.2 9.6		
	and trusses.								
	be fixed over the existing purlins, rafters, channels								
	22 microns using self drilling/ self tapping screws of 25mm length. (width upto 500-600 mm only), to								
38.31	both sides of the sheet and polyester top coat 20-								
no 30	o mpa steel grade 5-7 microns enovy primer on								
Dharw SOR pa	BC 0.4711111 17 0.02 tolerancemin Zinc-Alu Alloy								
	The total coated thickness (TCT) of the sheet shall								
4	painted galvalume Iron Accessories, like, plain, ridges, plain gutter, plain flashing, corner trim,etc.,							1	

SR. MANAGER SWAPT CITY
BHAGALPUR SWAPT CITY



22	10.12	concrete blocks 15x10x10 cm of 1:3:6(1 cement: 3 coarse sand : 6 graded stone aggregate 20 mm nominal size) or with wooden plugs and screws or rawl plugs and screws or with fixing clips or with bolts and	Sam	7	1.2	0.75		6.3	2,973.30	18731.79
		nuts as required, including providing and fixing of glass panes with glazing clips and special metal-sash putty of approved make complete including applying a priming coat of approved steel primer; excluding the cost of metal beading and other fitting except necessary hinges or pivots as required.				II.				
23		Carriage of Materials								
23		Cement	Mt.	60.22			-		290.27	17480.0594
)	-	Steel	Mt.	59.5025					290.27	17271.79068
-		Sand	Cum	149					896.66	133602.34
7		Stone Chips	Cum	130					1576.82	204986.6
+			Per thousand						767.08	76880,593
_)		DILLAS	i ci ciiousanu	100.223					707.08	11831449.75

SR MANAGER FIRE CHAIR



		RENOVATION AND EXTENSION O	F GYM	BUILDIN	G	
SL.	BCD	DESCRIPTION OF ITEMS	UNIT	Qty	RATE	AMOUNT
NO.	SOR-2018	CIVIL WORKS			+	
7		CONCRETE WORK			1	
1	4.1	Providing and laying in position cement concrete of				
7		specified grade excluding the cost of centring and				
		shuttering-all work up to plinth level.				
1.1	4.1.8	1.4.8 (1 Cement :4 coarse sand :8 graded stone aggregate 40	cum	29.70	2940.80	87,342.00
		mm nominal size)			2227.00	
1.2	4.1.6	1.3.6 (1 Cement :3 coarse sand :6 graded stone aggregate 40	cum	29.70	3307.00	98,218.00
1.3	4.17	mm nominal size) Making plinth protection 50 mm thick of cement concrete			-	
1.3	4.17	1:3:6 (1 cement :3 coarse sand : 6 graded stone aggregate 20				
1		mm nominal size) over 75 mm thick bed of dry brick ballast			1	
A		40 mm nominal size, well rammed and consolidated and				
)		grouted with fine sand, including finishing the top smooth.				
			Sqm	85.80	417.60	35,830.0
1.4	4.11	Providing and laying damp-proof Course 50 mm thick with				
		cement concrete 1:2:4(1cement:2:2 coarse sand :4 graded		271.15	245.50	// F/3 2
		stone aggregate 20mm nominal size)	sqm	271.15	245.50	66,567.3
2	11.79.A	Providing and laying factory made chamfered edge Cement Concrete paver blocks of required strength,thickness &				
).		size/shape, made by table vibratory method, to attain				
		superior smooth finish using PU or equivalent moulds, laid				
1		in required Grey colour & pattern over 50mm thick				
,		compacted bed of coarse sand,				
' I		compacting and proper embedding / laying of inter locking				
		paver blocks into the sand bedding layer through vibratory				
		compaction by using plate vibrator, filling the joints with				
		jamuna sand and cutting of paver blocks as per required				
	The second secon	size and pattern, finishing and sweeping extra sand in				
)		footpath, parks,lawns, drive ways or light traffic parking				
		etc. all complete as per manufacturer's specification and				
		direction of E/I.			10	
		(a) 80 mm thick c.c. paver block of M-35 grade with	Sqm	127.60	812.70	103,701.00
		REINFORCED CEMENT CONCRETE				
3		Reinforced cement concrete work in wall (any thickness),				
		including attached pilasters, buttresses, plinth and string				
		courses, fillets, columns, pillars, piers, abutments, posts and struts, etc. upt floor five level				
		excluding cost of centring, shuttering, finishin and				
		reinforcement.				
	5.2.1	1:1:2(1 cement: 1 coarse sand:2 graded stone aggregate 20				
	r	nm nominal size)	cum	12.994	7255.40	94,275.00
		Column		2		
L		Beam	cum	35.200	7255.40	255,390.00
-		Roof	cum	48.600	7255.40 7255.40	352,612.00
4		Chhajja with Stair Centring and shuttering including strutting, propping etc.	cum	18.113	7233.40	131,413.00
4		and removal of form for.				
4.1		Foundations, footings, Pile cap, bases of columns etc. for		455.5		
053/55		nass concrete.	sqm	172.800	186.30	32,193.00
4.2		intels, beams, plinth beams, girders, ressumers and	0.0	4E7.60	225 20	152 422 00
	С	antilevers.	sqm	457.60	335.30	153,433.00
1.3		Columns, Pillars, Piers, Abutments, Posts and Struts	sqm	226.80	425.80	96,571.00
.4		tairs,(excluding landings) except spiral stair cases.	sqm	26.40	384.70	10,156.00
1.5		suspended floors, roots, landings, balcnies and access	sqm	324.00	362.60	117,482.00
_		platform.	A		10 / W.	
5		Reinforcement for R.C.C. work including straightening,	M	of ZIN	Age a Cilly	
		utting, bending, placing in position and binding all		William Control	CMAR!	
-	T	omplete upto plinth level & above plinth level. Thermo-Mechanically Treated Bars TMT (Fe 500) 6mm to 25		Charles .	18 211. 10/18	
	7////		KG.	18040	C.76.70	1,383,690.00
	ln	nm as per Approved drawing	ı	18/2/20	all Alls	-//

NO.	BCD SOR-2018	DESCRIPTION OF ITEMS	UNIT	Qty	RATE	AMOUNT
	9.48.2	Providing and fixing M.S. grills of required pattern Providing in frames of windows etc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all 20 MM Square Bar	KG.	915	122.9	112,478.0
		BRICK WORK				
6	6.1C	Brick work with fly ash bricks as per IS 12894 (2002) & IS 3495 in foundations and plinth in :			5100 70	11/ 057.0
6.1	6.1.12C	Cement mortar 1:4 (1 cement: 6 coarse sand)	cum	22.8	5129.70	116,957.0
6.2	6.3C + 6.1.12 C	Extra for Brick work in superstructure above plinth level up to floor V cum	cum	79.8	5831.90	465,386.0
		DOOR WINDOW WORK AND STEEL WORK				
7	9.1.1	Providing wood work in frames of doors, windows, clerestory windows and other frames, wrought framed and fixed in position with hold fast lugs or with dash fasteners of required dia & length (hold fast lugs or dash fastener shall be paid for separately). Second Class Teak Wood	Cum	2.77	95749.10	264,995.0
8	9.5.1.1	Providing and fixing panelled or panelled and glazed shutters for doors, windows and clerestory windows, including ISI marked M.S. pressed butt hinges bright finished of required size with ecessery screws, excluding panelling which will be paid for separately, all complete as per direction of engineerin-charge. Second Class Teak Wood 35 mm	Sqm	125.66	2547.80	320,167.00
9		30 mm thick factory made Polyvinyl Chloride (PVC) door shutter made of styles and rails of a uPVC hollow section of size 60x30 mm and wall thickness 2 mm (± 0.2 mm), with inbuilt decorative moulding edging on one side. The styles and rails mitred and joint at the corners by means of M.S. galvanised/plastic brackets of size 75x220 mm having wall thickness 1.0 mm and stainless steel screws. The styles of the shutter reinforced by inserting galvanised M.S. tube of size 25x20 mm and 1 mm (± 0.1 mm) wall tickness. The lock rail made up of 'H' section, a uPVC hollow section of size 100x30 mm and 2 mm (± 0.2 mm) wall thickness fixed to the shutter styles by means of plastic/ galvanised M.S. 'U' cleats. The shutter frame filled with a uPVC multichambered single panel of size not less than 620 mm, having over all thickness of 20 mm and 1 mm (± 0.1 mm) wall thickness. The panels filled vertically and tie bar at two places by inserting horizontally 6 mm galvanised M.S. rod and fastened with nuts and washers, complete as per manufacturer's specification and direction	Sqm	8.40	2041.60	17,149.00
10	6	Providing and fixing ISI marked flush door shutters conforming to IS: 2202 (Part I) decorative type, core of block board nstruction with frame of 1 st class hard wood and well matched teak 3 ply veneering with vertical grains or cross bands and face veneers on both face of shuttersRs.Description 35 mm thick including stainless steel butt hinges with necessa	Sqm	15.12	2598.90	39,295.00


SL.	BCD	DESCRIPTION OF ITEMS	UNIT	Qty	RATE	AMOUNT
NO.	SOR-2018			Qty	KATE	AMOUNT
	11.36	Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-charge in skirting, risers of steps and dados over 12 mm thick bed of cement Mortar 1:3(1 cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete		171.600	739.80	126,950.00
1 12	11.41	Providing and laying vitrifed floor tiles in different sizes {thickness to be specified by the manufactruer) with water absorption's less than 0.08 % and conforming to IS: 15622 of approved make in all colours and shades, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand) including grouting the joint with white cement and matching pigments etc complete				
,	11.41.2	Size of tile 60x60cm	sqm ^	542.30	1520.90	824,784.00
13	11.27	Kota stone slabs 20 mm thick in risers of steps skirting. Dado & pillars laid on 12 mm (average(thick cement mortar 1:3(1 cement; 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slab including rubbing and polishing complete	sqm	255.20	1133.90	289,371.00
14	2740	Sheets Rubber tile LP Stud confirming to IS 809 4.0 mm thick	sqm	373.67	2193.74	819,734.00
15	22.5	ROOFING AND WATERPROOFING Providing and laying in situ five course water proofing treatment with glass fibre tissue reinforced bitumen over roof consisting of first coat of bitumen primer @ 0.40 kg. per sqm, 2nd & 4th courses of bonding material® 1.60 kg. per sqm which shall consist of blown type bitumen of grade 85/25 conforming to IS: 702, third layer of glass ffibre tissuue course as specified, fifth, the top most layer of stone grit 6 mm and down size or pea-sized gravel sprad @ 6 dmJ per sqm including preparation of surface excluding grading for slope etc. complete	sqm	297.0	383.20	113,810.00
)		FINISHING WORK				
) 16	13.11	12 mm thick Cement Plaster of mix Internal and outer				
	13.11.2	1:4 (Cement : Coarse sand)	sqm	1201.200	139.90	168,048.00
17		6 mm cement plaster to ceiling of mix :				
		1:4 (1 cement: 4 coarse sand)	sqm	574.20	110.90	63,679.00
18	13.80A.1	Providing and applying white cement based putty of average thickness 1 mm, of approved brand and manufacturer, over the plastered wall surface to prepare the surface even and smooth complete.	sqm	1775.40	46.50	82,556.00
) 19	13.77	Distempering with oil bound washable distemper of approved brand and manufacture to give an even shade:				
20	13 77 2	New work (two or more coats) over and including water tinnable priming coat with cement primer	sqm	1775.40	83.40	148,068.00
ŋ	13 94	Painting with synthetic enamel paint of approved brand				
21	13.94.1	and manufacture to give an even shade Two or more coats on new work over an under coat of suitable shade with ordinary paint of approved brand and manufacture sqm	sqm	125.664	96.10	12,076.00
-				3	chip.	

ORANGER RECH. DIN LTD.

SL. NO.	BCD SOR-2018	DESCRIPTION OF ITEMS	UNIT	Qty	RATE	AMOUNT
22	6.48A	Drain Work Providing 150mm wide brick drain in cement mortar (1:6) with av. 150mm clear depth and 125mm apron concrete (1: 4:8), over one brick designation 100-A flat soling in proper grade and slope at the base, the drain duly plastered in CM. (1:3) with punning over exposed surface all complete as per building specification and direction of E/i.	m	78.00	564.50	44,031.00
	Gem	GYM Equipments Commerciat Motorised Trade Mill				
23	Portal	Product id: 5116877-20575903247	No.	7.00	229000.00	1,603,000.00
24	Gem Portal	Commerciat Elliptical Cross Trainer Product id: 5116877-83621265430	No.	7.00	175000.00	1,225,000.00
25	Gem	Coomercial Gym S R Electronic Cycle	No.	10.00	24500.00	245,000.00
	Portal Gem	Product id: 5116877-88927229284 Commercial Smith Machine for Gym	No.	2.00	24900.00	49,800.00
26	Portal Gem	Product id: 5116877-14487013616 Commercial Cable Cross over for Gym				
27		Product id: 5116877-34916229864	No.	2.00	99996.00	199,992.00
28	Gem Portal	Big Gym Ball 95 CM Product id: 5116877-71866501753	No.	10.00	1399.97	13,999.70
29	Gem	Medicine Ball for 1 to 10 Kg. for the Gym MEDICINE BALL 1 KG (HRS) Product id: 5116877-7830289572	No.	10.00	599.00	5,990.00
30		5 Kg Product id: 5116877-61968411280	No.	5.00	1580.00	7,900.00
31		3 Kg Product id: 5116877-60249516699	No.	5.00	865.00	4,325.00
32	Portal	Bench press inclined MULTIPURPOSE ADJUSTABLE BENCH PRESS Product id: 5116877-80463679018	No.	2.00	22500.00	45,000.00
33	Com	Flat Bench (Adjustable) Olympic Flat Bench Product id: 5116877-27292292784	No.	3.00	24993.00	74,979.00
34	Gem	Orbit Elliptical machine/ELLIPTICAL EXERCISE MACHINE Product id: 5116877-62699339198	No.	6.00	24990.00	149,940.00
35		Generator Recumbent Byke (Fitness World) Product id: 5116877-89056790453	No.	6.00	175000.00	1,050,000.00
37	Gem !	Multi Gyms - Abdominal Crunch VIVA FITNESS Multi Abdominal Bench, DFT-637 Product id: 5116877-45115314272	No.	6.00	34425.00	206,550.00
38	Gem 4	45 Degree leg Press LEG PRESS (PREMIER) Product id: 5116877-49383134578	No.	2.00	24990.00	49,980.00
39	Gem -	Leg Extention / Leg Curl LEG SHAPER / LEG PRESS Product id: 5116877-78800892782	No.	2.00	37000.00	74,000.00
40	Portal I	Rowing Machine - ROWING MACHINE OUTDOOR Product id: 5116877-49654170141	No.	5.00	16300.00	81,500.00
11	Gem I Portal (Foam Roller for Gym RIS Interlocking Gym EVA Foam Floor Mat Tiles (80 sqft) Off white) Product id: 5116877-12475246144	No.	6.00	3999.00	23,994.00
12	Gem A	AB wheel for zym AB 75LTR MS WITH WHEEL HAND CART Product id: 5116877-66621574466	No.	6.00	11190.00	67,140.00

SL.	BCD SOR-2018	DESCRIPTION OF ITEMS	UNIT	Qty	RATE	AMOUNT
43	Gem Portal	Dumbles Set of 2 5kg Product id: 5116877-79020905998	No.	2.00	1139.00	2,278.00
44	Gem Portal	2.5 Kg Product id: 5116877-77263178090	No.	2.00	610.00	1,220.00
45	Gem Portal	10 Kg,	No.	2.00	1870.00	3,740.00
46	Gem Portal	7.5 Kg Product id: 5116877-2865259899	No.	2.00	2900.00	5,800.00
47	Gem Portal	17.5 Kg Product id: 5116877-25743480835	No.	2.00	4375.00	8,750.00
1 48 1	Gem Portal	Product id: 5116877-43525639692 8 Station Multi Gym (NA) (Fitness World Multi Station Gym 8)	No.	4.00	124900.00	499,600.00
49	Gem Portal	Mirror (3 m x 2 m) Product id: 5116877-10155089109	No.	5.00	5050.00	25,250.00
50	Gem Portal	Locker for gym (GODREJ 6 DOOR PLU BASE UNIT LOCKER WITHOUT STAND / PERSONAL LOCKER UNIT / COLLEGE / GYM) Product id: 5116877-51600775039	No.	10.00	15109.00	151,090.00
51	Gem Portal	Steam Bath	No.	2.00	100000.00	200,000.00
52	1	Rubber Mat for Gym Product id: 5116877-55066733872 Per Piece of 1.53 Sqm	No.	50.00	145.00	7,250.00
		Carriage		For Two Flo	or	
		Local Sand	Cum	5.50	262.05	1,441.00
53		Coarse Sand	Cum	127.74	1030.3	131,607.00
3		Stone Chips	Cum	102.27	2701.25	276,248.00
· -		Cement	MT	1581.42	472.68	747,505.00
1	Г	Steel	MT	18.04	328.25 TOTAL	5,922.00
, T	· ·	TOTAL COST OF CIVIL and Equipments			TOTAL	14,294,198
54		Internal water supply and sanitary installations	Job	4.00%	571,768	14,294,198 571,768
55		Internal Electric Installations	Job	12.50%	1,786,775	1,786,775
56	· L/s I	Provision for Air conditioning	Each	1.00	1,000,000	1,000,000
)57		Total cost				17,652,741


SR MANAGER TECH 2. SHARING ALPUR D. BHAGALPUR BHAGALPUR D.



APPENDIX 36: Estimate of Tennis Court - 2 courts						
SL.No.	BCD SOI 2018/ RCD SOF 2019	DESCRIPTION OF ITEM	UNIT	RATE	QTY.	AMOUNT (Rs.)
1	2	3	4	5	6	7
1.0	2.3	Clearing jungle including uprooting of rank vegetation ,grass, brush wood, trees and saplings of girth upto 30 cm measured at a height of 1 m above ground level and removal of rubbish upto a distance of 50 m outside the periphery of the area cleared.	100 sqm	579.8	1.70	985.66
1.0	2.28	Supplying and Filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete.	cum	238.60	70.00	16702
2.0	5.2 RCD	Providing and applying tack coat with bitumen emulsion using emulsion pressure distributor at the rate of 0.20 kg per sqm on the prepared bituminous/granular surface cleaned with mechanical broom.	SQM	11.20	670.00	7504
,———		CONCRETE WORK				
6.0	6.1A	Brick work with bricks of class designation 100A in foundation and plinth in:				
`	6.1.12 A	Cement mortar 1:4 (1 cement : 4 coarse sand)	cum	5037.2	8.00	40297.6
) 7.0	Gem	Providing and laying of ITF Classified imported material (Acry Coat Made In Europe) 8 layers System Synthetic Acrylic for Tennis Court: (1 Layer) Concrete Primer, (2 layers) Resurface, (3 layer) Cushion Rubber, (2 layers) Top Coat, making provision for fixing of fittings wherever required making it good, all complete, As per the direction of Engineer-in-charge	SQM	1614.00	670.00	1081380.00
)13.0	16.20	Welded steel wire fabric fencing with posts of specified material and of standard design placed and embedded in cement concrete blocks 45x45x 60 cm of mix 1:5:10 (1 cement:5 fine sand : 10 graded stone aggregate 40 mm nominal size), every 15th post, last but one end post and corner post shall be strutted on both sides and end post on one side only and struts embedded in cement concrete blocks 70x45x50 cm of the same mix, provided with welded steel wire fabric fixed between the posts fitted and fixed with G.I. staples on wooden plugs or tied to 6 mm bar nibs with G.I. binding wire (cost of posts, welded steel wire fabric, painting, earth work in excavation and concrete to be paid for separately).	SQM	26.80	330.00	8844.00
8.0	Gem	Providing and fixing tennis net and post socket system Length and width specified by the ITF, making provision for fixing of fittings wherever required making it good, all complete, As per the direction of Engineer-in-charge. Product id: 5116877-52973885830	Pair	2450.00	2.00	4900.00
9.0	15.15.2	Providing 20mm thick cement plaster 1:4 (1cement:4 coarse sand)	Sqm	194.30	65.00	12629.50
10.0		Finishing walls with texture exterior paint of required shade New work(two or more coats)	Sqm	233.16	65.00	15155.40
		Carriage Cost	A STATE OF THE STA			28008.51
		Total				₹ 12,16,407

RHARRER SHAFT CITY LTD.

SHAFT BHACALPUR




	APPENDIX 37: Cricket Stadium Ground : Estimate	of RCC Drain 0.5	5 x 0.75 M, Chaina	age 2.75 KM w	rith Grassing & Barricadd	ing
şr.	Description	Unit	Quantity	Rate (Rs)	Amount in (Rs)	SOR Reference
1	Earth Work					
7.1	Excavation for Structures (Earth work in excavation of foundation structures as per drawing and technical specification, including settir out, construction of shoring and bracing, removal of stumps and oth deleterious matter, dressing of sides and bottom and backfilling will approved material.)	ng er				RCD SOR 12.1 v B
a	Depth upto 1.5 m	cum	656.25	177.00	1,16,156.25	
1.2.1	Open timbering in trenches including strutting and shoring complete	te		-	-	
a	Depth exceeding 1.5 m but not exceeding 3 m	Sqm	656.25	60.10	39,440.63	BCD SOR - Item No. 2.20.2
	Dewatering and pumping out water in trenches			-		
1.3	Pumping out water caused by springs, tidal or river seepage, broke water mains or drains and the like. Refilling the Excavated Trenches (Backfilling)	n KL	1,312.50	92.20	1,21,012.50	BCD Item no 2.25
1.4	Back filling behind abutment, wing wall and return wall complete a per drawing and Technical specification	s	328.13	593.00	1,94,578.13	RCD 13.9 B (i)
1.5	Back filling behind abutment, wing wall and return wall complete a per drawing and Technical specification (Below Raft)	cum	437.50	593.00	2,59,437.50	RCD 13.9 B (i)
1,6	Clearing and Grubbing Road Land (Clearing and grubbing road land including uprooting rank vegetation, grass, bushes, shrubs, sapling and trees girth up to 300 mm, removal of stumps of trees cut earlie and disposal of unserviceable materials and stacking of serviceable material to be used or auctioned up to a lead of 1000 metres including removal and disposal of top organic soil not exceeding 150 mm in thickness.)	Hectare	0.11	47,489.00	5,194.11	RCD 2.3 i (a)
)	DISPOSAL OF EARTH			-		
2.7	Removal of unserviciable soil and disposal upto 1000 meters (Removal of unserviciable soil including excavation, loading and disposal upto 1000 meteres lead but excluding replacement by suitable soil which shall be paid separately)	Cum	328.13	93.70	30,745.31	RCD SOR - 2018/Item No. 3.11
)8	Labour for filling anti cement bags with local sand, stutching the bag and placing including supply of sutri etc. all complete job as per direction of Engineer in charge with carriage of local sand and cost of anti cement bag for different type of work at site.	Per 100 bags	1,320.00	2,622.87	34,62,188.40	WRD SOR 2018 5.7.40.1
2	CONCRETE WORK			-	-	
2.1	PCC 1:3:6 in foundation: Plain cement concrete 1:3:6 nominal mix in foundation with crushed stone aggregate 40 mm nominal size mechanically mixed, placed in foundation and compacted by vibration including curing for 14 days.			-	· .	
a	1:3:6 (1 Cement : 3 coarse sand : 6 graded stone aggregate 40 mm	Cum	61.25	3,364.00	2,06,045.00	RCD 12.4
2.2	nominal size) Centring and shuttering including strutting, proping etc. and removal or form work for	***************************************	0,000	1 ve #10000 (000 D.T. (200)	-,-5/5 25/50	
a	Foundations, footings, bases of columns etc. for mass concrete	Sqm	525.00	186.30	97,807.50	BCD 5.9.1
3	REINFORCED CEMENT CONCRETE WORK					
	RCC SLAB			-		
_)1	Plain/Reinforced cement concrete in sub-structure complete as per drawing and technical specifications RCC grade M30 - with batching plant, transit mixer and concrete pump	Cum	122.50	4,878.00	5,97,555.00	RCD 13.5G (p) i
	Centring and shuttering including strutting, proping etc. and removal or form work for			-	-	
	Foundations, footings, bases of columns etc. for mass concrete	Sqm	656.25	362.60	2,37,956.25	BCD 5.9.3
)2	Plain/Reinforced cement concrete in sub-structure complete as per drawing and technical specifications RCC grade M30 - with batching plant, transit mixer and concrete pump				-	ER TECH.
1	Centring and shuttering including strutting, proping etc. and removal	Cum	153.13	4,878.00	7,46,943,75	RCD (3.56 (p) i
). 2 A	or form work for Nalls (any thickness) including attached pilasters.	Sam	2.075.00	- 221 22	160 Stiller	JR SIIII'S ALPHA
,	Butteresses, plinth and string courses etc.	Sqm	2,975.00	321.30	9,55,867,50	BH 8610 5.9.2
1.3 I	REINFORCEMENT			-	V 11	•




3.1	Supplying, fitting and placing HYSD bar reinforcement in sustructure complete as per drawing and technical specifications	b-		-	-	
		MT	43.23	63,203.00	27,34,991.32	RCD 13.6
5	Constructing brick masonry circular manhole 1.52 m internal dia bottom and 0.56 m dia at top in cement mortar 1:4 (1 cement : 4 coars sand) inside cement plaster 12 mm thick with cement mortar 1:3 cement : 3 coarse sand) finished with a floating coat of neat cemer foundation concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stor aggregate 40 mm nominal size) and making necessary channel is cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stor aggregate 20 mm nominal size) finished with a floating coat of necement, all complete as per standard design:	se (1 at, ne in each ne	10.00			BCD SOR 19.13.1
6	Constructing brick masonry road gully chamber 110x50x77.5 cm with bricks in cement mortar 1:4 (1 cement : 4 coarse sand) with precast R.C.C. vertical grating complete as per standard design : (@ 1 per 20 m	st	7.00	4,115.30	28,807.10	BCD,Item 19.28.1
	Building I Company				2	
7	Providing and fixing M.S. grills of required pattern in frames of windowsvetc. with M.S. flats, square or round bars etc. including priming coat with approved steel primer all complete. (For silt trap for box drain)	g	125.00	114.20	14,275.00	BCD SOR 9.48.1
8	Surface dressing of the ground including removing vegetation and in equalities not exceding 15cm deep and disposal of rubbish, lead upto 50m and lift upto 1.5m	100 Sqm	225.00	1,126.90	2,53,552.50	2.29.1
)9	Supplying and Filling in plinth with local Earth/sand and under floors including, watering, ramming consolidating and dressing complete.	cum	6,750.00	238.60	16,10,550.00	2.28
10	Grassing with 'Doobs' Grass (Grassing with 'Doobs' grass including watering and maintenance of the lawn for 30 days or more till the grass forms a thick lawn free from weeds and fit for moving including supplying good earth if needed.) In rows 7.5 cm apart in either direction	5	22,500.00	19.30	4,34,250.00	11.2.ii
	Construction of a permanent type barricade made of steel components, 1.5 m high from road level, fitted with 3 horizontal rails 200 mm wide and 4 m long on 50 x 50 x 5 mm angle iron vertical support, painted with yellow and white strips, 150 mm in width at an angle of 450 C, complete as per IRC:SP:55-2001		150.00	4,163.00	6,24,450.00	8.44 A
)2	Providing and fixing 1.2 metres high GI barbed wire fencing with 1.8 m angle iron posts 40 mm x 40 mm x 6 mm placed every 3 metres center to center founded in M15 grade cement concrete, 0.6 metre below ground level, every 15th post, last but one end post and corner post shall be strutted on both sides and end post on one side only and provided with 9 horizontal lines and 2 diagonals interwoven with horizontal wires, fixed with GI staples, turn buckles etc complete as per clause 807		875.00	248.00	2,17,000.00	8.17
) .			•			
_	Sub Total				1,32,99,488	
)+	CARRIAGE OF MATERIALS				1,34,77,488	
	Brick	3803.80	Thousand	767.08	2917.82	
)	Local Sand	7187.50	Cum	262.05	1883484.38	
	Coarse Sand	153.99	Cum	1030.3	158656.49	
-	Stone Chips	299.82	Cum	2701.3	809900.39	
1	Cement Steel	2109.02 43.27	MT MT	328.25	692284.65	
)	Carriage Cost	43.47	IVI I	328.28	14205.70 3561449	
	Total Cost for the construction of drain with grassing and Barricadding of Cricket Stadium Ground				₹ 1,68,60,937	
طلسر	mirrordanis or Cricker oradium Ground					

SR. MANAGER TECH. 2 SR. MANAGER TECHNITO.



	Appendix 39: Development of Cleaveland Memorial						
Sr.	Description	Unit	Quantity	Rate (Rs)	Amount in (Rs)	SOR Reference	
1	Earth Work						
2	Surface dressing of the ground including removing vegetation and ir equalities not exceding 15cm deep and disposal of rubbish, lead upt 50m and lift upto 1.5m	o 100 Sqm	70.00	1,126.90	78,883.00	2.29.1	
3	Supplying and Filling in plinth with local Earth/sand and unde floors including, watering, ramming consolidating and dressing complete.	g cum	1,750.00	238.60	4,17,550.00	2.28	
4	Grassing with 'Doobs' Grass (Grassing with 'Doobs' grass including watering and maintenance of the lawn for 30 days or more till the grass forms a thick lawn free from weeds and fit for moving including supplying good earth if needed.) In rows 7.5 cm apart in either direction	e	7,000.00	19.30	1,35,100.00	11.2.ii	
5	Pathway at entry and along Water Fountain Supplying and Filling in plinth with local sand and under floor including, watering, ramming consolidating and dressing complete.	cum	72.00	238.60	17,179.20	2.28	
6	Paver Block for Pathway Providing and laying factory made chamfered edge Cement Concrete paver blocks of required strength, thickness & size/shape made by table vibratory method, to attain superior smooth finish using PU or equivalent moulds, laid in required Grey colour & patterr over 50mm thick compacted bed of coarse sand, compacting and proper embedding / laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with jamuna sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand in footpath, parks, lawns, drive ways or light traffic parking etc. all complete as per (a) 80 mm thick c.c. paver block of M-35 grade with approved colour design and pattern.	n l l . Sqm	480.00	812.70	3,90,096.00	11.79.1	
7	Water Fountain complete package in all respect (Excavation, RCC round wall, Lighting, Water motor, Cleaning and its drainage pattern etc.) as per Existing Condition and as per direction of E/I		2,00,000.00	1.00	2,00,000.00	Lump Sump	
8	Muroom Pathway Supplying and Filling in plinth with moorum under floors including, watering, ramming consolidating and dressing complete.	cum	23.44	176.90	4,146.09	16.3.10	
9	Renovation of Old Structure Plastering - 12 mm cement plaster of mix: 1:4	Sqm	1,008.00	139.90	1,41,019.20	13.11.2	
10	Applying one coat of cement primer of approved brand and manufacture on wall surface: Distemper primer	Sqm	1,008.00	31.70	31,953.60	13.78.2	
11	Distempering with oil bound washa ble distemper of approved brand and manufacture to give an even shade . Two or more coats on new work	Sqm	1,008.00	46.50	46,872.00	13.77.A . 1	
12	RCC at Entry Providing and laying in position specified grade of reinforced cement concrete excluding the cost of ring, shuttering, finishing and reinforcement-All work puto plinth level 1:1:5:3(1 cement: 1.5 coarse sand:3 graded stone aggregate 20 mm nominal size)	cum	27.00	4,902.30	1,32,362.10	5.1.2	
13	Granite at Platform Providing and fixing 18 mm thick gang saw cut, mirror polished,	Sqm	20.25	3,699.10	74,906.78	8.2.2.2	
14	Cost of Toilet 1 No. (Amount taken from estimate of Toilet) U-PVC pipes (working pressure 4 kg/cm2) Rubber (Seal) Ring 110				7,55,117		
15	mm dia .	per Meter	100.00	13.52	1,352	7191	
	Sub Total CARRIAGE OF MATERIALS				24,26,536		
	Brick	0.00	Thousand	767.08	0.00		
	Local Sand Coarse Sand	72.00 15.92	Cum	262.05 1030.3	18867.60 16398.73		
	Stone Chips	0.00	Cum Cum	2701.3	0.00	0	
	Cement	5.31	MT	328.25	1741.53	4.6	
	Steel	0.00	MT	328.28	0.00		
	Moorum Carriage Cost	23.44	Cum	304.88	7145.63 44153	CHAN	
	Total Cost for the construction of cleaveland Memorial with drain, grassing, Pathway, Toilets, Fountainwith Grassing etc.			100	₹ 24,70,690	DIN.	
		I		**	Hyman Chini		



·		X	APPENDIX - 40 ESTIMATE OF TOILET BLO	OCK (BIG)			
	S.No.	BCD SOR 2018	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT (Rs.)
	1	2.6	Earth work in excavation over areas (exceeding 30 cm in depth. 1.5 m in width as well as 10 sqm on plan) including disposal of excavated earth, lead upto 50m and lift upto 1.5m; disposed earth to be levelled and neatly dressed.				
\perp		2.6.1	All kinds of soil	Cum	4.55	279.10	1268.51
	2	2.26	Filling available excavated earth (excluding rock) in trenches, plinth, sides of foundations etc. in layers not exceeding 20cm in depth: consolidating each deposited layer by ramming and watering lead.	Cum	2.27	103.30	234.75
	3	2.28	Supplying and filling in plinth with local sand and under floors including, watering, ramming consolidating and dressing complete. Below Grade Beam Sand Filling (Up to plinth)		1.26	238.60	300.64 14733.55
+			Providing and laying in position cement concrete of		01.73	250.00	14733.33
	4	4.1	specified grade excluding the cost of centering and shuttering - All work upto plinth level.				,
		4.1.6	1:3: 6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40 mm nominal size)	Cum	3.94	3307.00	13029.58
	5	6.1A	Brick work with bricks of class designation 100A in foundation and plinth in :	Cum			
L		6.1.12 A	Cement mortar 1:4 (1 cement : 4 coarse sand)	cum	7.00	5037.20	35260.40
	6	6.18A	Half brick masonry with bricks of class designation 100A in foundation and plinth in :	1			
L		6.18.4A	Cement mortar 1:4 (1 cement : 4 coarse sand) Reinforced Cement Concrete Works	sqm	100.80	596.80	60157.44
	7	5.1.2	Providing and laying in position specified grade of reinforced cement concrete excluding the cost of Centring, shuttering, finishing and reinforcement-All work puto plinth level - 1:1:5:3(1 cement: 1.5 coarse sand:3 graded stone aggregate 20 mm nominal size) Column	Cum	3.28		
1			Gread Beam	Cum	2.10		
1			Tie Beam	Cum	1.40		
1	-		Roof Beam	Cum	1.75		
	-		Roof Chhajja	Cum Cum	6.36 1.62		
1	-		Total RCC Quantity	Cum	16.51	4902.30	80940.04
*	8	5.22	Reinforcement for RCC work including straightening. Cutting, bending, placing in position and binding all complete. Thermo-Mechanically Treated bars	Cunt	10.01	1702.00	00/10.01
			FMTC-500-10 mm dia.	kg	2592.17	76.70	198819.30
		5.9	Centring and shuttering including strutting, propping etc. and removal of form for:	J			
	9	5.9.6	Walls (any thickness) including attached pilasters. Butteresses, plinth and string courses etc. Column	Sqm	63.00	425.80	26,825.40
	,		Gread Beam	Sqm	30.80	335.30	10,327.24
			Tie Beam	Sqm	28.00	335.30	9,388.40
			Roof Beam	Sqm	30.80	335.30	10,327.24
	_		Roof	Sqm	50.88	321.30	16,346.14
			Chhajja	Sqm	13.50	321.30	4,337.55
	10	11.72 f	Providing designation 100 A one brick flat soling joints illed with local sand including cost of watering taxes, oyalty all complete as per building specification and lirection of E/I.	sqm	7.00	120×50	1942.50
		L^2		Ass	Dr. Mr.	e all	

ON CONTROLLING BHICHOLD



Г		APPENDIX - 40)			
		ESTIMATE OF TOILET BL	OCK (BIG)			
S.	No. BCD SO 2018	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT (Rs.)
1	1 11.36	Providing and fixing 1st quality ceramic glazed wall tile conforming to IS: 15622 (Thickness to be specified by the manufacture) of approved make in all colours, shade except burgundy, bottle green, black of any size a approved by Engineer -in-Charge in skirting, risers of step and dados over 12 mm thick bed of cement Motar 1: (1cement: 3 coarse sand) and jointing with grey cement slurry @ 3.3 kg per sqm including pointing in white cement mixed with pigment of matching shade complete.	es s s s sqm 3	246.40	739.80	1,82,286.72
1	2 11.38	Providing and laying Ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of is quality conforming to IS: 15622 of approved make it colours such shades except white, Ivory, Grey, Fume Red Brown, laid on 20 mm thick Cement motar 1:4 (1 cement: 4 coarse sand including pointing the joints with white cement and matching pigment etc., complete.	t ' Sqm	61.75	736.40	45,472.70
13	3 11.27	Kota stone slabs 25 mm thick in risers of steps, skirting, dado and pillars laid on 12 mm (average) thick cement mortar 1:3 (1 cement : 3 coarse sand) and jointed with grey cement slurry mixed with pigment to match the shade of the slabs, including rubbing and polishing complete.	Cam	23.40	1133.90	26533.26
		Plaster & Finishing Works				
14	13.11	12 mm cement plaster of mix 1:4 (1 cement : 4 coarse sand)	sam	1008.00	139.90	141019.20
15	13.24	6 mm cement plaster to ceiling of mix.	sqm	1000.00	139.90	141019.20
-	13.24.2	1:4 (1 cement : 4 coarse sand)	sqm	65.55	110.90	7269.50
16	13.78.2	Applying one coat of cement primer of approved brand and manufacture on wall surface: Distemper primer	Sqm	1,073.55	31.70	34031.54
17	13.77.A. 1	Distempering with oil bound washa ble distemper of approved brand and manufacture to give an even shade . Two or more coats on new work Inner Part	Sqm	536.78	46.50	24960.04
. 18	13.79	Finishing Wall with water proofing cement paint of approved brand and manufacture and of required shade to give an even shade Outer Face				
	13.79.1	New work (three or more coats)	sqm	536.78	68.30	36,661.73
19	22.8	Waterproofing Providing and laying integral cement based water proofing treatment including preparation of surface as required for treatment of roofs, balconies, terraces etc consisting of following operations:				
	22.8.1	With average thickness of 120mm and minimum thickness at Khurra as 65 mm.	sqm	61.75	2553.30	1,57,666.28
20	9.20	Providing and fixing ISI marked flush door shutters decorotive type core of block board construction with frame of 1st class hard wood and well matched teak ply veneering with vertical grains or cross or cross bands and face veneers on the both faces venears on the both face of shutters.			2,40	
	9.20.2	30mm thick including stainless steel butt hinges with necessary screws	sqrip	26.40	2474.40	65,324.16
19	9.1	Providing wood work in frames of doors, windows, clearstory windows and other frames, wrought framed and fixed in position	d	O IN	05/18/10/8	,
	9.1.	Second Class teak wood	cum	264	95749.10	2,52,777.62



		APPENDIX - 40 ESTIMATE OF TOILET BLO	OCK (BIG)			
S.No.	BCD SOR 2018	DESCRIPTION OF ITEM	UNIT	QTY.	RATE	AMOUNT (Rs.)
20	9.53	Providing 40 x 5 mm flat iron hold fast 40 cm long including fixing to frame with 10 mm diameter bots, nuts and wooden plugs and embeddings in cement concrete block 30x10x15 cm 1:3:6 mix (1 cement: 3 coarse sand: 6 graded stone aggregate 20 mm nominal size)	5	60.00	106.60	6,396.00
21	9.96	Providing and fixing aluminium sliding door bolt anodised (anodiccoating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with nuts and screws etc.				
	9.96.1	300 x 16 mm	each	10.00	220.40	2,204.00
22	9.96.2	250 x 16 mm Providing and fixing aluminium handles anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour and shade with necessary screws etc. complete:		10.00	195.50	1,955.00
	9.100.1	125 mm	each	20.00	54.00	1,080.00
23	9.101	Providing and fixing aluminium hanging floor door stopper anodized (anodic coating not less than grade AC 10 as per IS :1868) transparent or dyed to required colour and shade with necessary screws etc. complete.		2		
	9.101.2	Twin rubber stopper	each	10.00	40.40	404.00
24	9.97	Providing and fixing aluminium sliding tower bolt anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with nuts and screws etc.				
İ	9.97.1	300 x 10 mm	each	10.00	105.20	1,052.00
	9.97.4	150 x 10 mm	each	10.00	67.80	678.00
25	9.9	Providing and fixing glazed shutters for doors, windows and clerestory windows using 10kg/square meter (4mm thick) glass panes including black enamlled M.S butt hindge with necessary screws.				9
t	9.9.2.2	30 mm thick	sqm	26.40	1975.90	52,163.76
26	10.18	Providing and fixing circular cast iron box for ceiling fan clamp 140 mm internal dia, 73 mm height, 5 mm thick rim bottom and top lids, 1.5 mm thick M.S sheet with its top surface hacked for proper bonding top lid shall be screwed into the cast iron box by means of 3.3 mm dia round headed screws, one ;pcf at the corners. Clamps shall be made of 12mm dia M.S. bar bent to shape as per standard drawing.	each	10.00	141.30	1,413.00
27		Applying priming coat With ready mixed pink or grey primer of approved brand and manufacture on woodwork (hard and soft wood)	sqm	116.16	32.20	3,740.35
		Painting with synthetic enamel paint of approved brand				
H		and manufacture to give an even shed. Two or more coats on new work	sam	116.16	70.40	8,177.66
28	17.1	Providing and fixing water closet squattting pan (Indian Type WC pan) with 100mm sand cast iron P or S trap, 10 liter low fixture complete, including cutting and making good the wall and level white PVC flushing cistern, including flush pipe, manully control device(handle lever) confiming to IS:7231, with all fiftings and floors where ever required.	sqm	110.10	70.40	0,1//.00
		white Vitreous china, Orissa, Pattern WC pan of size 580x440 mm with integral type footrest.	Nos.	2.00	3390,90	6,781.80
			a	St. West	STATE OF STA	



30	7.7.1 7.7.7 8.53 3.53.1 8.51	Providing and fixing white vetreous china pedestal type water closet. (European type) with seat and lid, 10 ltr flow level white vitreous china flushing cistren and C P flush bend with fitting and CI brackest, 40mm flush bend, over flow arrangment with special of standreds make and mosqutoues proof coupling of approved municipal complete design complete, including painting of fittings and brackets, cutting and making good the walls. W.C. Pan with ISI marked white solid plastic seat. Providing and fixing white vitreous china flat back or wall corner type leaped urinal basin of 430x260x350 mm and 340x410x265 mm size repectively with automatic flushing cistren with standred flush pipe and CPP brass spreaders with brass union and GI claim complte, including painting of fittings and brackets, cutting and making good the wall and floor whenever required. Range of Two Urinal Basin with 5 ltr white PVC automatic flushing cistren. Providing and fixing wash basin with CI Brackest, 15mm CP brass pillar taps, 32mm CP brass waste of standred pattren including painting of fittings and brackets, cutting and making good the wall whereever required. White virterous China wash basin size 630x450mm with a pair of 15mm CP brass pillar taps White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to 15:8931. a 15mm nominal bore. Providing and fixing CP Brass long body bib cock of approved quality conferming to 15: standreds and weighinf not less than 690 grams	Nos. Nos. Nos. Nos.	5.00 6.00 4.00	4554.00 5121.70 2307.10 1520.00	22,770.0 22,770.0 30,730.2 13,842.6 6,080.0
30 17 31 18 32 17 33 17 34 18 18. 35 18 18. 36 18	17.3.1 17.4 17.4.2 17.7 7.7.1 7.7.7 8.53 8.53.1	water closet. (European type) with seat and lid, 10 ltr flow level white vitreous china flushing cistren and C P flush bend with fitting and CI brackest, 40mm flush bend, over flow arrangment with special of standreds make and mosqutoues proof coupling of approved municipal complete design complete, including painting of fittings and brackets, cutting and making good the walls. W.C. Pan with ISI marked white solid plastic seat. Providing and fixing white vitreous china flat back or wall corner type leaped urinal basin of 430x260x350 mm and 340x410x265 mm size repectively with automatic flushing cistren with standred flush pipe and CPP brass spreaders with brass union and GI claim complte, including painting of fittings and brackets, cutting and making good the wall and floor whenever required. Range of Two Urinal Basin with 5 ltr white PVC automatic flushing cistren. Providing and fixing wash basin with CI Brackest, 15mm CP brass pillar taps, 32mm CP brass waste of standred pattren including painting of fittings and brackets, cutting and making good the wall whereever required. White virterous China wash basin size 630x450mm with a pair of 15mm CP brass pillar taps White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS: 8931. a 15mm nominal bore.	Nos. Nos.	6.00 6.00 4.00	5121.70 2307.10 1520.00	30,730.2 13,842.6 6,080.0
30 1: 31 1: 32 17: 33 17: 34 18: 35 18: 36 18:	17.4 17.4.2 17.7 7.7.1 7.7.7 8.53 3.53.1 8.51	Providing and fixing white vitreous china flat back or wall corner type leaped urinal basin of 430x260x350 mm and 340x410x265 mm size repectively with automatic flushing cistren with standred flush pipe and CPP brass spreaders with brass union and GI claim complte, including painting of fittings and brackets, cutting and making good the wall and floor whenever required. Range of Two Urinal Basin with 5 ltr white PVC automatic flushing cistren. Providing and fixing wash basin with CI Brackest, 15mm CP brass pillar taps, 32mm CP brass waste of standred pattren including painting of fittings and brackets, cutting and making good the wall whereever required. White virterous China wash basin size 630x450mm with a pair of 15mm CP brass pillar taps White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore. Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	Nos. Nos.	6.00 6.00 4.00	5121.70 2307.10 1520.00	30,730.2 13,842.6 6,080.0
31 17 32 17 33 17 34 18 35 18 36 18	17.4.2 17.7 7.7.1 7.7.7 8.53 3.53.1	corner type leaped urinal basin of 430x260x350 mm and 340x410x265 mm size repectively with automatic flushing cistren with standred flush pipe and CPP brass spreaders with brass union and GI claim complte, including painting of fittings and brackets, cutting and making good the wall and floor whenever required. Range of Two Urinal Basin with 5 ltr white PVC automatic flushing cistren. Providing and fixing wash basin with CI Brackest, 15mm CP brass pillar taps, 32mm CP brass waste of standred pattren including painting of fittings and brackets, cutting and making good the wall whereever required. White virterous China wash basin size 630x450mm with a pair of 15mm CP brass pillar taps White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore. Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	Nos. Nos.	6.00	2307.10 1520.00	13,842.6
31 1 1 1 32 17 33 17 34 18 18. 35 18 18. 36 18	17.7 7.7.1 7.7.7 8.53 8.53.1 8.51	Providing and fixing wash basin with CI Brackest, 15mm CP brass pillar taps, 32mm CP brass waste of standred pattren including painting of fittings and brackets, cutting and making good the wall whereever required. White virterous China wash basin size 630x450mm with a pair of 15mm CP brass pillar taps White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore. 15 mm Nominal Bore Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	Nos. Nos.	6.00	2307.10 1520.00	13,842.6
32 17 33 17 34 18 35 18 36 18	7.7.1 7.7.7 8.53 3.53.1 8.51	CP brass pillar taps, 32mm CP brass waste of standred pattren including painting of fittings and brackets, cutting and making good the wall whereever required. White virterous China wash basin size 630x450mm with a pair of 15mm CP brass pillar taps White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore. 15 mm Nominal Bore Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	Nos.	4.00	1520.00	. 6,080.0
33 17 34 18 18. 35 18. 36 18	7.7.1 7.7.7 8.53 8.53.1 8.51	pair of 15mm CP brass pillar taps White virterous Chaina flat back wash basin size 450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore. 15 mm Nominal Bore Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	Nos.	4.00	1520.00	. 6,080.00
34 18 18. 35 18. 36 18	8.53 8.53.1 8.51	450x300mm with single 15mm CP brass pilar taps. Providing and fixing Cp brass angle valve for basin mixer and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore. 15 mm Nominal Bore Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	2			
34 18. 35 18 36 18	8.53 8.53.1 8.51	and geyser points of approved quality conferming to IS:8931. a 15mm nominal bore. 15 mm Nominal Bore Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	Nos.	18.00	512.90	9,232.20
35 18 18. 36 18	8.51	Providing and fixing CP Brass long body bib cock of approved quality conferming to IS: standreds and weighinf	Nos.	18.00	512.90	9,232.20
36 18			1			
17		15 mm Nominal Bore	Nos.	6.00	531.60	3,189.60
27 17	8.48 F	providing and placing on terrace (at all floor levels) polytheline water storges tank, ISI:12701 marked, with cover and sutaible loking arrangment and making necessary holes for inlet, Outlet and over flow pipes but without fittings and the base support for tank.	Litre	1000.00	7.90	7,900.00
37	7.32 q n	Providing and fixing mirror of superior glass (of approved quality) and of required shapes and size with plastic moulded frame of approved make and said with 6mm thick hard.				
		Oval shape 450 x 350 mm Mirror Septic Tank (2.3 mt x 1.1 mt)	Nos.	8.00	744.60	5,956.80
30 L	LS S	герас танк (2.5 mt х 1.1 mt)	Nos.	2.00	77700.00	1,55,400.00 17,99,388.38
39 L	LS I	nternal plumbing and electrification			5%	89,969.42 18,89,357.80
40 Analys	sis C	Carriage				,,
F	АВ	rick	Per Thousand	5359.90	767.08	4111.47
		ocal Sand	Cum 🕠	63.01	262.05	16511.77
		Coarse Sand	Cum	30.85	1030.3	31784.54
		tone Chips	Cum	18.20	2701.3	49166.51
E		ement	MT	17.58	328.25	5770.00
F	F St	teel	MT	707.59	328.25 L for 1 Toilet _	850.88 19,97,553



1	9
	ap
de	ins
10	
7 8	3
i.s	1110
rac	Chil
FF C	
·M	
Ž	
75	
re 2	
inas	,
Cha	
M, C	
.75	
x 0	
0.5	
rain	
SD	
RCC	1
of	1
ıate	۱
stin	١
 H	
nuc	1
Gro	١
es (١
urpo	ı
tipı	ı
Mul	
11: 1	
lix 4	
enc	I
App	

Sr. No.	Description	Unit	Quantity	Rate (Rs)	Amount in (Rs)	SOR Reference
1	Earth Work					
П	Excavation for Structures (Earth work in excavation of foundation of structures as per drawing and technical specification, including setting out, construction of shoring and bracing, removal of stumps and other deleterious matter, dressing of sides and bottom and backfilling with approved material.)					RCD SOR 12.1 v B
В	Depth upto 1.5 m	CIIB	1 687 50	177.00		
1.2	Timbering		1,007	177.00	2,98,687.50	
1.2.1	Open timbering in trenches including strutting and shoring complete (Measurement to be taken of the face area timbered):					
в	Depth exceeding 1.5 m but not exceeding 3 m	Sqm	1,687.50	60.10	1,01,418.75	BCD SOR - Item No.
	Dewatering and pumping out water in trenches				1	2.20.2
	D				1	
1.3	rumping out water caused by springs, tidal or river seepage, broken water mains or drains and the like.	KL	3,375.00	92.20	3,11,175.00	BCD Item no 2.25
	Refilling the Excavated Trenches (Backfilling)			ı		
1.4	back filling behind abutment, wing wall and return wall complete as per drawing and Technical specification	cum	843.75	593.00	5,00,343.75	RCD 13.9 B (i)
1.5	Back filling behind abutment, wing wall and return wall complete as per drawing and Technical specification (Below Raft)	cnm	1,125.00	593.00	6,67,125.00	RCD 13.9 B (i)
1.6	Clearing and Grubbing Road Land (Clearing and grubbing road land including uprooting rank vegetation, grass, bushes, shrubs, saplings and trees girth up to 300 mm, removal of stumps of trees cut earlier and disposal of unserviceable materials and stacking of serviceable material to be used or auctioned up to a lead of 1000 metres including removal and disposal of top organic soil not exceeding 150 mm in thickness.)	Hectare	. 0.28	47,489.00	13,356.28	RCD 2.3 i (a)



Ş.						
No.	Description	Unit	Quantity	Rate (Rs)	Amount in (Rs)	SOR Reference
	DISPOSAL OF EARTH			1	1	
	Romoviol of impoundable and a little			1	ı	
1.7	removal of unserviciable soil and disposal upto 1000 meters (Removal of unserviciable soil including excavation, loading and disposal upto 1000 meteres lead but excluding replacement by suitable soil which shall be paid separately)	Cum	843.75	93.70	79,059.38	RCD SOR - 2018/Item No. 3.11
	Labour for filling anti cement bags with local sand, stutching the bag					
1.8	and placing including supply of sutri etc. all complete job as per direction of Engineer in charge with carriage of local sand and cost of anti cement bag for different type of work at site.	Per 100 bags	1,320.00	2,622.87	34,62,188.40	WRD SOR 2018 5.7.40.1
c	CONCRETE WORK		5	1	t	
1	DOC 1000 C.				1	
7	foundation with crushed stone aggregate 40 mm nominal cize					
1.7	mechanically mixed, placed in foundation and compacted by vibration including curing for 14 days.			t	1	
ĸ	1:3:6 (1 Cement : 3 coarse sand : 6 graded stone aggregate 40 mm	mi)	15750	00 420 0		
			00.701	3,304.00	5,29,830.00	RCD 12.4
2.2	or form work for		3		1	
				:		
а	Foundations, footings, bases of columns etc. for mass concrete	Sqm	825.00	186.30	1,53,697.50	BCD 5.9.1


ON COMPRESIDENT TO



Sr. No.	Description	Unit	Ouantity	Rate (Rs)	Amount in (Re)	SOB B
			~	(car) amaz	(SAI) III (III)	SOM Kererence
				1		
8	REINFORCED CEMENT CONCRETE WORK					
	RCC SLAB				1	
3.1	Plain/Reinforced cement concrete in sub-structure complete as per drawing and technical specifications RCC grade M30 - with batching plant, transit mixer and concrete pump	Cum	315.00	4,878.00	15,36,570.00	RCD 13.5G (p) i
3.1 A				1	ı	
ro .	Foundations, footings, bases of columns etc. for mass concrete	Sqm	1,687.50	362.60	6,11,887.50	BCD 5.9.3
3.2	Plain/Reinforced cement concrete in sub-structure complete as per drawing and technical specifications RCC grade M30 - with batching plant, transit mixer and concrete pump				t	
		Cum	393.75	4,878.00	19 20 712 50	PCD 13 50 (a) :
3.2 A	Centring and shuttering including strutting, proping etc. and removal or form work for			,		(d) percentage
В	Foundations, footings, bases of columns etc. for mass concrete	Sqm	7,650.00	321.30	24,57,945.00	BCD 5.9.2
3.3	REINFORCEMENT			1		
3.3.1	Supplying, fitting and placing HYSD bar reinforcement in substructure complete as per drawing and technical specifications			ı	1	
		MT	111.27	63.203.00	70 32 834 82	2 CL U.J.
ΓO	Constructing brick masonry circular manhole 1.52 m internal dia at bottom and 0.56 m dia at top in cement mortar 1:4 (1 cement : 4 coarse sand) inside cement plaster 12 mm thick with cement mortar 1:3 (1 cement : 3 coarse sand) finished with a floating coat of neat cement, foundation concrete 1:3:6 (1 cement : 3 coarse sand : 6 graded stone aggregate 40 mm nominal size) and making necessary channel in cement concrete 1:2:4 (1 cement : 2 coarse sand : 4 graded stone aggregate 20 mm nominal size) finished with a floating coat of neat cement, all complete as per standard design:	each	20.00	31,068.40	6,21,368.00	BCD SOR 19.13.1

SR. MITTHERE SWAFF CHAIT





		Appendix	44 : Scu	lpture	Court					
Si.No.	Ref.BCI SOR 2018	Description Of work	Unit	No	Length	Breadth	Depth	Qty	Rate (Rs.)	Amount (Rs.)
\bigcap_{1}		EARTH WORK	1	+						
	2.8.1	Earth work in excavation in foundation trenches of drains (not exceeding 1.5 m in width or 10 sqm on plan including dressing of sides and ramming of bottoms, lift upto 1.5 m. including getting out the excavated soil and disposal of surplus excavated soil as directed, within a lead of 50 m.	t t					8		
		All kinds of soil	Cum	1	40	34	0.3	408	319.60	130397
1				-						
2	2.28	BACKFILLING Supply and filling in plinth with local sand and under floor including watering ,ramming consolidating and dressing complete		1	40	34	0.5	680	238.60	162248
)	2.29	Surface dressing of the ground including removing vegetation and in-equalities not exceding 15cm deep and disposal of rubbish, lead upto 50m and lift upto 1.5m								
	2.29.1	All kinds of soil	100 SQM	1	40	34		1360	1126.90	15325.84
)	2.32	Clearing jungle including uprooting of Rank vegetation ,grass, brush wood, trees and saplings of girth upto 30 cm measured at a height of 1 m above ground level and removal of rubbish upto a distance of 50 m outside the periphery of the area cleared.	100 SQM	1	40	34		1360	579.80	7885.28
.)_		GOVERNMENT WORK								
3	4.1	CONCRETE WORK Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level. 1:4:8 (1 Cement : 4 coarse sand : 8 graded stone)								
	4.1.8	aggregate 40 mm nominal size)	Cum	1				15.54	2940.80	45700
)	4.3	Centring and shuttering including strutting, propping etc. and removal or form work for							9	
	4.3.1	Foundations, footings, bases, columns	Sqm	1				1.05	185.90	196
4		REINFORCED CEMENT CONCRETE WORK								
)	5.2	Reinforced cement concrete in walls (any thickness) including attached pilasters, buttresses, plinth and string courses, fillets, columns, pillars, piers, abutments, posts and struts, etc. up to floor five level, excluding the cost of centring, shuttering, finishing and reinforcement.								
		1:1.5:3 (1 Cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size)	Cum	1				66.40	5723.30	380027
<i>J</i> 5		SHUTTERING								
)		Centring and Shuttering including strutting, propping etc. and removal of form for								
)	5.9.1	Foundations, footings, bases of columns etc. for mass concrete.	Sqm	1				105.40	186.30	19636
6		REINFORCEMENT				1			167	10.
)									rest .	Ma

O St. Hillight Blue Blue Blue Blue



		Reinforcement for R.C.C work including straightening cutting, bending, placing in position and binding alcomplete.	ÍI						
-	5.22.7 1	Thermo - Mechanically Treated bars TMTC - 500-10mm dia	n Kg	1			5212.4	76.70	399791
7		STEEL							
$\bigcap_{i=1}^{n}$	10.32	Steel work welded in built up sections/framed work including cutting hoisting, rixing in position and applying a priming coat of approved steel prime using structural steel, etc. as required.	ı						
	10.32.2	In gratings, frames, guard bar, ladders, railings, brackts Gates & similar works.	Kg	1			400	88.80	35520
	10.36	Providing and fixing stainless steel (Grade 304) railing made of Hollow tubes, channels, plates etc., including welding, grinding, buffing, polishing and making curvature (wherever required) and fitting the same with necessary stainless steel nuts and bolts complete, i/c fixing the railing with necessary accessories & stainless steel dash fasteners, stainless steel bolts etc., of required size, on the top of the floor or the side of waist slab with suitable arrangement as per approval of Engineer-incharge, (for payment purpose only weight of stainless steel members shall be considered excluding fixing accessories such as nuts, bolts, fasteners etc.).	Kg	1			2000	496.00	992000
8		TRINAV PUBLIC BENCH							
)	Gem Portal	Product id: 5116877-37860375338	No.	10			10.0	9,940	99400
)									
		PAVER BLOCK Providing and laying factory made chamfered edge Cement Concrete paver blocks of required strength, thickness & size/shape, made by table vibratory method, to attain superior smooth finish using PU or equivalent moulds, laid in required Grey colour & pattern over 50mm thick compacted bed of coarse sand, compacting and proper embedding / laying of inter locking paver blocks into the sand bedding layer through vibratory compaction by using plate vibrator, filling the joints with jamuna sand and cutting of paver blocks as per required size and pattern, finishing and sweeping extra sand in footpath, parks, lawns, drive ways or light traffic parking etc. all complete as per Manufacturer's specifications & direction of Engineer -in-Charge:	٠						¥
)		(a) 80 mm thick c.c. paver block of M-35 grade with approved colour design and pattern.	Sqm	1			300	812.7	243810
		Grassing with 'Doob' grass including watering and							
)	23.10	maintenance of the lawn for 30 days or more till the grass forms a thick lawn free form weeds and fit for moving including supplying good earth if needed.							~
I	23.10.3	In rows 5 cm apart in either direction.	100 Sqm	1.00			1000	855.4	8554
,									
)—								Total	24,01,539
\dashv					 A			riage Cost	4,38,376
كسر					 2 / 11	N &	St. In	Total Cost	28,39,915

Total C



		Appendix 47 : Esti	mate of	Dismant	ling forB	oundary	Wall			
S.No	BCD SOR 2018	Description	Unit	No	Length	Width	Height	Quantity	Rate (Rs)	Amount (Rs)
1	15.7	Demolishing brick work including stacking of serviceable material and disposal of unserviceable material within 50 meters lead:	-							
1		Wall	Cum	1	3910	0.125	1.8	879.75		
	15.7.4	Wall	Cum	1	3910	0.25	1.1	1075.25		
			Sub - Tota	l				1955	685.1	1339370.5
2	15.3	Demolishing R.C.C. work including stacking of steel bars and disposal of unserviceable material withing 50 metres lead:								
		Coloumn	Cum	1304	0.25	0.25	3.5	285.25		
		Beam	Cum	1	3910	0.25	0.25	244.38		
			Sub - Tota					529.63	1172.7	621091.238
			Total							1960462

SR HERLEN SHART CHULTO.



Appendix 48: Bondary Wall External ESTIMATE OF BOUNDARY WALL (30 M Length)

		ESTIMATE OF BOUNDARY WALL	(30 M Length)			
s.no.	BCD SOR 2018	DESCRIPTION OF ITEM	QTY.	UNIT	RATE (Rs.)	AMOUNT (Rs.)
1	Item no. 20.3A.1	Making 25cm (10") dia bore up to 1.5 depth below ground wit hand auger of approved quality in ordinary soil (vid classification of sol item-A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50 M lead including all lifts, all complete as per approved design and direction of E/I.	e y p 35	Meter	148.6	5,201.00
) 2	Item no. 20.3A.2	Making 63 cm (25") dia under-ream at required depth with hand auger of approved quality in ordinary soil (vide classification o soil item-A) true to plumb and without eccentricity in any stage o operation and disposal of the excavated earth up to 50M lead including all lifts, all complete as per approved design and direction of E/I.	f f 1 8	Each	158.6	1,268.80
3.	Item no. 2.8.1	Earth work in excavation in foundation trenches or drains(no exceeding 1.5 M in width 10 sqm on plan)including dressing of sides and ramming of bottoms lift upto 1.5 m including getting out the excaveted soil and disposal of surplus excaveted soil as directed, within a lead of 50.0m	10.2	Cum	319.6	6,136.32
4	Item no. 2.28	Supply and filling in plinth with local sand and under floors including watering,ramming,consolidating and dressing complete		Cum	238.6	2,290.56
) 5	Item no. 4.1.8	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:4:8 (1 Cement : 4 coarse sand : 8 graded stone aggregate 40 mm nominal size)	2	Cum	2940.8	8,822.40
) 6	Item no. 5.1.2	Providing and laying in position reinforced cement concrete of specified grade excluding the cost of centring and shuttering - all work upto plinth level.1:1.5:3 (1 Cement : 1.5 coarse sand : 3 graded stone aggregate 20 mm nominal size)		Cum	4902.3	58,827.60
7	Item no. 5.9.5	Centering and Shuttering including strutting, propping etc. and removel of from for lintel, beams, plinth beam, girdes, ressumers and cantilevers.		Sqm	335.3	16,765.00
8	6.1C	Brick work with fly ash bricks as per IS 12894(2002) & IS 3495 in foundations and plinth in :				
)	6.1.12C	Cement mortar 1.:4 (1 cement: 4 coarse sand)	2.00	Cum	5129.7	10,259.40
9	Item no. 13.13.4	Providing 20mm thick cement plaster 1:6 (1cement:6 coarse sand)	83.50	Sqm	173	14,445.93
10	Item no. 5.22	Reinforcement for RCC work including straighting, cutting, bending, placing in position and binding all complete - Thermo -Mechnically Treated bars (FE-500).				
/	5.22.7B	Thermo-Mechanically Treated bars TMTC-500-10mm dia.	942.00	Kg	76.7	72,251.40
) 11	Item no. 13.45.1	Finishing walls with texture exterior paint of required shade New work(two or more coats)	83.50	Sam	143.6	11 000 06
12	Item no.	Steel work welded in built up sections/framed worK including cutting hoisting, rixing in position and applying a priming coat of approved steel primer using structural steel, etc. as required.	554.6	Sqm Kg	88.8	11,990.96 49,248.48
13	2018, Item	Supplying and fixing of following sizes of medium class PVC conduit along with accessories in surface/ recess including cutting the wall and making good the same in case of recessed conduit as required. 20 mm	600	Meter	68	40,800.00
đ.						200222
)		CARRIAGE				2,98,307.85
,	A	Brick	988.00	Per Thousand	767.08	758
14		Local Sand	9.60	Cum	262.05	2,516
)		Coarse Sand	8.93	Cum	1030.3	9,204
-		Stone Chips Cement	13.38	Cum	2701.25 472.72	36,135
1		Steel	150	MT	328.25	6,336
		//	12 VOI	TOTAL COST		3,53,747
J		× m llia	apr alle		ST PER RMT	11,792

TOTAL COST PER 30 RMT 3,53,747


**COTAL COST PER RMT 11,792

**TOTAL COST PER 2.55 KM of Boundary wall 3,00,69,600




5		Appendix 49: BOUNDARY WALL	Internal (30	M LENC	GTH)	
3.No.	Reference	Item Description	Quantity	Unit	Rate (Rs.)	Total amount (Rs.)
	BCD SOR 20.3A.1	Making 25cm (10") dia bore up to 4 M depth below ground with hand auger of approved quality in ordinary soil (vide classification of sol item-A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50 M lead including all lifts, all complete as per approved design and direction of E/I.	35	Rmt	148.6	5201.00
2	BCD SOR 20.3A.2	Making 63 cm (25") dia under-ream at required depth with hand auger of approved quality in ordinary soil (vide classification of soil item-A) true to plumb and without eccentricity in any stage of operation and disposal of the excavated earth up to 50M lead including all lifts, all complete as per approved design and direction of E/I.	8	Each	158.6	1269.00
))))	2.8.1	Earth work in excavation in foundation trenches or drains(not exceding 1.5 M in width 10 sqm on plan)including dressing of sides and ramming of bottoms lift upto 1.5 m including getting out the excaveted soil and disposal of surplus excaveted soil as directed, within a lead of 50.0m	1.75	Cum	319.6	559.00
) 4	BCD SOR	Supply and filling in plinth with local sand and under floors including watering,ramming,consolidating and dressing complete	0.53	Cum	238.6	126.00
) 5	BCD SOR 4.1.8	Providing and laying in position cement concrete of specified grade excluding the cost of centring and shuttering-all work up to plinth level (1:4:8)	0.53	Cum	2940.8	1559.00
.)			1		1 6	

O CONTROL SHEET CHILD.



	BCD SOR 5.1.2	Reinforced cement concrete work in beams, suspended floors, roofs having slope up to 15 degree, landings, balconies, shelves, chajjas, lintels, bands, plain window sill, stair cases and spiral stair cases up to floor five level excluding the cost of centering, shuttering, finishing and reinforcement with ratio 1:1.5:3 (1 cement:1.5 coarse sand:3 graded stone aggregate 20 mm nominal size)	8	Cum	4902.3	24041.00
7	BCD SOR 5.9.5	Centring and Shuttering including strutting, propping etc. and removel of from for lintel, beams, plinth beam, girdes, ressumers and cantilevers.	49.96	Sqm	335.3	16752.00
8	BCD SOR 6.1.14C+6.3 C	Brick work with fly ash bricks as per IS 12894 (2002) & IS 3495 in foundations and plinth in : Cement mortar 1:6 (1 cement: 6 coarse sand)	5.36	Cum	5597.9	29977.00
9	BCD SOR 13.13.4	Providing 12 mm thick cement plaster 1:6 (1cement:6 coarse sand)	147.70	Sqm	173.00	25552.00
10	BCD SOR 5.22.7B	Reinforcement for RCC work including straighting, cutting, bending, placing in position and binding all complete - Thermo -Mechnically Treated bars (FE-500) 10 mm dia	441.00	Kg	76.7	33825.00
11	BCD SOR	Finishing walls with texture exterior paint of required shade				
)	A CONTRACTOR OF THE CONTRACTOR	New work(two or more coats)	147.70	Sqm	143.6	21210.00
)				TOTA	L COST	160071.00
		Carriage c	ost			21110.91
1		C	OST PER RU	JNNING	METRE	6039
)		TO	TAL COST I	FOR 1010	METRE	6099791

SHARINGER FECH. 2. BHICHEIR D.



SUMM	ARY OF PROJECT COST FOR ELECTRICAL OF SPORTS A	REA IN SANDY'S COMPOUND (PHASE 1)
SI	DESCRIPTION OF WORK AREA	AMOUNT (Rs.) (Phase 1)
1	City Gym	₹ 3,13,711.00
2	Basketball Court	₹ 24,53,602.00
3	Cleveland Memorial	₹ 7,18,472.38
4	Tennis Court	₹ 28,03,052.00
. 5	Power Station	₹ 95,04,685.53
	TOTAL COST	₹ 1,57,93,523

O CONTROL BURGING THE BURGING OF THE



City Order Catalogue Cat	SI.No.	DESCRIPTION OF WORK AREA			AMOUNT	Ŋ	
City Grant Cit	1 0	City Gym			₹3,13,7	11.00	
Tennis Courte (1979)	7 n	Basketball Court			₹ 24,53,	502.00	
Provide and finding 4 X 40 want suspended type LD burnlants provides achiefult and gave free symmetrical illumination burn of 15 X 200,000 EB 23.20 and 15 X 15					₹7,18,4	72.38	
TOTAL CSSI TOTAL	t u				₹ 28.03.	052.00	
Supplying and fining 4 Y 40 watt suspended type LED Unithaties provides soft-light and gate free symmetrical illumination of the controlled type LED Unithaties provides soft-light and gate free symmetrical illumination of the controlled type LED Unithaties provides soft-light and gate free symmetrical illumination of the controlled type LED Unithaties provides soft-light and gate free symmetrical illumination of the controlled type LED Unithaties provides soft-light and gate free symmetrical illumination of the controlled type LED Unithaties controlled the controlled that the controlled controlled that the controlled t	0	Power Station			₹ 95.04.	585.53	
Supplying and foing 4 X 40 wat suppended type LD intensing provides softlight and glore free symmetrical lituralisation complete with all accessories etc. including ball and socket arrangement. A commerce of some the complete with a supplying and foing 4 X 40 wat suspended type LD intensing provides or supplying and forming at X 40 wat suspended type LD intensing provides or supplying and forming between notes and connection with 1.5 sq mm fit PVC insulated copper conductor single core cable in surface/recessed medium dass PVC conduit, with modular surface light core cable in surface/recessed medium dass PVC conduit as required. Writing for light prover plug with 204 sq, mm fit PVC insulated copper conductor single core cable in surface/recessed medium dass PVC conduit as required. Writing for light prover plug with 204 sq, mm fit PVC insulated copper conductor single core cable in surface/recessed medium dass PVC conduit as required. Writing for light prover plug with 204 sq, mm fit PVC insulated copper conductor single core cable in surface/recessed medium dass PVC conduit as required. Writing for circuit/ submain wiring alongwith earth wire with the following sizes of fit PVC insulated copper conductor single core cable in surface/recessed medium dass PVC conduit as required. Writing for circuit/ submain wiring alongwith earth wire with the following sizes of fit PVC insulated copper conductor single core cable in surface/recessed medium dass PVC conduit as required. Writing for circuit/ submain wiring alongwith earth wire with the following sizes of fit PVC insulated copper conductor single core cable in surface/recessed medium dass PVC conduit as required. Writing for circuit/ submain wiring alongwith earth wire with the following sizes of fit PVC insulated copper conductor single core cable in surface or circuit/ submain wiring and fining plants and foreign foreign submained size of the PVC insulated copper conductor single core cable in surface foreign submained size of the PVC insulated copper co					₹1.57.93	522 91	
Supplying and frong 4 X 10 want suspended type LD Luminate provides soft-light and give free symmetrical liumhoidion completes with all and social eard carriedge and though 2 X 10 want suspended type LD Luminate provides soft-light and give free symmetrical liumhoidion with all all and social eard connection with 1.5 ag mm R PVC insulated copper conductor, 1.0 m R PVC insulated copper conductor single core cable and earthing etc. as required, Maker Bajal/Philipy/Havelly/CBS or equal with 1.5 ag mm R PVC insulated copper conductor single core cable in surface/Fecassed medium dass PVC conduit and the PVC insulated copper conductor single core cable for loope extressed medium dass PVC conduit and the PVC insulated copper conductor single core cable for loope or conductor single core cable in surface/Fecassed medium dass PVC conduit and the FVC insulated copper conductor single core cable in surface/Fecassed medium dass PVC conduit as required, 2.2.2.5 ag, mm + 1.1.2 ag, mm R PVC insulated copper conductor single core cable for loope extressed medium dass PVC conduit as required, 2.2.2.5 ag, mm + 1.1.2 ag, mm reart wire conductor, single medium dass PVC conduit as required, 2.2.2.5 ag, mm + 1.1.2 ag, mm reart wire conductor, single core cable in surface/Fecassed medium dass PVC conduit as required, 2.2.2.5 ag, mm + 1.1.2 ag, mm reart wire conductor, single core cable in surface/Fecassed medium dass PVC conduit as required, 2.2.2.5 ag, mm + 1.1.2 ag, mm reart wire conductor, single medium dass PVC conduit as required, 2.2.2.5 ag, mm + 1.1.2 ag, mm reart wire conductor, single core cable in surface/Fecassed medium das PVC conduit as required, 2.2.2.5 ag, mm + 1.1.2 ag, mm reart wire conductor, single for conductors and download in the following sizes of ft PVC insulated copper conductors and cover in from on surface or in recess, including providing and fixing simple accorded to the transfer of the conductor single medium das SU/AVCS and complete with buokder painting etc as required. If an without busher onland moun		City Gym	有理教育的	THE REAL PROPERTY.	がまでは新りた。 はまでは新りた。 はまである。 または、 はまである。 または、 はまである。 は、 は、 に、 に、 に、 に、 に、 に、 に、 に、 に、 に	17.77	
anapping and mines g x x 40 was trained and socket an arrangement, 2 no down roots of gate free symmetrical illumination with grant g x x 40 was trained as competen with all accessories aft. Including ball and socket arrangement, 2 no down roots of controlled with all accessories aft. Including ball and socket arrangement, 2 no down roots of controlled with a 1.5 sq mm RF PVC insulated copper conductor single core cable in surface/freessed medium class PVC conduit, with modular switch, modular plate sintable size 6.1 lbox etc 35 Withing for righty point/ a no nord versal for point/call bell point with 1.5 sq mm RF PVC insulated copper conductor single core cable for loop earthing 23 Withing for righty power plug with 2X4 sq, mm RF PVC insulated copper conductor single core cable for loop earthing 23 Withing for circult/ submain winning alongwith 1.0 A 4 sq, mm RF PVC insulated copper conductor single core cable for loop earthing 23 Withing for circult/ submain winning alongwith to NA sq, mm RF PVC insulated copper conductor single core cable for loop earthing 24 Withing for circult/ submain winning alongwith sarth wire with the following sizes of RF PVC insulated copper conductor single core cable for loop earthing 24 Withing for circult/ submain winning alongwith sarth wire with the following sizes of RF PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit as required, 2 X4 sq, mm + 1 x 4 sq, mm earth wire conductor single core cable in the existing surface/ recessed medium class PVC conduit as required, 2 X4 sq, mm + 1 x 4 sq, mm earth wire conductor single core cable in the existing surface/ recessed medium class PVC conduit surface or in recess, including providing and fining suitable size of look with modular pates and concurs etc. as required. Supplying and fining suitable size of look with modular pates and concurs etc. as required. Supplying and fining suitable size of look with modular pates and concurs etc. as required. Supplying and fining ploan roun	SI.No.	Constitution DESCRIPTION		Qty.	Rate (Rs.)	Ref: Rate	Amount (Re)
Witing for light point, fan point, exhaust fan point, with modular switch, modular plate, suitable size G1, box etc as nos. Witing for light point (an point) exhaust fan point, with modular switch, modular plate, suitable size G1, box etc as nos. 60 724.00 BCD Ele. SOR 2018. Item 1.3.1 Witing for light power plug with 2X4 st., mm RR PVC insulated copper conductor single core cable for loop earthing as nos 10 200.00 BCD Ele. SOR 2018. Item 1.3.1 Witing for circuit/ submain writing alongwith earth wire with the following sizes of RR PVC insulated copper conductor, single mit 200 200.00 BCD Ele. SOR 2018. Item 1.7.1 Witing for circuit/ submain writing alongwith earth wire with the following sizes of RR PVC insulated copper conductor, single mit 200 200.00 BCD Ele. SOR 2018. Item 1.7.3 Witing for circuit/ submain writing alongwith earth wire with the following sizes of RR PVC insulated copper conductor, single mit 200 200.00 BCD Ele. SOR 2018. Item 1.7.3 Witing for circuit/ submain writing alongwith earth wire with the following sizes of RR PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit as required. 2 X 4 sq. mm 1.1 X 45, mm earth wire core cable in surface/ recessed medium class PVC conduit as required. 2 X 4 sq. mm 1.1 X 45, mm earth wire core eable in surface/ recessed medium class PVC conduit service in recess, including providing and fixing size of RR PVC insulated copper conductors single core cable in the existing surface/ recessed medium class PVC conduit so that modular plate and cover in front on surface or in recess, including providing and fixing along socket outlet and 15/15A modular switch, connections etc. as required. Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board fabricated with powder painting etc as required. (But without busbar chanber, insulator, nut-bott with MS 40 X 40 X 5 mm angle stand for an outlet and 15/15A modular switch, connections etc. as required. Back III III III III III III III III III I	1	suppying and fixing 4" X 40 watt suspended type LED luminaire provides soft-light and glare free symmetrical illumination complete with all accessories etc. including ball and socket arrangement, 2 no. down rods of 20mm dia X 1.6 mm thick G.I. pipe upto 30 cm. length, painting and wiring the down rods and connection with 1.5 sq mm FR PVC insulated copper conductor, single core cable and earthing etc. as required. Make: Bajaj/Philips/Havells/C&S or equivalent		09	1380.00	BCD Ele. SOR 2018, Item 5.14	82800.00
medium class PVC conduit alongwith 1 No 4 sq. mm R PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit alongwith 1 No 4 sq. mm R PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit as required, 2 x 2.5 sq. mm + 1 x 2.5 sq. mm earth wire core cable in surface/ recessed medium class PVC conduit as required, 2 x 2.5 sq. mm + 1 x 4 sq. mm earth wire core cable in surface/ recessed medium class PVC conduit as required, 2 x 2.5 sq. mm + 1 x 4 sq. mm earth wire core cable in surface/ recessed medium class PVC conduit as required, 2 x 4 sq. mm + 1 x 4 sq. mm earth wire core cable in surface/ recessed medium class PVC conduit as required, 2 x 4 sq. mm + 1 x 4 sq. mm earth wire core cable in surface/ recessed medium class PVC conduit as required, 2 x 4 sq. mm + 1 x 4 sq. mm earth wire core cable in surface recessed medium class PVC conduit as required, 2 x 4 sq. mm + 1 x 4 sq. mm earth wire core cable in surface recessed medium class PVC conduit as required, 2 x 4 sq. mm + 1 x 4 sq. mm earth wire providing and fixing studies steed frow with modular plate and cover in front on surface or in recess, including providing and fixing studies size of R PVC insulated copper conductor single core cable in surface or in recess, including providing and fixing studies size of R PVC insulated switch, connections etc. as required, 1 x 400.00 SR Ele. SOR 2018, Item 1.33 supplying and fixing studies size of the vith modular solete pallar cubical type panel board, fabricated with 14 guage iron sheet suitable size of the studies of copper with powder painting etc as required, 1 suitable size of the x x x x x x x x x x x x x x x x x x x	2	Wiring for light point/ fan point/ exhaust fan point/call bell point with 1.5 sq.mm FR PVC insulated copper conductor single core cable in surface/recessed medium class PVC conduit, with modular switch, modular plate, suitable size G.I. box etc as required. Group C	10000	09	724.00		43440.00
writing for circuit/ submain writing alongwith earth wire with the following sizes of FR PVC insulated copper conductor, single Writing for circuit/ submain writing alongwith earth wire with the following sizes of FR PVC insulated copper conductor, single Writing for circuit/ submain writing alongwith earth wire with the following sizes of FR PVC insulated copper conductor, single Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed medium class PVC conduct are required, 2 x 4 sq. mm + 1 x 4 sq. mm earth wire Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed medium class PVC conduct are required, 2 x 4 sq. mm + 1 x 4 sq. mm earth wire Supplying and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in recess, including providing and fixing suitable size of box with modular plate and cover in front on surface or in	m	Wiring for light/ power plug with 2X4 sq. mm FR PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit alongwith 1 No 4 sq. mm FR PVC insulated copper conductor single core cable for loop earthing as required.		10	200.00		2,000.00
Core cable in surface / recessed medium dass PVC conduit as required, 2.X 4 sq. mm + 1.X 4 sq. mm earth wire Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed medium dass PVC conduit as required, 2.X 4 sq. mm earth wire Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed medium dass PVC conduit as required, 2.X 4 sq. mm earth wire Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed medium dass PVC conduit as required, 2.X 4 sq. mm earth wire Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed medium dass pVC conduits socket outlet and sold are not surface or in recess, including providing and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suitable size of box with modular switch, connections etc. as required. Supplying and fixing suita	4	volring for circuit/ submain wiring alongwith earth wire with the following sizes of FR PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required, 2 x 2.5 sq. mm+1 x 2.5 sq. mm earth wire		200	161.00		32,200.00
Publications are during and drawing sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed mtr 100 62.00 Item 1.15.3 Item	2	vering for circuity submain wiring alongwith earth wire with the following sizes of FR PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required, 2 X 4 sq. mm + 1 X 4 sq. mm earth wire		200	200.00		40,000.00
Supplying and fixing 5 pin 5/6 A modular socket outlet and 5/6 A modular switch, connections etc. as required. Supplying and fixing 5 pin 5/6 A modular socket outlet and 15/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/6 & 15/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/6 & 15/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/6 & 15/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/6 & 15/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/6 & 15/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/16 A modular switch, connections etc. as required. Supplying and fixing 1 pin 5/16 A modular switch or surface or in recess, including providing and fixing 1 pin 1/3 pin 1/	9	Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed PVC conduit as required 3x1.5 sq. mm		100	62.00	BCD Ele. SOR 2018, Item 1.15.3	6,200.00
Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing suitable fixing 6 pin 5/6 & 15/16 A modular socket outlet and 15/16 A modular switch, connections etc. as required. Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SEU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 x 40 x 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. 11,200.00 BCD Ele. SOR 2018, 11,200.00 Item 1710 Item 1710	7	supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 3 pin 5/6 A modular socket outlet and 5/6 A modular switch, connections etc. as required.		10	401.00	DSR Ele. SOR 2018, Item 1.31	4,010.00
Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 x 40 x 5 mm angle stand and complete with bowder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. 150.000 BCD Ele. SOR 2018, 150.000 BCD Ele. SOR 2018, 150.000 Item 1710 It	∞	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 6 pin 5/6 & 15/16 A modular socket outlet and 15/16 A modular switch, connections etc. as required.		10	495.00		4,950.00
Each 1 1,200.00 BCD Ele. SOR 2018, Item 1710	6 BHB	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq.		1	6,174.00	BCD Ele. SOR 2018, Item 8.10.3	6174.00
Man and a second	101	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	Each	1	1,200.00	BCD Ele. SOR 2018, Item 1710	1200.00
	HAGAL	MA TO					-



BCD Ele. SOR 2018, Item 2.12.1	BCD Ele. SOR 2018, 5285.00	BCD Ele. SOR 2018, 84300.00	Item 2208	313711.00	Bof. Date	MR 1302240.00	MR 1016640.00	BCD Ele. SOR 2018, Item 8.10.3	BCD Ele. SOR 2018,	BCD Ele. SOR 2018, 768.00	BCD Ele. SOR 2018, 42280.00	BCD Ele. SOR 2018, 84300.00	2453602.00	一年 のから ののできる ののできる ののできる できる ののできる できる ののできる ののできる ののできる ののできる かいかい かいかい かいかい かいかい かいかい かいかい かいかい かい	Ref: Rate Amount (Rs)	UP SOR 2018,Chapter 14 - LED LUMINAIRES, Item 1443	BCD Ele. SOR 2018, Item 2204
192.00 BC	105.70 BC	281.00 BC	4	Amount	Rate (Rc.)	162780.00	42360.00	6,174.00 BC	1.200.00 BC		105.70 BC	281.00 BC	Amount		Rate (Rs.)	18300.00 2C	105.70 BC
9	50	300			Otv.	∞	24		1	4	400	300			Qty.	27	300
Each	mtr	mtr			Unit	l	Nos.	Nos	Each	Each	mtr	mtr			Unit	nos.	mtr
poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. 6/32 amps, Single pole	בסו ע' ד	5.3 Core, 70 Sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor		Basketball Court	DESCRIPTION	accessories. Pole will be supplied with 15MC channel to mount 4 nos. 500 W LED flood light fittings with junction box and other accessories. Pole will be supplied with step ladder to access the top of the pole. Price is inclusive of suitable Foundation, bolt and Junction box. Make: Bajaj/Philips/Havells/Transrail/Valmont	Bajaj/Philips/Havells/C&S or equivalent	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	Supplying and fixing following rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. 6/32 amps, Single pole	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	5.5 core, 70 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor		Cleveland Memorial	Supply and fixingof decorative 40 to 45 Watt LED Post top indirect lightluminairehavingPressure die cast aluminiumbody and	Clear glass with driver set confirmingto IP 65 and above protection complete in all respect. CAT-AA CAT-AA	4 Cores, 16 Softma XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor
11	12	13		Ol No	ONITE .	1	2	3	4	ľ	9	7		SI.No.		BHASA	BHH



	P & F of IP65 IK10 protected IFD Bollard fixture Inth Eight Sixture					
м	for uniform distribution. The System level Luminous efficacy > 85 Lumen/W. SMD LEDs. CRI>70, CCT: 3000/4000/6000 K. The integral SMPS based electronic driver must be constant current and inbuilt surge protection of min. 4KV(L-N) and efficiency > 85%, PF>0.9 and input Voltage range of 90- 270V AC at 50Hz. System life of 50000 burning hours with 70% of Initial Lumens maintained. Light should include quick connecting cable coupled with various mounting accessories. Light output in Cool white or Warm White Colour as per engineers choice. Fixture must be in compliance with IS/CE Standards. 0.8 mtr high bollard Make: Bajaj/Philips/Havells/C&S or equivalent	each	20	4055.32	SOR RUIDP 2017, Item 58.34.2	81106.38
4	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	at.	300	00 000	BCD Ele. SOR 2018,	
	Laying of one number PVC insulated and PVC sheathed / YI BE source and I will be a supported and		200	126.00	Item 2205	37800.00
5	including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq.	mtr	009	77.00	DSR Ele. SOR 2018,	46200.00
	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover	T				
٥	plate having locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.	mtr	н	5125.00	BCD Ele. SOR 2018, Item 3-7	5125.00
7	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.	to	000	000	BCD Ele. SOR 2018.	
	Supplying and fixing Floor mounted outdoor foodox cillage in the contract of t	126	200	38.00	Item 3.16	11400.00
∞	for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (each panel 3 Sq. ft)	nos.	Н	6174.00	BCD Ele. SOR 2018, Item 8.10.3	6174.00
σ	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity					
,	Consulting to the state of the	each	1	1200.00	BCD Ele. SOR 2018,	1200.00
	Supplying, installation, testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twiliph/lang ON Anno					
10	OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (1output per phase) and suitable for three phase supply	each	Т	3657.00	DSR Ele. SOR 2018, Item 15.4.3	3657.00
					Total A 200	
	Tennis Court	THE PERSON NAMED IN COLUMN TWO IS NOT THE PERSON NAMED IN COLUMN TWO IS NAMED IN CO	いいいるというないのであるというないのである。	日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日	Discontinue of the continue of	/184/2.38
SI.No.		Unit	Oto.	Rate (Rc.)	Doft Date	
,	SITC of 14 M Octagonal Pole with ISMC channel to mount 4 nos. 500 W LED flood light fittings with junction box and other	1001	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	The state of the s	nei. naie	Amount (Ks)
н	accessories . Pole will be supplied with step ladder to access the top of the pole. Price is inclusice of suitable Foundation bolt and lunction how Make Bajai/Dhilling/Language (A. 1972)	Nos.	∞	162780.00	MR	1302240.00

J

Control of the second	Tennis Court	光光的景态景态景态	各名的智慧以思信思言 以思於以及以神史的自然的問題和問題	St.	24 44 51 51 51 51 51 51 5
SI.No.	DESCRIPTION		· · · · · · · · · · · · · · · · · · ·	一般の一体の大利を対する	
	CITY OF 14 A A A CITY OF THE C	Unit Oty.	v. Rate (Rs.)	Ref. Rate	Amount (De)
,	SILC OF 14 IN Octagonal Pole with ISMC channel to mount 4 nos. 500 W LED flood light fittings with junction box and other				Cultonine (no)
-	accessories . Pole will be supplied with step ladder to access the top of the pole. Price is inclusive of suitable Foundation half	- NON	0000000		
	and Junction box. Make: Bajaj/Philips/Havells/Transrajl/Valmont		162/80.00	MR	1302240.00
	SITC of SOOW IED Floodlight basing Become die and				
	dissipation of heat. Electrochemically brightened and anodized aluminum reflector. Heat				
	The state of the s				
2	With Baske, and 55 Clips. LED Colour Temp.: 5700K ±300K Luminaires provided with a mounting bracket for aiming adjustment				
	Power Fartor >= 0.95 Driver provided with huilt in clay in the	Nos 32	00 03507	200	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
	Solution		*C	MM	1355520.00
	protection (1966, Powder coated Finish: Make: Baiai/Philins/Havalls/Co.s.c. or acmityalant			-	
	The state of the s				
	The second second				

ARESTER CHITO.



ю	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)	Nos	Н	6,174.00	BCD Ele. SOR 2018, Item 8.10.3	6174.00
4	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	Each	Н	1.200.00	BCD Ele. SOR 2018,	00 0001
2	Supplying and fixing following rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. 6/32 amps, Single pole	Each	4	192.00	Item 1710 BCD Ele. SOR 2018,	00.0021
9	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor			300000000000000000000000000000000000000	Item 2.12.1 BCD Fle SOR 2018	
7	3.5 core, 70 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	mtr	200	105.70	Item 2204	52850.00
		mtr	300	281.00	BCD Ele. SOR 2018, Item 2208	84300.00
	Domos Crayle	The second second			Amount	2803052.00
SI.No.	Decription					
Н	Supply of 11KV grade, 3C x 300 Sq. mm Aluminium conductor, XLPE insulated, PVC sheathed, armoured screened cable. The cable should conform to IS: 7098 Part-2, 2011 with up to date amendment. APPROVED BRAND: Polycab/ Havells/ KEI/ RR / RPG	Unit Mtrs	Qty	Rate (Rs.) 1,311.36	SPDCL 2016,	Amount (Rs.) 39,34,090.91
2	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 11 KV grade of following size in the existing RCC/HUME/ METAL/ DWC HDPE pipe as required. Above 120 sq. mm and upto 400 sq. mm	Mtrs	3000	112.00	DSR SOR 2018,	3.36.000.00
m	Supplying and laying of following size DWC HDPE pipe ISI marked along with all accessories like socket, bend, couplers etc. conforming to IS 14930, Part II complete with fitting and cutting, jointing etc.direct in ground (75 cm below ground level) including excavation and refilling the trench but excluding sand cushioning and protective covering etc., complete as required. 200 mm dia (OD-200 mm & ID-175 mm nominal), approved make	Mtrs	0009	598.00	Item Code 8.3.2 DSR SoR 2018, Item Code 14.16.5	35,88,000.00
	Simplying and property of the second state of					
4	Supplying and making outdoor cable end termination with heat shrinkable jointing kit complete with all accessories including lugs suitable for following size of 3 core, XLPE aluminium conductor cable of 11 KV grade as required:	each	12	17,166.00	DSR Ele. SOR 2018, Item 10.5.4	2,05,992.00
Ŋ			U		DSR Ele. SOR 2018.	
	ferrules suitable for following size of 3 core, XLPE aluminium conductor cable of 11 KV grade as required: 300 sq. mm		o	19,314.00	Item 10.6.4	1,15,884.00
9	Supply, installation, testing and commissioning of new double pole structure for 11KV/433V upto encluding Rail Pole 2 Nos, Top channel set, A.B. Switches base channel set, Horn gap fuse base channel, Transformer base channel, Tanformer fastening angle, Support clamp for tansformer base channel, support clamp for AB switch base channel, Back clamp for transformer fastening angle, back clamp for horn gap fuse set, cable holding clamp, 11 kV 200 Amp. AB Switch 3 pole, 11 kV Horn Gap Fuse set with insulator, nut bolt, danger board making HT/LT busbar System, 315 kva DT star rated etc complete with all respect as	set	2	5,34,932.95	SPDCL 2016, DSS	10,69,865.91
7	Carthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover of at a harmy locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.	set	12	5,125.00	BCD Ele. SOR 2018, Item 3.2	61,500.00
80	Providing and fixing 6.5 WG dia G.L. wire on surface or in recess for loop earthing etc. as required.	Mtrs	200	38.00	BCD Ele. SOR 2018, Item 3.16	7,600.00

)

þ

DING Marion



SITC of DG Set complete with 1500 RPM Diesel Engine of suitable BHP & AC Brush less SPDP Alternator mounted on a common base Frame & coupled through a flexible coupling or close coupled. Alternator shall be self regulated with standard Alternator Protection (Over voltage, over speed & under voltage). Engine shall have residential silencer, up to 10 M exhaust piping, y electronic / Mechanical governor, Manual & electric/Auto Start, Batteries, Fuel tank (with Stand) & piping, control panel (16 G) and with Weatherproof, powder coated Accoustic enclosure for DG set for sound attenuation fabricated from 1.6 mm CRCA sheet and filled with foam as per CPCB norms latest amendments & 18 8183. The doors are fabricated from 1.6 mm CRCA sheet packed with accoustic material, floor of MS chequired plate 5.0 mmthick, All doors of pening are sealed with neoprene/ EPDN gaskets. The enclosure has built in fuel tank, residential silencer (isolated from main DG chamber) with protection and tripping of DG set against temperature of more than 50 °C. All controls for operation of DG set are from outside the enclosure with DG control panel having microprocessor based genset monitoring and control system mccb Ammeter, voltmeter, Pf meter, frequency meter, RWH meter, Ind. Lamps etc. mounted inside enclosure, visible and accessible from outside. The enclosure should be suitable for following capacity DG sets and alternator. Noise level is less than 75 db (A) at a distance of 1 Mtrs. duly certified by authorized agency. Complete in all inside the enclosure, with the following meters/indicators; (Incoming and outgoing voltage, Current in all phases, Frequency, KVA and power factor, Time indication for hours/ minutes of operation, Fuel Level in field tank, low fuel indication, Control Fuses, Stop button, Auto/Manual/Test selector switch, instrument, relay etc. essential for Automatic functioning of DG set with AMF panel Make:-for Engine-Cummins, Caterpillar, KOEL, for Alternator:-Stampford, Kirlosker-Green,CG	1	41,19,843.62	RUIDP SOR 2017,	41,19,843.62
			Amount	95 04 685 53
			***************************************	יייייייייייייייייייייייייייייייייייייי

.)

_)

ر

1.1

ON ONE FECH. 2. BHEALTH TO. BHEALTH BH



SUM	MARY OF PROJECT COST FOR ELECTRICAL OF GENERAL LIG COMPOUND (Phase 1)	SHTING OF SANDY'S
SI. NO.	DESCRIPTION OF WORK AREA	AMOUNT Phase 1 (Rs.)
1	Entrance plaza and Parking (ONE NO.)	₹ 5,04,226.00
2	Walkway	₹ 32,40,114.00
3	Cafetaria	₹ 2,89,666.00
4	Memorial renovation	₹ 5,47,563.00
5	Sculpture court	₹ 4,95,766.00
6	Station club renovation	₹ 10,92,035.00
7	Kid's play area	₹3,05,361.00
8 ,	High Mast & Solar Light	₹ 85,39,052.73
9	Renovation of existing OAT	₹ 9,65,805.00
10	Power Station	₹ 28,62,536.00
11	TOTAL COST	₹ 1,88,42,124.73

SR. MARIER SHARINGTON ID.



Bill of Quantities (Electrical) for Entrance Plaza with parking & water fountain of Sandish Park In Bhagalpur

12.00		OI Sailuis	I Park III	bnagaipur		
SI.NO.	Description	Unit	Qty.	Rate (Rs.)	Ref: Rate	Amount (Rs.)
H	Supply, installation, Testingand Commissioning of LED RGB/RGBW Linear Wall Washer luminaire for Facade lighting with aluminium extruded housing, of following wattage. Luminaire shall be capable of producing dynamic color changing light with 16 million colors by DMX/Ethernet based control. The beam angle of the fitting shall be narrow, medium, wide or asymmetric as per the requirement. Luminaire shall be complete with driver and capable of operating at line voltage without any separate power supply from 100 to 270 VAC, 50Hz, power factor > 0.9. Fixture shall be suitable to operate at ambient temperature range of -10° C to +50° C and shall be IP65 and IK 06 rated. Life time should be at least L70: 50000 burning hours at 50° C. Luminaire shall be conforming to BIS and shall be complete with all necessary accessories required for proper working of fixture including weather proof connection cables, water proof connectors etc. as required. 25 watt	each	œ	23,130.00	DSR E&M Facade 2018, Item 2.5	185,040.00
7	Supply and fixing of decorative 40 to 45 Watt LED Post top indirect light luminaire having Pressure die cast aluminium body and Clear glass with driver set confirming to IP 65 and above protection complete in all respect. CAT-AAA CAT-AAA	nos	10	18,300.00	UP SOR 2018 Chapter 14 - LED LUMINAIRES ,	183,000.00
ж	4 core, 6 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	nos	200	75.00	m	15,000.00
4	4 core, 10 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	mtr	200	95.20	BCD Ele. SOR 2018, Item 2217	19,040.00
2	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	mtr	300	105.70	BCD Ele. SOR 2018, Item 2204	31,710.00
9	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of following size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm	mtr	700	77.00	DSR Ele. SOR 2018, Item 7.3.1	53,900.00
7	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.	mtr	1	5,125.00	BCD Ele. SOR 2018, Item 3.2	5,125.00
∞ <i>€</i>	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.	set	10	38.00	BCD Ele. SOR 2018, Item 3.16	380.00

IN HAR BERNELLING

	guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (each panel 3 Sq. ft)	sou	1	6,174.00	8CD Ele. SOR 2018, Item 8.10.3	6,174.00
10 5	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	each	1	1,200.00	BCD Ele. SOR 2018, Item 1710	1,200.00
11 fr	Supplying,installation,testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (1output per phase) and suitable for three phase supply	each	1	3,657.00	DSR Ele. SOR 2018, Item 15.4.3	3,657.00
					Amount Rs.	504,226.00
	Bill of Quantities (Electrical) for Walkway of Sandi Park In Bhagalpur under Smart City Mission.	nder Smar	t City Mis	sion.		
SI	Description	Unit	Qty.	Rate (Rs.)	Ref: Rate	Amount (Rs.)
<i>y</i>) (Supply and fixingof decorative 40 to 45 Watt LED Post top indirect light luminaire having Pressure die				UP SOR 2018	
٦. د	cast audminiumbody and clear glass with driver set confirmingto IP 65 and above protection complete in all respect.	nos	133	18,300.00	Chapter 14 - LED	2,433,900.00
<u> </u>	CAT-AAA				LUMINAIRES,	
	CAT-AA				Item 1443	
	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
2 a	aluminium conductor	mtr	2700	105.70	2018, Item 2204	285,390.00
	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
м	aluminium conductor	mtr	700	126.00	2018, Item 2205	88,200.00
	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of				DSR Ele. SOR	
4	following size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm	mtr	3200	77.00	2018, Item 7.3.1	246,400.00
2	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal, coke	mtr	4	5 125 00	BCD Ele. SOR	20 500 00
10	and salt as required.		•		2018, Item 3.2	200000
	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.				BCD Ele. SOR	
٥		set	3200	38.00	2018, Item 3.16	121,600.00

 \bigcirc

 \bigcirc

 \cup

7	Suppying and fixing from incurred outdoor reeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)	sou	4	6,174.00	BCD Ele. SOR 2018, Item 8.10.3	24,696.00	
∞	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	each	4	1,200.00	BCD Ele. SOR 2018, Item 1710	4,800.00	
6	Supplying,installation,testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (Loutput per phase) and suitable for three phase supply	each	4	3,657.00	DSR Ele. SOR 2018, Item 15.4.3	14,628.00	
					Amount	3,240,114.00	
	Bill of Quantities (Electrical) for Cafetaria of Sandish Park In Bhagalpur under Smart City Mission.	under Sma	rt City M	ission.			
SL	Description	Unit	Otv.	Rate (Rs.)	Ref: Rate	Amount (Re)	
н	Supply and fixingof decorative 40 to 45 Watt LED Post top indirect lightluminairehavingPressure die cast aluminiumbody and Clear glass with driver set confirmingto IP 65 and above protection complete in all respect.	Son	∞	18 300 00	UP SOR 2018 Chapter 14 -	745 400 00	
	CAT-AA)		LLD LUMINAIRES, Item 1443	140,400.00	
2	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	mtr	300	105.70	BCD Ele. SOR 2018, Item 2204	31,710.00	
æ	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor	mtr	300	126.00	BCD Ele. SOR 2018, Item	37,800.00	
4	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of following size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm	mtr	009	77.00	DSR 20	46,200.00	
2	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.	mtr	1	5,125.00	BCD 2018	5,125.00	
o El	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.	set	300	38.00	BCD Ele. SOR 2018, Item 3.16	11,400.00	
14							

R. MANAGER FECH 2 CHYLTE.

BHACHEUR SHART CHYLTE.

7	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work.) (Each panel 3 Sq. ft)	nos	Н	6,174.00	BCD Ele. SOR 2018, Item 8.10.3	6,174.00
∞	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	each	1	1,200.00	BCD Ele. SOR 2018, Item 1710	1,200.00
6	Supplying,installation,testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (1output per phase) and suitable for three phase supply	each	. н	3,657.00	DSR Ele. SOR 2018, Item 15.4.3	3,657.00
					Total Amount	289,666.00
	Bill of Quantities (Electrical) for Memorial of Sandish Park In Bhagalpur under Smart City Mission.	under Sma	rt City M			
SL	Description	Unit	Qty.	Rate (Rs.)	Ref: Rate	Amount (Rs.)
н	Supply and fixing of decorative 40 to 45 Watt LED Post top indirect light luminaire having Pressure die cast aluminium body and Clear glass with driver set confirmingto IP 65 and above protection complete in all respect. CAT-AAA CAT-AA	nos	12	18,300.00	UP SOR 2018 Chapter 14 - LED LUMINAIRES	219,600.00
					2	

SL	Description	Unit	Qty.	Rate (Rs.)	Ref: Rate	Amount (Rs.)
					UP SOR 2018	
	cast aluminium body and Clear glass with driver set confirmingto IP 65 and above protection				Chapter 14 -	
Н	complete in all respect.	nos	12	18,300.00	LED	219,600.00
	CAT-AAA				LUMINAIRES	
	CAT-AA				Item 1443	
	P & F of IP68, IK10 protected LED Buried marker light / Step Light Fixture. Fixture made of powder coated die cast alluminium with Toughened Glass cover and appropriate beam angle lens to be used					
	13 per requirement, the system revel buildings entitled, must be 290 builden W. Figh Power LEDs at 1W/2W per LED. The driving current should be Minimum 350 mA per LED. CRI>70, CCT: 3000/6500 K.	*			SOR RUIDP	
7	The integral SMPS based electronic driver must be constant current and surge protection of min.	sou	20	1,662.00	2017, Item	83,100.00
	4KV(L-N) and efficiency > 85%, PF>0.9 and input Voltage range of 90-270V AC at 50Hz. System life of				58.33.4	
	50000 Burning hours with 70% of Initial Lumens maintained. Light should include quick connecting					
	cable coupled with Various mounting accessories. Light output in Cool white or Warm White Colour as per engineers choice. Fixture must be in compliance with IS/CE Standards. Step Light - 5W					
	Supplying and drawing following sizes of FRLS PVC insulated copper conductor, single core cable in				DSR Ele. SOR	
m	the existing surface/ recessed steel/ PVC conduit as required 2 x 1 5 sq. mm	mtr	200	41.00	2018, Item	8,200.00
					1.17.2	
	4 core. 16 sa mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with			E	BCD Ele. SOR	
4		mtr	009	105.70	2018, Item	63,420.00
					2204	

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

()

0

 \bigcirc

()

()

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcup

 \bigcirc

0

		/ Mission.	mart City	ur under S	Dill Ol Qualitities (Electrical) 101 Sculpture Court in Sandish Park in Bhagaipur under Smart City Mission.
547,563.00	Total Amount				The state of the s
10,971.00	DSR Ele. SOR 2018, Item 15.4.3	3,657.00	ю	each	Supplying, installation, testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (Loutput per phase) and suitable for three phase supply
3,600.00	BCD Ele. SOR 2018, Item 1710	1,200.00	3	each	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity
18,522.00	BCD Ele. SOR 2018, Item 8.10.3	6,174.00	3	nos	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)
22,800.00	BCD Ele. SOR 2018, Item 3.16	38.00	009	set	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.
10,250.00	BCD Ele. SOR 2018, Item 3.2	5,125.00	2	mtr	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.
00:008'69	DSR Ele. SOR 2018, Item 7.3.1	77.00	006	mtr	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of following size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm
37,800.00	BCD Ele. SOR 2018, Item 2205	126.00	300	mtr	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor

				THE CONTRACT		
SF	Description	Unit	Otv.	Rate (Rc.)	Ref. Rate	Amount (De)
	Supply and fixingof decorative 40 to 45 Watt LED Post top indirect lightluminairehavingPressure die				UP SOR 2018	Simodile (ns.)
,	cast aluminiumbody and Clear glass with driver set confirmingto IP 65 and above protection complete				Chapter 14 -	
н	in all respect.	nos	18	18,300.00	LED	329,400.00
	CAT-AAA				LUMINAIRES,	
	CAT-AA				Item 1443	
(4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
7	aluminium conductor	mtr	300	105.70	105.70 2018, Item	31,710.00
4					2204	
ુ	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
on of	aluminium conductor	mtr	300	126.00	126.00 2018, Item	37,800.00
5					2205	

OO T. STEELEN TO THE STATE OF T

4	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of following size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm	mtr	006	77.00	DSR Ele. SOR 2018, Item 7.3.1	69,300.00
ſΛ	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/coke and salt as required.	mtr	н	5,125.00	BCD Ele. SOR 2018, Item 3.2	5,125.00
9	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.	set	300	38.00	BCD Ele. SOR 2018, Item 3.16	11,400.00
7	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)	nos	П	6,174.00	BCD Ele. SOR 2018, Item 8.10.3	6,174.00
∞	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	each	1	1,200.00	BCD Ele. SOR 2018, Item 1710	1,200.00
6	Supplying,installation,testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (1output per phase) and suitable for three phase supply	each	Н	3,657.00	DSR Ele. SOR 2018, Item 15.4.3	3,657.00
					Total Amount	495,766.00
	Bill of Quantities (Electrical): for Station ClubSandy's Park In BHAGALPUR under Smart City Mission.	under Sma	art City !	Mission.		
S	Description	Unit	Qty.	Rate (Rs)	Ref: Rate	Amount (Rs.)
1	Wiring for light point/ fan point/ exhaust fan point/call bell point with 1.5 sq.mm FR PVC insulated copper conductor single core cable in surface/recessed medium class PVC conduit, with modular switch, modular plate, suitable size G.I. box etc as required. Group C	nos	300	724.00	BCD Ele. SOR 2018, Item 1.3.1	217,200.00
2	Wiring for light/ power plug with 2X4 sq. mm FR PVC insulated copper conductor single core cable in surface/ recessed medium class PVC conduit alongwith 1 No 4 sq. mm FR PVC insulated copper conductor single core cable for loop earthing as required.	sou	50	200.00	BCD Ele. SOR 2018, Item 1.5	10,000.00
ю	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FR PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required, 2 x 2.5 sq. mm+1 x 2.5 sq. mm earth wire	mtr	400	161.00	BCD Ele. SOR 2018, Item 1.7.1	64,400.00
4	Wiring for circuit/ submain wiring alongwith earth wire with the following sizes of FR PVC insulated copper conductor, single core cable in surface/ recessed medium class PVC conduit as required, 2 X 4 sq. mm + 1 X 4 sq. mm earth wire	mtr	300	200.00	BCD Ele. SOR 2018, Item 1.7.3	60,000.00

 \bigcirc

 \cap

 \bigcirc

 \cap

 \cap

 \bigcirc

 \bigcirc

 \bigcup

 \bigcirc

 \bigcirc

2	Supplying and drawing following sizes of FR PVC insulated copper conductor single core cable in the existing surface/ recessed PVC conduit as required 3x1.5 sq. mm	mtr	300	62.00	BCD Ele. SOR 2018, Item	18,600.00
9	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 3 pin 5/6 A modular socket outlet and 5/6 A modular switch, connections etc. as required.	each	20	401.00	DSR Ele. SOR 2018, Item	20,050.00
7	Supplying and fixing suitable size GI box with modular plate and cover in front on surface or in recess, including providing and fixing 6 pin 5/6 & 15/16 A modular socket outlet and 15/16 A modular switch, connections etc. as required.	each	50	495.00	DSR Ele. SOR 2018, Item	24,750.00
∞	Supplying and fixing stepped type electronic fan regulator on the existing modular plate switch box including connections but excluding modular plate etc. as required.	each	20	359.00	BCD Ele. SOR 2018, Item	7,180.00
6	Supplying and fixing 2 pin, 6 amp ceiling rose on the existing junction box/ wooden block including connection etc as required.	each	07	42.00	BCD Ele. SOR 2018, Item	2,940.00
10	Installation of exhaust fan in the existing opening, including making good the damage connection, testing, commissioning etc as required. Upto 450 mm sweep	each	10	198.00	2018, Item 1.50.1	1,980.00
11	P &F following capacity busbar chamber with 4 srtips of suitable size made of copper, heavy duty complete with all accessories including connections, earthing the body etc. as required. 200 Amps	each	2	7,742.00	BCD Ele. SOR 2018, Item 2.5.3	15,484.00
12	Providing and fixing following capacity four pole ONload/panel mounted changeover switches inside the existing cubical panel board including drilling holes in cubicle panel, making connections etc. as required. 125 Amp, four pole	each	2	7,252.00	BCD Ele. SOR 2018, Item 2.7.4	14,504.00
13	Supplying and fixing following way, horizontal type three pole & neutral, sheet steel, MCB distribution board, 415 volts, on surface/ recess, complete with tinned copper bus - bar, neutral bus bar, earth bar, din bar, interconnections, powder painted including earthing etc. as required. (But without MCB/RCCB/Isolator), 4 way (4 + 12), double door, horizontal type	each	4	2,388.00	BCD Ele. SOR 2018, Item 2.9.4	9,552.00
14	Supplying and fixing following rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. 6/32 amps, Single pole	each	09	192.00	BCD Ele. SOR 2018, Item 2 12 1	11,520.00
15	Supplying and fixing following rating, 240/415 volts, "C" curve, miniature circuit breaker suitable for inductive load of following load of single poles in the existing MCB DB complete with connections, testing and commissioning etc. as required. 50/63 amps, Tripole & neutral	each	4	1,635.00	BCD Ele. SOR 2018, Item 2.12.7	6,540.00
16	Supplying and fixing following rating, four pole, (three phase and neutral), 415 volts, residual current circuit breaker (RCCB), having a sensitivity current Upto 300 mill amperes in the existing MCB DB complete with connection, testing and commissioning etc. as required. 63 Amp	each	4	2,941.00	BCD Ele. SOR 2018, Item 2.18.3	11,764.00

ST. MANASHER SHERICHTON

17	Supplying and fixing 20 amps, 240 volts, SPN industrial type, socket outlet, with 2 pole and earth, metal enclosed plug top along with 20 amp "C" curve, SP MCB, in sheet steel enclosure, on surface or in recess, with chained metal cover for the socket outlet and complete with connection, testing and commissioning etc. as required.	each	r	996.00	BCD Ele. SOR 2018, Item 2.19	4,980.00
18	Supplying and fixing 30 amps, 415 volts, TPN industrial type, socket outlet, with 4 pole and earth, metal enclosed plug top along with 30 amps "C" curve, TP MCB, in sheet steel enclosure, on surface or in recess, with chained metal cover for the socket outlet andcomplete with connections, testing and commissioning etc. as required.	each	10	3,157.00	BCD Ele. SOR 2018, Item 2.25	31,570.00
19	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.	set	ю	5,125.00	BCD Ele. SOR 2018, Item 3.2	15,375.00
20	Providing and fixing 25 mm X 5 mm G.I strip on surface or in recess for connections etc. as required.	mtr	200	150.00	BCD Ele. SOR 2018, Item 3.15	30,000.00
21	Supplying and fixing single wall mounted 20/22 watt LED type batten fitting complete with electronic driver and LED tube etc directly on wall/ ceiling including connection with 1.5 sq. mm FR PVC insulated copper conductor and earthing the body etc. as required.	each	10	684.00	BCD Ele. SOR 2018, Item 5.9.3	6,840.00
22	Supplying and fixing indoor recess mounting 36 wattLED flat panel luminaire suitable for armstrong / grid ceiling and complete with electronic driver etc. directly on false ceiling including connection with 1.5 sq.mm FR PVC insulated copper conductor cable and earthing the body etc. as required.	each	30	4,023.00	BCD Ele. SOR 2018, Item 5.10.3	120,690.00
23	Supplying and fixing 90 watt LED type FLOOD light with die cast aluminium housing for ingress protection of IP65 and complete with all accessories etc and connection with FR PVC insulated copper conductor cable and earthing the body etc. as required.	each	4	8,501.00	BCD Ele. SOR 2018, Item 5.13.10	34,004.00
24	Fixing for Laying of one number PVC insulated and PVC sheathed/ XLPE power cable of 1.1 KV grade of following size on wall surfaceas required. Above 35 sq. mm and upto 95 sq. mm Upto 35 sq. mm (Clamped with 1 mm thick saddle)	mtr	300	29.00	BCD Ele. SOR 2018, Item 7.4.1	8,700.00
25	Fixing for Laying of one number PVC insulated and PVC sheathed/ XLPE power cable of 1.1 KV grade of following size on wall surfaceas required. Above 35 sq. mm and upto 95 sq. mm (Clamped with 25 x 3 mm NS flat clamp)	mtr	300	68.00	BCD Ele. SOR 2018, Item 7.4.2	20,400.00
26	Supply and installation of Regular/ standard model A.C ceiling fan of 1200 mm sweep including wiring the down rods of standard length (upto 30 cm) with 1.5 sq. mm FR PVC insulated copper coductor etc. as required.	nos	4	1,618.00	BCD Ele. SOR 2018, Item 8.11.2	6,472.00
27	4 core, 6 sq. mm, XLPE/PVC insulated PVC. sheathed (Heavy duty) Armoured electric cable with aluminium conductor	mtr	300	75.00	BCD Ele. SOR 2018, Item 2216	22,500.00
28	4 core, 10 sq. mm, XLPE/PVC insulated PVC. sheathed (Heavy duty) Armoured electric cable with aluminium conductor	mtr	200	95.20	BCD Ele. SOR 2018, Item 2217	19,040.00

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcup

U

 \bigcup

	4 core, 16 sq. mm, XLPE/PVC insulated PVC. sheathed (Heavy duty) Armoured electric cable with				BCD Ele. SOR	
29	aluminium conductor	mtr	200	105.70	2018, Item	21,140.00
					7704	
00	3.3 core, 2.3 sq. IIIIII, ALFE/FVC IIIsulated FVC. sneathed (Heavy duty) Armoured electric cable with				BCD Ele. SOR	
S .	aluminum conductor	mtr	100	126.00	2018, Item	12,600.00
					2205	
č	3.5 core, 35 sq. mm, XLPE/PVC insulated PVC. sheathed (Heavy duty) Armoured electric cable with				BCD Ele. SOR	
31	aluminium conductor	mtr	200	159.00	2018, Item	31,800.00
					2206	
ć	3.5 core, 50 sq. mm, XLPE/PVC insulated PVC. sheathed (Heavy duty) Armoured electric cable with				BCD Ele. SOR	
37	aluminium conductor	mtr	300	207.00	2018, Item	62,100.00
					2207	
ć	3.5 core, 95 sq. mm, XLPE/PVC insulated PVC. sheathed (Heavy duty) Armoured electric cable with				BCD Ele. SOR	
33	aluminium conductor	mtr	300	340.20	2018, Item	102,060.00
					2209	
1	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of				BCD Ele. SOR	
34	following size direct in ground including excavation, sand cushioning, protective covering and refilling	mtr	300	151.00	2018, Item	45,300.00
	the trench etc. as required. Above 35 sq. mm and upto 95 sq. mm				7.1.2	20
35	Supply, installation, lestingand Commissioning of LED RGB/RGBW Linear Wall Washer luminaire for Facade lighting with aluminium extruded housing, of following wattage. Luminaire shall be capable of producing dynamic color changing light with 16 million colors by DMX/Ethernet based control. The beam angle of the fitting shall be narrow, medium, wide or asymmetric as per the requirement. Luminaire shall be complete with driver and capable of operating at line voltage without any separate power supply from 100 to 270 VAC, 50Hz, power factor > 0.9. Fixture shall be suitable to operate at ambient temperature range of -10° C to +50° C and shall be IP65 and IK 06 rated. Life time should be at least L70: 50000 burning hours at 50° C. Luminaire shall be conforming to BIS and shall be complete with all necessary accessories required for proper working of fixture including weather proof connectors etc. as required. 25 watt	each	16	23,130.00	DSR E&M Facade 2018, Item 2.5	370,080.00
					Total Amount	1,092,035.00

	Bill of Quantities (Electrical) for Kid's Play Area in Sandish Park In Bhazalour under Smart City Mission	under Sm	nart City	Mission		
SI	Description	Unit	Ç	Unit Otv. Bate (Bs.)	Rof. Rato	Amount (Be)
		1000		(icul cami		Amodule (NS.)
	Supply and fixing of decorative 40 to 45 Watt LED Post top indirect light luminaire having Pressure die				UP SOR 2018	
	cast aluminiumbody and Clear glass with driver set confirming to IP 65 and above protection				Chapter 14 -	
1	complete in all respect.	Nos	∞	18.300.00	G	146 400 00
	CAT-AAA				LIMINAIDES	2000
	0 ** +**)				LOIVIINAIRES,	
	CAI-AA				Item 1443	
	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
2	aluminium conductor	mtr	400	105.70	105.70 2018, Item	42,280.00
					2204	

SHARINE SHARING

	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
က	aluminium conductor	mtr	300	126.00	2018, Item	37,800.00
					2205	
4	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of following size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm	mtr	009	77.00	DSR Ele. SOR 2018, Item 7.3.1	46,200.00
2	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/coke and salt as required.	mtr	7	5,125.00	BCD Ele. SOR 2018, Item 3.2	10,250.00
9	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.	set	300	38.00	BCD Ele. SOR 2018, Item 3.16	11,400.00
7	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)	Nos	Н	6,174.00	BCD Ele. SOR 2018, Item 8.10.3	6,174.00
∞	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity	Each	1	1,200.00	BCD Ele. SOR 2018, Item 1710	1,200.00
O	Supplying,installation,testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (1output per phase) and suitable for three phase supply	Each	н	3,657.00	DSR Ele. SOR 2018, Item 15.4.3	3,657.00
				П	Total Amount	305,361.00
	Bill of Quantities (Electrical) for Multipurpose Ground in Sandish Park In Bhagalpur under Smart City Mission	Ipur unde	r Smart (City Mission.		
SI	Description	Unit	Qty.	Rate (Rs.)	Ref: Rate	Amount (Rs.)
Н	Supply and fixing of 20 mtr High mast Pole of approved make with rising system, hot dip Galvanized inside & outside , having pole sheet thickness 4mm,top dia minimum150mm, bottom dia minimum 410mm, base plate 32mm thick, suitable for wind velocity as per IS 875 part 3 &.having no circumferential weld, with accessories for high mast such as head frame suitable for 6 to 12 luminaries & its control gear boxes,1.5 HP Power tool motor, 3 point suspension system with steel Nos wire rope 8 mm dia , double drum winch. Including making suitable Foundation as per manufacture drawing & site requirement along with foundation bolts, nuts, washers , anchor plates etc Complete in all respect as per direction and satisfaction to the Engineerin- charge.	sol	ω	403,409.09	UP SOR 2018 Chapter 6 - High Mast, Item 653	3,227,272.73

 \cap

 \bigcirc

 \cap

 \cap

 \cap

 \bigcirc

 \bigcirc

0

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

 \cup

 \bigcirc

 \cup

 \bigcirc

2	Supplying and fixing following LED street/ Flood light with die cast aluminium housing for ingress protection of IP65 and complete with all accessories etc on pole/ building including connection and Nos	Nos	64	26.964.00	BCD Ele. SOR	1 725 696 00
	earthing the body etc. as required. 200/220 watt FLOOD light					1,12,000,00
,	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
m	aluminium conductor	mtr	300	105.70		31,710.00
					2204	
	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with				BCD Ele. SOR	
4	aluminium conductor	mtr	2000	126.00	20	252,000.00
	Parity of any sumbor MIC in the Last of th		1		2205	and a
и	taying of othe fluriber PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of	0			DSR Ele. SOR	
n	lollowing size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm	mtr	2000	77.00	2018, Item	154,000.00
	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry				1.6.7	
9	enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.	mtr	10	5,125.00	BCD Ele. SOR 2018, Item 3.2	51,250.00
	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.				RCD Fla SOB	
7		set	100	38.00	2018, Item	3.800.00
					3.16	
	Supplying and fixing Floor mounted outdoor feeder pillar cubical type panel board, fabricated with 14 guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber,				BCD Ele. SOR	
∞	insulator, nut-bolt with MS 40 X 40 X 5 mm angle stand and complete with powder painting etc as	Nos	4	6,174.00	2018, Item	24,696.00
	required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)				8.10.3	
	50/63 amps ratings, TPN MCB, "C" curve 10 KA breaking capacity				BCD Ele. SOR	
6		Each	4	1,200.00	2018, Item	4,800.00
	Commissioning				1710	
10	configuration to be mounted in feeder pillars / Lighting DBs for automatic switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required 3 output (Loutout pay pass) and citizals for the control of the contro	Each	4	3,657.00	DSR Ele. SOR 2018, Item 15.4.3	14,628.00
	supply					

St. White But the but

11	S& F of all in one solar LED street light fixture with Integrated high efficient Monocrystalline panel with Lithium (LiFePO4) Ferro Phosphate battery with BIS approved make .luminaire should be secondary optic lenses for better distribution with delivered efficacy of > 100 Lumen perwatt.Bidder shall have in house R&D Laboratory which is recognised by ministry of Science & Technology department, Govt. Of India/NABL.Bidder shall have inhousepole &luminairem anufacturing facility.Luminaire can be supplied with Hybrid switch along with indicator to understand the source of power(either from solar or AC supply).shall have certificate tested from MNRE approved Lab.Guarantee for total system is two years .Note: All the above should be integrated and should be 1 system. Compact Solar LED Street Light - 90W(MONO) 18V/	Each	20	60,984.00	RUIDP Ele. SOR 2017, Item 15.4.3	3,049,200.00
					Total Amount	8,539,052.73
	Bill of Quantities (Electrical) for OAT in Sandish Park In Bhagalpur under Smart City Mission.	r Smart C	ity Missi	on.		
SI	Description	Unit	Qty.	Rate (Rs.)	Ref: Rate	Amount (Rs.)
-	Supply and fixing of decorative 40 to 45 Watt LED Post top indirect light luminaire having Pressure die cast aluminiumbody and Clear glass with driver set confirming to IP 65 and above protection complete in all respect. CAT-AAA CAT-AAA	nos	∞	18,300.00	UP SOR 2018 Chapter 14 - LED LUMINAIRES, Item 1443	146,400.00
7	P & F of IP68, IK10 protected LED Buried marker light / Step Light Fixture. Fixture made of powder coated die cast alluminium with Toughened Glass cover and appropriate beam angle lens to be used as per requirement. The System level Luminous efficacy must be >90 Lumen/W. High Power LEDs at 1W/2W per LED. The driving current should be Minimum 350 mA per LED. CRI>70, CCT: 3000/6500 K. The integral SMPS based electronic driver must be constant current and surge protection of min. 4KV(L-N) and efficiency > 85%, PF>0.9 and input Voltage range of 90-270V AC at 50Hz. System life of 50000 Burning hours with 70% of Initial Lumens maintained. Light should include quick connecting cable coupled with various mounting accessories. Light output in Cool white or Warm White Colour as per engineers choice. Fixture must be in compliance with IS/CE Standards. Step Light - 5W	nos	20	1,662.00	SOR RUIDP 2017, Item 58.33.4	83,100.00
т	Supplying and drawing following sizes of FRLS PVC insulated copper conductor, single core cable in the existing surface/ recessed steel/ PVC conduit as required. $2 \times 1.5 \text{ sq. mm}$	mtr	200	41.00	DSR Ele. SOR 2018, Item 1.17.2	8,200.00
4	Supply and fixing of 12.5 mtr High mast Pole of approved make with rising system, hot dip Galvanized inside & outside , having pole sheet thickness 3mm, top minimum100mm, bottom dia minimum 310mm, base plate 25mm thick, suitable for wind velocity as per IS 875 part 3. & having no circumferential weld, with accessories for high mast such as head frame suitable for 6 luminaries & its control gear boxes,0.75 HP Power tool motor, 3 point suspension system with steel wire rope 6mm dia , double drum winch Including making suitable Foundation as per manufacture drawing & site requirement along with foundation bolts, nuts, washers , anchor plates etc Complete in all respect. as per direction and satisfaction to the Engineer-in-charge.	nos	7	220000.00	UP SOR 2018 Chapter 6 (Supplementar y) - Mast, Item 651	440000.00

 \cap

 \bigcirc

 \bigcirc

 \bigcirc

 \bigcirc

()

0

 \bigcup

 \bigcirc

0

	ity Miccion	Tinger /more	Khagain	KINILL	ביי ליינייני ליינייני ליינייניין יכן ליינייניין יכן ליינייניין יכן ליינייניין יכן ליינייניין יכן ליינייניין יכן
965,805.00	Total Amount				Bill of Orandition (Florbeical) for Condition Market 12 11 11 11 11 11 11 11 11 11 11 11 11
3,657.00	DSR Ele. SOR 2018, Item 15.4.3	3,657.00	1	each	Supplying,installation,testing and commissioning of Astronomical time switch of following configuration to be mounted in feeder pillars / Lighting DBs for automatic switching On & OFF of street lights at sun set & sun rise or twilight(Auto ON, Auto OFF, Auto modes) with manual override facility with 12/24 hour display format with suitable battery and indication for relay status i/c programming at site complete as required. 3 output (1output per phase) and suitable for three phase supply
1,200.00	BCD Ele. SOR 2018, Item 1710	1,200.00	Н	each	50/55 gnips ratings, irrivitor, in turke 10 NA breaking capacity
6,174.00	BCD Ele. SOR 2018, Item 8.10.3	6,174.00	Н	nos	guage iron sheet suitable for panel mounted SFU/MCCB and complete with bus-bar chamber, insulator, nut-bolt with MS 40 X 5 mm angle stand and complete with powder painting etc as required. (But without busbar copper strip, MCCB, & PCC work) (Each panel 3 Sq. ft)
7,600.00	BCD Ele. SOR 2018, Item 3.16	38.00	200	set	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.
10,250.00	BCD Ele. SOR 2018, Item 3.2	5,125.00	2	mtr	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/ coke and salt as required.
38,500.00	DSR 20	77.00	200	mtr	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 1.1 KV grade of following size direct in ground including excavation and refilling the trench etc as required but excluding sand cushioning and protective covering. Upto 35 sq. mm
37,800.00	BCD Ele. SOR 2018, Item	126.00	300	mtr	4 core, 25 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor
21,140.00	BCD Ele. SOR 2018, Item 2204	105.70	200	mtr	4 core, 16 sq mm XLPE/PVC insulated PVC sheathed (heavy duty) armoured electric cable with aluminium conductor
161,784.00	BCD Ele. SOR 2018, Item 5.13.15	26,964.00	9	nos	Supplying and fixing following LED street/ Flood light with die cast aluminium housing for ingress protection of IP65 and complete with all accessories etc on pole/ building including connection and earthing the body etc. as required. 200/220 watt FLOOD light

1000 1,311.36 SPDCL 2016, Material Rate		Description	Unit	240	Pate (Dr.)	Dof. Date	
uminium conductor, XLPE insulated, PVC sheathed, conform to IS: 7098 Part-2, 2011 with up to date ells/ KEI/ RR / RPG Material Rate				4.7	nate (ns.)	nei. nate	Amount (RS.)
conform to IS: 7098 Part-2, 2011 with up to date mtr 1000 1,311.36 SPDCL 2016, Material Rate		Supply of 11KV grade, 3C x 300 Sq. mm Aluminium conductor, XLPE insulated, PVC sheathed.					
ells/ KEI/ RR / RPG	1	armoured screened cable. The cable should conform to 15: 7098 Part-2, 2011 with up to date	mtr	1000	1 311 36	SPDCL 2016,	
elis/ KEI/ KR / RPG	S	See the second Appropriate the second	-	200	1,011.00	Material Pate	
	1	Jajnendinent. APPROVED BRAND: Polycab/ Havelis/ REI/ RR / RPG				ואומובו ומו וימוב	

Alle Helical Children
7	Laying of one number PVC insulated and PVC sheathed / XLPE power cable of 11 KV grade of following size in the existing RCC/ HUME/ METAL/ DWC HDPE pipe as required. Above 120 sq. mm	mtr	1000	112.00	DSR SoR 2018, Item Code	112,000.00
					8.3.7	
	suppying and laying of following size DWC hors pipe is marked along with all accessories like socket, bend, couplers etc. conforming to IS 14930, Part II complete with fitting and cutting, jointing				DSR SoR 2018,	-
3	etc.direct in ground (75 cm below ground level) including excavation and refilling the trench but	mtr	2000	298.00	Item Code	1,196,000.00
	excluding sand cushioning and protective covering etc., complete as required. 200 mm dia (OD-200				14.16.5	
	mm & ID-175 mm nominal), approved make					
	Supplying and making outdoor cable end termination with heat shrinkable jointing kit complete with				DSR Ele. SOR	
4	all accessories including lugs suitable for following size of 3 core, XLPE aluminium conductor cable of	each	4	17,166.00	2018, Item	68,664.00
	11 KV grade as required : 300 sq. mm				10.5.4	
	Supplying and making straight through cable jointing with heat shrinkable jointing kit complete with			¥2	DSR Ele. SOR	
2	all accessories including ferrules suitable for following size of 3 core, XLPE aluminium conductor cable	each	9	19,314.00	2018, Item	115,884.00
	of 11 KV grade as required : 300 sq. mm				10.6.4	
	Supply, installation, testing and commissioning of new double pole structure for 11KV/433V upto					9
	encluding PSC Pole 400 kg 2 Nos, Top channel set, A.B. Switches base channel set, Horn gap fuse base					
	channel, Transformer base channel, Tanformer fastening angle, Support clamp for tansformer base				SPIC 12016	
9	channel, support clamp for AB switch base channel, Back clamp for transformer fastening angle, back	set	н	428,484.00	DSS DSS	428,484.00
	ciamp for norn gap fuse set, cable holding ciamp, 11 KV 200 Amp. AB Switch 3 pole, 11 KV Horn Gap					
	ruse set with insulator, nut boil, danger board making HT/LI busbar System, 200 KVa DI star rated					
	etc complete with all respect as per Local Discom Specification as required.				+	
	Earthing with G.I. earth pipe 4.5 metre long, 40 mm dia including accessories, and providing masonry				BCD Elo COB	
7	enclosure with cover plate having locking arrangement and watering pipe etc. with charcoal/ coke	set	4	5,125.00	DO18 Hem 3.7	20,500.00
	and salt as required.				2010, Itelii 3.2	
∞	Providing and fixing 6 SWG dia G.I. wire on surface or in recess for loop earthing etc. as required.	mtr	100	38.00	BCD Ele. SOR 2018, Item	3,800.00
					3.16	

 \bigcirc

 \bigcirc

 \bigcirc

()

 \bigcirc

 \bigcirc

 \bigcirc

 \cup

Alternator mounted on a common base Frame & coupled through a flexible coupling or close Alternator mounted on a common base Frame & coupled through a flexible coupling or close coupled. Alternator shall be self regulated with standard Alternator Protection (Over voltage, over speed & under voltage). Engine shall have residential silencer, up to 10 M exhaust piping, electronic/ Mechanical governor, Manual & electric/Auto Start, Batteries, Fuel tank (with Stand) & piping, control panel (16 G) with MCCB (4P; 25 KA), Ammeter, Voltmeter, Frequency Meter, Energy Meter & Hour Meter, Engine instruments panel, AVM and with Weatherproof, powder coated Accoustic enclosure for DG set for sound attenuation fabricated from 1.6 mm CRCA sheet steel (structure) with side wall fabricated from 1.6 mm CRCA sheet packed with accoustic material, floor of MS standards are fabricated from 1.6 mm CRCA sheet packed with accoustic material, floor of MS and tripping of DG set against temperature of more than 50 °C. All controls for operation of DG set are from outside the enclosure with DG control panel having microprocessor based genest monitoring and control system mccb Ammeter, voltmeter, Pf meter, frequency meter, KWH meter, Ind. Lamps etc. mounted inside enclosure , visible and accessible from outside. The enclosure should be suitable for following capacity DG sets and alternator. Noise level is less than 75 db (A) at a distance of 1 mtr. duly certified by authorized agency. Complete in all respect of following capacity: Radiator cooled and turbo charged, 100 KVA at 0.8 pf 415V 50Hz 3-Ø, with AMF Panel fitted inside the enclosure, with the following meters/indicators:(Incoming and outgoing voltage, Current in all phases, Frequency, KVA and power factor, Time indication for hours/ minutes of operation, Fuel Level in field tank, low fuel indication, Emergency Stop button, Auto/Manual/Test selector switch, MCCB/Circuit breaker for short-circuit and overload protection, Control Fuses, Erth Terminal, Automent, relay etc. esseential for A	iesel Engine of suitable BHP & AC Brush less SPDP me & coupled through a flexible coupling or close h standard Alternator Protection(Over voltage, overlential silencer, up to 10 M exhaust piping, electronic / start, Batteries, Fuel tank (with Stand) & piping, control r, Voltmeter, Frequency Meter, Energy Meter & Hour th Weatherproof, powder coated Accoustic enclosure om 1.6 mm CRCA sheet steel (structure) with side wall with foam as per CPCB norms latest amendments & IS RCA sheet packed with accoustic material, floor of MS ening are sealed with neoprene/ EPDN gaskets. The nere (isolated from main DG chamber) with protection more than 50 °C. All controls for operation of DG set control panel having microprocessor based genset r, voltmeter, Pf meter, frequency meter, KWH meter, ble and accessible from outside. The enclosure should d alternator. Noise level is less than 75 db (A) at a agency. Complete in all respect of following capacity: it 0.8 pf 415V 50Hz 3-Ø, with AMF Panel fitted inside cators:(Incoming and outgoing voltage, Current in all indication for hours/ minutes of operation, Fuel Level is indication for hours/ minutes of operation, Leu Level is indication for hours/ minutes of operation, Fuel Level is indication for hours/ minutes, Earth Terminal, Any r Automatic functioning of DG set with AMF panel	ach	1	917,204.00	RUIDP SOR 2017, Item- 66.18.2.9	917,204.00
				Amount		2 862 536 00
						4,004,330.00